



TEPCO

a Division of Central Expanded Metal, Inc.

405-258-0079



PERMAPAD development continues

weights, while maintaining the structural

integrity the PERMAPAD is known for.

with improved texture on the "NO

SKID" mounting surface and lower

PERMAPAD is plain and simple the plastic condenser pad of choice. It's strength and rigidity is unparalleled and offers a TRUE concrete alternative. Enjoy carrying an eco-friendly product that will outlast the equipment it holds.

PERMAPAD SIZES

| 2" PERMAPAD | 20 per pallet | |
|-------------|---------------|-----|
| 24 x 24 | 12 | lbs |
| 24 x 30 | 14 | lbs |
| 24 x 36 | 19 | lbs |
| 26 x 26 | 15 | lbs |
| 30 x 30 | 20.5 | lbs |
| 30 x 36 | 22.5 | lbs |
| 30 x 40 | 23 | lbs |
| 32 x32 | 28 | lbs |
| 32 x 42 | 29.5 | lbs |
| 33 x 45 | 29.5 | lbs |
| 36 x 36 | 32 | lbs |
| 36 x 48 | 35 | lbs |
| 3" PERMAPAD | 15 per pallet | |
| Sizes | Pad weight | |
| 24 x 24 | 13 | lbs |
| 24 x 36 | 25 | lbs |
| 30 x 30 | 22.5 | lbs |
| 30 x 40 | 27 | lbs |
| 32 x 32 | 26 | lbs |
| 33 x 45 | 39.5 | lbs |
| 36 x 36 | 31 | lbs |
| 36 x 48 | 43 | lbs |

PAD FEATURES

- Lighter weight than concrete
- Textured skid resistant surface
- UV Stabilized to provide long life (see warranty statement)
- Material formulation tightly controlled with state of the art equipment
- Drill and tap as needed
- Easy low cost installation
- Pads may be private labeled
- Made from 95% recycled polyethylene contained in a proprietary formulation

Select the contractor's pad of choice and give us a call today!



PERMAPAD (LEFT) accepts most fasteners to securely hold condensers and equipment to the surface of the pad. Pictured to the left are typical fasteners such as:

- Lag Bolts
- Wall board fasteners
- Alloy inserts screwed into the pad
- Expansion inserts
- Cement screws
- Sheet metal self tapping screws

Decks of less than 3/8 inch still permit all these fasteners to securely grip the pad and provide a reliable attachment to the pad.

PERMAPAD strength comes from a patented design that uses strategically placed ribs to enhance overall structural integrity. Tightly controlled deck thickness contributes to load bearing capacity. Rib and edge width provide a soil footprint larger than competition's thin ribbed injection molded pads.



Limited Lifetime Warranty

PERMAPAD is sold with a limited lifetime warranty that provides the original purchaser a warranty against defects in materials and workmanship. A complete printing of the warranty noting exclusions and conditions as well as the process for return of a suspect pad is available upon request. PERMAPAD is designed to support the base of a wide variety of lightweight to heavy-duty ground based equipment, such as air conditioning condensers, heat pumps, generators and swimming pool filters.