

# Design and Implementation of Programming Languages

## Project Specification

### Fall 2017

**Set-up:** For this assignment, edit a copy of `project.rkt`, which is attached. In particular, replace occurrences of "CHANGE" to complete the problems. Do not use expressions with side effects (`set!`, `set-mcar!`, etc.) in your code.

**Overview:** This project has to do with NUMEX (**N**umber-**E**xpression Programming Language). NUMEX programs are written directly in Racket by using the constructors defined by the structs defined at the beginning of `project.rkt` (Note: you must define missing ones). Here is the definition of NUMEX's syntax:

- If  $s$  is a Racket string, then `(var  $s$ )` is a NUMEX expression (variables).
- If  $n$  is a Racket integer, then `(int  $n$ )` is a NUMEX expression (constants).
- If  $e_1$  and  $e_2$  are NUMEX expressions, then `(add  $e_1$   $e_2$ )` is a NUMEX expression (addition).
- If  $e_1$  and  $e_2$  are NUMEX expressions, then `(mult  $e_1$   $e_2$ )` is a NUMEX expression (multiplication).
- If  $e_1$  is a NUMEX expression, then `(neg  $e_1$ )` is a NUMEX expression (negation).
- If  $s_1$  and  $s_2$  are Racket strings and  $e$  is a NUMEX expression, then `(fun  $s_1$   $s_2$   $e$ )` is a NUMEX expression (a function). In  $e$ ,  $s_1$  is bound to the function itself (for recursion) and  $s_2$  is bound to the only argument. Also, `(fun null  $s_2$   $e$ )` is allowed for anonymous nonrecursive functions.
- If  $e_1$  and  $e_2$  are NUMEX expressions, then `(islthan  $e_1$   $e_2$ )` is a NUMEX expression (comparison).
- If  $e_1$ ,  $e_2$ , and  $e_3$  are NUMEX expressions, then `(ifzero  $e_1$   $e_2$   $e_3$ )` is a NUMEX expression. It is a condition where the result is  $e_2$  if  $e_1$  is zero else the result is  $e_3$ . Only one of  $e_2$  and  $e_3$  is evaluated.
- If  $e_1$ ,  $e_2$ ,  $e_3$ , and  $e_4$  are NUMEX expressions, then `(ifgthan  $e_1$   $e_2$   $e_3$   $e_4$ )` is a NUMEX expression. It is a conditional where the result is  $e_3$  if  $e_1$  is strictly greater than  $e_2$  else the result is  $e_4$ . Only one of  $e_3$  and  $e_4$  is evaluated.
- If  $e_1$  and  $e_2$  are NUMEX expressions, then `(call  $e_1$   $e_2$ )` is a NUMEX expression (function call).
- If  $s$  is a Racket string, and  $e_1$  and  $e_2$  are NUMEX expressions, then `(mlet  $s$   $e_1$   $e_2$ )` is a NUMEX expression (a let expression where the value of  $e_1$  is bound to  $s$  in  $e_2$ ).

- If  $e_1$  and  $e_2$  are NUMEX expressions, then `(apair  $e_1$   $e_2$ )` is a NUMEX expression (pair constructor).
- If  $e_1$  is a NUMEX expression, then `(first  $e_1$ )` is a NUMEX expression (the first part of a pair).
- If  $e_1$  is a NUMEX expression, then `(second  $e_1$ )` is a NUMEX expression (the second part of a pair).
- `(munit)` is a NUMEX expression (holding no data, much like `()` in ML or `null` in Racket). Notice `(munit)` is a NUMEX expression, but `munit` is not.
- If  $e_1$  is a NUMEX expression, then `(ismunit  $e_1$ )` is a NUMEX expression (testing for `(munit)`).
- `(closure  $env$   $f$ )` is a NUMEX value where  $f$  is NUMEX function and  $env$  is an environment that maps variables to values. Closures do not appear in programs; they result from evaluating functions.

A NUMEX *value* is a NUMEX integer constant, a NUMEX closure, a NUMEX munit, or a NUMEX pair of NUMEX values. Similar to Racket, we can build list values out of nested pair values that end with a NUMEX munit. Such a NUMEX value is called a NUMEX list.

You should *not* assume NUMEX programs are syntactically correct (e.g., things like `(int "hi")` or `(int (int 37))` must be handled). And do *not* assume NUMEX programs are free of type errors like `(add (munit) (int 7))` or `(first (int 7))`.

**Instructions:** Upload your modified `project.rkt` and `projectTest.rkt` through the Moodle website.

## Problems:

### 1. Warm-Up

- (a) Write a Racket function `racketlist->numexlist` that takes a Racket list, which may even be a list of NUMEX values, and produces a NUMEX list with the same elements in the same order.
- (b) Write a Racket function `numexlist->racketlist` that takes a NUMEX list and produces a Racket list with the same elements in the same order.

### 2. Implementing NUMEX

Write an interpreter for NUMEX. It should be a Racket function `eval-exp` that takes a NUMEX expression `e` and either returns the NUMEX value that `e` evaluates to under the empty environment or calls Racket's error if evaluation encounters a run-time NUMEX type error or unbound NUMEX variables.

An NUMEX expression is evaluated in an environment (for evaluating variables, as usual). In your interpreter, use a Racket list of Racket pairs to represent this environment (which is initially empty) so that you can use the `envlookup` function, after completing it. Here is a description of the semantics of NUMEX expressions:

- All values (including closures) evaluate to themselves. For example, `(eval-exp (int 17))` would return `(int 17)`, not `17`.
- A variable evaluates to the value associated with it in the given environment.
- An addition (a multiplication) evaluates to the sum (product) of what its summands (factors) evaluate to.
- A negation (`neg e`) evaluates to the opposite (negation) of what `e` evaluates to.
- Functions are lexically scoped in the sense that a function evaluates to a closure holding the function and the current environment.
- The evaluation of `(islthan  $e_1$   $e_2$ )` involves the evaluation of  $e_1$  and  $e_2$ . The resulting values is `(int 1)` if the value of  $e_1$  is less than the value of  $e_2$ . Otherwise, the expression evaluates to `(int 0)`.
- For `(ifzero  $e_1$   $e_2$   $e_3$ )`, the expression  $e_1$  first evaluates to a value. If the resulting value is zero, the whole expression evaluates to what  $e_2$  evaluates to. The expression evaluates to the value of  $e_3$  otherwise.
- The evaluation of `(ifgthan  $e_1$   $e_2$   $e_3$   $e_4$ )` involves the evaluation of  $e_1$  and  $e_2$ . If the value of  $e_1$  is strictly greater than the value of  $e_2$ , then it evaluates to the value of  $e_3$ . Otherwise,  $e_4$  must be evaluated.
- For `(mlet  $s$   $e_1$   $e_2$ )`, the expression  $e_2$  evaluates to a value in an environment extended to map the name  $s$  to the evaluated value of  $e_1$ .
- For `(call  $e_1$   $e_2$ )`, the expression  $e_1$  first evaluates to a value. If the resulting value is not a closure, an error should be arisen. Otherwise, it evaluates the closure's function's body in the closure's environment extended to map the function's name

to the closure (unless the name field is null) and the function's argument to the result of the evaluation of  $e_2$ .

- The (apair  $e_1$   $e_2$ ) construct makes a (new) pair holding the results of the evaluations of  $e_1$  and  $e_2$ .
- If the result of evaluating  $e_1$  in (first  $e_1$ ) is an apair, then the first part is returned. Otherwise, it returns an error. Similarly, the evaluation of (second  $e_1$ ) is the second part of the given pair.
- For (ismunit  $e_1$ ), the expression  $e_1$  first evaluates to a value. If the resulting value is a munit expression, then the result is the NUMEX value (int 1), else it is the NUMEX value (int 0).

### 3. Extending the Language

NUMEX is a small language, but we can write Racket functions that act like NUMEX macros so that users of these functions feel like NUMEX is larger. The Racket functions produce NUMEX expressions that could then be put inside larger NUMEX expressions or passed to eval-exp. In implementing these Racket functions, do not use closure (which is used only internally in eval-exp). Also do not use eval-exp (we are creating a program, not running it).

- (a) Write a Racket function ifmunit that takes three NUMEX expressions  $e_1$ ,  $e_2$ , and  $e_3$ . It returns a NUMEX expression that first evaluates  $e_1$ . If the resulting value is NUMEX's munit, then it evaluates  $e_2$  and that is the overall result. Otherwise,  $e_3$  must be evaluated.
- (b) Write a Racket function mlet\* that takes a Racket list of Racket pairs  $((s_1 . e_1) \dots (s_i . e_i) \dots (s_n . e_n))$  and a final NUMEX expression  $e_{n+1}$ . In each pair, assume  $s_i$  is a Racket string and  $e_i$  is a NUMEX expression. mlet\* returns a NUMEX expression whose value is  $e_{n+1}$  evaluated in an environment where each  $s_i$  is a variable bound to the result of evaluating the corresponding  $e_i$  for  $1 \leq i \leq n$ . The bindings are done sequentially, so that each  $e_i$  is evaluated in an environment where  $s_1$  through  $s_{i-1}$  have been previously bound to the values  $e_1$  through  $e_{i-1}$ .
- (c) Write a Racket function ifeq that takes four NUMEX expressions  $e_1$ ,  $e_2$ ,  $e_3$ , and  $e_4$  and returns a NUMEX expression that acts like ifgthan except  $e_3$  is evaluated if and only if  $e_1$  and  $e_2$  are equal integers. Otherwise, the whole expression evaluates to what  $e_4$  evaluates to. Assume none of the arguments to ifeq use the NUMEX variables `_x` or `_y`. Use this assumption so that when an expression returned from ifeq is evaluated,  $e_1$  and  $e_2$  are evaluated exactly once each.

### 4. Using the Language

We can write NUMEX expressions directly in Racket using the constructors for the structs and (for convenience) the functions we wrote in the previous problem.

- (a) Bind to the Racket variable `numex-map` a NUMEX function that acts like `map` (as we use in ML). Your function should be curried: it should take a NUMEX function and return a NUMEX function that takes a NUMEX list and applies the function to every element of the list returning a new NUMEX list. Recall a NUMEX list is `munit` or a pair where the second component is a NUMEX list.
- (b) Bind to the Racket variable `numex-mapAddN` a NUMEX function that takes a NUMEX integer  $i$  and returns a NUMEX function that takes a NUMEX list of NUMEX integers and returns a new NUMEX list of NUMEX integers that adds  $i$  to every element of the list. Use `numex-map`.

## 5. Challenging Problem

Write a second version of `eval-exp` (bound to `eval-exp-c`) that builds closures with smaller environments: When building a closure, it uses an environment that is like the current environment but holds only variables that are free variables in the function part of the closure. (A free variable is a variable that appears in the function without being under some shadowing binding for the same variable.)

Avoid computing a function's free variables more than once. Do this by writing a function `compute-free-vars` that takes an expression and returns a different expression that uses `fun-challenge` everywhere in place of `fun`. The new struct `fun-challenge` (provided to you; do not change it) has a field `freevars` to store exactly the set of free variables for the function. Store this set as a Racket set of Racket strings. (Sets are predefined in Racket's standard library; consult the documentation for useful functions such as `set`, `set-add`, `set-member?`, `set-remove`, `set-union`, and any other functions you wish.)

You must have a top-level function `compute-free-vars` that works as just described — storing the free variables of each function in the `freevars` field — so the grader can test it directly. Then write a new “main part” of the interpreter that expects the sort of NUMEX expression that `compute-free-vars` returns. The case for function definitions is the interesting one.