Managing Ansible Configuration Files

Mohamed Amin AYED

Configured the ansible navigator EE with a rhel8 image to be pulled when missing

```
  GNU nano 5.6.1 /home/student/playbook-manage/ansible-navigator.yml
ansible-navigator:

  execution-environment:

    image: utility.lab.example.com/ee-supported-rhel8:latest

    pull:

      policy: missing

  playbook-artifact:

    enable: false
```

Checking and pulling the set image:

```
[student@workstation playbook-manage]$ ansible-navigator images
------------------------------------------------------------------------------
Execution environment image and pull policy overview
------------------------------------------------------------------------------
Execution environment image name:     utility.lab.example.com/ee-supported-rhel8:latest
Execution environment image tag:      latest
Execution environment pull arguments: None
Execution environment pull policy:    missing
Execution environment pull needed:    True
------------------------------------------------------------------------------
Updating the execution environment
------------------------------------------------------------------------------
Running the command: podman pull utility.lab.example.com/ee-supported-rhel8:latest
Trying to pull utility.lab.example.com/ee-supported-rhel8:latest...
Getting image source signatures
Copying blob 032147be31cb done
Copying blob cd9c7fb15159 done
```

➔

	Image	Tag	Execution environment	Created	Size
0	ee-supported-rhel8	latest	True	4 years ago	1.45 GB

Now to configure the core engine, let's start with setting the inventory fil in the core config:

```
  GNU nano 5.6.1            /home/student/playbook-manage/ansible.cfg
[defaults]

inventory = ./inventory
```

And then set the hosts in the inventory:

```
student@workstation:~/playbook-manage — nano inventory
  GNU nano 5.6.1                                  inventory
[myself]
workstation.lab.example.co
[intranetweb]
servera.lab.example.com
[internetweb]
serverb.lab.example.com
[web:children]
intranetweb
internetwe
```

Now let's run an example playbook:

```
[student@workstation playbook-manage]$ cat /home/student/playbook-manage/ping-myself.yml
---
- name: Validate inventory hosts
  hosts: myself
  gather_facts: no

  tasks:

    - name: Ping myself
      ansible.builtin.ping:
```

```
[student@workstation playbook-manage]$ ansible-navigator run ping-myself.yml -m
stdout

PLAY [Validate inventory hosts] ************************************************

TASK [Ping myself] *************************************************************
ok: [workstation.lab.example.com]

PLAY RECAP *********************************************************************
workstation.lab.example.com : ok=1    changed=0    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0
```

Run the other playbooks

```
[student@workstation playbook-manage]$ ls
ansible.cfg            inventory             ping-intranetweb.yml
ansible-navigator.log  ping-all.yml          ping-myself.yml
ansible-navigator.yml  ping-internetweb.yml  ping-web.yml
[student@workstation playbook-manage]$ ansible-navigator run -m stdout p*.yml
```

```
PLAY RECAP *********************************************************************
servera.lab.example.com    : ok=3    changed=0    unreachable=0    failed=0
kipped=0    rescued=0    ignored=0
serverb.lab.example.com    : ok=3    changed=0    unreachable=0    failed=0
kipped=0    rescued=0    ignored=0
workstation.lab.example.com : ok=2    changed=0    unreachable=0    failed=0
skipped=0    rescued=0    ignored=0
```

➔

Now lets retry but with the following connection instructions

```
 GNU nano 5.6.1      /home/student/playbook-manage/ansible.cfg
[default]
inventory = ./inventory
remote_user = student


[privilege_escalation]

become = true

become_method = sudo

become_user = root

become_ask_pass = true
```

- `remote_user` answers the question: which user to use to connect to remote host ? (root is dflt)
- `become` answers the question: should I change the user after connecting with remote user?
- `become_method` answers the question: how to change the user?
- `become_user` answers the question: which user to switch to?
- `become_ask_pass` answers the question is the remote user required to enter a password to switch to the new user?

```
[student@workstation playbook-manage]$ ansible-navigator run -m stdout ping-intr
anetweb.yml
BECOME password:
```

➔which justifies the password prompt