



Java SE 8 for the Really Impatient



Cay S. Horstmann

About This eBook

ePUB is an open, industry-standard format for eBooks. However, support of ePUB and its many features varies across reading devices and applications. Use your device or app settings to customize the presentation to your liking. Settings that you can customize often include font, font size, single or double column, landscape or portrait mode, and figures that you can click or tap to enlarge. For additional information about the settings and features on your reading device or app, visit the device manufacturer's Web site.

Many titles include programming code or configuration examples. To optimize the presentation of these elements, view the eBook in single-column, landscape mode and adjust the font size to the smallest setting. In addition to presenting code and configurations in the reflowable text format, we have included images of the code that mimic the presentation found in the print book; therefore, where the reflowable format may compromise the presentation of the code listing, you will see a "Click here to view code image" link. Click the link to view the print-fidelity code image. To return to the previous page viewed, click the Back button on your device or app.

Java SE 8 for the Really Impatient

Cay S. Horstmann

 Addison-Wesley

Upper Saddle River, NJ • Boston • Indianapolis • San Francisco
New York • Toronto • Montreal • London • Munich • Paris • Madrid
Capetown • Sydney • Tokyo • Singapore • Mexico City

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and the publisher was aware of a trademark claim, the designations have been printed with initial capital letters or in all capitals.

The author and publisher have taken care in the preparation of this book, but make no expressed or implied warranty of any kind and assume no responsibility for errors or omissions. No liability is assumed for incidental or consequential damages in connection with or arising out of the use of the information or programs contained herein.

For information about buying this title in bulk quantities, or for special sales opportunities (which may include electronic versions; custom cover designs; and content particular to your business, training goals, marketing focus, or branding interests), please contact our corporate sales department at corpsales@pearsoned.com or (800) 382-3419.

For government sales inquiries, please contact governmentsales@pearsoned.com.

For questions about sales outside the United States, please contact international@pearsoned.com.

Visit us on the Web: informit.com/aw

Cataloging-in-Publication Data is on file with the Library of Congress.

Copyright © 2014 Pearson Education, Inc.

All rights reserved. Printed in the United States of America. This publication is protected by copyright, and permission must be obtained from the publisher prior to any prohibited reproduction, storage in a retrieval system, or transmission in any form or by any means, electronic, mechanical, photocopying, recording, or likewise. To obtain permission to use material from this work, please submit a written request to Pearson Education, Inc., Permissions Department, One Lake Street, Upper Saddle River, New Jersey 07458, or you may fax your request to (201) 236-3290.

ISBN-13: 978-0-321-92776-7

ISBN-10: 0-321-92776-1

Text printed in the United States on recycled paper at RR Donnelley in Crawfordsville, Indiana.
First printing, January 2014

To Greg Doench, my editor for two decades, whose patience, kindness, and good judgment I greatly admire

Contents

[Preface](#)

[About the Author](#)

[1 LAMBDA EXPRESSIONS](#)

[1.1 Why Lambdas?](#)

[1.2 The Syntax of Lambda Expressions](#)

[1.3 Functional Interfaces](#)

[1.4 Method References](#)

[1.5 Constructor References](#)

[1.6 Variable Scope](#)

[1.7 Default Methods](#)

[1.8 Static Methods in Interfaces](#)

[Exercises](#)

[2 THE STREAM API](#)

[2.1 From Iteration to Stream Operations](#)

[2.2 Stream Creation](#)

[2.3 The `filter`, `map`, and `flatMap` Methods](#)

[2.4 Extracting Substreams and Combining Streams](#)

[2.5 Stateful Transformations](#)

[2.6 Simple Reductions](#)

[2.7 The Optional Type](#)

[2.7.1 Working with Optional Values](#)

[2.7.2 Creating Optional Values](#)

[2.7.3 Composing Optional Value Functions with `flatMap`](#)

[2.8 Reduction Operations](#)

[2.9 Collecting Results](#)

[2.10 Collecting into Maps](#)

[2.11 Grouping and Partitioning](#)

[2.12 Primitive Type Streams](#)

[2.13 Parallel Streams](#)

[2.14 Functional Interfaces](#)

[Exercises](#)

[3 PROGRAMMING WITH LAMBDAS](#)

[3.1 Deferred Execution](#)
[3.2 Parameters of Lambda Expressions](#)
[3.3 Choosing a Functional Interface](#)
[3.4 Returning Functions](#)
[3.5 Composition](#)
[3.6 Laziness](#)
[3.7 Parallelizing Operations](#)
[3.8 Dealing with Exceptions](#)
[3.9 Lambdas and Generics](#)
[3.10 Monadic Operations](#)
[Exercises](#)

[**4 JAVAFX**](#)

[4.1 A Brief History of Java GUI Programming](#)
[4.2 Hello, JavaFX!](#)
[4.3 Event Handling](#)
[4.4 JavaFX Properties](#)
[4.5 Bindings](#)
[4.6 Layout](#)
[4.7 FXML](#)
[4.8 CSS](#)
[4.9 Animations and Special Effects](#)
[4.10 Fancy Controls](#)
[Exercises](#)

[**5 THE NEW DATE AND TIME API**](#)

[5.1 The Time Line](#)
[5.2 Local Dates](#)
[5.3 Date Adjusters](#)
[5.4 Local Time](#)
[5.5 Zoned Time](#)
[5.6 Formatting and Parsing](#)
[5.7 Interoperating with Legacy Code](#)
[Exercises](#)

[**6 CONCURRENCY ENHANCEMENTS**](#)

[6.1 Atomic Values](#)
[6.2 ConcurrentHashMap Improvements](#)

[6.2.1 Updating Values](#)
[6.2.2 Bulk Operations](#)
[6.2.3 Set Views](#)
[6.3 Parallel Array Operations](#)
[6.4 Completable Futures](#)

[6.4.1 Futures](#)
[6.4.2 Composing Futures](#)
[6.4.3 The Composition Pipeline](#)
[6.4.4 Composing Asynchronous Operations](#)

[Exercises](#)

[7 THE NASHORN JAVASCRIPT ENGINE](#)

[7.1 Running Nashorn from the Command Line](#)

[7.2 Running Nashorn from Java](#)

[7.3 Invoking Methods](#)

[7.4 Constructing Objects](#)

[7.5 Strings](#)

[7.6 Numbers](#)

[7.7 Working with Arrays](#)

[7.8 Lists and Maps](#)

[7.9 Lambdas](#)

[7.10 Extending Java Classes and Implementing Java Interfaces](#)

[7.11 Exceptions](#)

[7.12 Shell Scripting](#)

[7.12.1 Executing Shell Commands](#)

[7.12.2 String Interpolation](#)

[7.12.3 Script Inputs](#)

[7.13 Nashorn and JavaFX](#)

[Exercises](#)

[8 MISCELLANEOUS GOODIES](#)

[8.1 Strings](#)

[8.2 Number Classes](#)

[8.3 New Mathematical Functions](#)

[8.4 Collections](#)

[8.4.1 Methods Added to Collection Classes](#)

[8.4.2 Comparators](#)

[8.4.3 The `Collections` Class](#)

[8.5 Working with Files](#)
[8.5.1 Streams of Lines](#)
[8.5.2 Streams of Directory Entries](#)
[8.5.3 Base64 Encoding](#)
[8.6 Annotations](#)
[8.6.1 Repeated Annotations](#)
[8.6.2 Type Use Annotations](#)
[8.6.3 Method Parameter Reflection](#)
[8.7 Miscellaneous Minor Changes](#)
[8.7.1 Null Checks](#)
[8.7.2 Lazy Messages](#)
[8.7.3 Regular Expressions](#)
[8.7.4 Locales](#)
[8.7.5 JDBC](#)
[Exercises](#)

[**9 JAVA 7 FEATURES THAT YOU MAY HAVE MISSED**](#)

[9.1 Exception Handling Changes](#)
[9.1.1 The try-with-resources Statement](#)
[9.1.2 Suppressed Exceptions](#)
[9.1.3 Catching Multiple Exceptions](#)
[9.1.4 Easier Exception Handling for Reflective Methods](#)
[9.2 Working with Files](#)
[9.2.1 Paths](#)
[9.2.2 Reading and Writing Files](#)
[9.2.3 Creating Files and Directories](#)
[9.2.4 Copying, Moving, and Deleting Files](#)
[9.3 Implementing the equals, hashCode, and compareTo Methods](#)
[9.3.1 Null-safe Equality Testing](#)
[9.3.2 Computing Hash Codes](#)
[9.3.3 Comparing Numeric Types](#)
[9.4 Security Requirements](#)
[9.5 Miscellaneous Changes](#)
[9.5.1 Converting Strings to Numbers](#)
[9.5.2 The Global Logger](#)
[9.5.3 Null Checks](#)
[9.5.4 ProcessBuilder](#)

[9.5.5 URLClassLoader](#)

[9.5.6 BitSet](#)

[Exercises](#)

[Index](#)

Preface

This book gives a concise introduction to the many new features of Java 8 (and a few features of Java 7 that haven't received much attention) for programmers who are already familiar with Java.

This book is written in the “impatient” style that I first tried out in a book called *Scala for the Impatient*. In that book, I wanted to quickly cut to the chase without lecturing the reader about the superiority of one paradigm over another. I presented information in small chunks organized to help you quickly retrieve it when needed. The approach was a big success in the Scala community, and I am employing it again in this book.

With Java 8, the Java programming language and library receive a major refresh. Lambda expressions make it possible to write “snippets of computations” in a concise way, so that you can pass them to other code. The recipient can choose to execute your computation when appropriate and as often as appropriate. This has a profound impact on building libraries.

In particular, working with collections has completely changed. Instead of specifying how to compute a result (“traverse from the beginning to the end, and if an element matches a condition, compute a value from it, and add that value to a sum”), you specify what you want (“give me the sum of all elements that match a condition”). The library is then able to reorder the computation—for example, to take advantage of parallelism. Or, if you just want to have the first hundred matches, it can stop the computation without you having to maintain a counter.

The brand-new *stream* API of Java 8 puts this idea to work. In the first chapter, you learn all about the syntax of lambda expressions, and [Chapter 2](#) gives a complete overview of streams. In [Chapter 3](#), I provide you with tips on how to effectively design your own libraries with lambdas.

With Java 8, developers of client-side applications need to transition to the JavaFX API since Swing is now in “maintenance mode.” [Chapter 4](#) gives a quick introduction to JavaFX for a programmer who needs to put together a graphical program—when a picture speaks louder than 1,000 strings.

Having waited for far too many years, programmers are finally able to use a well-designed date/time library. [Chapter 5](#) covers the `java.time` API in detail.

Each version of Java brings enhancements in the concurrency API, and Java 8 is no exception. In [Chapter 6](#), you learn about improvements in atomic counters, concurrent hash maps, parallel array operations, and composable futures.

Java 8 bundles Nashorn, a high-quality JavaScript implementation. In [Chapter 7](#), you will see how to execute JavaScript on the Java Virtual Machine, and how to interoperate with Java code.

[Chapter 8](#) collects miscellaneous smaller, but nevertheless useful, features of Java 8. [Chapter 9](#) does the same for Java 7, focusing on improved exception handling, the “new I/O” enhancements for working with files and directories, and other library enhancements that you may have missed.

My thanks go, as always, to my editor Greg Doench, who had the idea of a short book that brings experienced programmers up to speed with Java 8. Dmitry Kirsanov and Alina Kirsanova once again turned an XHTML manuscript into an attractive book with amazing speed and attention to detail. I am grateful to the reviewers who spotted many embarrassing errors and gave excellent suggestions for improvement. They are: Gail Anderson, Paul Anderson, James Denvir, Trisha Gee, Brian Goet

(special thanks for the very thorough review), Marty Hall, Angelika Langer, Mark Lawrence, Stuar Marks, Attila Szegedi, and Jim Weaver.

I hope that you enjoy reading this concise introduction to the new features of Java 8, and that it will make you a more successful Java programmer. If you find errors or have suggestions for improvement, please visit <http://horstmann.com/java8> and leave a comment. On that page, you will also find a link to an archive file containing all code examples from the book.

Cay Horstmann

San Francisco, 2013

About the Author

Cay S. Horstmann is the author of *Scala for the Impatient* (Addison-Wesley, 2012), is principal author of *Core Java™, Volumes I and II, Ninth Edition* (Prentice Hall, 2013), and has written a dozen other books for professional programmers and computer science students. He is a professor of computer science at San Jose State University and is a Java Champion.

Chapter 1. Lambda Expressions

Topics in This Chapter

- [1.1 Why Lambdas?](#)
- [1.2 The Syntax of Lambda Expressions](#)
- [1.3 Functional Interfaces](#)
- [1.4 Method References](#)
- [1.5 Constructor References](#)
- [1.6 Variable Scope](#)
- [1.7 Default Methods](#)
- [1.8 Static Methods in Interfaces](#)
- [Exercises](#)

Java was designed in the 1990s as an object-oriented programming language, when object-oriented programming was the principal paradigm for software development. Long before there was object-oriented programming, there were functional programming languages such as Lisp and Scheme, but their benefits were not much appreciated outside academic circles. Recently, functional programming has risen in importance because it is well suited for concurrent and event-driven (or “reactive”) programming. That doesn’t mean that objects are bad. Instead, the winning strategy is to blend object-oriented and functional programming. This makes sense even if you are not interested in concurrency. For example, collection libraries can be given powerful APIs if the language has a convenient syntax for function expressions.

The principal enhancement in Java 8 is the addition of functional programming constructs to its object-oriented roots. In this chapter, you will learn the basic syntax. The next chapter shows you how to put that syntax to use with Java collections, and in [Chapter 3](#) you will learn how to build your own functional libraries.

The key points of this chapter are:

- A lambda expression is a block of code with parameters.
- Use a lambda expression whenever you want a block of code executed at a later point in time.
- Lambda expressions can be converted to functional interfaces.
- Lambda expressions can access effectively final variables from the enclosing scope.
- Method and constructor references refer to methods or constructors without invoking them.
- You can now add default and static methods to interfaces that provide concrete implementations.
- You must resolve any conflicts between default methods from multiple interfaces.

1.1. Why Lambdas?

A “lambda expression” is a block of code that you can pass around so it can be executed later, once or multiple times. Before getting into the syntax (or even the curious name), let’s step back and

see where you have used similar code blocks in Java all along.

When you want to do work in a separate thread, you put the work into the `run` method of a `Runnable`, like this:

[Click here to view code image](#)

```
class Worker implements Runnable {  
    public void run() {  
        for (int i = 0; i < 1000; i++)  
            doWork();  
    }  
    ...  
}
```

Then, when you want to execute this code, you construct an instance of the `Worker` class. You can then submit the instance to a thread pool, or, to keep it simple, start a new thread:

```
Worker w = new Worker();  
new Thread(w).start();
```

The key point is that the `run` method contains code that you want to execute in a separate thread.

Or consider sorting with a custom comparator. If you want to sort strings by length instead of the default dictionary order, you can pass a `Comparator` object to the `sort` method:

[Click here to view code image](#)

```
class LengthComparator implements Comparator<String> {  
    public int compare(String first, String second) {  
        return Integer.compare(first.length(), second.length());  
    }  
}
```

[Click here to view code image](#)

```
Arrays.sort(strings, new LengthComparator());
```

The `sort` method keeps calling the `compare` method, rearranging the elements if they are out of order, until the array is sorted. You give the `sort` method a snippet of code needed to compare elements, and that code is integrated into the rest of the sorting logic, which you'd probably not care to reimplement.



NOTE

The call `Integer.compare(x, y)` returns zero if `x` and `y` are equal, a negative number if `x < y`, and a positive number if `x > y`. This static method has been added to Java 7 (see [Chapter 9](#)).

Note that you shouldn't compute `x - y` to compare `x` and `y` since that computation can overflow for large operands of opposite sign.

As another example for deferred execution, consider a button callback. You put the callback action into a method of a class implementing the listener interface, construct an instance, and register the instance with the button. That happens so often that many programmers use the “anonymous instance of anonymous class” syntax:

[Click here to view code image](#)

```
button.setOnAction(new EventHandler<ActionEvent>() {  
    public void handle(ActionEvent event) {
```

```
        System.out.println("Thanks for clicking!");
    }
});
```

What matters is the code inside the `handle` method. That code is executed whenever the button is clicked.



NOTE

Since Java 8 positions JavaFX as the successor to the Swing GUI toolkit, I use JavaFX in these examples. (See [Chapter 4](#) for more information on JavaFX.) Of course, the details don't matter. In every user interface toolkit, be it Swing, JavaFX, or Android, you give a button some code that you want to run when the button is clicked.

In all three examples, you saw the same approach. A block of code was passed to someone—a thread pool, a `sort` method, or a button. The code was called at some later time.

Up to now, giving someone a block of code hasn't been easy in Java. You couldn't just pass code blocks around. Java is an object-oriented language, so you had to construct an object belonging to a class that has a method with the desired code.

In other languages, it is possible to work with blocks of code directly. The Java designers have resisted adding this feature for a long time. After all, a great strength of Java is its simplicity and consistency. A language can become an unmaintainable mess if it includes every feature that yields marginally more concise code. However, in those other languages it isn't just easier to spawn a thread or to register a button click handler; large swaths of their APIs are simpler, more consistent, and more powerful. In Java, one could have written similar APIs that take objects of classes implementing a particular function, but such APIs would be unpleasant to use.

For some time now, the question was not whether to augment Java for functional programming, but how to do it. It took several years of experimentation before a design emerged that is a good fit for Java. In the next section, you will see how you can work with blocks of code in Java 8.

1.2. The Syntax of Lambda Expressions

Consider again the sorting example from the preceding section. We pass code that checks whether one string is shorter than another. We compute

[Click here to view code image](#)

```
Integer.compare(first.length(), second.length())
```

What are `first` and `second`? They are both strings. Java is a strongly typed language, and we must specify that as well:

[Click here to view code image](#)

```
(String first, String second)
-> Integer.compare(first.length(), second.length())
```

You have just seen your first *lambda expression*. Such an expression is simply a block of code, together with the specification of any variables that must be passed to the code.

Why the name? Many years ago, before there were any computers, the logician Alonzo Church

wanted to formalize what it means for a mathematical function to be effectively computable. (Curiously, there are functions that are known to exist, but nobody knows how to compute their values.) He used the Greek letter lambda (λ) to mark parameters. Had he known about the Java API he would have written

[Click here to view code image](#)

```
 $\lambda$ first. $\lambda$ second.Integer.compare(first.length(), second.length())
```



NOTE

Why the letter λ ? Did Church run out of other letters of the alphabet? Actually, the venerable *Principia Mathematica* used the \wedge accent to denote free variables, which inspired Church to use an uppercase lambda Λ for parameters. But in the end, he switched to the lowercase version. Ever since, an expression with parameter variables has been called a lambda expression.

You have just seen one form of lambda expressions in Java: parameters, the \rightarrow arrow, and an expression. If the code carries out a computation that doesn't fit in a single expression, write it exactly like you would have written a method: enclosed in {} and with explicit `return` statements. For example,

[Click here to view code image](#)

```
(String first, String second) -> {
    if (first.length() < second.length()) return -1;
    else if (first.length() > second.length()) return 1;
    else return 0;
}
```

If a lambda expression has no parameters, you still supply empty parentheses, just as with a parameterless method:

[Click here to view code image](#)

```
() -> { for (int i = 0; i < 1000; i++) doWork(); }
```

If the parameter types of a lambda expression can be inferred, you can omit them. For example,

[Click here to view code image](#)

```
Comparator<String> comp
= (first, second) // Same as (String first, String second)
-> Integer.compare(first.length(), second.length());
```

Here, the compiler can deduce that `first` and `second` must be strings because the lambda expression is assigned to a string comparator. (We will have a closer look at this assignment in the next section.)

If a method has a single parameter with inferred type, you can even omit the parentheses:

[Click here to view code image](#)

```
EventHandler<ActionEvent> listener = event ->
    System.out.println("Thanks for clicking!");
// Instead of (event) -> OR (ActionEvent event) ->
```



NOTE

You can add annotations or the `final` modifier to lambda parameters in the same way as for method parameters:

```
(final String name) -> ...
(@NonNull String name) -> ...
```

You never specify the result type of a lambda expression. It is always inferred from context. For example, the expression

[Click here to view code image](#)

```
(String first, String second) -> Integer.compare(first.length(), second.length())
```

can be used in a context where a result of type `int` is expected.



NOTE

It is illegal for a lambda expression to return a value in some branches but not in others. For example, `(int x) -> { if (x >= 0) return 1; }` is invalid.

1.3. Functional Interfaces

As we discussed, there are many existing interfaces in Java that encapsulate blocks of code, such as `Runnable` or `Comparator`. Lambdas are backwards compatible with these interfaces.

You can supply a lambda expression whenever an object of an interface with a single abstract method is expected. Such an interface is called a *functional interface*.



NOTE

You may wonder why a functional interface must have a single *abstract* method. Aren't all methods in an interface abstract? Actually, it has always been possible for an interface to redeclare methods from the `Object` class such as `toString` or `clone`, and these declarations do not make the methods abstract. (Some interfaces in the Java API redeclare `Object` methods in order to attach javadoc comments. Check out the `Comparator` API for an example.) More importantly, as you will see in [Section 1.7, “Default Methods,”](#) on page [14](#), in Java 8, interfaces can declare nonabstract methods.

To demonstrate the conversion to a functional interface, consider the `Arrays.sort` method. Its second parameter requires an instance of `Comparator`, an interface with a single method. Simply supply a lambda:

[Click here to view code image](#)

```
Arrays.sort(words,
(first, second) -> Integer.compare(first.length(), second.length()));
```

Behind the scenes, the `Arrays.sort` method receives an object of some class that implements `Comparator<String>`. Invoking the `compare` method on that object executes the body of the lambda

expression. The management of these objects and classes is completely implementation dependent, and it can be much more efficient than using traditional inner classes. It is best to think of a lambda expression as a function, not an object, and to accept that it can be passed to a functional interface.

This conversion to interfaces is what makes lambda expressions so compelling. The syntax is short and simple. Here is another example:

[Click here to view code image](#)

```
button.setOnAction(event ->
    System.out.println("Thanks for clicking!"));
```

That's a lot easier to read than the alternative with inner classes.

In fact, conversion to a functional interface is the *only* thing that you can do with a lambda expression in Java. In other programming languages that support function literals, you can declare function types such as `(String, String) -> int`, declare variables of those types, and use the variables to save function expressions. However, the Java designers decided to stick with the familiar concept of interfaces instead of adding function types to the language.



NOTE

You can't even assign a lambda expression to a variable of type `Object`—`Object` is not a functional interface.

The Java API defines a number of very generic functional interfaces in the `java.util.function` package. (We will have a closer look at these interfaces in [Chapters 2 and 3](#).) One of the interfaces, `BiFunction<T, U, R>`, describes functions with parameter types `T` and `U` and return type `R`. You can save our string comparison lambda in a variable of that type:

[Click here to view code image](#)

```
BiFunction<String, String, Integer> comp
    = (first, second) -> Integer.compare(first.length(), second.length());
```

However, that does not help you with sorting. There is no `Arrays.sort` method that wants a `BiFunction`. If you have used a functional programming language before, you may find this curious. But for Java programmers, it's pretty natural. An interface such as `Comparator` has a specific purpose, not just a method with given parameter and return types. Java 8 retains this flavor. When you want to do something with lambda expressions, you still want to keep the purpose of the expression in mind, and have a specific functional interface for it.

The interfaces in `java.util.function` are used in several Java 8 APIs, and you will likely see them elsewhere in the future. But keep in mind that you can equally well convert a lambda expression into a functional interface that is a part of whatever API you use today.



NOTE

You can tag any functional interface with the `@FunctionalInterface` annotation. This has two advantages. The compiler checks that the annotated entity is an interface with a single abstract method. And the javadoc page includes a statement that your interface is a functional interface.

It is not required to use the annotation. Any interface with a single abstract method is, by definition, a functional interface. But using the `@FunctionalInterface` annotation is a good idea.

Finally, note that checked exceptions matter when a lambda is converted to an instance of a functional interface. If the body of a lambda expression may throw a checked exception, that exception needs to be declared in the abstract method of the target interface. For example, the following would be an error:

[Click here to view code image](#)

```
Runnable sleeper = () -> { System.out.println("Zzz"); Thread.sleep(1000); };
// Error: Thread.sleep can throw a checked InterruptedException
```

Since the `Runnable.run` cannot throw any exception, this assignment is illegal. To fix the error, you have two choices. You can catch the exception in the body of the lambda expression. Or assign the lambda to an interface whose single abstract method can throw the exception. For example, the `call` method of the `Callable` interface can throw any exception. Therefore, you can assign the lambda to a `Callable<Void>` (if you add a statement `return null`).

1.4. Method References

Sometimes, there is already a method that carries out exactly the action that you'd like to pass on to some other code. For example, suppose you simply want to print the event object whenever a button is clicked. Of course, you could call

[Click here to view code image](#)

```
button.setOnAction(event -> System.out.println(event));
```

It would be nicer if you could just pass the `println` method to the `setOnAction` method. Here is how you do that:

[Click here to view code image](#)

```
button.setOnAction(System.out::println);
```

The expression `System.out::println` is a *method reference* that is equivalent to the lambda expression `x -> System.out.println(x)`.

As another example, suppose you want to sort strings regardless of letter case. You can pass this method expression:

[Click here to view code image](#)

```
Arrays.sort(strings, String::compareToIgnoreCase)
```

As you can see from these examples, the `::` operator separates the method name from the name of an object or class. There are three principal cases:

- *object::instanceMethod*
- *Class::staticMethod*
- *Class::instanceMethod*

In the first two cases, the method reference is equivalent to a lambda expression that supplies the

parameters of the method. As already mentioned, `System.out::println` is equivalent to `x -> System.out.println(x)`. Similarly, `Math::pow` is equivalent to `(x, y) -> Math.pow(x, y)`.

In the third case, the first parameter becomes the target of the method. For example, `String::compareToIgnoreCase` is the same as `(x, y) -> x.compareToIgnoreCase(y)`.



NOTE

When there are multiple overloaded methods with the same name, the compiler will try to find from the context which one you mean. For example, there are two versions of the `Math.max` method, one for integers and one for `double` values. Which one gets picked depends on the method parameters of the functional interface to which `Math::max` is converted. Just like lambda expressions, method references don't live in isolation. They are always turned into instances of functional interfaces.

You can capture the `this` parameter in a method reference. For example, `this::equals` is the same as `x -> this.equals(x)`. It is also valid to use `super`. The method expression

`super::instanceMethod`

uses `this` as the target and invokes the superclass version of the given method. Here is an artificial example that shows the mechanics:

[Click here to view code image](#)

```
class Greeter {  
    public void greet() {  
        System.out.println("Hello, world!");  
    }  
}  
  
class ConcurrentGreeter extends Greeter {  
    public void greet() {  
        Thread t = new Thread(super::greet);  
        t.start();  
    }  
}
```

When the thread starts, its `Runnable` is invoked, and `super::greet` is executed, calling the `greet` method of the superclass.



NOTE

In an inner class, you can capture the `this` reference of an enclosing class as `EnclosingClass.this::method` or `EnclosingClass.super::method`.

1.5. Constructor References

Constructor references are just like method references, except that the name of the method is `new`. For example, `Button::new` is a reference to a `Button` constructor. Which constructor? It depends on the context. Suppose you have a list of strings. Then you can turn it into an array of buttons, by calling the constructor on each of the strings, with the following invocation:

[Click here to view code image](#)

```
List<String> labels = ...;
Stream<Button> stream = labels.stream().map(Button::new);
List<Button> buttons = stream.collect(Collectors.toList());
```

We will discuss the details of the `stream`, `map`, and `collect` methods in [Chapter 2](#). For now, what's important is that the `map` method calls the `Button(String)` constructor for each list element. There are multiple `Button` constructors, but the compiler picks the one with a `String` parameter because it infers from the context that the constructor is called with a `String`.

You can form constructor references with array types. For example, `int[]::new` is a constructor reference with one parameter: the length of the array. It is equivalent to the lambda expression `x -> new int[x]`.

Array constructor references are useful to overcome a limitation of Java. It is not possible to construct an array of a generic type `T`. The expression `new T[n]` is an error since it would be erased to `new Object[n]`. That is a problem for library authors. For example, suppose we want to have an array of buttons. The `Stream` interface has a `toArray` method that returns an `Object` array:

[Click here to view code image](#)

```
Object[] buttons = stream.toArray();
```

But that is unsatisfactory. The user wants an array of buttons, not objects. The stream library solves that problem with constructor references. Pass `Button[]::new` to the `toArray` method:

[Click here to view code image](#)

```
Button[] buttons = stream.toArray(Button[]::new);
```

The `toArray` method invokes this constructor to obtain an array of the correct type. Then it fills and returns the array.

1.6. Variable Scope

Often, you want to be able to access variables from an enclosing method or class in a lambda expression. Consider this example:

[Click here to view code image](#)

```
public static void repeatMessage(String text, int count) {
    Runnable r = () -> {
        for (int i = 0; i < count; i++) {
            System.out.println(text);
            Thread.yield();
        }
    };
    new Thread(r).start();
}
```

Consider a call

```
repeatMessage("Hello", 1000); // Prints Hello 1,000 times in a separate thread
```

Now look at the variables `count` and `text` inside the lambda expression. Note that these variables are *not* defined in the lambda expression. Instead, these are parameter variables of the `repeatMessage` method.

If you think about it, something nonobvious is going on here. The code of the lambda expression

may run long after the call to `repeatMessage` has returned and the parameter variables are gone. How do the `text` and `count` variables stay around?

To understand what is happening, we need to refine our understanding of a lambda expression. A lambda expression has three ingredients:

1. A block of code

2. Parameters

3. Values for the *free* variables, that is, the variables that are not parameters and not defined inside the code

In our example, the lambda expression has two free variables, `text` and `count`. The data structure representing the lambda expression must store the values for these variables, in our case, "Hello" and 1000. We say that these values have been *captured* by the lambda expression. (It's an implementation detail how that is done. For example, one can translate a lambda expression into an object with a single method, so that the values of the free variables are copied into instance variables of that object.)



NOTE

The technical term for a block of code together with the values of the free variables is a *closure*. If someone gloats that their language has closures, rest assured that Java has them as well. In Java, lambda expressions are closures. In fact, inner classes have been closures all along. Java 8 gives us closures with an attractive syntax.

As you have seen, a lambda expression can capture the value of a variable in the enclosing scope. In Java, to ensure that the captured value is well-defined, there is an important restriction. In a lambda expression, you can only reference variables whose value doesn't change. For example, the following is illegal:

[Click here to view code image](#)

```
public static void repeatMessage(String text, int count) {
    Runnable r = () -> {
        while (count > 0) {
            count--; // Error: Can't mutate captured variable
            System.out.println(text);
            Thread.yield();
        }
    };
    new Thread(r).start();
}
```

There is a reason for this restriction. Mutating variables in a lambda expression is not threadsafe. Consider a sequence of concurrent tasks, each updating a shared counter.

[Click here to view code image](#)

```
int matches = 0;
for (Path p : files)
    new Thread(() -> { if (p has some property) matches++; }).start();
    // Illegal to mutate matches
```

If this code were legal, it would be very, very bad. The increment `matches++` is not atomic, and

there is no way of knowing what would happen if multiple threads execute that increment concurrently.



NOTE

Inner classes can also capture values from an enclosing scope. Before Java 8, inner classes were only allowed to access `final` local variables. This rule has now been relaxed to match that for lambda expressions. An inner class can access any effectively final local variable—that is, any variable whose value does not change.

Don't count on the compiler to catch all concurrent access errors. The prohibition against mutation only holds for local variables. If `matches` is an instance or static variable of an enclosing class, then no error is reported, even though the result is just as undefined.

Also, it's perfectly legal to mutate a shared object, even though it is unsound. For example,

[Click here to view code image](#)

```
List<Path> matches = new ArrayList<>();
for (Path p : files)
    new Thread(() -> { if (p has some property) matches.add(p); }).start();
// Legal to mutate matches, but unsafe
```

Note that the variable `matches` is *effectively final*. (An effectively final variable is a variable that is never assigned a new value after it has been initialized.) In our case, `matches` always refers to the same `ArrayList` object. However, the object is mutated, and that is not threadsafe. If multiple threads call `add`, the result is unpredictable.

There are safe mechanisms for counting and collecting values concurrently. In [Chapter 2](#), you will see how to use streams to collect values with certain properties. In other situations, you may want to use threadsafe counters and collections. See [Chapter 6](#) for more information on this important topic.



NOTE

As with inner classes, there is an escape hatch that lets a lambda expression update a counter in an enclosing local scope. Use an array of length 1, like this:

[Click here to view code image](#)

```
int[] counter = new int[1];
button.setOnAction(event -> counter[0]++);
```

Of course, code like this is not threadsafe. For a button callback, that doesn't matter, but in general, you should think twice before using this trick. You will see how to implement a threadsafe shared counter in [Chapter 6](#).

The body of a lambda expression has *the same scope as a nested block*. The same rules for name conflicts and shadowing apply. It is illegal to declare a parameter or a local variable in the lambda that has the same name as a local variable.

[Click here to view code image](#)

```
Path first = Paths.get("/usr/bin");
Comparator<String> comp =
    (first, second) -> Integer.compare(first.length(), second.length());
// Error: Variable first already defined
```

Inside a method, you can't have two local variables with the same name, and therefore, you can't introduce such variables in a lambda expression either.

When you use the `this` keyword in a lambda expression, you refer to the `this` parameter of the method that creates the lambda. For example, consider

[Click here to view code image](#)

```
public class Application() {
    public void doWork() {
        Runnable runner = () -> { ...; System.out.println(this.toString()); ... };
        ...
    }
}
```

The expression `this.toString()` calls the `toString` method of the `Application` object, *not* the `Runnable` instance. There is nothing special about the use of `this` in a lambda expression. The scope of the lambda expression is nested inside the `doWork` method, and `this` has the same meaning anywhere in that method.

1.7. Default Methods

Many programming languages integrate function expressions with their collections library. This often leads to code that is shorter and easier to understand than the loop equivalent. For example, consider a loop

[Click here to view code image](#)

```
for (int i = 0; i < list.size(); i++)
    System.out.println(list.get(i));
```

There is a better way. The library designers can supply a `forEach` method that applies a function to each element. Then you can simply call

[Click here to view code image](#)

```
list.forEach(System.out::println);
```

That's fine if the collections library has been designed from the ground up. But the Java collections library has been designed many years ago, and there is a problem. If the `Collection` interface gets new methods, such as `forEach`, then every program that defines its own class implementing `Collection` will break until it, too, implements that method. That is simply unacceptable in Java.

The Java designers decided to solve this problem once and for all by allowing interface methods with concrete implementations (called *default methods*). Those methods can be safely added to existing interfaces. In this section, we'll look into default methods in detail.



NOTE

In Java 8, the `forEach` method has been added to the `Iterable` interface, a superinterface of `Collection`, using the mechanism that I will describe in this section.

Consider this interface:

[Click here to view code image](#)

```
interface Person {  
    long getId();  
    default String getName() { return "John Q. Public"; }  
}
```

The interface has two methods: `getId`, which is an abstract method, and the default method `getName`. A concrete class that implements the `Person` interface must, of course, provide an implementation of `getId`, but it can choose to keep the implementation of `getName` or to override it.

Default methods put an end to the classic pattern of providing an interface and an abstract class that implements most or all of its methods, such as `Collection/AbstractCollection` or `WindowListener/WindowAdapter`. Now you can just implement the methods in the interface.

What happens if the exact same method is defined as a default method in one interface and then again as a method of a superclass or another interface? Languages such as Scala and C++ have complex rules for resolving such ambiguities. Fortunately, the rules in Java are much simpler. Here they are:

1. Superclasses win. If a superclass provides a concrete method, default methods with the same name and parameter types are simply ignored.
2. Interfaces clash. If a superinterface provides a default method, and another interface supplies a method with the same name and parameter types (default or not), then you must resolve the conflict by overriding that method.

Let's look at the second rule. Consider another interface with a `getName` method:

[Click here to view code image](#)

```
interface Named {  
    default String getName() { return getClass().getName() + "_" + hashCode(); }  
}
```

What happens if you form a class that implements both of them?

[Click here to view code image](#)

```
class Student implements Person, Named {  
    ...  
}
```

The class inherits two inconsistent `getName` methods provided by the `Person` and `Named` interfaces. Rather than choosing one over the other, the Java compiler reports an error and leaves it up to the programmer to resolve the ambiguity. Simply provide a `getName` method in the `Student` class. In that method, you can choose one of the two conflicting methods, like this:

[Click here to view code image](#)

```
class Student implements Person, Named {  
    public String getName() { return Person.super.getName(); }  
    ...  
}
```

Now assume that the `Named` interface does not provide a default implementation for `getName`:

```
interface Named {  
    String getName();  
}
```

Can the `student` class inherit the default method from the `Person` interface? This might be reasonable, but the Java designers decided in favor of uniformity. It doesn't matter how two interfaces conflict. If at least one interface provides an implementation, the compiler reports an error, and the programmer must resolve the ambiguity.



NOTE

Of course, if neither interface provides a default for a shared method, then we are in the pre-Java 8 situation, and there is no conflict. An implementing class has two choices: implement the method, or leave it unimplemented. In the latter case, the class is itself abstract.

We just discussed name clashes between two interfaces. Now consider a class that extends a superclass and implements an interface, inheriting the same method from both. For example, suppose that `Person` is a class and `Student` is defined as

[Click here to view code image](#)

```
class Student extends Person implements Named { ... }
```

In that case, only the superclass method matters, and any default method from the interface is simply ignored. In our example, `Student` inherits the `getName` method from `Person`, and it doesn't make any difference whether the `Named` interface provides a default for `getName` or not. This is the "class wins" rule.

The "class wins" rule ensures compatibility with Java 7. If you add default methods to an interface, it has no effect on code that worked before there were default methods.



CAUTION

You can never make a default method that redefines one of the methods in the `Object` class. For example, you can't define a default method for `toString` or `equals`, even though that might be attractive for interfaces such as `List`. As a consequence of the "classes win" rule, such a method could never win against `Object.toString` or `Object.equals`.

1.8. Static Methods in Interfaces

As of Java 8, you are allowed to add static methods to interfaces. There was never a technical reason why this should be outlawed. It simply seemed to be against the spirit of interfaces as abstract specifications.

Up to now, it has been common to place static methods in companion classes. You find pairs of interfaces and utility classes such as `Collection/Collections` or `Path/Paths` in the standard library.

Have a look at the `Paths` class. It only has a couple of factory methods. You can construct a path from a sequence of strings, such as `Paths.get("jdk1.8.0", "jre", "bin")`. In Java 8, one could have added this method to the `Path` interface:

[Click here to view code image](#)

```
public interface Path {  
    public static Path get(String first, String... more) {  
        return FileSystems.getDefault().getPath(first, more);  
    }  
    ...  
}
```

Then the `Paths` class is no longer necessary.

When you look at the `Collections` class, you will find two kinds of methods. A method such as

[Click here to view code image](#)

```
public static void shuffle(List<?> list)
```

would work well as a default method of the `List` interface

```
public default void shuffle()
```

You could then simply call `list.shuffle()` on any list.

For a factory method that doesn't work since you don't have an object on which to invoke the method. That is where static interface methods come in. For example,

[Click here to view code image](#)

```
public static <T> List<T> nCopies(int n, T o)  
    // Constructs a list of n instances of o.
```

could be a static method of the `List` interface. Then you would call `List.nCopies(10, "Fred")` instead of `Collections.nCopies(10, "Fred")` and it would be clear to the reader that the result is a `List`.

It is unlikely that the Java collections library will be refactored in this way, but when you implement your own interfaces, there is no longer a reason to provide a separate companion class for utility methods.

In Java 8, static methods have been added to quite a few interfaces. For example, the `Comparator` interface has a very useful static `comparing` method that accepts a “key extraction” function and yields a comparator that compares the extracted keys. To compare `Person` objects by name, use `Comparator.comparing(Person::name)`.

In this chapter, we have compared strings by length with the lambda expression `(first, second) -> Integer.compare(first.length(), second.length())`. But with the static `compare` method, we can do much better and simply use `Comparator.compare(String::length)`. This is a fitting way of closing this chapter because it demonstrates the power of working with functions. The `compare` method turns a function (the key extractor) into a more complex function (the key-based comparator). We will examine such “higher order functions” in more detail in [Chapter 3](#).

Exercises

1. Is the comparator code in the `Arrays.sort` method called in the same thread as the call to `sort` or a different thread?
2. Using the `listFiles(FileFilter)` and `isDirectory` methods of the `java.io.File` class, write a method that returns all subdirectories of a given directory. Use a lambda expression instead of a `FileFilter` object. Repeat with a method expression.
3. Using the `list(FilenameFilter)` method of the `java.io.File` class, write a method that

returns all files in a given directory with a given extension. Use a lambda expression, not a `FilenameFilter`. Which variables from the enclosing scope does it capture?

4. Given an array of `File` objects, sort it so that the directories come before the files, and within each group, elements are sorted by path name. Use a lambda expression, not a `Comparator`.

5. Take a file from one of your projects that contains a number of `ActionListener`, `Runnable`, or the like. Replace them with lambda expressions. How many lines did it save? Was the code easier to read? Were you able to use method references?

6. Didn't you always hate it that you had to deal with checked exceptions in a `Runnable`? Write a method `uncheck` that catches all checked exceptions and turns them into unchecked exceptions. For example,

[Click here to view code image](#)

```
new Thread(uncheck(
    () -> { System.out.println("Zzz"); Thread.sleep(1000); })).start();
// Look, no catch (InterruptedException)!
```

Hint: Define an interface `RunnableEx` whose `run` method may throw any exceptions. Then implement `public static Runnable uncheck(RunnableEx runner)`. Use a lambda expression inside the `uncheck` function.

Why can't you just use `Callable<Void>` instead of `RunnableEx`?

7. Write a static method `andThen` that takes as parameters two `Runnable` instances and returns a `Runnable` that runs the first, then the second. In the `main` method, pass two lambda expressions into a call to `andThen`, and run the returned instance.

8. What happens when a lambda expression captures values in an enhanced `for` loop such as this one?

[Click here to view code image](#)

```
String[] names = { "Peter", "Paul", "Mary" };
List<Runnable> runners = new ArrayList<>();
for (String name : names)
    runners.add(() -> System.out.println(name));
```

Is it legal? Does each lambda expression capture a different value, or do they all get the last value? What happens if you use a traditional loop `for (int i = 0; i < names.length; i++)`?

9. Form a subclass `Collection2` from `Collection` and add a default method `void forEachIf(Consumer<T> action, Predicate<T> filter)` that applies `action` to each element for which `filter` returns `true`. How could you use it?

10. Go through the methods of the `Collections` class. If you were king for a day, into which interface would you place each method? Would it be a default method or a static method?

11. Suppose you have a class that implements two interfaces `I` and `J`, each of which has a method `void f()`. Exactly what happens if `f` is an abstract, default, or static method of `I` and an abstract, default, or static method of `J`? Repeat where a class extends a superclass `S` and implements an interface `I`, each of which has a method `void f()`.

12. In the past, you were told that it's bad form to add methods to an interface because it would break existing code. Now you are told that it's okay to add new methods, provided you also

supply a default implementation. How safe is that? Describe a scenario where the new `stream` method of the `Collection` interface causes legacy code to fail compilation. What about binary compatibility? Will legacy code from a JAR file still run?

Chapter 2. The Stream API

Topics in This Chapter

- [2.1 From Iteration to Stream Operations](#)
- [2.2 Stream Creation](#)
- [2.3 The `filter`, `map`, and `flatMap` Methods](#)
- [2.4 Extracting Substreams and Combining Streams](#)
- [2.5 Stateful Transformations](#)
- [2.6 Simple Reductions](#)
- [2.7 The Optional Type](#)
- [2.8 Reduction Operations](#)
- [2.9 Collecting Results](#)
- [2.10 Collecting into Maps](#)
- [2.11 Grouping and Partitioning](#)
- [2.12 Primitive Type Streams](#)
- [2.13 Parallel Streams](#)
- [2.14 Functional Interfaces](#)
- [Exercises](#)

Streams are the key abstraction in Java 8 for processing collections of values and specifying what you want to have done, leaving the scheduling of operations to the implementation. For example, if you want to compute the average of the values of a certain method, you specify that you want to call the method on each element and get the average of the values. You leave it to the stream library to parallelize the operation, using multiple threads for computing sums and counts of each segment and combining the results.

The key points of this chapter are:

- Iterators imply a specific traversal strategy and prohibit efficient concurrent execution.
- You can create streams from collections, arrays, generators, or iterators.
- Use `filter` to select elements and `map` to transform elements.
- Other operations for transforming streams include `limit`, `distinct`, and `sorted`.
- To obtain a result from a stream, use a reduction operator such as `count`, `max`, `min`, `findFirst`, or `findAny`. Some of these methods return an `Optional` value.
- The `Optional` type is intended as a safe alternative to working with `null` values. To use it safely, take advantage of the `ifPresent` and `orElse` methods.
- You can collect stream results in collections, arrays, strings, or maps.
- The `groupingBy` and `partitioningBy` methods of the `Collectors` class allow you to split the contents of a stream into groups, and to obtain a result for each group.
- There are specialized streams for the primitive types `int`, `long`, and `double`.

- When you work with parallel streams, be sure to avoid side effects, and consider giving up ordering constraints.
- You need to be familiar with a small number of functional interfaces in order to use the stream library.

2.1. From Iteration to Stream Operations

When you process a collection, you usually iterate over its elements and do some work with each of them. For example, suppose we want to count all long words in a book. First, let's put them into a list:

[Click here to view code image](#)

```
String contents = new String(Files.readAllBytes(
    Paths.get("alice.txt")), StandardCharsets.UTF_8); // Read file into string
List<String> words = Arrays.asList(contents.split("[\\P{L}]+"));
// Split into words; nonletters are delimiters
```

Now we are ready to iterate:

[Click here to view code image](#)

```
int count = 0;
for (String w : words) {
    if (w.length() > 12) count++;
}
```

What's wrong with it? Nothing really—except that it is hard to parallelize the code. That's where the Java 8 bulk operations come in. In Java 8, the same operation looks like this:

[Click here to view code image](#)

```
long count = words.stream().filter(w -> w.length() > 12).count();
```

The `stream` method yields a *stream* for the `words` list. The `filter` method returns another stream that contains only the words of length greater than twelve. The `count` method reduces that stream to a result.

A stream seems superficially similar to a collection, allowing you to transform and retrieve data. But there are significant differences:

1. A stream does not store its elements. They may be stored in an underlying collection or generated on demand.
2. Stream operations don't mutate their source. Instead, they return new streams that hold the result.
3. Stream operations are *lazy* when possible. This means they are not executed until their result is needed. For example, if you only ask for the first five long words instead of counting them all, then the `filter` method will stop filtering after the fifth match. As a consequence, you can even have infinite streams!

In this chapter, you will learn all about streams. Many people find stream expressions easier to read than the loop equivalents. Moreover, they can be easily parallelized. Here is how you count long words in parallel:

[Click here to view code image](#)

```
long count = words.parallelStream().filter(w -> w.length() > 12).count();
```

Simply changing `stream` into `parallelStream` allows the stream library to do the filtering and counting in parallel.

Streams follow the “what, not how” principle. In our stream example, we describe what needs to be done: get the long words and count them. We don’t specify in which order, or in which thread, this should happen. In contrast, the loop at the beginning of this section specifies exactly how the computation should work, and thereby forgoes any chances of optimization.

When you work with streams, you set up a pipeline of operations in three stages.

1. You create a stream.

2. You specify *intermediate operations* for transforming the initial stream into others, in one or more steps.

3. You apply a *terminal operation* to produce a result. This operation forces the execution of the lazy operations that precede it. Afterwards, the stream can no longer be used.

In our example, the stream was created with the `stream` or `parallelStream` method. The `filter` method transformed it, and `count` was the terminal operation.



NOTE

Stream operations are *not* executed on the elements in the order in which they are invoked on the streams. In our example, nothing happens until `count` is called. When the `count` method asks for the first element, then the `filter` method starts requesting elements, until it finds one that has `length > 12`.

In the next section, you will see how to create a stream. The subsequent three sections deal with stream transformations. They are followed by five sections on terminal operations.

2.2. Stream Creation

You have already seen that you can turn any collection into a stream with the `stream` method that Java 8 added to the `Collection` interface. If you have an array, use the static `Stream.of` method instead.

[Click here to view code image](#)

```
Stream<String> words = Stream.of(contents.split("[\\P{L}]+"));
// split returns a String[] array
```

The `of` method has a varargs parameter, so you can construct a stream from any number of arguments:

[Click here to view code image](#)

```
Stream<String> song = Stream.of("gently", "down", "the", "stream");
```

Use `Arrays.stream(array, from, to)` to make stream from a part of an array.

To make a stream with no elements, use the static `Stream.empty` method:

[Click here to view code image](#)

```
Stream<String> silence = Stream.empty();
// Generic type <String> is inferred; same as Stream.<String>empty()
```

The `Stream` interface has two static methods for making infinite streams. The `generate` method takes a function with no arguments (or, technically, an object of the `Supplier<T>` interface—see [Section 2.14, “Functional Interfaces,”](#) on page [42](#)). Whenever a stream value is needed, that function is called to produce a value. You can get a stream of constant values as

[Click here to view code image](#)

```
Stream<String> echos = Stream.generate(() -> "Echo");
```

or a stream of random numbers as

[Click here to view code image](#)

```
Stream<Double> randoms = Stream.generate(Math::random);
```

To produce infinite sequences such as 0 1 2 3 ..., use the `iterate` method instead. It takes a “seed” value and a function (technically, a `UnaryOperator<T>`), and repeatedly applies the function to the previous result. For example,

[Click here to view code image](#)

```
Stream<BigInteger> integers
= Stream.iterate(BigInteger.ZERO, n -> n.add(BigInteger.ONE));
```

The first element in the sequence is the seed `BigInteger.ZERO`. The second element is `f(seed)`, or 1 (as a big integer). The next element is `f(f(seed))`, or 2, and so on.



NOTE

A number of methods that yield streams have been added to the API with the Java 8 release. For example, the `Pattern` class now has a method `splitAsStream` that splits a `CharSequence` by a regular expression. You can use the following statement to split a string into words:

[Click here to view code image](#)

```
Stream<String> words
= Pattern.compile("[\\P{L}]+").splitAsStream(contents);
```

The static `Files.lines` method returns a `Stream` of all lines in a file. The `Stream` interface has `AutoCloseable` as a superinterface. When the `close` method is called on the stream, the underlying file is also closed. To make sure that this happens, it is best to use the Java 7 `try-with-resources` statement:

[Click here to view code image](#)

```
try (Stream<String> lines = Files.lines(path)) {
    Do something with lines
}
```

The stream, and the underlying file with it, will be closed when the `try` block exits normally or through an exception.

2.3. The `filter`, `map`, and `flatMap` Methods

A stream transformation reads data from a stream and puts the transformed data into another stream. You have already seen the `filter` transformation that yields a new stream with all elements that match a certain condition. Here, we transform a stream of strings into another stream containing only long words:

[Click here to view code image](#)

```
List<String> wordList = ...;
Stream<String> words = wordList.stream();
Stream<String> longWords = words.filter(w -> w.length() > 12);
```

The argument of `filter` is a `Predicate<T>`—that is, a function from `T` to `boolean`.

Often, you want to transform the values in a stream in some way. Use the `map` method and pass the function that carries out the transformation. For example, you can transform all words to lowercase like this:

[Click here to view code image](#)

```
Stream<String> lowercaseWords = words.map(String::toLowerCase);
```

Here, we used `map` with a method expression. Often, you will use a lambda expression instead:

[Click here to view code image](#)

```
Stream<Character> firstChars = words.map(s -> s.charAt(0));
```

The resulting stream contains the first character of each word.

When you use `map`, a function is applied to each element, and the return values are collected in a new stream. Now suppose that you have a function that returns not just one value but a stream of values, such as this one:

[Click here to view code image](#)

```
public static Stream<Character> characterStream(String s) {
    List<Character> result = new ArrayList<>();
    for (char c : s.toCharArray()) result.add(c);
    return result.stream();
}
```

For example, `characterStream("boat")` is the stream `['b', 'o', 'a', 't']`. Suppose you map this method on a stream of strings:

[Click here to view code image](#)

```
Stream<Stream<Character>> result = words.map(w -> characterStream(w));
```

You will get a stream of streams, like `[... ['y', 'o', 'u', 'r'], ['b', 'o', 'a', 't'], ...]` To flatten it out to a stream of characters `[... 'y', 'o', 'u', 'r', 'b', 'o', 'a', 't', ...]`, use the `flatMap` method instead of `map`:

[Click here to view code image](#)

```
Stream<Character> letters = words.flatMap(w -> characterStream(w))
// Calls characterStream on each word and flattens the results
```



NOTE

You may find a `flatMap` method in classes other than streams. It is a general concept in computer science. Suppose you have a generic type `G` (such as `Stream`) and functions `f` from

some type T to $G<U>$ and g from U to $G<V>$. Then you can compose them, that is, first apply f and then g , by using `flatMap`. This is a key idea in the theory of *monads*. But don't worry—you can use `flatMap` without knowing anything about monads.

2.4. Extracting Substreams and Combining Streams

The call `stream.limit(n)` returns a new stream that ends after n elements (or when the original stream ends if it is shorter). This method is particularly useful for cutting infinite streams down to size. For example,

[Click here to view code image](#)

```
Stream<Double> randoms = Stream.generate(Math::random).limit(100);
```

yields a stream with 100 random numbers.

The call `stream.skip(n)` does the exact opposite. It discards the first n elements. This is handy in our book reading example where, due to the way the `split` method works, the first element is an unwanted empty string. We can make it go away by calling `skip`:

[Click here to view code image](#)

```
Stream<String> words = Stream.of(contents.split("[\\P{L}]+")).skip(1);
```

You can concatenate two streams with the static `concat` method of the `Stream` class:

[Click here to view code image](#)

```
Stream<Character> combined = Stream.concat(
    characterStream("Hello"), characterStream("World"));
// Yields the stream ['H', 'e', 'l', 'l', 'o', 'W', 'o', 'r', 'l', 'd']
```

Of course, the first stream should not be infinite—otherwise the second wouldn't ever get a chance.



TIP

The `peek` method yields another stream with the same elements as the original, but a function is invoked every time an element is retrieved. That is handy for debugging:

[Click here to view code image](#)

```
Object[] powers = Stream.iterate(1.0, p -> p * 2)
    .peek(e -> System.out.println("Fetching " + e))
    .limit(20).toArray();
```

When an element is actually accessed, a message is printed. This way you can verify that the infinite stream returned by `iterate` is processed lazily.

2.5. Stateful Transformations

The stream transformations of the preceding sections were *stateless*. When an element is retrieved from a filtered or mapped stream, the answer does not depend on the previous elements. There are also a few stateful transformations. For example, the `distinct` method returns a stream that yields elements from the original stream, in the same order, except that duplicates are suppressed. The stream must obviously remember the elements that it has already seen.

[Click here to view code image](#)

```
Stream<String> uniqueWords  
= Stream.of("merrily", "merrily", "merrily", "gently").distinct();  
// Only one "merrily" is retained
```

The `sorted` method must see the entire stream and sort it before it can give out any elements—after all, the smallest one might be the last one. Clearly, you can't sort an infinite stream.

There are several `sorted` methods. One works for streams of `Comparable` elements, and another accepts a `Comparator`. Here, we sort strings so that the longest ones come first:

[Click here to view code image](#)

```
Stream<String> longestFirst =  
words.sorted(Comparator.comparing(String::length).reversed());
```

Of course, you can sort a collection without using streams. The `sorted` method is useful when the sorting process is a part of a stream pipeline.



NOTE

The `Collections.sort` method sorts a collection in place, whereas `Stream.sorted` returns a new sorted stream.

2.6. Simple Reductions

Now that you have seen how to create and transform streams, we will finally get to the most important point—getting answers from the stream data. The methods that we cover in this section are called *reductions*. They reduce the stream to a value that can be used in your program. Reductions are *terminal operations*. After a terminal operation has been applied, the stream ceases to be usable.

You have already seen a simple reduction: the `count` method that returns the number of elements of the stream.

Other simple reductions are `max` and `min` that return the largest or smallest value. There is a twist—these methods return an `Optional<T>` value that either wraps the answer or indicates that there is none (because the stream happened to be empty). In the olden days, it was common to return `null` in such a situation. But that can lead to null pointer exceptions when an unusual situation arises in an incompletely tested program. In Java 8, the `Optional` type is the preferred way of indicating a missing return value. We discuss the `Optional` type in detail in the next section. Here is how you can get the maximum of a stream:

[Click here to view code image](#)

```
Optional<String> largest = words.max(String::compareToIgnoreCase);  
if (largest.isPresent())  
    System.out.println("largest: " + largest.get());
```

The `findFirst` returns the first value in a nonempty collection. It is often useful when combined with `filter`. For example, here we find the first word that starts with the letter Q, if it exists:

[Click here to view code image](#)

```
Optional<String> startsWithQ  
= words.filter(s -> s.startsWith("Q")).findFirst();
```

If you are okay with any match, not just the first one, then use the `findAny` method. This is effective when you parallelize the stream since the first match in any of the examined segments will complete the computation.

[Click here to view code image](#)

```
Optional<String> startsWithQ  
= words.parallel().filter(s -> s.startsWith("Q")).findAny();
```

If you just want to know there is a match, use `anyMatch`. That method takes a predicate argument, so you won't need to use `filter`.

[Click here to view code image](#)

```
boolean aWordStartsWithQ  
= words.parallel().anyMatch(s -> s.startsWith("Q"));
```

There are also methods `allMatch` and `noneMatch` that return `true` if all or no elements match a predicate. These methods always examine the entire stream, but they still benefit from being run in parallel.

2.7. The Optional Type

An `Optional<T>` object is either a wrapper for an object of type `T` or for no object. It is intended as a safer alternative than a reference of type `T` that refers to an object or `null`. But it is only safer if you use it right.

The `get` method gets the wrapped element if it exists, or throws a `NoSuchElementException` if it doesn't. Therefore,

[Click here to view code image](#)

```
Optional<T> optionalValue = ...;  
optionalValue.get().someMethod()
```

is no safer than

```
T value = ...;  
value.someMethod();
```

As you saw in the preceding section, the `isPresent` method reports whether an `Optional<T>` object has a value. But

[Click here to view code image](#)

```
if (optionalValue.isPresent()) optionalValue.get().someMethod();
```

is no easier than

[Click here to view code image](#)

```
if (value != null) value.someMethod();
```

In the next section, you will see how you should really work with `Optional` values.

2.7.1. Working with Optional Values

The key to using `Optional` effectively is to use a method that either *consumes the correct value* or *produces an alternative*.

There is a second form of the `ifPresent` method that accepts a function. If the optional value

exists, it is passed to that function. Otherwise, nothing happens. Instead of using an `if` statement, you call

[Click here to view code image](#)

```
optionalValue.ifPresent(v -> Process v);
```

For example, if you want to add the value to a set if it is present, call

[Click here to view code image](#)

```
optionalValue.ifPresent(v -> results.add(v));
```

or simply

[Click here to view code image](#)

```
optionalValue.ifPresent(results::add);
```

When calling this version of `ifPresent`, no value is returned. If you want to process the result, use `map` instead:

[Click here to view code image](#)

```
Optional<Boolean> added = optionalValue.map(results::add);
```

Now `added` has one of three values: `true` or `false` wrapped into an `Optional`, if `optionalValue` was present, or an empty optional otherwise.



NOTE

This `map` method is the analog of the `map` method of the `Stream` interface that you have seen in [Section 2.3, “The filter, map, and flatMap Methods,”](#) on page [25](#). Simply imagine an optional value as a stream of size zero or one. The result again has size zero or one, and in the latter case, the function has been applied.

You have just seen how to gracefully consume an optional value when it is present. The other strategy for working with optional values is to produce an alternative if no value is present. Often, there is a default that you want to use when there was no match, perhaps the empty string:

[Click here to view code image](#)

```
String result = optionalString.orElse("");  
// The wrapped string, or "" if none
```

You can also invoke code to compute the default,

[Click here to view code image](#)

```
String result = optionalString.orElseGet(() -> System.getProperty("user.dir"));  
// The function is only called when needed
```

Or, if you want to throw another exception if there is no value,

[Click here to view code image](#)

```
String result = optionalString.orElseThrow(NoSuchElementException::new);  
// Supply a method that yields an exception object
```

2.7.2. Creating Optional Values

So far, we have discussed how to consume an `Optional` object that someone else created. If you write a method that creates an `Optional` object, there are several static methods for that purpose. Either create an `Optional.of(result)` or `Optional.empty()`. For example,

[Click here to view code image](#)

```
public static Optional<Double> inverse(Double x) {  
    return x == 0 ? Optional.empty() : Optional.of(1 / x);  
}
```

The `ofNullable` method is intended as a bridge from the use of `null` values to optional values. `Optional.ofNullable(obj)` returns `Optional.of(obj)` if `obj` is not `null`, and `Optional.empty()` otherwise.

2.7.3. Composing Optional Value Functions with `flatMap`

Suppose you have a method `f` yielding an `Optional<T>`, and the target type `T` has a method `g` yielding an `Optional<U>`. If they were normal methods, you could compose them by calling `s.f().g()`. But that composition doesn't work here, since `s.f()` has type `Optional<T>`, has not `T`. Instead, call

[Click here to view code image](#)

```
Optional<U> = s.f().flatMap(T::g);
```

If `s.f()` is present, then `g` is applied to it. Otherwise, an empty `Optional<U>` is returned.

Clearly, you can repeat that process if you have more methods or lambdas that yield `Optional` values. You can then build a pipeline of steps that succeeds only when all parts do, simply by chaining calls to `flatMap`.

For example, consider the safe `inverse` method of the preceding section. Suppose we also have a safe square root:

[Click here to view code image](#)

```
public static Optional<Double> squareRoot(Double x) {  
    return x < 0 ? Optional.empty() : Optional.of(Math.sqrt(x));  
}
```

Then you can compute the square root of the inverse as

[Click here to view code image](#)

```
Double result = inverse(x).flatMap(MyMath::squareRoot);
```

or, if you prefer,

[Click here to view code image](#)

```
Double result = Optional.of(-4.0).flatMap(Test::inverse).flatMap(Test::squareRoot);
```

If either the `inverse` method or the `squareRoot` returns `Optional.empty()`, the result is empty.



NOTE

You have already seen a `flatMap` method in the `Stream` interface (see [Section 2.3, “The filter, map, and flatMap Methods,”](#) on page [25](#)). That method was used to compose two

methods that yield streams, by flattening out the resulting stream of streams. The `Optional.flatMap` method works in the same way if you consider an optional value to be a stream of size zero or one.

2.8. Reduction Operations

If you want to compute a sum, or combine the elements of a stream to a result in another way, you can use one of the `reduce` methods. The simplest form takes a binary function and keeps applying it, starting with the first two elements. It's easy to explain this if the function is the sum:

[Click here to view code image](#)

```
Stream<Integer> values = ...;
Optional<Integer> sum = values.reduce((x, y) -> x + y)
```

In this case, the `reduce` method computes $v_0 + v_1 + v_2 + \dots$, where the v_i are the stream elements. The method returns an `Optional` because there is no valid result if the stream is empty.



NOTE

In this case, you can write `values.reduce(Integer::sum)` instead of `values.reduce((x, y) -> x + y)`.

In general, if the `reduce` method has a reduction operation op , the reduction yields $v_0 op v_1 op v_2 op \dots$, where we write $v_i op v_{i+1}$ for the function call $op(v_i, v_{i+1})$. The operation should be *associative*: It shouldn't matter in which order you combine the elements. In math notation, $(x op y) op z = x op (y op z)$. This allows efficient reduction with parallel streams.

There are many associative operations that might be useful in practice, such as sum and product, string concatenation, maximum and minimum, set union and intersection. An example of an operation that is not associative is subtraction. For example, $(6 - 3) - 2 \neq 6 - (3 - 2)$.

Often, there is an *identity* e such that $e op x = x$, and you can use that element as the start of the computation. For example, 0 is the identity for addition. Then call the second form of `reduce`:

[Click here to view code image](#)

```
Stream<Integer> values = ...;
Integer sum = values.reduce(0, (x, y) -> x + y)
// Computes 0 + v_0 + v_1 + v_2 + ...
```

The identity value is returned if the stream is empty, and you no longer need to deal with the `Optional` class.

Now suppose you have a stream of objects and want to form the sum of some property, such as all lengths in a stream of strings. You can't use the simple form of `reduce`. It requires a function $(T, T) \rightarrow T$, with the same types for the arguments and the result. But in this situation, you have two types. The stream elements have type `String`, and the accumulated result is an integer. There is a form of `reduce` that can deal with this situation.

First, you supply an “*accumulator*” function $(total, word) \rightarrow total + word.length()$. That function is called repeatedly, forming the cumulative total. But when the computation is parallelized,

there will be multiple computations of this kind, and you need to combine their results. You supply a second function for that purpose. The complete call is

[Click here to view code image](#)

```
int result = words.reduce(0,
    (total, word) -> total + word.length(),
    (total1, total2) -> total1 + total2);
```



NOTE

In practice, you probably won't use the `reduce` method a lot. It is usually easier to map to a stream of numbers and use one of its methods to compute sum, max, or min. (We discuss streams of numbers in [Section 2.12, “Primitive Type Streams,”](#) on page 39.) In this particular example, you could have called `words.mapToInt(String::length).sum()`, which is both simpler and more efficient, since it doesn't involve boxing.

2.9. Collecting Results

When you are done with a stream, you often just want to look at the results instead of reducing them to a value. You can call the `iterator` method, which yields an old-fashioned iterator that you can use to visit the elements. Or you can call `toArray` and get an array of the stream elements.

Since it is not possible to create a generic array at runtime, the expression `stream.toArray()` returns an `Object[]` array. If you want an array of the correct type, pass in the array constructor:

[Click here to view code image](#)

```
String[] result = words.toArray(String[]::new);
// words.toArray() has type Object[]
```

Now suppose you want to collect the results in a `HashSet`. If the collection is parallelized, you can't put the elements directly into a single `HashSet` because a `HashSet` object is not threadsafe. For that reason, you can't use `reduce`. Each segment needs to start out with its own empty hash set, and `reduce` only lets you supply one identity value. Instead, use `collect`. It takes three arguments:

1. A *supplier* to make new instances of the target object, for example, a constructor for a hash set
 2. An *accumulator* that adds an element to the target, for example, an `add` method
 3. An *combiner* that merges two objects into one, such as `addAll`
-



NOTE

The target object need not be a collection. It could be a `StringBuilder` or an object that tracks a count and a sum.

Here is how the `collect` method works for a hash set:

[Click here to view code image](#)

```
HashSet<String> result = stream.collect(HashSet::new, HashSet::add, HashSet::addAll);
```

In practice, you don't have to do that because there is a convenient `Collector` interface for these three functions, and a `Collectors` class with factory methods for common collectors. To collect a stream into a list or set, you can simply call

[Click here to view code image](#)

```
List<String> result = stream.collect(Collectors.toList());
```

or

[Click here to view code image](#)

```
Set<String> result = stream.collect(Collectors.toSet());
```

If you want to control which kind of set you get, use the following call instead:

[Click here to view code image](#)

```
TreeSet<String> result = stream.collect(Collectors.toCollection(TreeSet::new));
```

Suppose you want to collect all strings in a stream by concatenating them. You can call

[Click here to view code image](#)

```
String result = stream.collect(Collectors.joining());
```

If you want a delimiter between elements, pass it to the `joining` method:

[Click here to view code image](#)

```
String result = stream.collect(Collectors.joining(", "));
```

If your stream contains objects other than strings, you need to first convert them to strings, like this:

[Click here to view code image](#)

```
String result = stream.map(Object::toString).collect(Collectors.joining(", "));
```

If you want to reduce the stream results to a sum, average, maximum, or minimum, then use one of the methods `summarizing(Int|Long|Double)`. These methods take a function that maps the stream objects to a number and yield a result of type `(Int|Long|Double)SummaryStatistics`, with methods for obtaining the sum, average, maximum, and minimum.

[Click here to view code image](#)

```
IntSummaryStatistics summary = words.collect(  
    Collectors.summarizingInt(String::length));  
double averageWordLength = summary.getAverage();  
double maxWordLength = summary.getMax();
```



NOTE

So far, you have seen how to reduce or collect stream values. But perhaps you just want to print them or put them in a database. Then you can use the `forEach` method:

[Click here to view code image](#)

```
stream.forEach(System.out::println);
```

The function that you pass is applied to each element. On a parallel stream, it's your responsibility to ensure that the function can be executed concurrently. We discuss this in [Section 2.13, “Parallel Streams,”](#) on page [40](#).

On a parallel stream, the elements can be traversed in arbitrary order. If you want to execute them in stream order, call `forEachOrdered` instead. Of course, you might then give up most or all of the benefits of parallelism.

The `forEach` and `forEachOrdered` methods are terminal operations. You cannot use the stream again after calling them. If you want to continue using the stream, use `peek` instead—see [Section 2.4, “Extracting Substreams and Combining Streams,”](#) on page [26](#).

2.10. Collecting into Maps

Suppose you have a `Stream<Person>` and want to collect the elements into a map so that you can later look up people by their ID. The `Collectors.toMap` method has two function arguments that produce the map keys and values. For example,

[Click here to view code image](#)

```
Map<Integer, String> idToName = people.collect(  
    Collectors.toMap(Person::getId, Person::getName));
```

In the common case that the values should be the actual elements, use `Function.identity()` for the second function.

[Click here to view code image](#)

```
Map<Integer, Person> idToPerson = people.collect(  
    Collectors.toMap(Person::getId, Function.identity()));
```

If there is more than one element with the same key, the collector will throw an `IllegalStateException`. You can override that behavior by supplying a third function argument that determines the value for the key, given the existing and the new value. Your function could return the existing value, the new value, or a combination of them.

Here, we construct a map that contains, for each language in the available locales, as key its name in your default locale (such as "German"), and as value its localized name (such as "Deutsch").

[Click here to view code image](#)

```
Stream<Locale> locales = Stream.of(Locale.getAvailableLocales());  
Map<String, String> languageNames = locales.collect(  
    Collectors.toMap(  
        l -> l.getDisplayLanguage(),  
        l -> l.getDisplayLanguage(l),  
        (existingValue, newValue) -> existingValue));
```

We don't care that the same language might occur twice—for example, German in Germany and in Switzerland, and we just keep the first entry.

However, suppose we want to know all languages in a given country. Then we need a `Map<String, Set<String>>`. For example, the value for "Switzerland" is the set [French, German, Italian]. At first, we store a singleton set for each language. Whenever a new language is found for a given country, we form the union of the existing and the new set.

[Click here to view code image](#)

```
Map<String, Set<String>> countryLanguageSets = locales.collect(  
    Collectors.toMap(  
        l -> l.getDisplayCountry(),  
        l -> Collections.singleton(l.getDisplayLanguage()),  
        (a, b) -> { // Union of a and b
```

```
Set<String> r = new HashSet<>(a);
r.addAll(b);
return r; }));
```

You will see a simpler way of obtaining this map in the next section.

If you want a `TreeMap`, then you supply the constructor as the fourth argument. You must provide a merge function. Here is one of the examples from the beginning of the section, now yielding a `TreeMap`:

[Click here to view code image](#)

```
Map<Integer, Person> idToPerson = people.collect(
    Collectors.toMap(
        Person::getId,
        Function.identity(),
        (existingValue, newValue) -> { throw new IllegalStateException(); },
        TreeMap::new));
```



NOTE

For each of the `toMap` methods, there is an equivalent `toConcurrentMap` method that yields a concurrent map. A single concurrent map is used in the parallel collection process. When used with a parallel stream, a shared map is more efficient than merging maps, but of course, you give up ordering.

2.11. Grouping and Partitioning

In the preceding section, you saw how to collect all languages in a given country. But the process was a bit tedious. You had to generate a singleton set for each map value, and then specify how to merge the existing and new values. Forming groups of values with the same characteristic is very common, and the `groupingBy` method supports it directly.

Let's look at the problem of grouping locales by country. First form this map:

[Click here to view code image](#)

```
Map<String, List<Locale>> countryToLocales = locales.collect(
    Collectors.groupingBy(Locale::getCountry));
```

The function `Locale::getCountry` is the *classifier function* of the grouping. You can now look up all locales for a given country code, for example

[Click here to view code image](#)

```
List<Locale> swissLocales = countryToLocales.get("CH");
// Yields locales [it_CH, de_CH, fr_CH]
```



NOTE

A quick refresher on locales: Each locale has a language code (such as `en` for English) and a country code (such as `US` for the United States). The locale `en_US` describes English in the United States, and `en_IE` is English in Ireland. Some countries have multiple locales. For example, `ga_IE` is Gaelic in Ireland, and, as the preceding example shows, my JVM knows three locales in Switzerland.

When the classifier function is a predicate function (that is, a function returning a `boolean` value), the stream elements are partitioned into two lists: those where the function returns `true` and the complement. In this case, it is more efficient to use `partitioningBy` instead of `groupingBy`. For example, here we split all locales into those that use English, and all others:

[Click here to view code image](#)

```
Map<Boolean, List<Locale>> englishAndOtherLocales = locales.collect(  
    Collectors.partitioningBy(l -> l.getLanguage().equals("en")));  
List<Locale>> englishLocales = englishAndOtherLocales.get(true);
```



NOTE

If you call the `groupingByConcurrent` method, you get a concurrent map that, when used with a parallel stream, is concurrently populated. This is entirely analogous to the `toConcurrentMap` method.

The `groupingBy` method yields a map whose values are lists. If you want to process those lists in some way, you supply a “downstream collector.” For example, if you want sets instead of lists, you can use the `Collectors.toSet` collector that you saw in the preceding section:

[Click here to view code image](#)

```
Map<String, Set<Locale>> countryToLocaleSet = locales.collect(  
    groupingBy(Locale::getCountry, toSet()));
```



NOTE

In this example, as well as the remaining examples of this chapter, I assume a static import of `java.util.stream.Collectors.*` to make the expressions easier to read.

Several other collectors are provided for downstream processing of grouped elements:

- `counting` produces a count of the collected elements. For example,

[Click here to view code image](#)

```
Map<String, Long> countryToLocaleCounts = locales.collect(  
    groupingBy(Locale::getCountry, counting()));
```

counts how many locales there are for each country.

- `summing(Int|Long[Double])` takes a function argument, applies the function to the downstream elements, and produces their sum. For example,

[Click here to view code image](#)

```
Map<String, Integer> stateToCityPopulation = cities.collect(  
    groupingBy(City::getState, summingInt(City::getPopulation)));
```

computes the sum of populations per state in a stream of cities.

- `maxBy` and `minBy` take a comparator and produce maximum and minimum of the downstream elements. For example,

[Click here to view code image](#)

```
Map<String, City> stateToLargestCity = cities.collect(
    groupingBy(City::getState,
        maxBy(Comparator.comparing(City::getPopulation))));
```

produces the largest city per state.

- mapping applies a function to downstream results, and it requires yet another collector for processing its results. For example,

[Click here to view code image](#)

```
Map<String, Optional<String>> stateToLongestCityName = cities.collect(
    groupingBy(City::getState,
        mapping(City::getName,
            maxBy(Comparator.comparing(String::length)))));
```

Here, we group cities by state. Within each state, we produce the names of the cities and reduce by maximum length.

The mapping method also yields a nicer solution to a problem from the preceding section, to gather a set of all languages in a country.

[Click here to view code image](#)

```
Map<String, Set<String>> countryToLanguages = locales.collect(
    groupingBy(l -> l.getDisplayCountry(),
        mapping(l -> l.getDisplayLanguage(),
            toSet())));
```

In the preceding section, I used `toMap` instead of `groupingBy`. In this form, you don't need to worry about combining the individual sets.

- If the grouping or mapping function has return type `int`, `long`, or `double`, you can collect elements into a summary statistics object, as discussed in [Section 2.9, “Collecting Results,”](#) on page [33](#). For example,

[Click here to view code image](#)

```
Map<String, IntSummaryStatistics> stateToCityPopulationSummary = cities.collect(
    groupingBy(City::getState,
        summarizingInt(City::getPopulation)));
```

Then you can get the sum, count, average, minimum, and maximum of the function values from the summary statistics objects of each group.

- Finally, the reducing methods apply a general reduction to downstream elements. There are three forms: `reducing(binaryOperator)`, `reducing(identity, binaryOperator)`, and `reducing(identity, mapper, binaryOperator)`. In the first form, the identity is `null`. (Note that this is different from the forms of `Stream::reduce`, where the method without an identity parameter yields an `Optional` result.) In the third form, the `mapper` function is applied and its values are reduced.

Here is an example that gets a comma-separated string of all city names in each state. We map each city to its name and then concatenate them.

[Click here to view code image](#)

```
Map<String, String> stateToCityNames = cities.collect(
    groupingBy(City::getState,
        reducing("", City::getName,
            (s, t) -> s.length() == 0 ? t : s + ", " + t))));
```

As with `Stream.reduce`, `Collectors.reducing` is rarely necessary. In this case, you can

achieve the same result more naturally as

[Click here to view code image](#)

```
Map<String, String> stateToCityNames = cities.collect(  
    groupingBy(City::getState,  
               mapping(City::getName,  
                      joining(", "))));
```

Frankly, the downstream collectors can yield very convoluted expressions. You should only use them in connection with `groupingBy` or `partitioningBy` to process the “downstream” map values. Otherwise, simply apply methods such as `map`, `reduce`, `count`, `max`, or `min` directly on streams.

2.12. Primitive Type Streams

So far, we have collected integers in a `Stream<Integer>`, even though it is clearly inefficient to wrap each integer into a wrapper object. The same is true for the other primitive types `double`, `float`, `long`, `short`, `char`, `byte`, and `boolean`. The stream library has specialized types `IntStream`, `LongStream`, and `DoubleStream` that store primitive values directly, without using wrappers. If you want to store `short`, `char`, `byte`, and `boolean`, use an `IntStream`, and for `float`, use a `DoubleStream`. The library designers didn’t think it was worth adding another five stream types.

To create an `IntStream`, you can call the `IntStream.of` and `Arrays.stream` methods:

[Click here to view code image](#)

```
IntStream stream = IntStream.of(1, 1, 2, 3, 5);  
stream = Arrays.stream(values, from, to); // values is an int[] array
```

As with object streams, you can also use the static `generate` and `iterate` methods. In addition, `IntStream` and `LongStream` have static methods `range` and `rangeClosed` that generate integer ranges with step size one:

[Click here to view code image](#)

```
IntStream zeroToNinetyNine = IntStream.range(0, 100); // Upper bound is excluded  
IntStream zeroToHundred = IntStream.rangeClosed(0, 100); // Upper bound is included
```

The `CharSequence` interface has methods `codePoints` and `chars` that yield an `IntStream` of the Unicode codes of the characters or of the code units in the UTF-16 encoding. (If you don’t know what code units are, you probably shouldn’t use the `chars` method. Read up on the sordid details in *Core Java, 9th Edition, Volume 1*, Section 3.3.3.)

[Click here to view code image](#)

```
String sentence = "\uD835\uDD46 is the set of octonions.";  
// \uD835\uDD46 is the UTF-16 encoding of the letter ☈, unicode U+1D546
```

```
IntStream codes = sentence.codePoints();  
// The stream with hex values 1D546 20 69 73 20 ...
```

When you have a stream of objects, you can transform it to a primitive type stream with the `mapToInt`, `mapToLong`, or `mapToDouble` methods. For example, if you have a stream of strings and want to process their lengths as integers, you might as well do it in an `IntStream`:

[Click here to view code image](#)

```
Stream<String> words = ...;
IntStream lengths = words.mapToInt(String::length);
```

To convert a primitive type stream to an object stream, use the `boxed` method:

[Click here to view code image](#)

```
Stream<Integer> integers = Integer.range(0, 100).boxed();
```

Generally, the methods on primitive type streams are analogous to those on object streams. Here are the most notable differences:

- The `toArray` methods return primitive type arrays.
- Methods that yield an optional result return an `OptionalInt`, `OptionalLong`, or `OptionalDouble`. These classes are analogous to the `Optional` class, but they have methods `getAsInt`, `getAsLong`, and `getAsDouble` instead of the `get` method.
- There are methods `sum`, `average`, `max`, and `min` that return the sum, average, maximum, and minimum. These methods are not defined for object streams.
- The `summaryStatistics` method yields an object of type `IntSummaryStatistics`, `LongSummaryStatistics`, or `DoubleSummaryStatistics` that can simultaneously report the sum, average, maximum, and minimum of the stream.



NOTE

The `Random` class has methods `ints`, `longs`, and `doubles` that return primitive type streams of random numbers.

2.13. Parallel Streams

Streams make it easy to parallelize bulk operations. The process is mostly automatic, but you need to follow a few rules. First of all, you must have a parallel stream. By default, stream operations create sequential streams, except for `Collection.parallelStream()`. The `parallel` method converts any sequential stream into a parallel one. For example:

[Click here to view code image](#)

```
Stream<String> parallelWords = Stream.of(wordArray).parallel();
```

As long as the stream is in parallel mode when the terminal method executes, all lazy intermediate stream operations will be parallelized.

When stream operations run in parallel, the intent is that the same result is returned as if they had run serially. It is important that the operations are *stateless* and can be executed in an arbitrary order.

Here is an example of something you cannot do. Suppose you want to count all short words in a stream of strings:

[Click here to view code image](#)

```
int[] shortWords = new int[12];
words.parallel().forEach(
    s -> { if (s.length() < 12) shortWords[s.length()]++; });
// Error—race condition!
System.out.println(Arrays.toString(shortWords));
```

This is very, very bad code. The function passed to `forEach` runs concurrently in multiple threads, updating a shared array. That's a classic race condition. If you run this program multiple times, you are quite likely to get a different sequence of counts in each run, each of them wrong.

It is your responsibility to ensure that any functions that you pass to parallel stream operations are threadsafe. In our example, you could use an array of `AtomicInteger` objects for the counters (see Exercise 12). Or you could simply use the facilities of the streams library and group strings by length (see Exercise 13).

By default, streams that arise from ordered collections (arrays and lists), from ranges, generators, and iterators, or from calling `Stream.sorted`, are *ordered*. Results are accumulated in the order of the original elements, and are entirely predictable. If you run the same operations twice, you will get exactly the same results.

Ordering does not preclude parallelization. For example, when computing `stream.map(fun)`, the stream can be partitioned into n segments, each of which is concurrently processed. Then the results are reassembled in order.

Some operations can be more effectively parallelized when the ordering requirement is dropped. By calling the `Stream.unordered` method, you indicate that you are not interested in ordering. One operation that can benefit from this is `stream.distinct`. On an ordered stream, `distinct` retains the first of all equal elements. That impedes parallelization—the thread processing a segment can't know which elements to discard until the preceding segment has been processed. If it is acceptable to retain *any* of the unique elements, all segments can be processed concurrently (using a shared set to track duplicates).

You can also speed up the `limit` method by dropping ordering. If you just want any n elements from a stream and you don't care which ones you get, call

[Click here to view code image](#)

```
Stream<T> sample = stream.parallel().unordered().limit(n);
```

As discussed in [Section 2.10, “Collecting into Maps,”](#) on page 34, merging maps is expensive. For that reason, the `Collectors.groupingByConcurrent` method uses a shared concurrent map. Clearly, to benefit from parallelism, the order of the map values will not be the same as the stream order. Even on an ordered stream, that collector has a “characteristic” of being unordered, so that it can be used efficiently without having to make the stream unordered. You still need to make the stream parallel, though:

[Click here to view code image](#)

```
Map<String, List<String>> result = cities.parallel().collect(
    Collectors.groupingByConcurrent(City::getState));
// Values aren't collected in stream order
```



CAUTION

It is very important that you don't modify the collection that is backing a stream while carrying out a stream operation (even if the modification is threadsafe). Remember that streams don't collect their own data—the data is always in a separate collection. If you were to modify that collection, the outcome of the stream operations would be undefined. The JDK documentation

refers to this requirement as *noninterference*. It applies both to sequential and parallel streams.

To be exact, since intermediate stream operations are lazy, it is possible to mutate the collection up to the point when the terminal operation executes. For example, the following is correct:

[Click here to view code image](#)

```
List<String> wordList = ...;
Stream<String> words = wordList.stream();
wordList.add("END"); // Ok
long n = words.distinct().count();
```

But this code is not:

[Click here to view code image](#)

```
Stream<String> words = wordList.stream();
words.forEach(s -> if (s.length() < 12) wordList.remove(s));
// Error—interference
```

2.14. Functional Interfaces

In this chapter, you have seen many operations whose argument is a function. For example, the `Streams.filter` method takes a function argument:

[Click here to view code image](#)

```
Stream<String> longWords = words.filter(s -> s.length() >= 12);
```

In the javadoc of the `Stream` class, the `filter` method is declared as follows:

[Click here to view code image](#)

```
Stream<T> filter(Predicate<? super T> predicate)
```

To understand the documentation, you have to know what a `Predicate` is. It is an interface with one nondefault method returning a `boolean` value:

[Click here to view code image](#)

```
public interface Predicate {
    boolean test(T argument);
}
```

In practice, one usually passes a lambda expression or method reference, so the name of the method doesn't really matter. The important part is the `boolean` return type. When reading the documentation of `Stream.filter`, just remember that a `Predicate` is a function returning a `boolean`.



NOTE

When you look closely at the declaration of `Stream.filter`, you will note the wildcard type `Predicate<? super T>`. This is common for function parameters. For example, suppose `Employee` is a subclass of `Person`, and you have a `Stream<Employee>`. You can filter the stream (where `T` is `Employee`) with a `Predicate<Employee>`, a `Predicate<Person>`, or a `Predicate<Object>`. This flexibility is particularly important for supplying method references. For example, you may want to use `Person::isAlive` to filter a `Stream<Employee>`. That only

works because of the wildcard in the parameter of the `filter` method.

Table 2–1 summarizes the functional interfaces that occur as parameters of the `Stream` and `Collectors` methods. You will see additional functional interfaces in the next chapter.

Functional Interface	Parameter Types	Return Type	Description
<code>Supplier<T></code>	None	<code>T</code>	Supplies a value of type <code>T</code>
<code>Consumer<T></code>	<code>T</code>	<code>void</code>	Consumes a value of type <code>T</code>
<code>BiConsumer<T, U></code>	<code>T, U</code>	<code>void</code>	Consumes values of types <code>T</code> and <code>U</code>
<code>Predicate<T></code>	<code>T</code>	<code>boolean</code>	A Boolean-valued function
<code>ToIntFunction<T></code> <code>ToLongFunction<T></code> <code>ToDoubleFunction<T></code>	<code>T</code>	<code>int</code> <code>long</code> <code>double</code>	An <code>int</code> -, <code>long</code> -, or <code>double</code> -valued function
<code>IntFunction<R></code> <code>LongFunction<R></code> <code>DoubleFunction<R></code>	<code>int</code> <code>long</code> <code>double</code>	<code>R</code>	A function with argument of type <code>int</code> , <code>long</code> , or <code>double</code>
<code>Function<T, R></code>	<code>T</code>	<code>R</code>	A function with argument of type <code>T</code>
<code>BiFunction<T, U, R></code>	<code>T, U</code>	<code>R</code>	A function with arguments of types <code>T</code> and <code>U</code>
<code>UnaryOperator<T></code>	<code>T</code>	<code>T</code>	A unary operator on the type <code>T</code>
<code>BinaryOperator<T></code>	<code>T, T</code>	<code>T</code>	A binary operator on the type <code>T</code>

Table 2–1 Functional Interfaces Used in the Stream API

Exercises

1. Write a parallel version of the `for` loop in [Section 2.1, “From Iteration to Stream Operations,”](#) on page 22. Obtain the number of processors. Make that many separate threads, each working on a segment of the list, and total up the results as they come in. (You don’t want the threads to update a single counter. Why?)
2. Verify that asking for the first five long words does not call the `filter` method once the fifth long word has been found. Simply log each method call.
3. Measure the difference when counting long words with a `parallelStream` instead of a `stream`. Call `System.currentTimeMillis` before and after the call, and print the difference. Switch to a larger document (such as *War and Peace*) if you have a fast computer.
4. Suppose you have an array `int[] values = { 1, 4, 9, 16 }`. What is `Stream.of(values)`? How do you get a stream of `int` instead?

5. Using `Stream.iterate`, make an infinite stream of random numbers—not by calling `Math.random` but by directly implementing a *linear congruential generator*. In such a generator, you start with $x_0 = \text{seed}$ and then produce $x_{n+1} = (a x_n + c) \% m$, for appropriate values of a , c , and m . You should implement a method with parameters `a`, `c`, `m`, and `seed` that yields a stream`<Long>`. Try out $a = 25214903917$, $c = 11$, and $m = 2^{48}$.

6. The `characterStream` method in [Section 2.3, “The filter, map, and flatMap Methods,”](#) on page [25](#), was a bit clumsy, first filling an array list and then turning it into a stream. Write a stream-based one-liner instead. One approach is to make a stream of integers from `0` to `s.length() - 1` and map that with the `s::charAt` method reference.

7. Your manager asks you to write a method `public static <T> boolean isFinite(Stream<T> stream)`. Why isn’t that such a good idea? Go ahead and write it anyway.

8. Write a method `public static <T> Stream<T> zip(Stream<T> first, Stream<T> second)` that alternates elements from the streams `first` and `second`, stopping when one of them runs out of elements.

9. Join all elements in a `Stream<ArrayList<T>>` to one `ArrayList<T>`. Show how to do this with the three forms of `reduce`.

10. Write a call to `reduce` that can be used to compute the average of a `Stream<Double>`. Why can’t you simply compute the sum and divide by `count()`?

11. It should be possible to concurrently collect stream results in a single `ArrayList`, instead of merging multiple array lists, provided it has been constructed with the stream’s size, since concurrent set operations at disjoint positions are threadsafe. How can you achieve that?

12. Count all short words in a parallel `Stream<String>`, as described in [Section 2.13, “Parallel Streams,”](#) on page [40](#), by updating an array of `AtomicInteger`. Use the atomic `getAndIncrement` method to safely increment each counter.

13. Repeat the preceding exercise, but filter out the short strings and use the `collect` method with `Collectors.groupingBy` and `Collectors.counting`.

Chapter 3. Programming with Lambdas

Topics in This Chapter

- [3.1 Deferred Execution](#)
- [3.2 Parameters of Lambda Expressions](#)
- [3.3 Choosing a Functional Interface](#)
- [3.4 Returning Functions](#)
- [3.5 Composition](#)
- [3.6 Laziness](#)
- [3.7 Parallelizing Operations](#)
- [3.8 Dealing with Exceptions](#)
- [3.9 Lambdas and Generics](#)
- [3.10 Monadic Operations](#)
- [Exercises](#)

In the first two chapters, you saw the basic syntax and semantics of lambda expressions as well as the stream API that makes extensive use of them. In this chapter, you will learn how to create your own libraries that make use of lambda expressions and functional interfaces.

The key points of this chapter are:

- The main reason for using a lambda expression is to defer the execution of the code until an appropriate time.
- When a lambda expression is executed, make sure to provide any required data as inputs.
- Choose one of the existing functional interfaces if you can.
- It is often useful to write methods that return an instance of a functional interface.
- When you work with transformations, consider how you can compose them.
- To compose transformations lazily, you need to keep a list of all pending transformations and apply them in the end.
- If you need to apply a lambda many times, you often have a chance to split up the work into subtasks that execute concurrently.
- Think what should happen when you work with a lambda expression that throws an exception.
- When working with generic functional interfaces, use `? super` wildcards for argument types, `? extends` wildcards for return types.
- When working with generic types that can be transformed by functions, consider supplying `map` and `flatMap`.

3.1. Deferred Execution

The point of all lambdas is *deferred execution*. After all, if you wanted to execute some code right now, you'd do that, without wrapping it inside a lambda. There are many reasons for executing code later, such as

- Running the code in a separate thread
- Running the code multiple times
- Running the code at the right point in an algorithm (for example, the comparison operation in sorting)
- Running the code when something happens (a button was clicked, data has arrived, and so on)
- Running the code only when necessary

It is a good idea to think through what you want to achieve when you set out programming with lambdas.

Let us look at a simple example. Suppose you log an event:

[Click here to view code image](#)

```
logger.info("x: " + x + ", y: " + y);
```

What happens if the log level is set to suppress `INFO` messages? The message string is computed and passed to the `info` method, which then decides to throw it away. Wouldn't it be nicer if the string concatenation only happened when necessary?

Running code only when necessary is a use case for lambdas. The standard idiom is to wrap the code in a no-arg lambda:

```
() -> "x: " + x + ", y: " + y
```

Now we need to write a method that

1. Accepts the lambda
2. Checks whether it should be called
3. Calls it when necessary

To accept the lambda, we need to pick (or, in rare cases, provide) a functional interface. We discuss the process of choosing an interface in more detail in [Section 3.3, “Choosing a Functional Interface,”](#) on page [50](#). Here, a good choice is a `Supplier<String>`. The following method provides lazy logging:

[Click here to view code image](#)

```
public static void info(Logger logger, Supplier<String> message) {
    if (logger.isLoggable(Level.INFO))
        logger.info(message.get());
}
```

We use the `isLoggable` method of the `Logger` class to decide whether `INFO` messages should be logged. If so, we invoke the lambda by calling its abstract method, which happens to be called `get`.



NOTE

Deferring logging messages is such a good idea that the Java 8 library designers beat me to it. The `info` method, as well as the other logging methods, now have variants that accept a `Supplier<String>`. You can directly call `logger.info(() -> "x: " + x + ", y: " + y)`. However, see Exercise 1 for a potentially useful refinement.

3.2. Parameters of Lambda Expressions

When you ask your user to supply a comparator, it is pretty obvious that the comparator has two arguments—the values to be compared.

[Click here to view code image](#)

```
Arrays.sort(names,
    (s, t) -> Integer.compare(s.length(), t.length())); // Compare strings s and t
```

Now consider a different example. This method repeats an action multiple times:

[Click here to view code image](#)

```
public static void repeat(int n, IntConsumer action) {
    for (int i = 0; i < n; i++) action.accept(i);
}
```

Why an `IntConsumer` and not a `Runnable`? We tell the action in which iteration it occurs, which might be useful information. The action needs to capture that input in a parameter

[Click here to view code image](#)

```
repeat(10, i -> System.out.println("Countdown: " + (9 - i)));
```

Another example is an event handler

[Click here to view code image](#)

```
button.setOnAction(event -> action);
```

The `event` object carries information that the action may need.

In general, you want to design your algorithm so that it passes any required information as arguments. For example, when editing an image, it makes sense to have the user supply a function that computes the color for a pixel. Such a function might need to know not just the current color, but also where the pixel is in the image, or what the neighboring pixels are.

However, if these arguments are rarely needed, consider supplying a second version that doesn't force users into accepting unwanted arguments:

[Click here to view code image](#)

```
public static void repeat(int n, Runnable action) {
    for (int i = 0; i < n; i++) action.run();
}
```

This version can be called as

[Click here to view code image](#)

```
repeat(10, () -> System.out.println("Hello, World!"));
```

3.3. Choosing a Functional Interface

In most functional programming languages, function types are *structural*. To specify a function that maps two strings to an integer, you use a type that looks something like `Function2<String, String, Integer>` or `(String, String) -> int`. In Java, you instead declare the intent of the function, using a functional interface such as `Comparator<String>`. In the theory of programming languages this is called *nominal* typing.

Of course, there are many situations where you want to accept “any function” without particular semantics. There are a number of generic function types for that purpose (see [Table 3–1](#)), and it’s a very good idea to use one of them when you can.

Functional Interface	Parameter Types	Return Type	Abstract Method Name	Description	Other Methods
Runnable	none	void	run	Runs an action without arguments or return value	
Supplier<T>	none	T	get	Supplies a value of type T	
Consumer<T>	T	void	accept	Consumes a value of type T	chain
BiConsumer<T, U>	T, U	void	accept	Consumes values of types T and U	chain
Function<T, R>	T	R	apply	A function with argument of type T	compose, andThen, identity
BiFunction<T, U, R>	T, U	R	apply	A function with arguments of types T and U	andThen
UnaryOperator<T>	T	T	apply	A unary operator on the type T	compose, andThen, identity
BinaryOperator<T>	T, T	T	apply	A binary operator on the type T	andThen
Predicate<T>	T	boolean	test	A Boolean-valued function	and, or, negate, isEqual
BiPredicate<T, U>	T, U	boolean	test	A Boolean-valued function with two arguments	and, or, negate

Table 3–1 Common Functional Interfaces

For example, suppose you write a method to process files that match a certain criterion. Should you use the descriptive `java.io.FileFilter` class or a `Predicate<File>`? I strongly recommend that you use the standard `Predicate<File>`. The only reason not to do so would be if you already have

many useful methods producing `FileFilter` instances.



NOTE

Most of the standard functional interfaces have nonabstract methods for producing or combining functions. For example, `Predicate isEqual(a)` is the same as `a::equals`, provided `a` is not `null`. And there are default methods `and`, `or`, `negate` for combining predicates. For example, `Predicate isEqual(a). or(Predicate isEqual(b))` is the same as `x -> a.equals(x) || b.equals(x)`.

Consider another example. We want to transform images, applying a `Color -> Color` function to each pixel. For example, the brightened image in [Figure 3–1](#) is obtained by calling

[Click here to view code image](#)

```
Image brightenedImage = transform(image, Color::brighter);
```



Figure 3–1 The original and transformed image

There is a standard functional interface for this purpose: `UnaryOperator<Color>`. That is a good choice, and there is no need to come up with a `ColorTransformer` interface.

Here is the implementation of the `transform` method. Note the call to the `apply` method.

[Click here to view code image](#)

```
public static Image transform(Image in, UnaryOperator<Color> f) {
    int width = (int) in.getWidth();
    int height = (int) in.getHeight();
    WritableImage out = new WritableImage(width, height);
    for (int x = 0; x < width; x++)
        for (int y = 0; y < height; y++)
            out.getPixelWriter().setColor(x, y,
                f.apply(in.getPixelReader().getColor(x, y)));
    return out;
}
```



NOTE

This method uses the `Color` and `Image` classes from JavaFX, not from `java.awt`. See [Chapter 4](#) for more information on JavaFX.

[Table 3–2](#) lists the 34 available specializations for primitive types `int`, `long`, and `double`. Use the specializations when you can to reduce autoboxing.

Functional Interface	Parameter Types	Return Type	Abstract Method Name
<code>BooleanSupplier</code>	none	<code>boolean</code>	<code>getAsBoolean</code>
<code>PSupplier</code>	none	<code>p</code>	<code>getAsP</code>
<code>PConsumer</code>	<code>p</code>	<code>void</code>	<code>accept</code>
<code>ObjPConsumer<T></code>	<code>T, p</code>	<code>void</code>	<code>accept</code>
<code>PFunction<T></code>	<code>p</code>	<code>T</code>	<code>apply</code>
<code>PToQFunction</code>	<code>p</code>	<code>q</code>	<code>applyAsQ</code>
<code>ToPFunction<T></code>	<code>T</code>	<code>p</code>	<code>applyAsP</code>
<code>ToPBiFunction<T, U></code>	<code>T, U</code>	<code>p</code>	<code>applyAsP</code>
<code>PUnaryOperator</code>	<code>p</code>	<code>p</code>	<code>applyAsP</code>
<code>PBinaryOperator</code>	<code>p, p</code>	<code>p</code>	<code>applyAsP</code>
<code>PPredicate</code>	<code>p</code>	<code>boolean</code>	<code>test</code>

p, q is `int`, `long`, `double`;
 P, Q is `Int`, `Long`, `Double`

Table 3–2 Functional Interfaces for Primitive Types

Sometimes, you need to supply your own functional interface because there is nothing in the standard library that works for you. Suppose you want to modify colors in an image, allowing users to specify a function `(int, int, Color) -> Color` that computes a new color depending on the (x, y) location in the image. In that case, you can define your own interface:

[Click here to view code image](#)

```
@FunctionalInterface
public interface ColorTransformer {
    Color apply(int x, int y, Color colorAtXY);
}
```



NOTE

I called the abstract method `apply` because that is used for the majority of standard functional interfaces. Should you call the method `process` or `transform` or `getColor` instead? It doesn't

matter much to users of the color manipulation code—they will usually supply a lambda expression. Sticking with the standard name simplifies the life of the implementor.

3.4. Returning Functions

In a functional programming language, functions are first-class citizens. Just like you can pass numbers to methods and have methods that produce numbers, you can have arguments and return values that are functions. This sounds abstract, but it is very useful in practice. Java is not quite a functional language because it uses functional interfaces, but the principle is the same. You have seen many methods that accept functional interfaces. In this section, we consider methods whose return type is a functional interface.

Consider again image transformations. If you call

[Click here to view code image](#)

```
Image brightenedImage = transform(image, Color::brighter);
```

the image is brightened by a fixed amount. What if you want it even brighter, or not quite so bright? Could you supply the desired brightness as an additional parameter to `transform`?

[Click here to view code image](#)

```
Image brightenedImage = transform(image,
    (c, factor) -> c.deriveColor(0, 1, factor, 1), // Brighten c by factor
    1.2); // Use a factor of 1.2
```

One would have to overload `transform`:

[Click here to view code image](#)

```
public static <T> Image transform(Image in, BiFunction<Color, T> f, T arg)
```

That can be made to work (see Exercise 6), but what if one wants to supply two arguments? Or three? There is another way. We can make a method that returns the appropriate `UnaryOperator<Color>`, with the brightness set:

[Click here to view code image](#)

```
public static UnaryOperator<Color> brighten(double factor) {
    return c -> c.deriveColor(0, 1, factor, 1);
}
```

Then we can call

[Click here to view code image](#)

```
Image brightenedImage = transform(image, brighten(1.2));
```

The `brighten` method returns a function (or, technically, an instance of a functional interface). That function can be passed to another method (here, `transform`) that expects such an interface.

In general, don't be shy to write methods that produce functions. This is useful to customize the functions that you pass to methods with functional interfaces. For example, consider the `Arrays.sort` method with a `Comparator` argument. There are many ways of comparing values, and you can write a method that yields a comparator for your needs—see Exercise 7. Then you can call `Arrays.sort(values, comparatorGenerator(customization arguments))`.



NOTE

As you will see in [Chapter 8](#), the `Comparator` class has several methods that yield or modify comparators.

3.5. Composition

A single-argument function transforms one value into another. If you have two such transformations, then doing one after the other is also a transformation. Consider image manipulation: Let's first brighten an image, then turn it to grayscale (see [Figure 3–2](#)).




Figure 3–2 First, the image is brightened, and then grayscale is applied.



NOTE

In the printed book, everything is in grayscale. Just run the program in the companion code to see the effect.

That is easy to do with our `transform` method:

[Click here to view code image](#)

```
Image image = new Image("eiffel-tower.jpg");
Image image2 = transform(image, Color::brighter);
Image finalImage = transform(image2, Color::grayscale);
```

But this is not very efficient. We need to make an intermediate image. For large images, that requires a considerable amount of storage. If we could compose the image operations and then apply the composite operation to each pixel, that would be better.

In this case, the image operations are instances of `UnaryOperator<Color>`. That type has a method `compose` that, for rather depressing reasons that are explored in Exercise 10, is not useful for us. But it is easy to roll our own:

[Click here to view code image](#)

```
public static <T> UnaryOperator<T> compose(UnaryOperator<T> op1,
    UnaryOperator<T> op2) {
    return t -> op2.apply(op1.apply(t));
}
```

Now we can call

[Click here to view code image](#)

```
Image finalImage = transform(image, compose(Color::brighter, Color::grayscale));
```

That is much better. Now the composed transformation is directly applied to each pixel, and there is no need for an intermediate image.

Generally, when you build a library where users can carry out one effect after another, it is a good idea to give library users the ability to compose these effects. See Exercise 11 for another example.

3.6. Laziness

In the preceding section, you saw how users of an image transformation method can precompose operations to avoid intermediate images. But why should they have to do that? Another approach is for the library to accumulate all operations and then fuse them. This is, of course, what the stream library does.

If you do lazy processing, your API needs to distinguish between intermediate operations, which accumulate the tasks to be done, and terminal operations which deliver the result. In the image processing example, we can make `transform` lazy, but then it needs to return another object that is not an `Image`. For example,

[Click here to view code image](#)

```
LatentImage latent = transform(image, Color::brighter);
```

A `LatentImage` can simply store the original image and a sequence of image operations.

[Click here to view code image](#)

```
public class LatentImage {
    private Image in;
    private List<UnaryOperator<Color>> pendingOperations;
    ...
}
```

This class also needs a `transform` method:

[Click here to view code image](#)

```
LatentImage transform(UnaryOperator<Color> f) {
    pendingOperations.add(f);
    return this;
}
```

To avoid duplicate `transform` methods, you can follow the approach of the stream library where an initial `stream()` operation is required to turn a collection into a stream. Since we can't add a method to the `Image` class, we can provide a `LatentImage` constructor or a static factory method.

[Click here to view code image](#)

```
LatentImage latent = LatentImage.from(image)
    .transform(Color::brighter).transform(Color::grayscale);
```

You can only be lazy for so long. Eventually, the work needs to be done. We can provide a

`toImage` method that applies all operations and returns the result:

[Click here to view code image](#)

```
Image finalImage = LatentImage.from(image)
    .transform(Color::brighter).transform(Color::grayscale)
    .toImage();
```

Here is the implementation of the method:

[Click here to view code image](#)

```
public Image toImage() {
    int width = (int) in.getWidth();
    int height = (int) in.getHeight();
    WritableImage out = new WritableImage(width, height);
    for (int x = 0; x < width; x++)
        for (int y = 0; y < height; y++) {
            Color c = in.getPixelReader().getColor(x, y);
            for (UnaryOperator<Color> f : pendingOperations) c = f.apply(c);
            out.getPixelWriter().setColor(x, y, c);
        }
    return out;
}
```



CAUTION

In real life, implementing lazy operations is quite a bit harder. Usually you have a mixture of operations, and not all of them can be applied lazily. See Exercises 12 and 13.

3.7. Parallelizing Operations

When expressing operations as functional interfaces, the caller gives up control over the processing details. As long as the operations are applied so that the correct result is achieved, the caller has nothing to complain about. In particular, the library can make use of concurrency. For example, in image processing we can split the image into multiple strips and process each strip separately.

Here is a simple way of carrying out an image transformation in parallel. This code operates on `Color[][][]` arrays instead of `Image` objects because the JavaFX `PixelWriter` is not threadsafe.

[Click here to view code image](#)

```
public static Color[][][] parallelTransform(Color[][][] in, UnaryOperator<Color> f) {
    int n = Runtime.getRuntime().availableProcessors();
    int height = in.length;
    int width = in[0].length;
    Color[][][] out = new Color[height][width];
    try {
        ExecutorService pool = Executors.newCachedThreadPool();
        for (int i = 0; i < n; i++) {
            int fromY = i * height / n;
            int toY = (i + 1) * height / n;
            pool.submit(() -> {
                for (int x = 0; x < width; x++)
                    for (int y = fromY; y < toY; y++)
                        out[y][x] = f.apply(in[y][x]);
            });
        }
        pool.shutdown();
        pool.awaitTermination(1, TimeUnit.HOURS);
    }
```

```

    }
    catch (InterruptedException ex) {
        ex.printStackTrace();
    }
    return out;
}

```

This is, of course, just a proof of concept. Supporting image operations that combine multiple pixels would be a major challenge.

In general, when you are given an object of a functional interface and you need to invoke it many times, ask yourself whether you can take advantage of concurrency.

3.8. Dealing with Exceptions

When you write a method that accepts lambdas, you need to spend some thought on handling and reporting exceptions that may occur when the lambda expression is executed.

When an exception is thrown in a lambda expression, it is propagated to the caller. There is nothing special about executing lambda expressions, of course. They are simply method calls on some object that implements a functional interface. Often it is appropriate to let the expression bubble up to the caller.

Consider, for example:

[Click here to view code image](#)

```

public static void doInOrder(Runnable first, Runnable second) {
    first.run();
    second.run();
}

```

If `first.run()` throws an exception, then the `doInOrder` method is terminated, `second` is never run, and the caller gets to deal with the exception.

But now suppose we execute the tasks asynchronously.

[Click here to view code image](#)

```

public static void doInOrderAsync(Runnable first, Runnable second) {
    Thread t = new Thread() {
        public void run() {
            first.run();
            second.run();
        }
    };
    t.start();
}

```

If `first.run()` throws an exception, the thread is terminated, and `second` is never run. However, the `doInOrderAsync` returns right away and does the work in a separate thread, so it is not possible to have the method rethrow the exception. In this situation, it is a good idea to supply a handler:

[Click here to view code image](#)

```

public static void doInOrderAsync(Runnable first, Runnable second,
    Consumer<Throwable> handler) {
    Thread t = new Thread() {
        public void run() {
            try {
                first.run();
                second.run();
            } catch (Throwable t) {
                handler.accept(t);
            }
        }
    };
    t.start();
}

```

```

        }
    };
    t.start();
}
}

```

Now suppose that `first` produces a result that is consumed by `second`. We can still use the handler.

[Click here to view code image](#)

```

public static <T> void doInOrderAsync(Supplier<T> first, Consumer<T> second,
    Consumer<Throwable> handler) {
    Thread t = new Thread() {
        public void run() {
            try {
                T result = first.get();
                second.accept(result);
            } catch (Throwable t) {
                handler.accept(t);
            }
        }
    };
    t.start();
}
}

```

Alternatively, we could make `second` a `BiConsumer<T, Throwable>` and have it deal with the exception from `first`—see Exercise 16.

It is often inconvenient that methods in functional interfaces don't allow checked exceptions. Of course, your methods can accept functional interfaces whose methods allow checked exceptions, such as `Callable<T>` instead of `Supplier<T>`. A `Callable<T>` has a method that is declared as `T call() throws Exception`. If you want an equivalent for a `Consumer` or a `Function`, you have to create it yourself.

You sometimes see suggestions to “fix” this problem with a generic wrapper, like this:

[Click here to view code image](#)

```

public static <T> Supplier<T> unchecked(Callable<T> f) {
    return () -> {
        try {
            return f.call();
        }
        catch (Exception e) {
            throw new RuntimeException(e);
        }
        catch (Throwable t) {
            throw t;
        }
    };
}
}

```

Then you can pass a

[Click here to view code image](#)

```

unchecked(() -> new String(Files.readAllBytes(
    Paths.get("/etc/passwd")), StandardCharsets.UTF_8))

```

to a `Supplier<String>`, even though the `readAllBytes` method throws an `IOException`.

That is a solution, but not a complete fix. For example, this method cannot generate a `Consumer<T>` or a `Function<T, U>`. You would need to implement a variation of `unchecked` for each functional interface.

3.9. Lambdas and Generics

Generally, lambdas work well with generic types. You have seen a number of examples where we wrote generic mechanisms, such as the `unchecked` method of the preceding section. There are just a couple of issues to keep in mind.

One of the unhappy consequences of type erasure is that you cannot construct a generic array at runtime. For example, the `toArray()` method of `Collection<T>` and `Stream<T>` cannot call `T[] result = new T[n]`. Therefore, these methods return `Object[]` arrays. In the past, the solution was to provide a second method that accepts an array. That array was either filled or used to create a new one via reflection. For example, `Collection<T>` has a method `toArray(T[] a)`. With lambdas, you have a new option, namely to pass the constructor. That is what you do with streams:

[Click here to view code image](#)

```
String[] result = words.toArray(String[]::new);
```

When you implement such a method, the constructor expression is an `IntFunction<T[]>`, since the size of the array is passed to the constructor. In your code, you call `T[] result = constr.apply(n)`.

In this regard, lambdas help you overcome a limitation of generic types. Unfortunately, in another common situation lambdas suffer from a different limitation. To understand the problem, recall the concept of type variance.

Suppose `Employee` is a subtype of `Person`. Is a `List<Employee>` a special case of a `List<Person>`? It seems that it should be. But actually, it would be unsound. Consider this code:

[Click here to view code image](#)

```
List<Employee> staff = ....;
List<Person> tenants = staff; // Not legal, but suppose it was
tenants.add(new Person("John Q. Public")); // Adds Person to staff!
```

Note that `staff` and `tenants` are references to the same list. To make this type error impossible, we must disallow the conversion from `List<Employee>` to `List<Person>`. We say that the type parameter `T` of `List<T>` is *invariant*.

If `List` was immutable, as it is in a functional programming language, then the problem would disappear, and one could have a *covariant* list. That is what is done in languages such as Scala. However, when generics were invented, Java had very few immutable generic classes, and the language designers instead embraced a different concept: use-site variance, or “wildcards.”

A method can decide to accept a `List<? extends Person>` if it only reads from the list. Then you can pass either a `List<Person>` or a `List<Employee>`. Or it can accept a `List<? super Employee>` if it only writes to the list. It is okay to write employees into a `List<Person>`, so you can pass such a list. In general, reading is covariant (subtypes are okay) and writing is contravariant (supertypes are okay). Use-site variance is just right for mutable data structures. It gives each service the choice which variance, if any, is appropriate.

However, for function types, use-site variance is a hassle. A function type is *always* contravariant in its arguments and covariant in its return value. For example, if you have a `Function<Person, Employee>`, you can safely pass it on to someone who needs a `Function<Employee, Person>`. They will only call it with employees, whereas your function can handle any person. They will expect the

function to return a person, and you give them something even better.

In Java, when you declare a generic functional interface, you can't specify that function arguments are always contravariant and return types always covariant. Instead, you have to repeat it for each use. For example, look at the javadoc for `Stream<T>`:

[Click here to view code image](#)

```
void forEach(Consumer<? super T> action)
Stream<T> filter(Predicate<? super T> predicate)
<R> Stream<R> map(Function<? super T, ? extends R> mapper)
```

The general rule is that you use `super` for argument types, `extends` for return types. That way, you can pass a `Consumer<Object>` to `forEach` on a `Stream<String>`. If it is willing to consume any object, surely it can consume strings.

But the wildcards are not always there. Look at

[Click here to view code image](#)

```
T reduce(T identity, BinaryOperator<T> accumulator)
```

Since `T` is the argument *and* return type of `BinaryOperator`, the type does not vary. In effect, the contravariance and covariance cancel each other out.

As the implementor of a method that accepts lambda expressions with generic types, you simply add `? super` to any argument type that is not also a return type, and `? extends` to any return type that is not also an argument type.

For example, consider the `doInOrderAsync` method of the preceding section. Instead of

[Click here to view code image](#)

```
public static <T> void doInOrderAsync(Supplier<T> first,
Consumer<T> second, Consumer<Throwable> handler)
```

it should be

[Click here to view code image](#)

```
public static <T> void doInOrderAsync(Supplier<? extends T> first,
Consumer<? super T> second, Consumer<? super Throwable> handler)
```

3.10. Monadic Operations

When you work with generic types, and with functions that yield values from these types, it is useful to supply methods that let you *compose* these functions—that is, carry out one after another. In this section, you will see a design pattern for providing such compositions.

Consider a generic type `G<T>` with one type parameter, such as `List<T>` (zero or more values of type `T`), `Optional<T>` (zero or one values of type `T`), or `Future<T>` (a value of type `T` that will be available in the future).

Also consider a function `T -> U`, or a `Function<T, U>` object.

It often makes sense to apply this function to a `G<T>` (that is, a `List<T>`, `Optional<T>`, `Future<T>`, and so on). How this works exactly depends on the nature of the generic type `G`. For example, applying a function f to a `List` with elements e_1, \dots, e_n means creating a list with elements $f(e_1), \dots, f(e_n)$.

Applying f to an `Optional<T>` containing v means creating an `Optional<U>` containing $f(v)$. But if

f is applied to an empty `Optional<T>` without a value, the result is an empty `Optional<U>`. Applying *f* to a `Future<T>` simply means to apply it whenever it is available. The result is a `Future<U>`.

By tradition, this operation is usually called `map`. There is a `map` method for `Stream` and `Optional`. The `CompletableFuture` class that we will discuss in [Chapter 6](#) has an operation that does just what `map` should do, but it is called `thenApply`. There is no `map` for a plain `Future<V>`, but it is not hard to supply one (see Exercise 21).

So far, that is a fairly straightforward idea. It gets more complex when you look at functions $T \rightarrow G<U>$ instead of functions $T \rightarrow U$. For example, consider getting the web page for a URL. Since it takes some time to fetch the page, that is a function `URL -> Future<String>`. Now suppose you have a `Future<URL>`, a URL that will arrive sometime. Clearly it makes sense to map the function to that `Future`. Wait for the URL to arrive, then feed it to the function and wait for the string to arrive. This operation has traditionally been called `flatMap`.

The name `flatMap` comes from sets. Suppose you have a “many-valued” function—a function computing a set of possible answers. And then you have another such function. How can you compose these functions? If $f(x)$ is the set $\{y_1, \dots, y_n\}$, you apply g to each element, yielding $\{g(y_1), \dots, g(y_n)\}$. But each of the $g(y_i)$ is a *set*. You want to “flatten” the set of sets so that you get the set of all possible values of both functions.

There is a `flatMap` for `Optional<T>` as well. Given a function $T \rightarrow Optional<U>$, `flatMap` unwraps the value in the `Optional` and applies the function, except if either the source or target option was not present. It does exactly what the set-based `flatMap` would have done on sets with size 0 or 1.

Generally, when you design a type `G<T>` and a function $T \rightarrow U$, think whether it makes sense to define a `map` that yields a `G<U>`. Then, generalize to functions $T \rightarrow G<U>$ and, if appropriate, provide `flatMap`.



NOTE

These operations are important in the theory of monads, but you don’t need to know the theory to understand `map` and `flatMap`. The concept of mapping a function is both straightforward and useful, and the point of this section is to make you aware of it.

Exercises

1. Enhance the lazy logging technique by providing conditional logging. A typical call would be `logIf(Level.FINEST, () -> i == 10, () -> "a[10] = " + a[10])`. Don’t evaluate the condition if the logger won’t log the message.

2. When you use a `ReentrantLock`, you are required to lock and unlock with the idiom

```
myLock.lock();
try {
    some action
} finally {
    myLock.unlock();
}
```

Provide a method `withLock` so that one can call

[Click here to view code image](#)

```
withLock(myLock, () -> { some action })
```

3. Java 1.4 added assertions to the language, with an `assert` keyword. Why were assertions not supplied as a library feature? Could they be implemented as a library feature in Java 8?

4. How many functional interfaces with `Filter` in their name can you find in the Java API? Which ones add value over `Predicate<T>`?

5. Here is a concrete example of a `ColorTransformer`. We want to put a frame around an image, like this:



First, implement a variant of the `transform` method of [Section 3.3, “Choosing a Functional Interface,”](#) on page [50](#), with a `ColorTransformer` instead of an `UnaryOperator<Color>`. Then call it with an appropriate lambda expression to put a 10 pixel gray frame replacing the pixels on the border of an image.

6. Complete the method

[Click here to view code image](#)

```
public static <T> Image transform(Image in, BiFunction<Color, T> f, T arg)
```

from [Section 3.4, “Returning Functions,”](#) on page [53](#).

7. Write a method that generates a `Comparator<String>` that can be normal or reversed, case-sensitive or case-insensitive, space-sensitive or space-insensitive, or any combination thereof. Your method should return a lambda expression.

8. Generalize Exercise 5 by writing a static method that yields a `ColorTransformer` that adds a frame of arbitrary thickness and color to an image.

9. Write a method `lexicographicComparator(String... fieldNames)` that yields a

comparator that compares the given fields in the given order. For example, a `lexicographicComparator("lastname", "firstname")` takes two objects and, using reflection, gets the values of the `lastname` field. If they are different, return the difference, otherwise move on to the `firstname` field. If all fields match, return 0.

10. Why can't one call

[Click here to view code image](#)

```
UnaryOperator op = Color::brighter;
Image finalImage = transform(image, op.compose(Color::grayscale));
```

Look carefully at the return type of the `compose` method of `UnaryOperator<T>`. Why is it not appropriate for the `transform` method? What does that say about the utility of structural and nominal types when it comes to function composition?

11. Implement static methods that can compose two `ColorTransformer` objects, and a static method that turns a `UnaryOperator<Color>` into a `ColorTransformer` that ignores the `x`- and `y`-coordinates. Then use these methods to add a gray frame to a brightened image. (See Exercise 5 for the gray frame.)

12. Enhance the `LatentImage` class in [Section 3.6, “Laziness,”](#) on page 56, so that it supports both `UnaryOperator<Color>` and `ColorTransformer`. Hint: Adapt the former to the latter.

13. Convolution filters such as blur or edge detection compute a pixel from neighboring pixels. To blur an image, replace each color value by the average of itself and its eight neighbors. For edge detection, replace each color value c with $4c - n - e - s - w$, where the other colors are those of the pixel to the north, east, south, and west. Note that these cannot be implemented lazily, using the approach of [Section 3.6, “Laziness,”](#) on page 56, since they require the image from the previous stage (or at least the neighboring pixels) to have been computed. Enhance the lazy image processing to deal with these operations. Force computation of the previous stage when one of these operators is evaluated.

14. To deal with lazy evaluation on a per-pixel basis, change the transformers so that they are passed a `PixelReader` object from which they can read other pixels in the image. For example, `(x, y, reader) -> reader.get(width - x, y)` is a mirroring operation. The convolution filters from the preceding exercises can be easily implemented in terms of such a reader. The straightforward operations would simply have the form `(x, y, reader) -> reader.get(x, y).grayscale()`, and you can provide an adapter from `UnaryOperation<Color>`. A `PixelReader` is at a particular level in the pipeline of operations. Keep a cache of recently read pixels at each level in the pipeline. If a reader is asked for a pixel, it looks in the cache (or in the original image at level 0); if that fails, it constructs a reader that asks the previous transform.

15. Combine the lazy evaluation of [Section 3.6, “Laziness,”](#) on page 56, with the parallel evaluation of [Section 3.7, “Parallelizing Operations,”](#) on page 57.

16. Implement the `doInOrderAsync` of [Section 3.8, “Dealing with Exceptions,”](#) on page 58, where the second parameter is a `BiConsumer<T, Throwable>`. Provide a plausible use case. Do you still need the third parameter?

17. Implement a `doInParallelAsync(Runnable first, Runnable second, Consumer<Throwable>)` method that executes `first` and `second` in parallel, calling the handler if either method throws an exception.

18. Implement a version of the `unchecked` method in [Section 3.8, “Dealing with Exceptions,”](#) on page [58](#), that generates a `Function<T, U>` from a lambda that throws checked exceptions. Note that you will need to find or provide a functional interface whose abstract method throws arbitrary exceptions.

19. Look at the `Stream<T>` method `<U> U reduce(U identity, BiFunction<U, ? super T, U> accumulator, BinaryOperator<U> combiner)`. Should `U` be declared as `? super U` in the first type argument to `BiFunction`? Why or why not?

20. Supply a static method `<T, U> List<U> map(List<T>, Function<T, U>)`.

21. Supply a static method `<T, U> Future<U> map(Future<T>, Function<T, U>)`. Return an object of an anonymous class that implements all methods of the `Future` interface. In the `get` methods, invoke the function.

22. Is there a `flatMap` operation for `CompletableFuture`? If so, what is it?

23. Define a `map` operation for a class `Pair<T>` that represents a pair of objects of type `T`.

24. Can you define a `flatMap` method for `Pair<T>`? If so, what is it? If not, why not?

Chapter 4. JavaFX

Topics in This Chapter

- [4.1 A Brief History of Java GUI Programming](#)
- [4.2 Hello, JavaFX!](#)
- [4.3 Event Handling](#)
- [4.4 JavaFX Properties](#)
- [4.5 Bindings](#)
- [4.6 Layout](#)
- [4.7 FXML](#)
- [4.8 CSS](#)
- [4.9 Animations and Special Effects](#)
- [4.10 Fancy Controls](#)
- [Exercises](#)

JavaFX is the recommended user interface toolkit for writing rich client applications with Java. JavaFX is now bundled with all supported versions of Oracle's Java platform. In this chapter, you will learn the basics of JavaFX development. If you develop rich client user interface platforms, you will see how to transition from Swing to JavaFX. If you don't, skim over the chapter anyway so you can understand the sample applications we use elsewhere when it is convenient to illustrate a concept with a graphical program.

The key points of this chapter are:

- A scene graph is made up of nodes which may contain other nodes.
- A scene is displayed on a stage (a top-level window, the surface of an applet, or the full screen).
- Some controls (such as buttons) emit events, but most JavaFX events come from property changes.
- JavaFX properties emit change and invalidation events.
- When you bind a property to another, it is updated when the other one changes.
- JavaFX uses layout panes that work similar to layout managers in Swing.
- You can specify layout with the FXML markup language.
- You can use CSS to change the visual appearance of your application.
- It is easy to implement animations and special effects.
- JavaFX provides some advanced controls out of the box, such as charts, an embedded WebKit browser, and a media player.

4.1. A Brief History of Java GUI Programming

When Java was born, the Internet was in its infancy and personal computers were on every desktop. Business applications were implemented with “fat clients”—programs with lots of buttons

and sliders and text fields that communicated with a server. This was considered a lot nicer than the “dumb terminal” applications from an even earlier era. Java 1.0 included the AWT, a toolkit for graphical user interfaces, that had the distinction of being cross-platform. The idea was to serve up the fat clients over the nascent Web, eliminating the cost of managing and updating the applications on every desktop.

The AWT had a noble idea: provide a common programming interface for the native buttons, sliders, text fields, and so on of various operating systems. But it didn’t work very well. There were subtle differences in the functionality of the user interface widgets in each operating system, and what should have been “write once, run anywhere” turned into “write many times, debug everywhere.”

Next came Swing. The central idea behind Swing was not to use the native widgets, but to paint its own. That way, the user interface would look and feel the same on every platform. Or, if users preferred, they could ask for the native look and feel of their platform, and the Swing widgets would be painted to match the native ones. Of course, all that painting was slow, and users complained. After a while, computers got faster, and users complained that Swing was ugly—indeed, it had fallen behind the native widgets that had been spruced up with animations and fancy effects. More ominously, Flash was increasingly used to create user interfaces with even flashier effects that didn’t use the native controls at all.

In 2007, Sun Microsystems introduced a new technology, called JavaFX, as a competitor to Flash. It ran on the Java VM but had its own programming language, called JavaFX Script. The language was optimized for programming animations and fancy effects. Programmers complained about the need to learn a new language, and they stayed away in droves. In 2011, Oracle released a new version, JavaFX 2.0, that had a Java API and no longer needed a separate programming language. As of Java 7 update 6, JavaFX 2.2 has been bundled with the JDK and JRE. Since it wouldn’t be a true part of Java if it didn’t have crazy jumps in version numbers, the version accompanying Java 8 is called JavaFX 8.

Of course, Flash is now a bad memory, and most user interfaces live in a browser or a mobile device. Still, there are situations where a “fat client” on a desktop makes users more productive. Also, Java now runs on ARM processors, and there are embedded systems that need user interfaces, such as kiosks and in-car displays. JavaFX is what Oracle wants us to use for those applications. Why didn’t Oracle just put the good parts of JavaFX into Swing? Swing would have to be redesigned from the ground up to run efficiently on modern graphics hardware. Oracle decided that it wasn’t worth the trouble and declared that Swing will not be further developed.

In this chapter, we go over the basics of writing user interfaces in JavaFX, focusing on boring business applications with buttons, sliders, and text fields, not the flashy effects that were the original motivation behind JavaFX.

4.2. Hello, JavaFX!

Let’s start with a simple program that shows a message (see [Figure 4–1](#)). Like in Swing, use a *label*:

[Click here to view code image](#)

```
Label message = new Label("Hello, JavaFX!");
```



Figure 4–1 The “Hello, World” program for JavaFX



NOTE

Note that there are no unsightly `J` prefixes. In Swing, the equivalent control was called `JLabel` to distinguish it from the AWT `Label`.

We increase the font size:

```
message.setFont(new Font(100));
```

This `Font` constructor makes a `Font` object representing the default font at 100 points.

In JavaFX, you put everything you want to show onto *ascene*. There, you can decorate and animate your “actors”—that is, your controls and shapes. In our program, we won’t do any decorating or animating, but we still need the scene. And the scene must reside in a *stage*. That is a top-level window if the program runs on a desktop, or a rectangular area if it runs as an applet. The stage is passed as a parameter to the `start` method that you must override in a subclass of the `Application` class.

[Click here to view code image](#)

```
public class HelloWorld extends Application {  
    public void start(Stage stage) {  
        Label message = new Label("Hello, JavaFX!");  
        message.setFont(new Font(100));  
        stage.setScene(new Scene(message));  
        stage.setTitle("Hello");  
        stage.show();  
    }  
}
```



NOTE

As you see from this example, no `main` method is required to launch a JavaFX application. In previous versions of JavaFX, you were required to include a `main` method of the form

[Click here to view code image](#)

```
public class MyApp extends Application {  
    public static void main(String[] args) {  
        launch(args);  
    }  
    ...  
}
```

4.3. Event Handling

Graphical user interfaces are event driven. Users click on buttons, adjust sliders, and so on. As they carry out these actions, the UI reacts and updates itself.

As in Swing, you add an event handler to a button so you can be notified when it is clicked. Lambda expressions make this very simple:

[Click here to view code image](#)

```
Button red = new Button("Red");
red.setOnAction(event -> message.setTextFill(Color.RED));
```

When the button is clicked, the lambda is called. In this case, it sets the text color to red.

However, with most JavaFX controls, event handling is different. Consider a slider, as shown in [Figure 4–2](#). When the slider is adjusted, its value changes. However, you shouldn't listen to the low-level events that the slider emits to indicate those changes. Instead, the slider has a JavaFX *property* called `value`, and the property emits events when it changes. We will discuss properties in detail in the next section, but here is how you can listen to the property's events and adjust the font size of the message:

[Click here to view code image](#)

```
slider.valueProperty().addListener(property
-> message.setFont(new Font(slider.getValue())));
```




Figure 4–2 Processing slider events

Listening to properties is very common in JavaFX. For example, if you want to change a part of the user interface as a user enters text into a text field, add a listener to the `text` property.



NOTE

Buttons are special. Clicking a button doesn't change one of its properties.

4.4. JavaFX Properties

A *property* is an attribute of a class that you can read or write. Commonly, the property is backed by a field, and the property getter and setter simply read and write that field. But the getter and setter can also take other actions, such as reading values from a database or sending out change notifications. In many programming languages, there is convenient syntax for invoking property getters and setters. Typically, using the property on the right-hand side of an assignments calls the getter, and using it on the left-hand side calls the setter.

[Click here to view code image](#)

```
value = obj.property;
```

```
// In many languages (but not Java), this calls the property getter  
obj.property = value; // And this calls the property setter
```

Sadly, Java does not have such syntax. But it has supported properties by convention since Java 1.1. The JavaBeans specification states that a property should be inferred from a getter/setter pair. For example, a class with methods `String getText()` and `void setText(String newValue)` is deemed to have a `text` property. The `Introspector` and `BeanInfo` classes in the `java.beans` package let you enumerate all properties of a class.

The JavaBeans specification also defines *bound properties*, where objects emit property change events when the setters are invoked. JavaFX does not make use of this part of the specification. Instead, a JavaFX property has a third method, besides the getter and setter, that returns an object implementing the `Property` interface. For example, a `JavaFXtext` property has a method `Property<String> textProperty()`. You can attach a listener to the property object. That's different from old-fashioned JavaBeans. In JavaFX, the property object, not the bean, sends out notifications. There is a good reason for this change. Implementing bound JavaBeans properties required boilerplate code to add, remove, and fire listeners; in JavaFX it's much simpler because there are library classes that do all that work.

Let's see how we can implement a property `text` in a class `Greeting`. Here is the simplest way to do that:

[Click here to view code image](#)

```
public class Greeting {  
    private StringProperty text = new SimpleStringProperty("");  
    public final StringProperty textProperty() { return text; }  
    public final void setText(String newValue) { text.set(newValue); }  
    public final String getText() { return text.get(); }  
}
```

The `StringProperty` class wraps a string. It has methods for getting and setting the wrapped value and for managing listeners. As you can see, implementing a JavaFX property requires some boilerplate code, and there is unfortunately no way in Java to generate the code automatically. But at least you won't have to worry about managing listeners.

It is not a requirement to declare property getters and setters as `final`, but the JavaFX designers recommend it.



NOTE

With this pattern, a property object is needed for each property, whether anyone listens to it or not. Exercise 2 explores a useful optimization for the pattern, creating the property objects lazily.

In the preceding example, we defined a `StringProperty`. For a primitive type property, use one of `IntegerProperty`, `LongProperty`, `DoubleProperty`, `FloatProperty`, or `BooleanProperty`. There are also `ListProperty`, `MapProperty`, and `SetProperty` classes. For everything else, use an `ObjectProperty<T>`. All these are abstract classes with concrete subclasses `SimpleIntegerProperty`, `SimpleObjectProperty<T>`, and so on.



NOTE

If all you care about is managing listeners, your property methods can return objects of type `ObjectProperty<T>`, or even the `Property<T>` interface. The more specialized classes are useful to make computations with the properties, as explained in [Section 4.5, “Bindings,”](#) on page [75](#).



NOTE

The property classes have methods `getValue` and `setValue` in addition to the `get` and `set` methods. In the `StringProperty` class, `get` is identical to `getValue`, and `set` to `setValue`. But for primitive types, they are different. For example, in an `IntegerProperty`, `getValue` returns an `Integer`, and `get` returns an `int`. Generally, use `get` and `set` unless you write generic code that needs to work with properties of any type.

There are two kinds of listeners that can be attached to a property. A `ChangeListener` is notified when the property value has changed, and an `InvalidationListener` is called when the property value *may* have changed. The distinction matters if a property is evaluated *lazily*. As you will see in the next section, some properties are computed from others, and the computation is only done when necessary. The `ChangeListener` callback tells you the old and new value, which means it has to compute the new value. The `InvalidationListener` doesn’t compute the new value, but that means you might get a callback when the value hasn’t actually changed.

In most situations, that difference is immaterial. It doesn’t matter much whether you get the new value as a callback parameter or from the property. And usually, it is not worth worrying about computed properties that happen to stay unchanged even though one of their inputs changed. In the preceding section, I used an `InvalidationListener` because it made the code simpler.



CAUTION

It is a bit tricky to use the `ChangeListener` interface for numeric properties. One would like to call

[Click here to view code image](#)

```
slider.valueProperty().addListener((property, oldValue, newValue)
    -> message.setFont(new Font(newValue)));
```

But that does not work. `DoubleProperty` implements `Property<Number>` and not `Property<Double>`. Therefore, the type for `oldValue` and `newValue` is `Number` and not `Double`, so you have to manually unbox:

[Click here to view code image](#)

```
slider.valueProperty().addListener((property, oldValue, newValue)
    -> message.setFont(new Font(newValue.doubleValue())));
```

The raison d'être for JavaFX properties is the notion of *binding*: automatically updating one property when another one changes. Consider, for example, the application in [Figure 4–3](#). When the user edits the top address, the bottom one is updated as well.




Figure 4–3 The bound text property updates automatically.

This is achieved by binding one property to the other:

[Click here to view code image](#)

```
billing.textProperty().bind(shipping.textProperty());
```

Under the hood, a change listener is added to the text property of `shipping` that sets the text property of `billing`.

You can also call

[Click here to view code image](#)

```
billing.textProperty().bindBidirectional(shipping.textProperty());
```

If either of the properties changes, the other is updated.

To undo a binding, call `unbind` or `unbindBidirectional`.

The binding mechanism solves a common problem in user interface programming. For example, consider a date field and a calendar picker. When the user picks a date from the calendar, the date field should be automatically updated, as should be the date property of the model.

Of course, in many situations, one property depends on another, but the relationship is more complex. Consider [Figure 4–4](#). We always want the circle centered in the scene. That is, its `centerX` property should be one half of the `width` property of the scene.




Figure 4–4 The center of this circle is bound to half the width and height of the scene.

To achieve this, we need to produce a computed property. The `Bindings` class has static methods for this purpose. For example, `Bindings.divide(scene.widthProperty(), 2)` is a property whose value is one half of the scene width. When the scene width changes, so does that property. All that remains is to bind that computed property to the circle's `centerX` property:

[Click here to view code image](#)

```
circle.centerXProperty().bind(Bindings.divide(scene.widthProperty(), 2));
```



NOTE

Alternatively, you can call `scene.widthProperty().divide(2)`. With more complex expressions, the static `Bindings` methods seems a bit easier to read, particularly if you use

[Click here to view code image](#)

```
import static javafx.beans.binding.Bindings.*;
```

and write `divide(scene.widthProperty(), 2)`.

Here is a more realistic example. We want to disable the `Smaller` and `Larger` buttons when the gauge is too small or large ([Figure 4–5](#)).




Figure 4–5 When the gauge reaches either end, a button is disabled.

[Click here to view code image](#)

```
smaller.disableProperty().bind(Bindings.lessThanOrEqualTo(gauge.widthProperty(), 0));
```

```
larger.disableProperty().bind(Bindings.greaterThanOrEqualTo(gauge.widthProperty(), 100));
```

When the width is ≤ 0 , the `Smaller` button is disabled. When the width is ≥ 100 , the `Larger` button is disabled.

[Table 4–1](#) lists all operators that the `Bindings` class provides. One or both of the arguments implement the `Observable` interface or one of its subinterfaces. The `Observable` interface provides methods for adding and removing an `InvalidationListener`. The `ObservableValue` interface adds `ChangeListener` management and a `getValue` method. Its subinterfaces provide methods to get the value in the appropriate type. For example, the `get` method of `ObservableStringValue` returns a `String` and the `get` method of `ObservableIntegerValue` returns an `int`. The return types of the methods of the `Bindings` are subinterfaces of the `Binding` interface, itself a subinterface of the `Observable` interface. A `Binding` knows about all properties on which it depends.

Method Name	Arguments
add, subtract, multiply, divide, max, min	Two of <code>ObservableNumberValue</code> , <code>int</code> , <code>long</code> , <code>float</code> , <code>double</code>
negate	An <code>ObservableNumberValue</code>
greaterThan, greaterThanOrEqualTo, lessThan, lessThanOrEqualTo	Two of <code>ObservableNumberValue</code> , <code>int</code> , <code>long</code> , <code>float</code> , <code>double</code> or two of <code>ObservableStringValue</code> , <code>String</code>
equal, notEqual	Two of <code>ObservableObjectValue</code> , <code>ObservableNumberValue</code> , <code>int</code> , <code>long</code> , <code>float</code> , <code>double</code> , <code>Object</code>
equalIgnoreCase, notEqualIgnoreCase	Two of <code>ObservableStringValue</code> , <code>String</code>
isEmpty, isNotEmpty	An <code>Observable(List Map Set StringValue)</code>
isNull, isNotNull	An <code>ObservableObjectValue</code>
length	An <code>ObservableStringValue</code>
size	An <code>Observable(List Map Set)</code>
and, or	Two <code>ObservableBooleanValue</code>
not	An <code>ObservableBooleanValue</code>

convert	An ObservableValue that is converted to a string binding
concat	A sequence of objects whose <code>toString</code> values are concatenated. If any of the objects is an ObservableValue that changes, the concatenation changes too.
format	An optional locale, a <code>MessageFormat</code> string, and a sequence of objects that are formatted. If any of the objects is an ObservableValue that changes, the formatted string changes too.
<code>valueAt</code> <code>(double float integer long)ValueAt</code> <code>stringValueAt</code>	An ObservableList and an index, or an ObservableMap and a key
<code>create(Boolean Double Float Integer Long Object String)Binding</code>	A Callable and a list of dependencies
<code>select</code> <code>select(Boolean Double Float Integer Long String)</code>	An Object or ObservableValue and a sequence of public property names, yielding the property <i>obj.p₁.p₂. . . . p_n</i>
when	Yields a builder for a conditional operator. The binding <code>when(b).then(v₁).otherwise(v₂)</code> yields <i>v₁</i> or <i>v₂</i> , depending on whether the ObservableBooleanValue <i>b</i> is true or not. Here, <i>v₁</i> or <i>v₂</i> can be regular or observable values. The conditional value is recomputed whenever an observable value changes.

Table 4–1 Operators Supplied by the `Bindings` Class

In practice, you don't need to worry about all of these interfaces. You combine properties and you get something that you can bind to another property.

Building up a computed property with the methods of the `Bindings` class can get quite baroque. There is another approach for producing computed bindings that you may find easier. Simply put the expression that you want to have computed into a lambda, and supply a list of dependent properties. When any of the properties changes, the lambda is recomputed. For example,

[Click here to view code image](#)

```
larger.disableProperty().bind(
    createBooleanBinding(
        () -> gauge.getWidth() >= 100, // This expression is computed...
        gauge.widthProperty())); // ...when this property changes
```

Exercise 5 suggests a slightly more elegant way of lazily evaluating bindings with lambda expressions.



NOTE

In the JavaFX Script language, the compiler analyzed binding expressions and automatically figured out the dependent properties. You just declared `disable bind gauge.width >= 100`, and the compiler attached a listener to the `gauge.width` property. Of course, in Java, the programmer needs to supply this information.

4.6. Layout

When a graphical user interface contains multiple controls, they need to be arranged on the screen in a functional and attractive way. One way to obtain a layout is with a design tool. The tool's user, often a graphics designer, drags images of the controls onto a design view and arranges, resizes, and configures them. However, this approach can be problematic when the sizes of the elements change, for example, because labels have different lengths in international versions of a program.

Alternatively, the layout can be achieved programmatically, by writing code in a setup method that adds the user interface controls to specific positions. That is what was done in Swing, using layout manager objects.

Another approach is to specify the layout in a declarative language. For example, web pages are laid out with HTML and CSS. Similarly, Android has an XML language for specifying layouts.

JavaFX supports all three approaches. The JavaFX SceneBuilder is a visual GUI builder. You can download it from www.oracle.com/technetwork/java/javafx/overview. Figure 4–6 shows a screenshot.




Figure 4–6 The JavaFX SceneBuilder

We won't discuss the SceneBuilder program further. When you understand the concepts of this section, you will find it straightforward to use.

Programmatic layout is very similar to Swing. However, instead of layout managers that are added to arbitrary panels, one uses *panes*—containers with a layout policy. For example, a `BorderPane` has five areas: North, West, South, East, and Center. Here we place a button into each:

[Click here to view code image](#)

```
BorderPane pane = new BorderPane();
pane.setTop(new Button("Top"));
pane.setLeft(new Button("Left"));
pane.setCenter(new Button("Center"));
pane.setRight(new Button("Right"));
pane.setBottom(new Button("Bottom"));
stage.setScene(new Scene(pane));
```

[Figure 4–7](#) shows the result.



Figure 4–7 The `BorderPane` layout



NOTE

With the Swing `BorderLayout`, buttons were expanded to fill each region of the layout. In JavaFX, a button does not expand past its natural size.

Now suppose you want more than one button in the South area. Use an `HBox` (see [Figure 4–8](#)):

[Click here to view code image](#)

```
HBox box = new HBox(10); // ten pixels between controls
box.getChildren().addAll(yesButton, noButton, maybeButton);
```



Figure 4–8 Laying out buttons with an `HBox`

Of course, there is a `VBox` for laying out controls vertically. The layout in [Figure 4–8](#) was achieved like this:

```
VBox pane = new VBox(10);
pane.getChildren().addAll(question, buttons);
pane.setPadding(new Insets(10));
```

Note the `padding` property. Without it, the label and the buttons would touch the window border.



CAUTION

In JavaFX, dimensions are specified in pixels. In our example, we use ten pixels for the box spacing and padding. This is not really appropriate nowadays, when pixel densities can vary widely. One way to overcome this is to compute dimensions in rem, as you would do in CSS3. (A rem or “root em” is the height of the default font of the document root.)

[Click here to view code image](#)

```
final double rem = new Text("").getLayoutBounds().getHeight();  
pane.setPadding(new Insets(0.8 * rem));
```

There is only so much you can achieve with horizontal and vertical boxes. Just as Swing had the `GridBagLayout` as “the mother of all layout managers,” JavaFX has the `GridPane`. Think of a `GridPane` as an equivalent of an HTML table. You can set the horizontal and vertical alignment of all cells. If desired, cells can span multiple rows and columns. Consider the login dialog in [Figure 4–9](#).



Figure 4–9 A `GridPane` can arrange the controls for this login dialog.

Note the following:

- The labels “User name:” and “Password:” are right aligned.
- The buttons are in an `HBox` that spans two rows.

When you add a child to a `GridPane`, specify its column and row index (in that order; think *x*- and *y*-coordinates).

```
pane.add(usernameLabel, 0, 0);  
pane.add(username, 1, 0);  
pane.add(passwordLabel, 0, 1);  
pane.add(password, 1, 1);
```

If a child spans multiple columns or rows, specify the spans after the positions. For example, the button panel spans two columns and one row:

```
pane.add(buttons, 0, 2, 2, 1);
```

If you want a child to span all remaining rows or columns, you can use `GridPane.REMAINDER`.

To set the horizontal alignment of a child, use the static `setHalignment` method, and pass the child reference and a constant `LEFT`, `CENTER`, or `RIGHT` from the `HPos` enumeration.

[Click here to view code image](#)

```
GridPane.setHalignment(usernameLabel, HPos.RIGHT);
```

Similarly, for vertical alignment, call `setValignment` and use `TOP`, `CENTER`, or `BOTTOM` from the `VPos` enumeration.



NOTE

These static calls look rather inelegant in Java code, but they make sense in the FXML markup language—see the next section.



CAUTION

Do *not* center the `HBox` with the buttons inside the grid. That box has expanded to the full horizontal size, and centering will not change its position. Instead, tell the `HBox` to center its contents:

```
buttons.setAlignment(Pos.CENTER);
```

You will also want to provide some spacing around the rows and columns and some padding around the table:

[Click here to view code image](#)

```
pane.setHgap(0.8 * em);
pane.setVgap(0.8 * em);
pane.setPadding(new Insets(0.8 * em));
```



TIP

For debugging, it can be useful to see the cell boundaries (see [Figure 4–10](#)). Call

[Click here to view code image](#)

```
pane.setGridLinesVisible(true);
```

If you want to see the borders of an individual child (for example, to see whether it has grown to fill the entire cell), set its border. This is most easily done with CSS:

[Click here to view code image](#)

```
buttons.setStyle("-fx-border-color: red;");
```




Figure 4–10 Use visible grid lines when debugging a `GridPane`.

These layout panes should suffice for the majority of applications. [Table 4–2](#) shows all layouts that come with JavaFX.

Pane Class	Description
HBox, VBox	Lines up children horizontally or vertically.
GridPane	Lays out children in a tabular grid, similar to the Swing GridBagLayout.
TilePane	Lays out children in a grid, giving them all the same size, similar to the Swing GridLayout.
BorderPane	Provides the areas North, East, South, West, and Center, similar to the Swing BorderLayout.
FlowPane	Flows children in rows, making new rows when there isn't sufficient space, similar to the Swing FlowLayout.
AnchorPane	Children can be positioned in absolute positions, or relative to pane's boundaries. This is the default in the SceneBuilder layout tool.
StackPane	Stacks children above each other. Can be useful for decorating components, such as stacking a button over a colored rectangle.

Table 4–2 JavaFX Layouts



NOTE

In this section, we built up user interfaces by manually nesting panes and controls. JavaFX Script had a “builder” syntax for describing such nested structures (called the “scene graph”). JavaFX 2 used builder classes to imitate that syntax. Here is how to build up the login dialog:

[Click here to view code image](#)

```
GridPane pane = GridPaneBuilder.create()
    .hgap(10)
    .vgap(10)
    .padding(new Insets(10))
    .children(
        usernameLabel = LabelBuilder.create()
            .text("User name:")
            .build(),
        passwordLabel = LabelBuilder.create()
            .text("Password:")
            .build(),
        username = TextFieldBuilder.create().build(),
        password = PasswordFieldBuilder.create().build(),
        buttons = HBoxBuilder.create()
            .spacing(10)
            .alignment(Pos.CENTER)
            .children(
                okButton = ButtonBuilder.create()
                    .text("Ok")
                    .build(),
                cancelButton = ButtonBuilder.create()
                    .text("Cancel")
                    .build())
            .build())
    .build();
```

That’s amazingly verbose, and it’s not even the full story—one still needed to specify the grid constraints. Builders have been deprecated in JavaFX 8, not because they are so verbose, but

because of an implementation issue. To save code, builders have an inheritance tree that parallels the inheritance of the corresponding nodes. For example, `GridPaneBuilder` extends `PaneBuilder` because `GridPane` extends `Pane`. But now you have a problem. What should `PaneBuilder.children` return? If it only returns a `PaneBuilder`, then the user has to be very careful to first configure the subclass properties, then the superclass properties. The JavaFX designers tried to solve this problem with generics. The methods of a `PaneBuilder` return a `B`, so that a `GridPaneBuilder` can extend `PaneBuilder<GridPaneBuilder>`. Wait, that can't work—`GridPaneBuilder` is itself generic, so that would have to be a `GridPaneBuilder<GridPaneBuilder>`, or really a `GridPaneBuilder<GridPaneBuilder<something>>`. This circularity was overcome with some tricks, but those tricks are unsound, and they won't work in future versions of Java. Thus, builders were withdrawn.

If you like builders, you can use Scala or Groovy and their JavaFX bindings (<https://code.google.com/p/scalafx>, <http://groovyfx.org>).

4.7. FXML

The markup language that JavaFX uses to describe layouts is called FXML. I discuss it in some detail because the concepts are interesting beyond the needs of JavaFX, and the implementation is fairly general.

Here is the FXML markup for the login dialog of the preceding section:

[Click here to view code image](#)

```
<?xml version="1.0" encoding="UTF-8"?>

<?import java.lang.*?>
<?import java.util.*?>
<?import javafx.scene.control.*?>
<?import javafx.scene.layout.*?>

<GridPane hgap="10" vgap="10">
    <padding>
        <Insets top="10" right="10" bottom="10" left="10"/>
    </padding>
    <children>
        <Label text="User name:" GridPane.columnIndex="0" GridPane.rowIndex="0"
               GridPane.halignment="RIGHT" />
        <Label text="Password: " GridPane.columnIndex="0" GridPane.rowIndex="1"
               GridPane.halignment="RIGHT" />
        <TextField GridPane.columnIndex="1" GridPane.rowIndex="0"/>
        <PasswordField GridPane.columnIndex="1" GridPane.rowIndex="1" />
        <HBox GridPane.columnIndex="0" GridPane.rowIndex="2"
              GridPane.columnSpan="2" alignment="CENTER" spacing="10">
            <children>
                <Button text="Ok" />
                <Button text="Cancel" />
            </children>
        </HBox>
    </children>
</GridPane>
```

Have a closer look at the FXML file. Note the “processing instructions” `<?import ...?>` for importing Java packages. (In general, XML processing instructions are an “escape hatch” for application-specific processing of XML documents.)

Now look at the structure of the document. First off, the nesting of the `GridPane`, the labels and text fields, the `HBox` and its button children reflects the nesting that we built up with Java code in the preceding section.

Most of the attributes correspond to property setters. For example,

```
<GridPane hgap="10" vgap="10">
```

means "construct a `GridPane` and then set the `hgap` and `vgap` properties."

When an attribute starts with a class name and a static method, that method is invoked. For example,

[Click here to view code image](#)

```
<TextField GridPane.columnIndex="1" GridPane.rowIndex="0"/>
```

means that the static methods `GridPane.setColumnIndex(thisTextField, 1)` and `GridPane.setRowIndex(thisTextField, 0)` will be called.



NOTE

Generally, an FXML element is constructed with its default constructor and then customized by calling property setters or static methods, in the spirit of the JavaBeans specification. There are a few exceptions that we will consider later.

When a property value is too complex to express as a string, one uses nested elements instead of attributes. Consider, for example,

[Click here to view code image](#)

```
<GridPane hgap="10" vgap="10">
  <padding>
    <Insets top="10" right="10" bottom="10" left="10"/>
  </padding>
  ...
```

The `padding` property has type `Insets`, and the `Insets` object is constructed with an `<Insets ...>` child element that specifies how to set its properties.

Finally, there is a special rule for list properties. For example, `children` is a list property, and calling

[Click here to view code image](#)

```
<HBox ...>
  <children>
    <Button text="Ok" />
    <Button text="Cancel" />
  </children>
</HBox>
```

adds the buttons to the list returned by `getChildren`.

You can write FXML files by hand, or you can use the SceneBuilder program that I mentioned in the preceding section. Once you have such a file, load it like this:

[Click here to view code image](#)

```
public void start(Stage stage) {
```

```

try {
    Parent root = FXMLLoader.load(getClass().getResource("dialog.fxml"));
    stage.setScene(new Scene(root));
    stage.show();
} catch (IOException ex) {
    ex.printStackTrace();
    System.exit(0);
}

```

Of course, this is not yet useful by itself. The user interface is displayed, but the program cannot access the values that the user provides. One way of establishing a connection between the controls and the program is to use `id` attributes, as you would in JavaScript. Provide the `id` attributes in the FXML file:

[Click here to view code image](#)

```
<TextField id="username" GridPane.columnIndex="1" GridPane.rowIndex="0"/>
```

In the program, look up the control:

[Click here to view code image](#)

```
TextField username = (TextField) root.lookup("#username");
```

But there is a better way. You can use the `@FXML` annotation to “inject” the control objects into a *controller* class. The controller class must implement the `Initializable` interface. In the controller’s `initialize` method, you wire up the binders and event handlers. Any class can be the controller, even the FX application itself.

For example, here is a controller for our login dialog:

[Click here to view code image](#)

```

public class LoginDialogController implements Initializable {
    @FXML private TextField username;
    @FXML private PasswordField password;
    @FXML private Button okButton;

    public void initialize(URL url, ResourceBundle rb) {
        okButton.disableProperty().bind(
            Bindings.createBooleanBinding(
                () -> username.getText().length() == 0
                    || password.getText().length() == 0,
                username.textProperty(),
                password.textProperty()));
        okButton.setOnAction(event ->
            System.out.println("Verifying " + username.getText()
                + ":" + password.getText()));
    }
}
```

In the FXML file, provide the names of the controller’s instance variables to the corresponding control elements in the FXML file, using the `fx:id` (not `id`) attribute:

[Click here to view code image](#)

```
<TextField fx:id="username" GridPane.columnIndex="1" GridPane.rowIndex="0"/>
<PasswordField fx:id="password" GridPane.columnIndex="1" GridPane.rowIndex="1" />
<Button fx:id="okButton" text="Ok" />
```

In the root element, you also need to declare the controller class, using the `fx:controller` attribute:

[Click here to view code image](#)

```
<GridPane xmlns:fx="http://javafx.com/fxml" hgap="10" vgap="10"
    fx:controller="LoginDialogController">
```

Note the namespace attribute to introduce the FXML namespace.



NOTE

If your controller doesn't have a default constructor (perhaps, because it is being initialized with a reference to a business service), you can set it programmatically:

[Click here to view code image](#)

```
FXMLLoader loader = new FXMLLoader(getClass().getResource(...));
loader.setController(new Controller(service));
Parent root = (Parent) loader.load();
```



CAUTION

If you set the controller programmatically, really use the code from the preceding note. The following code will compile, but it will invoke the static `FXMLLoader.load` method, ignoring the constructed loader:

[Click here to view code image](#)

```
FXMLLoader loader = new FXMLLoader();
loader.setController(...);
Parent root = (Parent) loader.load(getClass().getResource(...));
// Error—calls static method
```

When the FXML file is loaded, the scene graph is constructed, and references to the named control objects are injected into the annotated fields of the controller object. Then its `initialize` method is called.

It is even possible do much of the initialization in the FXML file. You can define simple bindings, and you can set annotated controller methods as event listeners. The syntax is documented at http://docs.oracle.com/javafx/2/api/javafx/fxml/doc-files/introduction_to_fxml.html. However, let's not dwell on these features. It seems better to separate the visual design from the program behavior, so that a user interface designer can produce the design and a programmer can implement the behavior.



NOTE

It is also possible to add scripts in JavaScript or another scripting language to an FXML file. We will discuss this briefly in [Chapter 7](#).

4.8. CSS

JavaFX lets you change the visual appearance of the user interface with CSS, which is usually more convenient than supplying FXML attributes or calling Java methods.

You can load a CSS style sheet programmatically and have it applied to a scene graph:

[Click here to view code image](#)

```
Scene scene = new Scene(pane);
scene.getStylesheets().add("scene.css");
```

In the style sheet, you can reference any controls that have an ID. For example, here is how you can control the appearance of a `GridPane`. In the code, set the ID:

[Click here to view code image](#)

```
GridPane pane = new GridPane();
pane.setId("pane");
```

Don't set any padding or spacing in the code. Instead, use CSS.

[Click here to view code image](#)

```
#pane {
    -fx-padding: 0.5em;
    -fx-hgap: 0.5em;
    -fx-vgap: 0.5em;
    -fx-background-image: url("metal.jpg")
}
```

Unfortunately, you can't use the familiar CSS attributes but need to know FX-specific attributes that start with `-fx-`. The attribute names are formed by changing the property names to lowercase and using hyphens instead of camel case. For example, the `textAlignment` property turns into `-fx-text-alignment`. You can find all supported attributes in the JavaFX CSS reference at <http://docs.oracle.com/javafx/2/api/javafx/scene/doc-files/cssref.html>.

Using CSS is nicer than cluttering up the code with layout minutiae. Moreover, you can easily use resolution-independent em units. Of course CSS can be used both for good and for evil (see [Figure 4–11](#)), and I hope you will resist the temptation to apply gratuitous background textures to your login dialogs.



Figure 4–11 Using CSS to style a user interface

Instead of styling by individual IDs, you can use style classes. Add the class to the node object:

[Click here to view code image](#)

```
HBox buttons = new HBox();
buttons.getStyleClass().add("buttonrow");
```

Then style it, using the CSS class notation:

```
.buttonrow {
    -fx-spacing: 0.5em;
}
```

Every JavaFX control and shape class belongs to a CSS class whose name is the decapitalized Java class name. For example, all `Label` nodes have class `label`. Here is how you can change the

font for all labels to Comic Sans:

[Click here to view code image](#)

```
.label {  
    -fx-font-family: "Comic Sans MS";  
}
```

But please don't.

You can also use CSS with FXML layouts. Attach the stylesheet to the root pane:

[Click here to view code image](#)

```
<GridPane id="pane" stylesheets="scene.css">
```

Supply `id` or `styleClass` attributes in the FXML code. For example,

```
<HBox styleClass="buttonrow">
```

Then you can specify most styling in CSS, and use FXML only for layout. Unfortunately, you can't completely remove all styling from the FXML. For example, there is currently no way to specify grid cell alignment in CSS.



NOTE

You can also apply a CSS style programmatically, such as

[Click here to view code image](#)

```
buttons.setStyle("-fx-border-color: red;");
```

That can be handy for debugging, but in general, it seems better to use an external stylesheet.

4.9. Animations and Special Effects

When JavaFX was born, special effects were all the rage, and JavaFX makes it easy to produce shadows, blurs, and movement. You will find dozens of pretty demos on the Web with swirling bubbles moving aimlessly, text jumping nervously, and so on. I thought you'd enjoy some useful tips on how to bring these animations to the world of business applications. [Figure 4–12](#) shows an application where the Yes button increases in size while the No button fades into the background and the Maybe button rotates.



Figure 4–12 Buttons that grow, fade, and turn

JavaFX defines a number of *transitions* that, over a period of time, vary a property of a node. Here is how you grow a node by 50% in both *x* and *y* directions over three seconds:

[Click here to view code image](#)

```
ScaleTransition st = new ScaleTransition(Duration.millis(3000));  
st.setByX(1.5);  
st.setByY(1.5);
```

```
st.setNode(yesButton);  
st.play();
```

The node can be any node in a scene graph, such as a circle in an animation of soap bubbles or the ever more enticing Yes button in our example.

As set up, the transition will end when its goal is met. You can cycle it indefinitely like this:

[Click here to view code image](#)

```
st.setCycleCount(Animation.INDEFINITE);  
st.setAutoReverse(true);
```

Now the node will get bigger, then smaller, then bigger again, and so on.

The `FadeTransition` changes the opacity of a node. Here is how the No button fades into the background:

[Click here to view code image](#)

```
FadeTransition ft = new FadeTransition(Duration.millis(3000));  
ft.setFromValue(1.0);  
ft.setToValue(0);  
ft.setNode(noButton);  
ft.play();
```

All JavaFX nodes can be rotated around their center. The `RotateTransition` changes the node's `rotate` property. The following code animates the rotation of the Maybe button:

[Click here to view code image](#)

```
RotateTransition rt = new RotateTransition(Duration.millis(3000));  
rt.setByAngle(180);  
rt.setCycleCount(Animation.INDEFINITE);  
rt.setAutoReverse(true);  
rt.setNode(maybeButton);  
rt.play();
```

You can compose transitions with the `ParallelTransition` and `SequentialTransition` combinators, performing them in parallel or one after the other. If you need to animate multiple nodes, you can place them into a `Group` node and animate that. When you need to create this kind of behavior, the JavaFX classes are a joy to work with.

Special effects are also very easy to do. If you need a drop shadow for a spiffy caption, make a `DropShadow` effect and set it as the `effect` property of a node. [Figure 4–13](#) shows the result with a `Text` node. Here is the code:

[Click here to view code image](#)

```
DropShadow dropShadow = new DropShadow();  
dropShadow.setRadius(5.0);  
dropShadow.setOffsetX(3.0);  
dropShadow.setOffsetY(3.0);  
dropShadow.setColor(Color.GRAY);  
  
Text text = new Text();  
text.setFill(Color.RED);  
text.setText("Drop shadow");  
text.setFont(Font.font("sans", FontWeight.BOLD, 40));  
text.setEffect(dropShadow);
```



Figure 4–13 JavaFX effects

To set a glow or a blur effect is just as simple:

[Click here to view code image](#)

```
text2.setEffect(new Glow(0.8));  
text3.setEffect(new GaussianBlur());
```

Admittedly, the glow effect looks a bit cheesy and the blur effect doesn't seem to have many applications in the world of business, but it is impressive how easy it is to produce these effects.

4.10. Fancy Controls

Of course, JavaFX has combo boxes, tab panes, trees, and tables, just like Swing does, as well as a few user interface controls that Swing never got, such as a date picker and an accordion. It would take an entire book to describe these in detail. In this section, I want to dispel any remaining Swing nostalgia by showing you three fancy controls that are far beyond what Swing had to offer.

[Figure 4–14](#) shows one of many charts that you can make with JavaFX, out of the box, without having to install any third-party libraries.




Figure 4–14 A JavaFX pie chart

And it's easy as pie:

[Click here to view code image](#)

```
ObservableList<PieChart.Data> pieChartData =
    FXCollections.observableArrayList(
        new PieChart.Data("Asia", 4298723000.0),
        new PieChart.Data("North America", 355361000.0),
        new PieChart.Data("South America", 616644000.0),
        new PieChart.Data("Europe", 742452000.0),
        new PieChart.Data("Africa", 1110635000.0),
        new PieChart.Data("Oceania", 38304000.0));
final PieChart chart = new PieChart(pieChartData);
chart.setTitle("Population of the Continents");
```

Altogether, there are half a dozen chart types that you can use and customize. See <http://docs.oracle.com/javafx/2/charts/chart-overview.htm> for more information.

In Swing, you could show HTML in a `JEditorPane`, but the rendering was poor for most real-world HTML. That's understandable—implementing a browser is hard work. In fact, it is so hard that most browsers are built on top of the open source WebKit engine. JavaFX does the same. A `WebView` displays an embedded native WebKit window (see [Figure 4–15](#)).




Figure 4–15 Browsing the Web

Here is the code to show a web page:

[Click here to view code image](#)

```
String location = "http://horstmann.com";
WebView browser = new WebView();
WebEngine engine = browser.getEngine();
engine.load(location);
```

The browser is live—you can click on links in the usual way. JavaScript works as well. However, if you want to display status line or popup messages from JavaScript, you need to install notification handlers and implement your own status line and popups.



NOTE

WebView does not support any plugins, so you cannot use it to show Flash animations or PDF documents. It also doesn't show applets.

Prior to JavaFX, media playback was pitiful in Java. A Java Media Framework was available as an optional download, but it did not get much love from the developers. Of course, implementing audio and video playback is even harder than writing a browser. Therefore, JavaFX leverages an existing toolkit, the open source GStreamer framework.

To play a video, construct a `Media` object from an URL string, construct a `MediaPlayer` to play it, and a `MediaView` to show the player:

[Click here to view code image](#)

```
Path path = Paths.get("moonlanding.mp4");
String location = path.toUri().toString();
Media media = new Media(location);
MediaPlayer player = new MediaPlayer(media);
player.setAutoPlay(true);
MediaView view = new MediaView(player);
view.setOnError(e -> System.out.println(e));
```

As you can see in [Figure 4–16](#), the video is played—but, unfortunately, there are no video controls. You can add your own (see <http://docs.oracle.com/javafx/2/media/playercontrol.htm>), but it would have been nice to supply a default set of controls.



Figure 4–16 Playing a video



NOTE

Ever so often, GStreamer can't handle a particular video file. The error handler in the code sample displays GStreamer messages so that you can diagnose playback problems.

That brings us to the end of this quick tour through JavaFX. JavaFX is the future of desktop Java. It has a few rough edges, mostly due to a hurried transformation from the original scripting language. But it is certainly no harder to use than Swing, and it has many more useful and attractive controls than Swing ever had.

Exercises

1. Write a program with a text field and a label. As with the Hello, JavaFX program, the label should have the string Hello, FX in a 100 point font. Initialize the text field with the same string. Update the label as the user edits the text field.

2. Consider a class with many JavaFX properties, such as a chart or table. Chances are that in a particular application, most properties never have listeners attached to them. It is therefore wasteful to have a property object per property. Show how the property can be set up on demand, first using a regular field for storing the property value, and then using a property object only when the `xxxProperty()` method is called for the first time.

3. Consider a class with many JavaFX properties, most of which are never changed from a default. Show how the property can be set up on demand, when it is set to a nondefault value or when the `xxxProperty()` method is called for the first time.

4. Enhance the program in [Section 4.5, “Bindings,”](#) on page [75](#) so that the circle stays centered and always touches at least two of the sides of the scene.

5. Write methods

[Click here to view code image](#)

```
public static <T, R> ObservableValue<R> observe(
    Function<T, R> f, ObservableValue<T> t)
public static <T, U, R> ObservableValue<R> observe(
    BiFunction<T, U, R> f, ObservableValue<T> t, ObservableValue<U> u)
```

that return observable values whose `getValue` method returns the value of the lambda expression, and whose invalidation and change listeners are fired when any of the inputs become invalid or change. For example,

[Click here to view code image](#)

```
larger.disableProperty().bind(observe(
    t -> t >= 100, gauge.widthProperty()));
```

6. Center the top and bottom buttons in [Figure 4–7](#).

7. Find out how to set the border of a control without using CSS.

8. Since there is no JavaFX-specific knowledge in parsing FXML files, come up with an example where you load an object that has nothing to do with JavaFX, with some nested objects, and set the properties in FXML syntax. Extra credit if you use injection.

9. Animate a circle, representing a planet, so it travels along an elliptical orbit. Use a `PathTransition`.

10. Using the web viewer, implement a browser with a URL bar and a back button. Hint: `WebEngine.getHistory()`.

Chapter 5. The New Date and Time API

Topics in This Chapter

- [5.1 The Time Line](#)
- [5.2 Local Dates](#)
- [5.3 Date Adjusters](#)
- [5.4 Local Time](#)
- [5.5 Zoned Time](#)
- [5.6 Formatting and Parsing](#)
- [5.7 Interoperating with Legacy Code](#)
- [Exercises](#)

Time flies like an arrow, and we can easily set a starting point and count forward and backwards in seconds. So why is it so hard to deal with time? The problem is humans. All would be easy if we could just tell each other: “Meet me at 1371409200, and don’t be late!” But we want time to relate to daylight and the seasons. That’s where things get complicated. Java 1.0 had a `Date` class that was, in hindsight, unbelievably naïve, and had most of its methods deprecated in Java 1.1 when a `Calendar` class was introduced. Its API wasn’t stellar, its instances were mutable, and it didn’t deal with issues such as leap seconds. The third time is a charm, and the `java.time` API that is introduced in Java 8 has remedied the flaws of the past and should serve us for quite some time. In this chapter, you will learn what makes time computations so vexing, and how the new Date and Time API solves these issues.

The key points of this chapter are:

- All `java.time` objects are immutable.
- An `Instant` is a point on the time line (similar to a `Date`).
- In Java time, each day has exactly 86,400 seconds (i.e., no leap seconds).
- A `Duration` is the difference between two instants.
- `LocalDateTime` has no time zone information.
- `TemporalAdjuster` methods handle common calendar computations, such as finding the first Tuesday of a month.
- `ZonedDateTime` is a point in time in a given time zone (similar to `GregorianCalendar`).
- Use a `Period`, not a `Duration`, when advancing zoned time, in order to account for daylight savings time changes.
- Use `DateTimeFormatter` to format and parse dates and times.

5.1. The Time Line

Historically, the fundamental time unit, the second, was derived from Earth’s rotation around its axis. There are 24 hours or $24 \times 60 \times 60 = 86400$ seconds in a full revolution, so it seems just a question of astronomical measurements to precisely define a second. Unfortunately, Earth wobbles

slightly, and a more precise definition was needed. In 1967, a new precise definition of a second, matching the historical definition, was derived from an intrinsic property of atoms of caesium-133. Since then, a network of atomic clocks keeps the official time.

Ever so often, the official time keepers synchronize the absolute time with the rotation of Earth. At first, the official seconds were slightly adjusted, but starting in 1972, “leap seconds” were occasionally inserted. (In theory, a second might need to be removed once in a while, but that has not yet happened.) There is talk of changing the system again. Clearly, leap seconds are a pain, and many computer systems instead use “smoothing” where time is artificially slowed down or sped up just before the leap second, keeping 86,400 seconds per day. This works because the local time on a computer isn’t all that precise, and computers are used to synchronizing themselves with an external time service.

The Java Date and Time API specification requires that Java uses a time scale that

- Has 86,400 seconds per day
- Exactly matches the official time at noon each day
- Closely matches it elsewhere, in a precisely defined way

That gives Java the flexibility to adjust to future changes in the official time.

In Java, an `Instant` represents a point on the time line. An origin, called the *epoch*, is arbitrarily set at midnight of January 1, 1970 at the prime meridian that passes through the Greenwich Royal Observatory in London. This is the same convention used in the Unix/POSIX time. Starting from the origin, time is measured in 86,400 seconds per day, forwards and backwards, in nanosecond precision. The `Instant` values go back as far as a billion years (`Instant.MIN`). That’s not quite enough to express the age of the universe (around 13.5 billion years), but it should be enough for all practical purposes. After all, a billion years ago, the earth was covered in ice and populated by microscopic ancestors of today’s plants and animals. The largest value, `Instant.MAX`, is December 31 of the year 1,000,000,000. The static method call `Instant.now()` gives the current instant. You can compare two instants with the `equals` and `compareTo` methods in the usual way, so you can use instants as timestamps.

To find out the difference between two instants, use the static method `Duration.between`. For example, here is how you can measure the running time of an algorithm:

[Click here to view code image](#)

```
Instant start = Instant.now();
runAlgorithm();
Instant end = Instant.now();
Duration timeElapsed = Duration.between(start, end);
long millis = timeElapsed.toMillis();
```

A `Duration` is the amount of time between two instants. You can get the length of a `Duration` in conventional units by calling `toNanos`, `toMillis`, `toSeconds`, `toMinutes`, `toHours`, or `toDays`.

Durations require more than a `long` value for their internal storage. The number of seconds is stored in a `long`, and the number of nanoseconds in an additional `int`. If you want to make computations in nanosecond accuracy, and you actually need the entire range of a `Duration`, then you can use one of the methods in [Table 5–1](#). Otherwise, you can just call `toNanos` and do your calculations with `long` values.

Method	Description
<code>plus, minus</code>	Adds a duration to, or subtracts a duration from, this Instant or Duration.
<code>plusNanos, plusMillis, plusSeconds, plusMinutes, plusHours, plusDays</code>	Adds a number of the given time units to this Instant or Duration.
<code>minusNanos, minusMillis, minusSeconds, minusMinutes, minusHours, minusDays</code>	Subtracts a number of the given time units from this Instant or Duration.
<code>multipliedBy, dividedBy, negated</code>	Returns a duration that is obtained by multiplying or dividing this Duration by a given long, or by -1. Note that you can scale only durations, not instants.
<code>isZero, isNegative</code>	Checks whether this Duration is zero or negative.

Table 5–1 Arithmetic Operations for Time Instants and Durations



NOTE

It takes almost 300 years of nanoseconds to overflow a long.

For example, if you want to check whether an algorithm is at least ten times faster than another, you can compute

[Click here to view code image](#)

```
Duration timeElapsed2 = Duration.between(start2, end2);
boolean overTenTimesFaster =
    timeElapsed.multipliedBy(10).minus(timeElapsed2).isNegative();
// Or timeElapsed.toNanos() * 10 < timeElapsed2.toNanos()
```



NOTE

The `Instant` and `Duration` classes are immutable, and all methods, such as `multipliedBy` or `minus`, return a new instance.

5.2. Local Dates

Now let us turn from absolute time to human time. There are two kinds of human time in the new Java API, *local date/time* and *zoned time*. Local date/time has a date and/or time of day, but no associated time zone information. A local date is, for example, June 14, 1903 (the day on which Alonzo Church, inventor of the lambda calculus, was born). Since that date has neither a time of day nor time zone information, it does not correspond to a precise instant of time. In contrast, July 16, 1969, 09:32:00 EDT (the launch of Apollo 11) is a zoned date/time, representing a precise instant on the time line.

There are many calculations where time zones are not required, and in some cases they can even be

a hindrance. Suppose you schedule a meeting every week at 10:00. If you add 7 days (that is, $7 \times 24 \times 60 \times 60$ seconds) to the last zoned time, and you happen to cross the daylight savings time boundary, the meeting will be an hour too early or too late!

For that reason, the API designers recommend that you do not use zoned time unless you really want to represent absolute time instances. Birthdays, holidays, schedule times, and so on are usually best represented as local dates or times.

A `LocalDate` is a date, with a year, month, and day of the month. To construct one, you can use the `now` or `of` static methods:

[Click here to view code image](#)

```
LocalDate today = LocalDate.now(); // Today's date
LocalDate alonzosBirthday = LocalDate.of(1903, 6, 14);
alonzoBirthday = LocalDate.of(1903, Month.JUNE, 14);
// Uses the Month enumeration
```

Unlike the irregular conventions in Unix and `java.util.Date`, where months are zero-based and years are counted from 1900, you supply the usual numbers for the month of year. Alternatively, you can use the `Month` enumeration.

[Table 5–2](#) shows the most useful methods for working with `LocalDate` objects.

Method	Description
<code>now, of</code>	These static methods construct a <code>LocalDate</code> , either from the current time or from a given year, month, and day.
<code>plusDays, plusWeeks, plusMonths, plusYears</code>	Adds a number of days, weeks, months, or years to this <code>LocalDate</code> .
<code>minusDays, minusWeeks, minusMonths, minusYears</code>	Subtracts a number of days, weeks, months, or years from this <code>LocalDate</code> .
<code>plus, minus</code>	Adds a <code>Duration</code> or <code>Period</code> .
<code>withDayOfMonth, withDayOfYear, withMonth, withYear</code>	Returns a new <code>LocalDate</code> with the day of month, day of year, month, or year changed to the given value.
<code>getDayOfMonth</code>	Gets the day of the month (between 1 and 31).
<code>getDayOfYear</code>	Gets the day of the year (between 1 and 366).
<code>getDayOfWeek</code>	Gets the day of the week, returning a value of the <code>DayOfWeek</code> enumeration.

getMonth, getMonthValue	Gets the month as a value of the Month enumeration, or as a number between 1 and 12.
getYear	Gets the year, between -999,999,999 and 999,999,999.
until	Gets the Period, or the number of the given ChronoUnits, between two dates.
isBefore, isAfter	Compares this LocalDate with another.
isLeapYear	Returns true if the year is a leap year—that is, if it is divisible by 4 but not by 100, or divisible by 400. The algorithm is applied for all past years, even though that is historically inaccurate. (Leap years were invented in the year -46, and the rules involving divisibility by 100 and 400 were introduced in the Gregorian calendar reform of 1582. The reform took over 300 years to become universal.)

Table 5–2 LocalDate Methods

For example, *Programmer’s Day* is the 256th day of the year. Here is how you can easily compute it:

[Click here to view code image](#)

```
LocalDate programmersDay = LocalDate.of(2014, 1, 1).plusDays(255);
// September 13, but in a leap year it would be September 12
```

Recall that the difference between two time instants is a Duration. The equivalent for local dates is a Period, which expresses a number of elapsed years, months, or days. You can call birthday.plus(Period.ofYears(1)), to get the birthday next year. Of course, you can also just call birthday.plusYears(1). But birthday.plus(Duration.ofDays(365)) won’t produce the correct result in a leap year.

The until method yields the difference between two local dates. For example,

[Click here to view code image](#)

```
independenceDay.until(christmas)
```

yields a period of 5 months and 21 days. That is actually not terribly useful because the number of days per month varies. To find the number of days, use

[Click here to view code image](#)

```
independenceDay.until(christmas, ChronoUnit.DAYS) // 174 days
```



CAUTION

Some methods in [Table 5–2](#) could potentially create nonexistent dates. For example, adding one month to January 31 should not yield February 31. Instead of throwing an exception, these methods return the last valid day of the month. For example,

[Click here to view code image](#)

```
LocalDate.of(2016, 1, 31).plusMonths(1)
```

and

[Click here to view code image](#)

```
LocalDate.of(2016, 3, 31).minusMonths(1)
```

yield February 29, 2016.

The `getDayOfWeek` yields the weekday, as a value of the `DayOfWeek` enumeration. `DayOfWeek.MONDAY` has the numerical value 1, and `DayOfWeek.SUNDAY` has the value 7. For example,

[Click here to view code image](#)

```
LocalDate.of(1900, 1, 1).getDayOfWeek().getValue()
```

yields 1. The `DayOfWeek` enumeration has convenience methods `plus` and `minus` to compute weekdays modulo 7. For example, `DayOfWeek.SATURDAY.plus(3)` yields `DayOfWeek.TUESDAY`.



NOTE

The weekend days actually come at the end of the week. This is different from `java.util.Calendar`, where Sunday has value 1 and Saturday value 7.

In addition to `LocalDate`, there are also classes `MonthDay`, `YearMonth`, and `Year` to describe partial dates. For example, December 25 (with the year unspecified) can be represented as a `MonthDay`.

5.3. Date Adjusters

For scheduling applications, you often need to compute dates such as “the first Tuesday of every month.” The `TemporalAdjusters` class provides a number of static methods for common adjustments. You pass the result of an adjustment method to the `with` method. For example, the first Tuesday of a month can be computed like this:

[Click here to view code image](#)

```
LocalDate firstTuesday = LocalDate.of(year, month, 1).with(
    TemporalAdjusters.nextOrSame(DayOfWeek.TUESDAY));
```

As always, the `with` method returns a new `LocalDate` object without modifying the original. [Table 5–3](#) shows the available adjusters.

Method	Description
<code>next(weekday), previous(weekday)</code>	Next or previous date that falls on the given weekday
<code>nextOrSame(weekday), previousOrSame(weekday)</code>	Next or previous date that falls on the given weekday, starting from the given date
<code>dayOfWeekInMonth(n, weekday)</code>	The nth weekday in the month
<code>lastInMonth(weekday)</code>	The last weekday in the month
<code>firstDayOfMonth(), firstDayOfNextMonth(), firstDayOfNextYear(), lastDayOfMonth(), lastDayOfPreviousMonth(), lastDayOfYear()</code>	The date described in the method name

Table 5–3 Date Adjusters in the TemporalAdjusters Class

You can also roll your own adjuster by implementing the `TemporalAdjuster` interface. Here is an adjuster for computing the next weekday.

[Click here to view code image](#)

```
TemporalAdjuster NEXT_WORKDAY = w -> {
    LocalDate result = (LocalDate) w;
    do {
        result = result.plusDays(1);
    } while (result.getDayOfWeek().getValue() >= 6);
    return result;
};

LocalDate backToWork = today.with(NEXT_WORKDAY);
```

Note that the parameter of the lambda expression has type `Temporal`, and it must be cast to `LocalDate`. You can avoid this cast with the `ofDateAdjuster` method that expects a lambda of type `UnaryOperator<LocalDate>`.

[Click here to view code image](#)

```
TemporalAdjuster NEXT_WORKDAY = TemporalAdjusters.ofDateAdjuster(w -> {
    LocalDate result = w; // No cast
    do {
        result = result.plusDays(1);
    } while (result.getDayOfWeek().getValue() >= 6);
    return result;
});
```

5.4. Local Time

A `LocalTime` represents a time of day, such as 15:30:00. You can create an instance with the `now` or `of` methods:

[Click here to view code image](#)

```
LocalTime rightNow = LocalTime.now();
LocalTime bedtime = LocalTime.of(22, 30); // OR LocalTime.of(22, 30, 0)
```

[Table 5–4](#) shows common operations with local times. The `plus` and `minus` operations wrap

around a 24-hour day. For example,

[Click here to view code image](#)

```
LocalTime wakeup = bedtime.plusHours(8); // wakeup is 6:30:00
```

Method	Description
now, of	These static methods construct a LocalTime, either from the current time, or from the given hours, minutes, and optionally, seconds and nanoseconds.
plusHours, plusMinutes, plusSeconds, plusNanos	Adds a number of hours, minutes, seconds, or nanoseconds to this LocalTime.
minusHours, minusMinutes, minusSeconds, minusNanos	Subtracts a number of hours, minutes, seconds, or nanoseconds from this LocalTime.
plus, minus	Adds a Duration.
withHour, withMinute, withSecond, withNano	Returns a new LocalTime with the hour, minute, second, or nanosecond changed to the given value.
getHour, getMinute, getSecond, getNano	Gets the hour, minute, second, or nanosecond of this LocalTime.
toSecondOfDay, toNanoOfDay	Returns the number of seconds or nanoseconds between midnight and this LocalTime.
isBefore, isAfter	Compares this LocalTime with another.

Table 5–4 LocalTime Methods



NOTE

LocalTime doesn't concern itself with AM/PM. That silliness is left to a formatter—see [Section 5.6, “Formatting and Parsing,” on page 112](#).

There is a `LocalDateTime` class, representing a date and time. That class is suitable for storing points in time in a fixed time zone, for example, for a schedule of classes or events. However, if you need to make calculations that span the daylight savings time, or if you need to deal with users in different time zones, you should use the `ZonedDateTime` class that we discuss next.

5.5. Zoned Time

Time zones, perhaps because they are an entirely human creation, are even messier than the complications caused by the earth's irregular rotation. In a rational world, we'd all follow the clock in Greenwich, and some of us would eat our lunch at 02:00, others at 22:00. Our stomachs would figure it out. This is actually done in China, which spans four conventional time zones. Elsewhere, we have time zones with irregular and shifting boundaries, and, to make matters worse, the daylight savings time.

As capricious as the time zones may appear to the enlightened, they are a fact of life. When you implement a calendar application, it needs to work for people who fly from one country to another. When you have a conference call at 10:00 in New York, but happen to be in Berlin, you expect to be alerted at the correct local time.

The Internet Assigned Numbers Authority (IANA) keeps a database of all known time zones around the world (<https://www.iana.org/time-zones>), which is updated several times per year. The bulk of the updates deals with the changing rules for daylight savings time. Java uses the IANA database.

Each time zone has an ID, such as `America/New_York` or `Europe/Berlin`. To find out all available time zones, call `ZoneId.getAvailableIds`. At the time of this writing, there were almost 600 IDs.

Given a time zone ID, the static method `ZoneId.of(id)` yields a `ZoneId` object. You can use that object to turn a `LocalDateTime` object into a `ZonedDateTime` object by calling `local.atZone(zoneId)`, or you can construct a `ZonedDateTime` by calling the static method `ZonedDateTime.of(year, month, day, hour, minute, second, nano, zoneId)`. For example,

[Click here to view code image](#)

```
ZonedDateTime apollo11Launch = ZonedDateTime.of(1969, 7, 16, 9, 32, 0, 0,  
    ZoneId.of("America/New_York"));  
// 1969-07-16T09:32-04:00[America/New_York]
```

This is a specific instant in time. Call `apollo11Launch.toInstant` to get the `Instant`. Conversely, if you have an instant in time, call `instant.atZone(ZoneId.of("UTC"))` to get the `ZonedDateTime` at the Greenwich Royal Observatory, or use another `ZoneId` to get it elsewhere on the planet.



NOTE

UTC stands for “coordinated universal time,” and the acronym is a compromise between the aforementioned English and the French “temps universel coordonné,” having the distinction of being incorrect in either language. UTC is the time at the Greenwich Royal Observatory, without daylight savings time.

Many of the methods of `ZonedDateTime` are the same as those of `LocalDateTime` (see [Table 5–5](#)). Most are straightforward, but daylight savings time introduces some complications.

Method	Description
now, of, ofInstant	These static methods construct a ZonedDateTime from the current time, or from a year, month, day, hour, minute, second, nanosecond (or a LocalDate and LocalTime), and ZoneId, or from an Instant and ZoneId.
plusDays, plusWeeks, plusMonths, plusYears, plusHours, plusMinutes, plusSeconds, plusNanos	Adds a number of temporal units to this ZonedDateTime.
minusDays, minusWeeks, minusMonths, minusYears, minusHours, minusMinutes, minusSeconds, minusNanos	Subtracts a number of temporal units from this LocalDate.
plus, minus	Adds a Duration or Period.
withDayOfMonth, withDayOfYear, withMonth, withYear, withHour, withMinute, withSecond, withNano	Returns a new ZonedDateTime, with one temporal unit changed to the given value.
withZoneSameInstant, withZoneSameLocal	Returns a new ZonedDateTime in the given time zone, either representing the same instant or the same local time.
getDayOfMonth	Gets the day of the month (between 1 and 31).
getDayOfYear	Gets the day of the year (between 1 and 366).
getDayOfWeek	Gets the day of the week, returning a value of the DayOfWeek enumeration.
getMonth, getMonthValue	Gets the month as a value of the Month enumeration, or as a number between 1 and 12.
getYear	Gets the year, between -999,999,999 and 999,999,999.
getHour, getMinute, getSecond, getNano	Gets the hour, minute, second, or nanosecond of this ZonedDateTime.
getOffset	Gets the offset from UTC, as a ZoneOffset instance. Offsets can vary from -12:00 to +14:00. Some time zones have fractional offsets. Offsets change with daylight savings time.
toLocalDate, toLocalTime, toInstant	Yields the local date or local time, or the corresponding instant.
isBefore, isAfter	Compares this ZonedDateTime with another.

Table 5–5 ZonedDateTime Methods

When daylight savings time starts, clocks advance by an hour. What happens when you construct a time that falls into the skipped hour? For example, in 2013, Central Europe switched to daylight savings time on March 31 at 2:00. If you try to construct nonexistent time March 31 2:30, you actually get 3:30.

[Click here to view code image](#)

```
ZonedDateTime skipped = ZonedDateTime.of(  
    LocalDate.of(2013, 3, 31),  
    LocalTime.of(2, 30),  
    ZoneId.of("Europe/Berlin"));  
// Constructs March 31 3:30
```

Conversely, when daylight time ends, clocks are set back by an hour, and there are two instants with the same local time! When you construct a time within that span, you get the earlier of the two.

[Click here to view code image](#)

```
ZonedDateTime ambiguous = ZonedDateTime.of(  
    LocalDate.of(2013, 10, 27), // End of daylight savings time  
    LocalTime.of(2, 30),  
    ZoneId.of("Europe/Berlin"));  
// 2013-10-27T02:30+02:00[Europe/Berlin]  
ZonedDateTime anHourLater = ambiguous.plusHours(1);  
// 2013-10-27T02:30+01:00[Europe/Berlin]
```

An hour later, the time has the same hours and minutes, but the zone offset has changed.

You also need to pay attention when adjusting a date across daylight savings time boundaries. For example, if you set a meeting for next week, don't add a duration of seven days:

[Click here to view code image](#)

```
ZonedDateTime nextMeeting = meeting.plus(Duration.ofDays(7));  
// Caution! Won't work with daylight savings time
```

Instead, use the `Period` class.

[Click here to view code image](#)

```
ZonedDateTime nextMeeting = meeting.plus(Period.ofDays(7)); // OK
```



CAUTION

There is also an `OffsetDateTime` class that represents times with an offset from UTC, but without time zone rules. That class is intended for specialized applications that specifically require the absence of those rules, such as certain network protocols. For human time, use `ZonedDateTime`.

5.6. Formatting and Parsing

The `DateTimeFormatter` class provides three kinds of formatters to print a date/time value:

- Predefined standard formatters (see [Table 5–6](#))

Formatter	Description	Example
BASIC_ISO_DATE	Year, month, day, zone offset without separators	19690716-0500
ISO_LOCAL_DATE, ISO_LOCAL_TIME, ISO_LOCAL_DATE_TIME	Separators -, :, T	1969-07-16, 09:32:00, 1969-07-16T09:32:00
ISO_OFFSET_DATE, ISO_OFFSET_TIME, ISO_OFFSET_DATE_TIME	Like ISO_LOCAL_XXX, but with zone offset	1969-07-16-05:00, 09:32:00-05:00, 1969-07-16T09:32:00-05:00
ISO_ZONED_DATE_TIME	With zone offset and zone ID	1969-07-16T09:32:00-05:00[America/New_York]
ISO_INSTANT	In UTC, denoted by the Z zone ID	1969-07-16T14:32:00Z
ISO_DATE, ISO_TIME, ISO_DATE_TIME	Like ISO_OFFSET_DATE, ISO_OFFSET_TIME, ISO_ZONED_DATE_TIME, but the zone information is optional	1969-07-16-05:00, 09:32:00-05:00, 1969-07-16T09:32:00-05:00[America/New_York]
ISO_ORDINAL_DATE	The year and day of year, for LocalDate	1969-197
ISO_WEEK_DATE	The year, week, and day of week, for LocalDate	1969-W29-3
RFC_1123_DATE_TIME	The standard for email timestamps, codified in RFC 822 and updated to four digits for the year in RFC 1123	Wed, 16 Jul 1969 09:32:00 -0500

Table 5–6 Predefined Formatters

- Locale-specific formatters
- Formatters with custom patterns

To use one of the standard formatters, simply call its `format` method:

[Click here to view code image](#)

```
String formatted = DateTimeFormatter.ISO_DATE_TIME.format(apollo11launch);
// 1969-07-16T09:32:00-05:00[America/New_York]
```

The standard formatters are mostly intended for machine-readable timestamps. To present dates and times to human readers, use a locale-specific formatter. There are four styles, SHORT, MEDIUM, LONG, and FULL, for both date and time—see [Table 5–7](#).

Style	Date	Time
SHORT	7/16/69	9:32 AM
MEDIUM	Jul 16, 1969	9:32:00 AM
LONG	July 16, 1969	9:32:00 AM EDT
FULL	Wednesday, July 16, 1969	9:32:00 AM EDT

Table 5–7 Locale-Specific Formatting Styles

The static methods `ofLocalizedDate`, `ofLocalizedTime`, and `ofLocalDateTime` create such a formatter. For example:

[Click here to view code image](#)

```
DateTimeFormatter formatter = DateTimeFormatter.ofLocalDateTime(FormatStyle.LONG);
String formatted = formatter.format(apollo11launch);
// July 16, 1969 9:32:00 AM EDT
```

These methods use the default locale. To change to a different locale, simply use the `withLocale` method.

[Click here to view code image](#)

```
formatted = formatter.withLocale(Locale.FRENCH).format(apollo11launch);
// 16 juillet 1969 09:32:00 EDT
```



NOTE

The `java.time.format.DateTimeFormatter` class is intended as a replacement for `java.util.DateFormat`. If you need an instance of the latter for backwards compatibility, call `formatter.toFormat()`.

Finally, you can roll your own date format by specifying a pattern. For example,

[Click here to view code image](#)

```
formatter = DateTimeFormatter.ofPattern("E yyyy-MM-dd HH:mm");
```

formats a date in the form `Wed 1969-07-16 09:32`. Each letter denotes a different time field, and the number of times the letter is repeated selects a particular format, according to rules that are arcane and seem to have organically grown over time. [Table 5–8](#) shows the most useful pattern elements.

ChronoField or Purpose	Examples
ERA	G: AD, GGGG: Anno Domini, GGGGG: A
YEAR_OF_ERA	yy: 69, yyyy: 1969
MONTH_OF_YEAR	M: 7, MM: 07, MMM: Jul, MMMM: July, MMMMM: J
DAY_OF_MONTH	d: 6, dd: 06
DAY_OF_WEEK	e: 3, E: Wed, EEEE: Wednesday, EEEEE: W
HOUR_OF_DAY	H: 9, HH: 09
CLOCK_HOUR_OF_AM_PM	K: 9, KK: 09
AMPM_OF_DAY	a: AM
MINUTE_OF_HOUR	mm: 02
SECOND_OF_MINUTE	ss: 00
NANO_OF_SECOND	nnnnnn: 000000
Time zone ID	VV: America/New_York
Time zone name	z: EDT, zzzz: Eastern Daylight Time
Zone offset	x: -04, xx: -0400, xxx: -04:00, XXX: same, but use Z for zero
Localized zone offset	O: GMT-4, O000: GMT-04:00

Table 5–8 Commonly Used Formatting Symbols for Date/Time Formats

To parse a date/time value from a string, use one of the static `parse` methods. For example,

[Click here to view code image](#)

```
LocalDate churchsBirthday = LocalDate.parse("1903-06-14");
ZonedDateTime apollo11Launch =
    ZonedDateTime.parse("1969-07-16 03:32:00-0400",
        DateTimeFormatter.ofPattern("yyyy-MM-dd HH:mm:ssxx"));
```

The first call uses the standard `ISO_LOCAL_DATE` formatter, the second one a custom formatter.

5.7. Interoperating with Legacy Code

As a brand-new creation, the Java Date and Time API will have to interoperate with existing classes, in particularicular, the ubiquitous `java.util.Date`, `java.util.GregorianCalendar`, and `java.sql.Date/Time/Timestamp`.

The `Instant` class is a close analog to `java.util.Date`. In Java 8, that class has two added methods: the `toInstant` method that converts a `Date` to an `Instant`, and the static `from` method that converts in the other direction.

Similarly, `ZonedDateTime` is a close analog to `java.util.GregorianCalendar`, and that class has gained conversion methods in Java 8. The `toZonedDateTime` method converts a `GregorianCalendar` to a `ZonedDateTime`, and the static `from` method does the opposite conversion.

Another set of conversions is available for the date and time classes in the `java.sql` package. You can also pass a `DateTimeFormatter` to legacy code that uses `java.text.Format`. [Table 5–9](#) summarizes these conversions.

Classes	To Legacy Class	From Legacy Class
Instant ↔ <code>java.util.Date</code>	<code>Date.from(instant)</code>	<code>date.toInstant()</code>
ZonedDateTime ↔ <code>java.util.GregorianCalendar</code>	<code>GregorianCalendar.from(zonedDateTime)</code>	<code>cal.toZonedDateTime()</code>
Instant ↔ <code>java.sql.Timestamp</code>	<code>TimeStamp.from(instant)</code>	<code>timestamp.toInstant()</code>
LocalDateTime ↔ <code>java.sql.Timestamp</code>	<code>Timestamp.valueOf(localDateTime)</code>	<code>timeStamp.toLocalDateTime()</code>
LocalDate ↔ <code>java.sql.Date</code>	<code>Date.valueOf(localDate)</code>	<code>date.toLocalDate()</code>
LocalTime ↔ <code>java.sql.Time</code>	<code>Time.valueOf(localTime)</code>	<code>time.toLocalTime()</code>
DateTimeFormatter → <code>java.text.DateFormat</code>	<code>formatter.toFormat()</code>	None
<code>java.util.TimeZone</code> → <code>ZoneId</code>	<code>Timezone.getTimeZone(id)</code>	<code>timeZone.toZoneId()</code>
<code>java.nio.file.attribute.FileTime</code> → <code>Instant</code>	<code>FileTime.from(instant)</code>	<code>fileTime.toInstant()</code>

Table 5–9 Conversions between `java.time` Classes and Legacy Classes

Exercises

1. Compute Programmer’s Day without using `plusDays`.
2. What happens when you add one year to `LocalDate.of(2000, 2, 29)`? Four years? Four times one year?
3. Implement a method `next` that takes a `Predicate<LocalDate>` and returns an adjuster yielding the next date fulfilling the predicate. For example,

[Click here to view code image](#)

```
today.with(next(w -> getDayOfWeek().getValue() < 6))
```

computes the next workday.

4. Write an equivalent of the Unix `cal` program that displays a calendar for a month. For example, `java Cal 3 2013` should display

1	2	3				
4	5	6	7	8	9	10
11	12	13	14	15	16	17

18 19 20 21 22 23 24
25 26 27 28 29 30 31

indicating that March 1 is a Friday. (Show the weekend at the end of the week.)

5. Write a program that prints how many days you have been alive.
6. List all Friday the 13th in the twentieth century.
7. Implement a `TimeInterval` class that represents an interval of time, suitable for calendar events (such as a meeting on a given date from 10:00 to 11:00). Provide a method to check whether two intervals overlap.
8. Obtain the offsets of today's date in all supported time zones for the current time instant, turning `ZoneId.getAvailableIds` into a stream and using stream operations.
9. Again using stream operations, find all time zones whose offsets aren't full hours.
10. Your flight from Los Angeles to Frankfurt leaves at 3:05 pm local time and takes 10 hours and 50 minutes. When does it arrive? Write a program that can handle calculations like this.
11. Your return flight leaves Frankfurt at 14:05 and arrives in Los Angeles at 16:40. How long is the flight? Write a program that can handle calculations like this.
12. Write a program that solves the problem described at the beginning of [Section 5.5, “Zoned Time,”](#) on page [109](#). Read a set of appointments in different time zones and alert the user which ones are due within the next hour in local time.

Chapter 6. Concurrency Enhancements

Topics in This Chapter

- [6.1 Atomic Values](#)
- [6.2 ConcurrentHashMap Improvements](#)
- [6.3 Parallel Array Operations](#)
- [6.4 Completable Futures](#)
- [Exercises](#)

Concurrent programming is hard, and it is harder without the right tools. Early Java releases had minimal support for concurrency, and programmers busily created code with deadlocks and race conditions. The robust `java.util.concurrent` package didn't appear until Java 5. That package gives us threadsafe collections and thread pools, allowing many application programmers to write concurrent programs without using locks or starting threads. Unfortunately, `java.util.concurrent` is a mix of useful utilities for the application programmer and power tools for library authors, without much effort to separate the two. In this chapter, we focus squarely on the needs of the application programmer.

The key points of this chapter are:

- Updating atomic variables has become simpler with the `updateAndGet/accumulateAndGet` methods.
- `LongAccumulator/DoubleAccumulator` are more efficient than `AtomicLong/AtomicDouble` under high contention.
- Updating entries in a `ConcurrentHashMap` has become simpler with the `compute and merge` methods.
- `ConcurrentHashMap` now has bulk operations `search, reduce, forEach, with` variants operating on keys, values, keys and values, and entries.
- A set view lets you use a `ConcurrentHashMap` as a `Set`.
- The `Arrays` class has methods for parallel sorting, filling, and prefix operations.
- Completable futures let you compose asynchronous operations.

6.1. Atomic Values

Since Java 5, the `java.util.concurrent.atomic` package provided classes for lock-free mutation of variables. For example, you can safely generate a sequence of numbers like this:

[Click here to view code image](#)

```
public static AtomicLong nextNumber = new AtomicLong();
// In some thread ...
long id = nextNumber.incrementAndGet();
```

The `incrementAndGet` method atomically increments the `AtomicLong` and returns the post-increment value. That is, the operations of getting the value, adding 1, setting it, and producing the new value cannot be interrupted. It is guaranteed that the correct value is computed and returned, even

if multiple threads access the same instance concurrently.

There are methods for atomically setting, adding, and subtracting values, but if you want to make a more complex update, you have to use the `compareAndSet` method. For example, suppose you want to keep track of the largest value that is observed by different threads. The following won't work:

[Click here to view code image](#)

```
public static AtomicLong largest = new AtomicLong();
// In some thread...
largest.set(Math.max(largest.get(), observed)); // Error—race condition!
```

This update is not atomic. Instead, compute the new value and use `compareAndSet` in a loop:

[Click here to view code image](#)

```
do {
    oldValue = largest.get();
    newValue = Math.max(oldValue, observed);
} while (!largest.compareAndSet(oldValue, newValue));
```

If another thread is also updating `largest`, it is possible that it has beat this thread to it. Then `compareAndSet` will return `false` without setting the new value. In that case, the loop tries again, reading the updated value and trying to change it. Eventually, it will succeed replacing the existing value with the new one. This sounds tedious, but the `compareAndSet` method maps to a processor operation that is faster than using a lock.

In Java 8, you don't have to write the loop boilerplate any more. Instead, you provide a lambda expression for updating the variable, and the update is done for you. In our example, we can call

[Click here to view code image](#)

```
largest.updateAndGet(x -> Math.max(x, observed));
```

or

[Click here to view code image](#)

```
largest.accumulateAndGet(observed, Math::max);
```

The `accumulateAndGet` method takes a binary operator that is used to combine the atomic value and the supplied argument.

There are also methods `getAndUpdate` and `getAndAccumulate` that return the old value.



NOTE

These methods are also provided for the classes `AtomicInteger`, `AtomicIntegerArray`, `AtomicIntegerFieldUpdater`, `AtomicLongArray`, `AtomicLongFieldUpdater`, `AtomicReference`, `AtomicReferenceArray`, and `AtomicReferenceFieldUpdater`.

When you have a very large number of threads accessing the same atomic values, performance suffers because the optimistic updates require too many retries. Java 8 provides classes `LongAdder` and `LongAccumulator` to solve this problem. A `LongAdder` is composed of multiple variables whose collective sum is the current value. Multiple threads can update different summands, and new summands are automatically provided when the number of threads increases. This is efficient in the

common situation where the value of the sum is not needed until after all work has been done. The performance improvement can be substantial—see Exercise 3.

If you anticipate high contention, you should simply use a `LongAdder` instead of an `AtomicLong`. The method names are slightly different. Call `increment` to increment a counter or `add` to add a quantity, and `sum` to retrieve the total.

[Click here to view code image](#)

```
final LongAdder adder = new LongAdder();
for (...) {
    pool.submit(() -> {
        while (...) {
            ...
            if (...) adder.increment();
        }
    });
...
long total = adder.sum();
```



NOTE

Of course, the `increment` method does *not* return the old value. Doing that would undo the efficiency gain of splitting the sum into multiple summands.

The `LongAccumulator` generalizes this idea to an arbitrary accumulation operation. In the constructor, you provide the operation, as well as its neutral element. To incorporate new values, call `accumulate`. Call `get` to obtain the current value. The following has the same effect as a `LongAdder`:

[Click here to view code image](#)

```
LongAccumulator adder = new LongAccumulator(Long::sum, 0);
// In some thread...
adder.accumulate(value);
```

Internally, the accumulator has variables a_1, a_2, \dots, a_n . Each variable is initialized with the neutral element (0 in our example).

When `accumulate` is called with value v , then one of them is atomically updated as $a_i = a_i \text{ op } v$, where `op` is the accumulation operation written in infix form. In our example, a call to `accumulate` computes $a_i = a_i + v$ for some i .

The result of `get` is $a_1 \text{ op } a_2 \text{ op } \dots \text{ op } a_n$. In our example, that is the sum of the accumulators, $a_1 + a_2 + \dots + a_n$.

If you choose a different operation, you can compute maximum or minimum (see Exercise 4). In general, the operation must be associative and commutative. That means that the final result must be independent of the order in which the intermediate values were combined.

There are also `DoubleAdder` and `DoubleAccumulator` that work in the same way, except with `double` values.



NOTE

Another addition to Java 8 is the `StampedLock` class that can be used to implement optimistic

reads. I don't recommend that application programmers use locks, but here is how it is done. You first call `tryOptimisticRead`, upon which you get a "stamp." Read your values and check whether the stamp is still valid (i.e., no other thread has obtained a write lock). If so, you can use the values. If not, get a read lock (which blocks any writers). Here is an example.

[Click here to view code image](#)

```
public class Vector {  
    private int size;  
    private Object[] elements;  
    private StampedLock lock = new StampedLock();  
  
    public Object get(int n) {  
        long stamp = lock.tryOptimisticRead();  
        Object[] currentElements = elements;  
        int currentSize = size;  
        if (!lock.validate(stamp)) { // Someone else had a write lock  
            stamp = lock.readLock(); // Get a pessimistic lock  
            currentElements = elements;  
            currentSize = size;  
            lock.unlockRead(stamp);  
        }  
        return n < currentSize ? currentElements[n] : null;  
    }  
    ...  
}
```

6.2. ConcurrentHashMap Improvements

A classic programmer's saying is, "If you can only have one data structure, make it a hash table." Since Java 5, the `ConcurrentHashMap` has been a workhorse of concurrent programming. A `ConcurrentHashMap` is, of course, threadsafe—multiple threads can add and remove elements without damaging the internal structure. Moreover, it is quite efficient, allowing multiple threads to update different parts of the table concurrently without blocking each other.



NOTE

Some applications use humongous concurrent hash maps, so large that the `size` method is insufficient because it returns an `int`. What is one to do with a map that has over two billion entries? Java 8 introduces a `mappingCount` method that returns the size as a `long`.



NOTE

A hash map keeps all entries with the same hash code in the same "bucket." Some applications use poor hash functions, and as a result all entries end up in a small number of buckets, severely degrading performance. Even generally reasonable hash functions, such as that of the `String` class, can be problematic. For example, an attacker can slow down a program by crafting a large number of strings that hash to the same value. As of Java 8, the concurrent hash map organizes the buckets as trees, not lists, when the key type implements `Comparable`, guaranteeing $O(\log(n))$ performance.

6.2.1. Updating Values

The original version of `ConcurrentHashMap` only had a few methods for atomic updates, which made for somewhat awkward programming. Suppose we want to count how often certain features are observed. As a simple example, suppose multiple threads encounter words, and we want to count their frequencies.

Can we use a `ConcurrentHashMap<String, Long>`? Consider the code for incrementing a count. Obviously, the following is not threadsafe:

[Click here to view code image](#)

```
Long oldValue = map.get(word);
Long newValue = oldValue == null ? 1 : oldValue + 1;
map.put(word, newValue); // Error—might not replace oldValue
```

Another thread might be updating the exact same count at the same time.



NOTE

Some programmers are surprised that a supposedly threadsafe data structure permits operations that are not threadsafe. But there are two entirely different considerations. If multiple threads modify a plain `HashMap`, they can destroy the internal structure (an array of linked lists). Some of the links may go missing, or even go in circles, rendering the data structure unusable.

That will never happen with a `ConcurrentHashMap`. In the example above, the code for `get` and `put` will never corrupt the data structure. But, since the sequence of operations is not atomic, the result is not predictable.

One remedy is to use the `replace` operation, replacing a known old value with a new one, just as you have seen in the preceding section:

[Click here to view code image](#)

```
do {
    oldValue = map.get(word);
    newValue = oldValue == null ? 1 : oldValue + 1;
} while (!map.replace(word, oldValue, newValue));
```

Alternatively, you can use a `ConcurrentHashMap<String, AtomicLong>` or, with Java 8, a `ConcurrentHashMap<String, LongAdder>`. Then the update code is:

[Click here to view code image](#)

```
map.putIfAbsent(word, new LongAdder());
map.get(word).increment();
```

The first statement ensures that there is a `LongAdder` present that we can increment atomically. Since `putIfAbsent` returns the mapped value (either the existing one or the newly put one), you can combine the two statements:

[Click here to view code image](#)

```
map.putIfAbsent(word, new LongAdder()).increment();
```

Java 8 provides methods that make atomic updates more convenient. The `compute` method is called with a key and a function to compute the new value. That function receives the key and the associated

value, or `null` if there is none, and it computes the new value. For example, here is how we can update a map of integer counters:

[Click here to view code image](#)

```
map.compute(word, (k, v) -> v == null ? 1 : v + 1);
```



NOTE

You cannot have `null` values in a `ConcurrentHashMap`. There are many methods that use a `null` value as an indication that a given key is not present in the map.

There are also variants `computeIfPresent` and `computeIfAbsent` that only compute a new value when there is already an old one, or when there isn't yet one. A map of `LongAdder` counters can be updated with

[Click here to view code image](#)

```
map.computeIfAbsent(word, k -> new LongAdder()).increment();
```

That is almost like the call to `putIfAbsent` that you saw before, but the `LongAdder` constructor is only called when a new counter is actually needed.

You often need to do something special when a key is added for the first time. The `merge` method makes this particularly convenient. It has a parameter for the initial value that is used when the key is not yet present. Otherwise, the function that you supplied is called, combining the existing value and the initial value. (Unlike `compute`, the function does *not* process the key.)

[Click here to view code image](#)

```
map.merge(word, 1L, (existingValue, newValue) -> existingValue + newValue);
```

or, more simply,

[Click here to view code image](#)

```
map.merge(word, 1L, Long::sum);
```

It doesn't get more concise than that. See Exercise 5 for another compelling application of the `merge` method.



NOTE

If the function that is passed to `compute` or `merge` returns `null`, the existing entry is removed from the map.



CAUTION

When you use `compute` or `merge`, keep in mind that the function that you supply should not do a lot of work. While that function runs, some other updates to the map may be blocked. Of course, that function should also not update other parts of the map.

6.2.2. Bulk Operations

Java 8 provides bulk operations on concurrent hash maps that can safely execute even while other threads operate on the map. The bulk operations traverse the map and operate on the elements they find as they go along. No effort is made to freeze a snapshot of the map in time. Unless you happen to know that the map is not being modified while a bulk operation runs, you should treat its result as an approximation of the map's state.

There are three kinds of operations:

- `search` applies a function to each key and/or value, until the function yields a non-null result. Then the search terminates and the function's result is returned.
- `reduce` combines all keys and/or values, using a provided accumulation function.
- `forEach` applies a function to all keys and/or values.

Each operation has four versions:

- `operationKeys`: operates on keys.
- `operationValues`: operates on values.
- `operation`: operates on keys and values.
- `operationEntries`: operates on `Map.Entry` objects.

With each of the operations, you need to specify a *parallelism threshold*. If the map contains more elements than the threshold, the bulk operation is parallelized. If you want the bulk operation to run in a single thread, use a threshold of `Long.MAX_VALUE`. If you want the maximum number of threads to be made available for the bulk operation, use a threshold of 1.

Let's look at the `search` methods first. Here are the versions:

[Click here to view code image](#)

```
U searchKeys(long threshold, BiFunction<? super K, ? extends U> f)
U searchValues(long threshold, BiFunction<? super V, ? extends U> f)
U search(long threshold, BiFunction<? super K, ? super V, ? extends U> f)
U searchEntries(long threshold, BiFunction<Map.Entry<K, V>, ? extends U> f)
```

For example, suppose we want to find the first word that occurs more than 1,000 times. We need to search keys and values:

[Click here to view code image](#)

```
String result = map.search(threshold, (k, v) -> v > 1000 ? k : null);
```

Then `result` is set to the first match, or to `null` if the search function returns `null` for all inputs.

The `forEach` methods have two variants. The first one simply applies a *consumer* function for each map entry, for example

[Click here to view code image](#)

```
map.forEach(threshold,
(k, v) -> System.out.println(k + " -> " + v));
```

The second variant takes an additional *transformer* function, which is applied first, and its result is passed to the consumer:

[Click here to view code image](#)

```
map.forEach(threshold,
```

```
(k, v) -> k + " -> " + v, // Transformer  
System.out::println); // Consumer
```

The transformer can be used as a filter. Whenever the transformer returns `null`, the value is silently skipped. For example, here we only print the entries with large values:

[Click here to view code image](#)

```
map.forEach(threshold,  
(k, v) -> v > 1000 ? k + " -> " + v : null, // Filter and transformer  
System.out::println); // The nulls are not passed to the consumer
```

The `reduce` operations combine their inputs with an accumulation function. For example, here is how you can compute the sum of all values.

[Click here to view code image](#)

```
Long sum = map.reduceValues(threshold, Long::sum);
```

As with `forEach`, you can also supply a transformer function. Here we compute the length of the longest key:

[Click here to view code image](#)

```
Integer maxlen = map.reduceKeys(threshold,  
String::length, // Transformer  
Integer::max); // Accumulator
```

The transformer can act as a filter, by returning `null` to exclude unwanted inputs. Here, we count how many entries have value > 1000 :

[Click here to view code image](#)

```
Long count = map.reduceValues(threshold,  
v -> v > 1000 ? 1L : null,  
Long::sum);
```



NOTE

If the map is empty, or all entries have been filtered out, the `reduce` operation returns `null`. If there is only one element, its transformation is returned, and the accumulator is not applied.

There are specializations for `int`, `long`, and `double` outputs with suffix `ToInt`, `ToLong`, and `ToDouble`. You need to transform the input to a primitive value and specify a default value and an accumulator function. The default value is returned when the map is empty.

[Click here to view code image](#)

```
long sum = map.reduceValuesToLong(threshold,  
Long::longValue, // Transformer to primitive type  
0, // Default value for empty map  
Long::sum); // Primitive type accumulator
```



CAUTION

These specializations act differently from the object versions where there is only one element to be considered. Instead of returning the transformed element, it is accumulated with the default. Therefore, the default must be the neutral element of the accumulator.

6.2.3. Set Views

Suppose you want a large, threadsafe set instead of a map. There is no `ConcurrentHashSet` class, and you know better than trying to create your own. Of course, you can use a `ConcurrentHashMap` with bogus values, but then you get a map, not a set, and you can't apply operations of the set interface.

The `static newKeySet` method yields a `Set<K>` that is actually a wrapper around a `ConcurrentHashMap<K, Boolean>`. (All map values are `Boolean.TRUE`, but you don't actually care since you just use it as a set.)

[Click here to view code image](#)

```
Set<String> words = ConcurrentHashMap.<String>newKeySet();
```

Of course, if you have an existing map, the `keySet` method yields the set of keys. That set is mutable. If you remove the set's elements, the keys (and their values) are removed from the map. But it doesn't make sense to add elements to the key set, because there would be no corresponding values to add. Java 8 adds a second `keySet` method to `ConcurrentHashMap`, with a default value, to be used when adding elements to the set:

[Click here to view code image](#)

```
Set<String> words = map.keySet(1L);
words.add("Java");
```

If "Java" wasn't already present in `words`, it now has a value of one.

6.3. Parallel Array Operations

The `Arrays` class now has a number of parallelized operations. The static `Arrays.parallelSort` method can sort an array of primitive values or objects. For example,

[Click here to view code image](#)

```
String contents = new String(Files.readAllBytes(
    Paths.get("alice.txt")), StandardCharsets.UTF_8); // Read file into string
String[] words = contents.split("[\\P{L}]+"); // Split along nonletters
Arrays.parallelSort(words);
```

When you sort objects, you can supply a `Comparator`. With all methods, you can supply the bounds of a range, such as

[Click here to view code image](#)

```
values.parallelSort(values.length / 2, values.length); // Sort the upper half
```



NOTE

At first glance, it seems a bit odd that these methods have `parallel` in their name, since the user shouldn't care how the sorting happens. However, the API designers wanted to make it

clear that the sorting is parallelized. That way, users are on notice to avoid comparators with side effect.

The `parallelSetAll` method fills an array with values that are computed from a function. The function receives the element index and computes the value at that location.

[Click here to view code image](#)

```
Arrays.parallelSetAll(values, i -> i % 10);
// Fills values with 0 1 2 3 4 5 6 7 8 9 0 1 2 ...
```

Clearly, this operation benefits from being parallelized. There are versions for all primitive type arrays and for object arrays.

Finally, there is a `parallelPrefix` method that replaces each array element with the accumulation of the prefix for a given associative operation. Huh? Here is an example. Consider the array `[1, 2, 3, 4, ...]` and the `*` operation. After executing `Arrays.parallelPrefix(values, (x, y) -> x * y)`, the array contains

[Click here to view code image](#)

```
[1, 1 × 2, 1 × 2 × 3, 1 × 2 × 3 × 4, ...]
```

Perhaps surprisingly, this computation can be parallelized. First, join neighboring elements, as indicated here:

[Click here to view code image](#)

```
[1, 1 × 2, 3, 3 × 4, 5, 5 × 6, 7, 7 × 8]
```

The gray values are left alone. Clearly, one can make this computation in parallel in separate regions of the array. In the next step, update the indicated elements by multiplying them with elements that are one or two positions below:

[Click here to view code image](#)

```
[1, 1 × 2, 1 × 2 × 3, 1 × 2 × 3 × 4, 5, 5 × 6, 5 × 6 × 7, 5 × 6 × 7 × 8]
```

This can again be done in parallel. After $\log(n)$ steps, the process is complete. This is a win over the straightforward linear computation if sufficient processors are available. On special-purpose hardware, this algorithm is commonly used, and users of such hardware are quite ingenious in adapting it to a variety of problems. Exercise 9 gives a simple example.

6.4. Completable Futures

The `java.util.concurrent` library provides a `Future<T>` interface to denote a value of type `T` that will be available at some point in the future. However, up to now, futures were rather limited. In the following sections, you will see how *completable futures* make it possible to compose asynchronous operations.

6.4.1. Futures

Here is a quick refresher on futures. Consider a method

[Click here to view code image](#)

```
public void Future<String> readPage(URL url)
```

The method reads a web page in a separate thread, which is going to take a while. When you call

[Click here to view code image](#)

```
Future<String> contents = readPage(url);
```

the method returns right away, and you hold in your hands a `Future<String>`. Now suppose we want to extract all URLs from the page in order to build a web crawler. We have a class `Parser` with a method

[Click here to view code image](#)

```
public static List<URL> getLinks(String page)
```

How can we apply that method to the future object? Unfortunately, there is only one way. First, call the `get` method on the future to get its value when it becomes available. Then, process the result:

[Click here to view code image](#)

```
String page = contents.get();
List<URL> links = Parser.getLinks(page);
```

But the call to `get` is a blocking call. We are really no better off than with a method `public String readPage(URL url)` that blocks until the result is available.

Now in fairness, there has been some support for futures in `java.util.concurrent`, but an essential piece was missing. There was no easy way of saying: “When the result becomes available, here is how to process it.” This is the crucial feature that the new `CompletableFuture<T>` class provides.

6.4.2. Composing Futures

Let’s change the `readPage` method so that it returns a `CompletableFuture<String>`. Unlike a plain `Future`, a `CompletableFuture` has a method `thenApply` to which you can pass the post-processing function.

[Click here to view code image](#)

```
CompletableFuture<String> contents = readPage(url);
CompletableFuture<List<String>> links = contents.thenApply(Parser::getLinks);
```

The `thenApply` method doesn’t block either. It returns another future. When the first future has completed, its result is fed to the `getLinks` method, and the return value of that method becomes the final result.

This *composability* is the key aspect of the `CompletableFuture` class. Composing future actions solves a serious problem in programming asynchronous applications. The traditional approach for dealing with nonblocking calls is to use event handlers. The programmer registers a handler for the next action after completion. Of course, if the next action is also asynchronous, then the next action after that is in a different event handler. Even though the programmer thinks in terms of “first do step 1, then step 2, then step 3,” the program logic becomes dispersed in different places. It gets worse when one has to add error handling. Suppose step 2 is “the user logs in”; then we may need to repeat that step since the user can mistype the credentials. Trying to implement such a control flow in a set of event handlers, or to understand it once it has been implemented, is challenging.

With completable futures, you just specify what you want to have done, and in which order. It won’t all happen right away, of course, but what is important is that all the code is in one place.

6.4.3. The Composition Pipeline

In [Chapter 2](#), you saw how a stream pipeline starts with stream creation, then goes through one or more transformations, and finishes with a terminal operation. The same is true for a pipeline of futures.

Start out by generating a `CompletableFuture`, usually with the static method `supplyAsync`. That method requires a `Supplier<T>`, that is, a function with no parameters yielding a `T`. The function is called on a separate thread. In our example, we can start out the pipeline with

[Click here to view code image](#)

```
CompletableFuture<String> contents
    = CompletableFuture.supplyAsync(() -> blockingReadPage(url));
```

There is also a static `runAsync` method that takes a `Runnable`, yielding a `CompletableFuture<Void>`. This is useful if you simply want to schedule one action after another, without passing data between them.



NOTE

All methods ending in `Async` have two variants. One of them runs the provided action on the common `ForkJoinPool`. The other has a parameter of type `java.util.concurrent.Executor`, and it uses the given executor to run the action.

Next, you can call `thenApply` or `thenApplyAsync` to run another action, either in the same thread or another. With either method, you supply a function and you get a `CompletableFuture<U>`, where `U` is the return type of the function. For example, here is a two-stage pipeline for reading and processing the web page:

[Click here to view code image](#)

```
CompletableFuture<List<String>> links
    = CompletableFuture.supplyAsync(() -> blockingReadPage(url))
        .thenApply(Parser::getLinks);
```

You can have additional processing steps. Eventually, you'll be done, and you will need to save the results somewhere. Here, we just print the result.

[Click here to view code image](#)

```
CompletableFuture<Void> links
    = CompletableFuture.supplyAsync(() -> blockingReadPage(url))
        .thenApply(Parser::getLinks)
        .thenAccept(System.out::println);
```

The `thenAccept` method takes a `Consumer`—that is, a function with return type `void`.

Ideally, you would never call `get` on a future. The last step in the pipeline simply deposits the result where it belongs.



NOTE

You don't explicitly start the computation. The static `supplyAsync` method starts it automatically, and the other methods cause it to be continued.

6.4.4. Composing Asynchronous Operations

There is a large number of methods for working with completable futures. Let us first look at those that deal with a single future (see [Table 6–1](#)). For each method shown, there are also two `Async` variants that I don't show. As noted in the preceding section, one of them uses the common `ForkJoinPool`, and the other has an `Executor` parameter. In the table, I use a shorthand notation for the ponderous functional interfaces, writing `T -> U` instead of `Function<? super T, U>`. These aren't actual Java types, of course.

Method	Parameter	Description
<code>thenApply</code>	<code>T -> U</code>	Apply a function to the result.
<code>thenCompose</code>	<code>T -> CompletableFuture<U></code>	Invoke the function on the result and execute the returned future.
<code>handle</code>	<code>(T, Throwable) -> U</code>	Process the result or error.
<code>thenAccept</code>	<code>T -> void</code>	Like <code>thenApply</code> , but with <code>void</code> result.
<code>whenComplete</code>	<code>(T, Throwable) -> void</code>	Like <code>handle</code> , but with <code>void</code> result.
<code>thenRun</code>	<code>Runnable</code>	Execute the <code>Runnable</code> with <code>void</code> result.

Table 6–1 Adding an Action to a `CompletableFuture<T>` Object

You have already seen the `thenApply` method. The calls

[Click here to view code image](#)

```
CompletableFuture<U> future.thenApply(f);  
CompletableFuture<U> future.thenApplyAsync(f);
```

return a future that applies `f` to the result of `future` when it is available. The second call runs `f` in yet another thread.

The `thenCompose` method, instead of taking a function `T -> U`, takes a function `T -> CompletableFuture<U>`. That sounds rather abstract, but it can be quite natural. Consider the action of reading a web page from a given URL. Instead of supplying a method

[Click here to view code image](#)

```
public String blockingReadPage(URL url)
```

it is more elegant to have that method return a future:

[Click here to view code image](#)

```
public CompletableFuture<String> readPage(URL url)
```

Now, suppose we have another method that gets the URL from user input, perhaps from a dialog that won't reveal the answer until the user has clicked the OK button. That, too, is an event in the future:

[Click here to view code image](#)

```
public CompletableFuture<URL> getURLInput(String prompt)
```

Here we have two functions `T -> CompletableFuture<U>` and `U -> CompletableFuture<V>`. Clearly, they compose to a function `T -> CompletableFuture<V>` by calling the second function when the first one has completed. That is exactly what `thenCompose` does.

The third method in [Table 6–1](#) focuses on a different aspect that I have ignored so far: failure. When an exception is thrown in a `CompletableFuture`, it is captured and wrapped in an unchecked `ExecutionException` when the `get` method is called. But perhaps `get` is never called. In order to handle an exception, use the `handle` method. The supplied function is called with the result (or `null` if none) and the exception (or `null` if none), and it gets to make sense of the situation.

The remaining methods have `void` result and are usually used at the end of a processing pipeline.

Now let us turn to methods that combine multiple futures (see [Table 6–2](#)).

Method	Parameters	Description
<code>thenCombine</code>	<code>CompletableFuture<U>, (T, U) -> V</code>	Execute both and combine the results with the given function.
<code>thenAcceptBoth</code>	<code>CompletableFuture<U>, (T, U) -> void</code>	Like <code>thenCombine</code> , but with <code>void</code> result.
<code>runAfterBoth</code>	<code>CompletableFuture<?>, Runnable</code>	Execute the runnable after both complete.
<code>applyToEither</code>	<code>CompletableFuture<T>, T -> V</code>	When a result is available from one or the other, pass it to the given function.
<code>acceptEither</code>	<code>CompletableFuture<T>, T -> void</code>	Like <code>applyToEither</code> , but with <code>void</code> result.
<code>runAfterEither</code>	<code>CompletableFuture<?>, Runnable</code>	Execute the runnable after one or the other completes.
<code>static allOf</code>	<code>CompletableFuture<?>...</code>	Complete with <code>void</code> result after all given futures complete.
<code>static anyOf</code>	<code>CompletableFuture<?>...</code>	Complete with <code>void</code> result after any of the given futures completes.

Table 6–2 Combining Multiple Composition Objects

The first three methods run a `CompletableFuture<T>` and a `CompletableFuture<U>` action in parallel and combine the results.

The next three methods run two `CompletableFuture<T>` actions in parallel. As soon as one of them finishes, its result is passed on, and the other result is ignored.

Finally, the static `allOf` and `anyOf` methods take a variable number of completable futures and yield a `CompletableFuture<Void>` that completes when all of them, or any one of them, completes. No results are propagated.



NOTE

Technically speaking, the methods in this section accept parameters of type `CompletionStage`, not `CompletableFuture`. That is an interface type with almost forty abstract methods, currently implemented only by `CompletableFuture`. Most programmers wouldn't casually implement that interface, so I don't dwell on the distinction.

Exercises

1. Write a program that keeps track of the longest string that is observed by a number of threads. Use an `AtomicReference` and an appropriate accumulator.
2. Does a `LongAdder` help with yielding a sequence of increasing IDs? Why or why not?
3. Generate 1,000 threads, each of which increments a counter 100,000 times. Compare the performance of using `AtomicLong` versus `LongAdder`.
4. Use a `LongAccumulator` to compute the maximum or minimum of the accumulated elements.
5. Write an application in which multiple threads read all words from a collection of files. Use a `ConcurrentHashMap<String, Set<File>>` to track in which files each word occurs. Use the `merge` method to update the map.
6. Repeat the preceding exercise, but use `computeIfAbsent` instead. What is the advantage of this approach?
7. In a `ConcurrentHashMap<String, Long>`, find the key with maximum value (breaking ties arbitrarily). Hint: `reduceEntries`.
8. How large does an array have to be for `Arrays.parallelSort` to be faster than `Arrays.sort` on your computer?
9. You can use the `parallelPrefix` method to parallelize the computation of Fibonacci numbers. We use the fact that the n th Fibonacci number is the top left coefficient of F^n , where $F = \begin{pmatrix} 1 & 1 \\ 1 & 0 \end{pmatrix}$. Make an array filled with 2×2 matrices. Define a `Matrix` class with a multiplication method, use `parallelSetAll` to make an array of matrices, and use `parallelPrefix` to multiply them.
10. Write a program that asks the user for a URL, then reads the web page at that URL, and then displays all the links. Use a `CompletableFuture` for each stage. Don't call `get`. To prevent your program from terminating prematurely, call

[Click here to view code image](#)

```
ForkJoinPool.commonPool().awaitQuiescence(10, TimeUnit.SECONDS);
```

11. Write a method

[Click here to view code image](#)

```
public static <T> CompletableFuture<T> repeat(  
    Supplier<T> action, Predicate<T> until)
```

that asynchronously repeats the action until it produces a value that is accepted by the `until` function, which should also run asynchronously. Test with a function that reads a `java.net.PasswordAuthentication` from the console, and a function that simulates a validity

check by sleeping for a second and then checking that the password is "secret". Hint: Use recursion.

Chapter 7. The Nashorn JavaScript Engine

Topics in This Chapter

- [7.1 Running Nashorn from the Command Line](#)
- [7.2 Running Nashorn from Java](#)
- [7.3 Invoking Methods](#)
- [7.4 Constructing Objects](#)
- [7.5 Strings](#)
- [7.6 Numbers](#)
- [7.7 Working with Arrays](#)
- [7.8 Lists and Maps](#)
- [7.9 Lambdas](#)
- [7.10 Extending Java Classes and Implementing Java Interfaces](#)
- [7.11 Exceptions](#)
- [7.12 Shell Scripting](#)
- [7.13 Nashorn and JavaFX](#)
- [Exercises](#)

For many years, Java bundled the Rhino JavaScript interpreter, an open source JavaScript interpreter written in Java. It is called Rhino because a well-regarded JavaScript book has the image of a rhinoceros on its cover. Rhino works just fine, but it isn't particularly fast. Oracle's engineers realized that they could build a much more efficient JavaScript interpreter using the new JVM instructions designed for dynamic languages. Thus, the Nashorn project was born. Nashorn is the German word for rhinoceros—literally, nose-horn. (You get extra karma for pronouncing it nas-horn, not na-shorn.) Nashorn is very fast, and it lets you integrate Java with JavaScript on a highly performant virtual machine. It is also incredibly compliant with the ECMAScript standard for JavaScript. If you are thinking of giving your users the ability to script your application, or if you are intrigued by the ease of use of reactive programming environments such as node.js, check out Nashorn in Java 8. Not only do you get the benefits of a reasonably well-designed scripting language (i.e., JavaScript), but you have the full power of the JVM behind it.

The key points of this chapter are:

- Nashorn is the successor to the Rhino JavaScript interpreter, with greater performance and fidelity to the JavaScript standard.
- Nashorn is a pleasant environment for experimenting with the Java API.
- You can run JavaScript through the `jjs` interpreter, or from Java via the scripting API.
- Use the predefined JavaScript objects for the most common packages, or the `Java.type` function to access any package.
- Beware of intricacies in the conversion of strings and numbers between JavaScript and Java.
- JavaScript offers a convenient syntax for working with Java lists and maps, as well as

JavaBeans properties.

- You can convert JavaScript functions to Java interfaces in a way that is very similar to using lambda expressions.
- You can extend Java classes and implement Java interfaces in JavaScript, but there are limitations.
- Nashorn has good support for writing shell scripts in JavaScript.
- You can write JavaFX programs in JavaScript, but the integration is not as good as it might be.

7.1. Running Nashorn from the Command Line

Java 8 ships with a command-line tool called `jjs`. Simply launch it, and issue JavaScript commands.

```
$ jjs
jjs> 'Hello, World'
Hello, World
```

You get what's called a "read-eval-print" loop, or REPL, in the world of Lisp, Scala, and so on. Whenever you enter an expression, its value is printed.

```
jjs> 'Hello, World!'.length
13
```



NOTE

As a reminder, in JavaScript, strings can be delimited by '`....`' or "`....`". In this chapter, I will use single quotes for JavaScript strings to give you a visual clue that the code is JavaScript, not Java.

You can define functions and call them:

[Click here to view code image](#)

```
jjs> function factorial(n) { return n <= 1 ? 1 : n * factorial(n - 1) }
function factorial(n) { return n <= 1 ? 1 : n * factorial(n - 1) }
jjs> factorial(10)
3628800
```

You can call Java methods:

[Click here to view code image](#)

```
var input = new java.util.Scanner(
    new java.net.URL('http://horstmann.com').openStream())
input.useDelimiter('$')
var contents = input.next()
```

Now, when you type `contents`, you see the contents of the web page.

Look how refreshing this is. You didn't have to worry about exceptions. You can make experiments dynamically. I wasn't quite sure whether I could read the entire contents by setting the delimiter to `$`, but I tried it out and it worked. And I didn't have to write `public static void main`. I didn't have to compile a thing. I didn't have to make a project in my IDE. The REPL is the easiest way to explore an API. It is a bit odd that one drives Java from JavaScript, but it is also convenient. Note how



TIP

There are two annoyances that keep the JavaScript REPL from being as refreshing as its equivalent in Scala. The Scala REPL has command completion. When you press the Tab key, you get a list of possible completions of the current expression. Admittedly, that is a difficult trick to pull off for dynamically typed languages such as JavaScript. A more fundamental omission is command-line recall. Pressing the ↑ key should get you the previous command. If it doesn't, try installing `rlwrap` and run `rlwrap jjs`. Alternatively, you can run `jjs` inside Emacs. Don't worry—this won't hurt a bit. Start Emacs and hit M-x (i.e., Alt+x or Esc x) `shell` Enter, then type `jjs`. Type expressions as usual. Use M-p and M-n to recall the previous or next line, and the left and right arrow keys to move within a line. Edit a command, then press Enter to see it executed.

7.2. Running Nashorn from Java

In the preceding section, you saw one use case for Nashorn scripting: to experiment with Java APIs from the `jjs` REPL. Another use case is to allow users of your programs to run scripts. In the desktop world, this is quite common. For example, all Microsoft Office applications can be scripted with a language called VB Script that is a descendant of the Basic language. Quite a few people write such scripts, and this capability leads to a form of vendor lock. It is difficult to adopt an alternate office suite that won't run those scripts. If you want to lock in the users of your Java desktop or server app, you can provide the same capabilities.

Running a Nashorn script from Java uses the script engine mechanism that has been introduced in Java 6. You can use that mechanism to execute scripts in any JVM language with a script engine, such as Groovy, JRuby, or Jython. There are also script engines for languages that run outside the JVM such as PHP or Scheme.

To run a script, you need to get a `ScriptEngine` object. If the engine is registered, you can simply get it by name. Java 8 includes an engine with name "nashorn". Here is how to use it:

[Click here to view code image](#)

```
ScriptEngineManager manager = new ScriptEngineManager();
ScriptEngine engine = manager.getEngineByName("nashorn");
Object result = engine.eval("'Hello, World!'.length");
System.out.println(result);
```

You can also read a script from a Reader:

[Click here to view code image](#)

```
Object result = engine.eval(Files.newBufferedReader(path));
```

To make a Java object available to your scripts, use the `put` method of the `ScriptEngine` interface. For example, you can make a JavaFX stage visible, so that you can populate it using JavaScript code:

[Click here to view code image](#)

```
public void start(Stage stage) {
    engine.put("stage", stage);
```

```
        engine.eval(script); // Script code can access the object as stage  
    }
```

Instead of putting variables into the global scope, you can collect them in an object of type `Bindings` and pass that object to the `eval` method:

[Click here to view code image](#)

```
Bindings scope = engine.createBindings();  
scope.put("stage", stage);  
engine.eval(script, scope);
```

This is useful if a set of bindings should not persist for future calls to the `eval` method.

7.3. Invoking Methods

In the preceding section, you saw how the script engine can make Java objects accessible to JavaScript. You can then invoke methods on the provided variables. For example, if the Java code calls

```
engine.put("stage", stage);
```

then the JavaScript code can call

```
stage.setTitle('Hello')
```

In fact, you can also use the syntax

```
stage.title = 'Hello'
```

Nashorn supports a convenient property syntax for getters and setters. If the expression `stage.title` occurs to the left of the `=` operator, it is translated to an invocation of the `setTitle` method. Otherwise it turns into a call `stage.getTitle()`.

You can even use the JavaScript bracket notation to access properties:

```
stage['title'] = 'Hello'
```

Note that the argument of the `[]` operator is a string. In this context, that isn't useful, but you can call `stage[str]` with a string variable and thereby access arbitrary properties.



NOTE

In JavaScript, semicolons at the end of a line are optional. Many JavaScript programmers put them in anyway, but in this chapter, I omit them so that you can easily distinguish between Java and JavaScript code snippets.

JavaScript has no concept of method overloading. There can be only one method with a given name, and it can have any number of parameters of any type. Nashorn attempts to pick the correct Java method, following the number and types of the parameters.

In almost all cases, there is only one Java method that matches the supplied parameters. If there is not, you can manually pick the correct method with the following rather strange syntax:

```
list['remove(Object)'](1)
```

Here, we specify the `remove(Object)` method that removes the `Integer` object 1 from the list. (There is also a `remove(int)` method that removes the object at position 1.)

7.4. Constructing Objects

When you want to construct objects in JavaScript (as opposed to having them handed to you from the script engine), you need to know how to access Java packages. There are two mechanisms.

There are global objects `java`, `javax`, `javafx`, `com`, `org`, and `edu` that yield package and class objects via the dot notation. For example,

[Click here to view code image](#)

```
var javaNetPackage = java.net // A JavaPackage object  
var URL = java.net.URL // A JavaClass object
```

If you need to access a package that does not start with one of the above identifiers, you can find it in the `Package` object, such as `Package.ch.cern`.

Alternatively, call the `Java.type` function:

[Click here to view code image](#)

```
var URL = Java.type('java.net.URL')
```

This is a bit faster than `java.net.URL`, and you get better error checking. (If you make a spelling error such as `java.net.Url`, Nashorn will think it is a package.) But if you want speed and good error handling, you probably shouldn't be using a scripting language in the first place, so I will stick with the shorter form.



NOTE

The Nashorn documentation suggests that class objects should be defined at the top of a script file, just like you place imports at the top of a Java file:

[Click here to view code image](#)

```
var URL = Java.type('java.net.URL')  
var JMath = Java.type('java.lang.Math')  
// Avoids conflict with JavaScript Math object
```

Once you have a class object, you can call static methods:

```
JMath.floorMod(-3, 10)
```

To construct an object, pass the class object to the JavaScript `new` operator. Pass any constructor parameters in the usual way:

[Click here to view code image](#)

```
var URL = java.net.URL  
var url = new URL('http://horstmann.com')
```

If you aren't concerned about efficiency, you can also call

[Click here to view code image](#)

```
var url = new java.net.URL('http://horstmann.com')
```



CAUTION

If you use `Java.type` with `new`, you need an extra set of parentheses:

[Click here to view code image](#)

```
var url = new (Java.type('java.net.URL'))('http://horstmann.com')
```

If you need to specify an inner class, you can do so with the dot notation:

[Click here to view code image](#)

```
var entry = new java.util.AbstractMap.SimpleEntry('hello', 42)
```

Alternatively, if you use `Java.type`, use a `$`, like the JVM does:

[Click here to view code image](#)

```
var Entry = Java.type('java.util.AbstractMap$SimpleEntry')
```

7.5. Strings

Strings in Nashorn are, of course, JavaScript objects. For example, consider the call

[Click here to view code image](#)

```
'Hello'.slice(-2) // Yields 'lo'
```

Here, we call the JavaScript method `slice`. There is no such method in Java.

But the call

```
'Hello'.compareTo('World')
```

also works, even though in JavaScript there is no `compareTo` method. (You just use the `<` operator.)

In this case, the JavaScript string is converted to a Java string. In general, a JavaScript string is converted to a Java string whenever it is passed to a Java method.

Also note that *any* JavaScript object is converted to a string when it is passed to a Java method with a `String` parameter. Consider

[Click here to view code image](#)

```
var path = java.nio.file.Paths.get('/home/')
// A JavaScript RegExp is converted to a Java String!
```

Here, `/home/` is a regular expression. The `Paths.get` method wants a `String`, and it gets one, even though it makes no sense in this situation. One shouldn't blame Nashorn for this. It follows the general JavaScript behavior to turn anything into a string when a string is expected. The same conversion happens for numbers and Boolean values. For example, `'Hello'.slice('-2')` is perfectly valid. The string `'-2'` is silently converted to the number `-2`. It is features such as this one that make programming in a dynamically typed language an exciting adventure.

7.6. Numbers

JavaScript has no explicit support for integers. Its `Number` type is the same as the Java `double` type. When a number is passed to Java code that expects an `int` or `long`, any fractional part is silently removed. For example, `'Hello'.slice(-2.99)` is the same as `'Hello'.slice(-2)`.

For efficiency, Nashorn keeps computations as integers when possible, but that difference is generally transparent. Here is one situation when it is not:

[Click here to view code image](#)

```
var price = 10
java.lang.String.format('Price: %.2f', price)
// Error: f format not valid for java.lang.Integer
```

The value of `price` happens to be an integer, and it is assigned to an `Object` since the `format` method has an `Object...` `varargs` parameter. Therefore, Nashorn produces a `java.lang.Integer`. That causes the `format` method to fail, since the `f` format is intended for floating-point numbers. In this case, you can force conversion to `java.lang.Double` by calling the `Number` function:

[Click here to view code image](#)

```
java.lang.String.format('Unit price: %.2f', Number(price))
```

7.7. Working with Arrays

To construct a Java array, first make a class object:

[Click here to view code image](#)

```
var intArray = Java.type('int[]')
var StringArray = Java.type('java.lang.String[]')
```

Then call the `new` operator and supply the length of the array:

[Click here to view code image](#)

```
var numbers = new intArray(10) // A primitive int[] array
var names = new StringArray(10) // An array of String references
```

Then use the bracket notation in the usual way:

```
numbers[0] = 42
print(numbers[0])
```

You get the length of the array as `numbers.length`. To iterate through all values of the `names` array, use

[Click here to view code image](#)

```
for each (var elem in names)
  Do something with elem
```

This is the equivalent of the enhanced `for` loop in Java. If you need the index values, use the following loop instead:

[Click here to view code image](#)

```
for (var i in names)
  Do something with i and names[i]
```



CAUTION

Even though this loop looks just like the enhanced `for` loop in Java, it visits the index values. JavaScript arrays can be sparse. Suppose you initialize a JavaScript array as

```
var names = []
names[0] = 'Fred'
names[2] = 'Barney'
```

Then the loop `for (var i in names) print(i)` prints 0 and 2.

Java and JavaScript arrays are quite different. When you supply a JavaScript array where a Java array is expected, Nashorn will carry out the conversion. But sometimes, you need to help it along. Given a JavaScript array, use the `Java.to` method to obtain the equivalent Java array:

[Click here to view code image](#)

```
var javaNames = Java.to(names, StringArray) // An array of type String[]
```

Conversely, use `Java.from` to turn a Java array into a JavaScript array:

[Click here to view code image](#)

```
var jsNumbers = Java.from(numbers)
jsNumbers[-1] = 42
```

You need to use `Java.to` to resolve overload ambiguities. For example,

[Click here to view code image](#)

```
java.util.Arrays.toString([1, 2, 3])
```

is ambiguous since Nashorn can't decide whether to convert to an `int[]` or `Object[]` array. In that situation, call

[Click here to view code image](#)

```
java.util.Arrays.toString(Java.to([1, 2, 3], Java.type('int[]')))
```

or simply

[Click here to view code image](#)

```
java.util.Arrays.toString(Java.to([1, 2, 3], 'int[]'))
```

7.8. Lists and Maps

Nashorn provides “syntactic sugar” for Java lists and maps. You can use the bracket operator with any Java `List` to invoke the `get` and `set` methods:

[Click here to view code image](#)

```
var names = java.util.Arrays.asList('Fred', 'Wilma', 'Barney')
var first = names[0]
names[0] = 'Duke'
```

The bracket operator also works for Java maps:

[Click here to view code image](#)

```
var scores = new java.util.HashMap
```

```
scores['Fred'] = 10 // Calls scores.put('Fred', 10)
```

To visit all elements in the map, you can use the JavaScript `for each` loops:

[Click here to view code image](#)

```
for (var key in scores) ...
for each (var value in scores) ...
```

If you want to process keys and values together, simply iterate over the entry set:

[Click here to view code image](#)

```
for each (var e in scores.entrySet())
Process e.key and e.value
```



NOTE

The `for each` loop works for any Java class that implements the `Iterable` interface.

7.9. Lambdas

JavaScript has anonymous functions, such as

[Click here to view code image](#)

```
var square = function(x) { return x * x }
// The right-hand side is an anonymous function
var result = square(2)
// The () operator invokes the function
```

Syntactically, such an anonymous function is very similar to a Java lambda expression. Instead of an arrow after the parameter list, you have the keyword `function`.

You can use an anonymous function as a functional interface argument of a Java method, just like you could use a lambda expression in Java. For example,

[Click here to view code image](#)

```
java.util.Arrays.sort(words,
    function(a, b) { return java.lang.Integer.compare(a.length, b.length) })
// Sorts the array by increasing length
```

Nashorn supports shorthand for functions whose body is a single expression. For such functions, you can omit the braces and the `return` keyword:

[Click here to view code image](#)

```
java.util.Arrays.sort(words,
    function(a, b) java.lang.Integer.compare(a.length, b.length))
```

Again, note the similarity with a Java lambda expression `(a, b) -> Integer.compare(a.length, b.length)`.



NOTE

That shorthand notation (called an “expression closure”) is not part of the official JavaScript

language standard (ECMAScript 5.1), but it is also supported by the Mozilla JavaScript implementation.

7.10. Extending Java Classes and Implementing Java Interfaces

To extend a Java class, or to implement a Java interface, use the `Java.extend` function. Supply the class object of the superclass or interface and a JavaScript object with the methods that you want to override or implement.

For example, here is an iterator that produces an infinite sequence of random numbers. We override two methods, `next` and `hasNext`. For each method, we provide an implementation as an anonymous JavaScript function:

[Click here to view code image](#)

```
var RandomIterator = Java.extend(java.util.Iterator, {
    next: function() Math.random(),
    hasNext: function() true
}) // RandomIterator is a class object
var iter = new RandomIterator() // Use it to construct an instance
```



NOTE

When calling `Java.extend`, you can specify any number of superinterfaces as well as a superclass. Place all class objects before the object with the implemented methods.

Another Nashorn syntax extension lets you define anonymous subclasses of interfaces or abstract classes. When `new JavaClassObject` is followed by a JavaScript object, an object of the extended class is returned. For example,

[Click here to view code image](#)

```
var iter = new java.util.Iterator {
    next: function() Math.random(),
    hasNext: function() true
}
```

If the supertype is abstract and has only one abstract method, you don't even have to give the method name. Instead, pass the function as if it was a constructor parameter:

[Click here to view code image](#)

```
var task = new java.lang.Runnable(function() { print('Hello') })
// task is an object of an anonymous class implementing Runnable
```



CAUTION

When extending a *concrete* class, you cannot use that constructor syntax. For example, `new java.lang.Thread(function() { print('Hello') })` calls a `Thread` constructor, in this case the constructor `Thread(Runnable)`. The call to `new` returns an object of class `Thread`, not of a subclass of `Thread`.

If you want instance variables in your subclass, add them to the JavaScript object. For example here is an iterator that produces ten random numbers:

[Click here to view code image](#)

```
var iter = new java.util.Iterator {
    count: 10,
    next: function() { this.count--; return Math.random() },
    hasNext: function() this.count > 0
}
```

Note that the JavaScript methods `next` and `hasNext` refer to the instance variable as `this.count`.

It is possible to invoke a superclass method when overriding a method, but it is quite finicky. The call `Java.super(obj)` yields an object on which you can invoke the superclass method of the class to which `obj` belongs, but you must have that object available. Here is a way to achieve that:

[Click here to view code image](#)

```
var arr = new (Java.extend(java.util.ArrayList)) {
    add: function(x) {
        print('Adding ' + x);
        return Java.super(arr).add(x)
    }
}
```

When you call `arr.add('Fred')`, a message is printed before the value is added to the array list. Note that the call `Java.super(arr)` requires the `arr` variable, which is being set to the value returned by `new`. Calling `Java.super(this)` does not work—that only gets the JavaScript object that defines the method, not the Java proxy. The `Java.super` mechanism is only useful for defining individual objects, not subclasses.



NOTE

Instead of calling `Java.super(arr).add(x)`, you can also use the syntax `arr.super$add(x)`.

7.11. Exceptions

When a Java method throws an exception, you can catch it in JavaScript in the usual way:

[Click here to view code image](#)

```
try {
    var first = list.get(0)
    ...
} catch (e) {
    if (e instanceof java.lang.IndexOutOfBoundsException)
        print('list is empty')
}
```

Note that there is only one `catch` clause, unlike in Java where you can catch expressions by type. That, too, is in the spirit of dynamic languages where all type inquiry happens at runtime.

7.12. Shell Scripting

If you need to automate a repetitive task on your computer, chances are that you have put the commands in a *shell script*, a script that replays a set of OS-level commands. I have a directory

`~/bin` filled with dozens of shell scripts: to upload files to my web site, my blog, my photo storage, and to my publisher's FTP site; to convert images to blog size; to bulk-email my students; to back up my computer at two o'clock in the morning.

For me, these are bash scripts, but in the olden days when I used Windows they were batch files. So what is wrong with that? The problem comes once you have a need for branches and loops. For some reason, most implementors of command shells are terrible at programming language design. The way variables, branches, loops, and functions are implemented in bash is simply awful, and the batch language in Windows is even worse. I have a few bash scripts that started out modest but have over time accreted so much cruft that they are unmanageable. This is a common problem.

Why not just write these scripts in Java? Java is quite verbose. If you call external commands via `Runtime.exec`, you need to manage standard input/output/error streams. The Nashorn designers want you to consider JavaScript as an alternative. The syntax is comparatively lightweight, and Nashorn offers some conveniences that are specifically geared towards shell programmers.

7.12.1. Executing Shell Commands

To use the scripting extensions in Nashorn, run

```
jjs -scripting
```

or

```
jrunscript
```

Now you can execute shell commands by including them in backquotes, for example

```
`ls -al`
```

The standard output and standard error streams of the last command are captured in `$OUT` and `$ERR`. The exit code of the command is in `$EXIT`. (By convention, an exit code of zero means success, and non-zero codes describe error conditions.)

You can also capture the standard output by assigning the result of the backquoted command to a variable:

```
var output = `ls -al`
```

If you want to supply standard input for a command, use

```
$EXEC(command, input)
```

For example, this command passes the output of `ls -al` to `grep -v class`:

[Click here to view code image](#)

```
$EXEC('grep -v class', `ls -al`)
```

It's not quite as pretty as a pipe, but you can easily implement a pipe if you need it—see Exercise 6.

7.12.2. String Interpolation

Expressions inside `${...}` are evaluated within doubly quoted and backquoted strings. This is called “string interpolation.” For example,

[Click here to view code image](#)

```
var cmd = "javac -classpath ${classpath} ${mainclass}.java"  
$EXEC(cmd)
```

or simply

[Click here to view code image](#)

```
`javac -classpath ${classpath} ${mainclass}.java`
```

injects the contents of the variables `classpath` and `mainclass` into the command.

You can use arbitrary expressions inside the `${...}`:

[Click here to view code image](#)

```
var message = "The current time is ${java.time.Instant.now()}"  
// Sets message to a string such as The current time is 2013-10-12T21:48:58.545Z
```

As with the bash shell, string interpolation does not work inside singly quoted strings.

[Click here to view code image](#)

```
var message = 'The current time is ${java.time.Instant.now()}'  
// Sets message to The current time is ${java.time.Instant.now()}
```

Strings are also interpolated in “here documents”—inline documents in a script. These inline documents are useful when a command reads multiple lines from standard input and the script author doesn’t want to put the input in a separate file. As an example, here is how you can feed commands to the GlassFish administration tool:

```
name='myapp'  
dir='/opt/apps/myapp'  
$EXEC("asadmin", <<END)  
start-domain  
start-database  
deploy ${name} ${dir}  
exit  
END
```

The `<<END` construct means: “Insert the string that starts on the next line and is terminated by the line `END`.” (Instead of `END`, you can use any identifier that doesn’t appear inside the string.)

Note that the name and location of the application are interpolated.

String interpolation and here documents are only available in scripting mode.

7.12.3. Script Inputs

You can supply command-line arguments to a script. Since it is possible to include multiple script files on the `jjs` command line, you need to separate the script files and arguments with a `--`:

[Click here to view code image](#)

```
jjs script1.js script2.js -- arg1 arg2 arg3
```



NOTE

That is a little ugly. If you have only one script file, you can instead run

[Click here to view code image](#)

```
jrunscript -f script.js arg1 arg2 arg3
```



TIP

The first line of a script can be a “shebang,” the symbols `#!` followed by the location of the script interpreter. For example,

```
#!/opt/java/bin/jjs
```

or

```
#!/opt/java/bin/jrunscript -f
```

Then you can make the script file executable and simply run it as `path/script.js`.

When a script starts with a shebang, scripting mode is automatically activated.



CAUTION

If your script has arguments, and you use `jjs` in the shebang, script users will need to supply the `--: path/script.js -- arg1 arg2 arg3`. Users will not love you for that. Use `jrunscript` instead.

In the script file, you receive the command-line arguments in the `arguments` array:

[Click here to view code image](#)

```
var deployCommand = "deploy ${arguments[0]} ${arguments[1]}"
```

With `jjs` (but not with `jrunscript`), you can use `$ARG` instead of `arguments`. If you use that variable with string interpolation, you need two dollar signs:

[Click here to view code image](#)

```
var deployCommand = "deploy ${$ARG[0]} ${$ARG[1]}"
```

In your script, you can obtain the shell’s environment variables through the `ENV` object:

[Click here to view code image](#)

```
var javaHome = $ENV.JAVA_HOME
```

In scripting mode, you can prompt the user for input with the `readLine` function:

[Click here to view code image](#)

```
var username = readLine('Username: ')
```



CAUTION

To prompt for a password, call

[Click here to view code image](#)

```
var password = java.lang.System.console().readPassword('Password: ')
```

Finally, to exit a script, use the `exit` function. You can supply an optional exit code.

[Click here to view code image](#)

```
if (username.length == 0) exit(1)
```

7.13. Nashorn and JavaFX

Nashorn provides a convenient way of launching JavaFX applications. Simply put the instructions that you would normally put into the `start` method of the `Application` subclass into the script. Use `$STAGE` for the `Stage` parameter. You don't even have to call `show` on the `Stage` object—that is done for you. For example, here is the “Hello” program from [Chapter 4](#) in JavaScript:

[Click here to view code image](#)

```
var message = new javafx.scene.control.Label("Hello, JavaFX!");
message.font = new javafx.scene.text.Font(100);
$STAGE.scene = new javafx.scene.Scene(message);
$STAGE.title = "Hello";
```

Run the script with the `-fx` option, like this:

```
jjs -fx myJavaFxApp.js
```

That is all there is to it. A label with a message “Hello, JavaFX!” is displayed in a 100-point font in a window whose title is “Hello”—see [Figure 7–1](#).



Figure 7–1 The Hello JavaFX application in JavaScript

All the boilerplate is gone, and you have the convenient property notation, that is,

[Click here to view code image](#)

```
message.font = new Font(100)
```

instead of

```
message.setFont(new Font(100))
```



NOTE

If you need to override the `init` or `stop` lifecycle methods of the `Application` class in addition to `start`, include the methods that you need in your script, at the top level. With the `-fx` option, you then get a subclass of `Application` with the script methods.

Now let us look at event handling. As you have seen in [Chapter 4](#), most FX events are handled through listeners to FX properties. Here, the JavaScript story isn't so pretty. Recall that an FX property has two listener interfaces, `InvalidationListener` and `ChangeListener`, both added

with the `addListener` method. In Java, you can call `addListener` with a lambda expression, and the compiler is able to figure out from the parameter types which of the two listeners to add. But in JavaScript, function parameters have no types. Suppose we have a slider to control the font size. We'd like to add a listener that updates the size when the slider value changes:

[Click here to view code image](#)

```
slider.valueProperty().addListener(function(property)
    message.font = new Font(slider.value))
// Error—Nashorn can't determine which listener type to add
```

That doesn't work. Nashorn doesn't know whether you want to add an `InvalidationListener` or a `ChangeListener`, and it doesn't know that you don't actually care.

To fix this, you need to make the choice:

[Click here to view code image](#)

```
slider.valueProperty().addListener(
    new javafx.beans.InvalidationListener(function(property)
        message.font = new Font(slider.value)))
```

That's more heavyweight than the Java equivalent—not something one wants to see in a lightweight scripting language. There is nobody to blame for this, really. The JavaFX designers made the decision to overload the `addListener` method, which was perfectly reasonable in the context of Java 7 and mostly works with Java 8 lambda expressions. Compatibility with scripting languages was perhaps not their major concern, particularly since they had just abandoned another scripting language.

But it should be a cautionary tale. When you design a Java API, remember Atwood's law: "Any application that can be written in JavaScript will eventually be written in JavaScript." Design your API so that it can be accessed nicely from JavaScript.

And there is another sad aspect about the JavaFX support in Nashorn. Recall how in the olden days of JavaFX Script, it was easy to describe the layout of a scene like this:

[Click here to view code image](#)

```
Frame {
    title: "Hello"
    content: Label {
        text: "Hello, World!"
    }
}
```

Doesn't it almost look like JavaScript? Well, Nashorn/JavaFX developers, tear down that wall and turn it into JavaScript! Then we can write both the UI layout and event handling in JavaScript and Atwood's law will be fulfilled.

Exercises

1. Pick some part of the Java API that you want to explore—for example, the `ZonedDateTime` class. Run some experiments in `jjs`: construct objects, call methods, and observe the returned values. Did you find it easier than writing test programs in Java?

2. Run `jjs` and, using the stream library, interactively work out a solution for the following problem: Print all unique long words (> 12 characters) from a file in sorted order. First read the words, then filter the long words, and so on. How does this interactive approach compare to

your usual workflow?

3. Run `jjs`. Call

[Click here to view code image](#)

```
var b = new java.math.BigInteger('1234567890987654321')
```

Then display `b` (simply by typing `b` and Enter). What do you get? What is the value of `b.mod(java.math.BigInteger.TEN)`? Why is `b` displayed so strangely? How can you display the actual value of `b`?

4. Construct a nonliteral JavaScript string by extracting a substring from another string, and invoke the `getClass` method. What class do you get? Then pass the object to `java.lang.String.class.cast`. What happens? Why?

5. At the end of [Section 7.10, “Extending Java Classes and Implementing Java Interfaces](#),” on page [146](#), you saw how to extend `ArrayList` so that every call to `add` is logged. But that only worked for a single object. Write a JavaScript function that is a factory for such objects, so that one can generate any number of logging array lists.

6. Write a JavaScript function `pipe` that takes a sequence of shell commands and pipes the output of one to the input of the next, returning the final output. For example, `pipe('find .', 'grep -v class', 'sort')`. Simply call `$EXEC` repeatedly.

7. The solution of the preceding exercise is not quite as good as a Unix pipe because the second command only starts when the first one has finished. Remedy that by using the `ProcessBuilder` class.

8. Write a script that prints the values of all environment variables.

9. Write a script `nextYear.js` that obtains the age of the user and then prints `Next year, you will be ..., adding 1 to the input. The age can be specified on the command line or the AGE environment variable. If neither are present, prompt the user.`

10. Write a JavaFX program in JavaScript that reads data from a source of your choice and renders a pie chart. Was it easier or harder than developing the program in Java? Why?

Chapter 8. Miscellaneous Goodies

Topics in This Chapter

- [8.1 Strings](#)
- [8.2 Number Classes](#)
- [8.3 New Mathematical Functions](#)
- [8.4 Collections](#)
- [8.5 Working with Files](#)
- [8.6 Annotations](#)
- [8.7 Miscellaneous Minor Changes](#)
- [Exercises](#)

Java 8 is a big release with important language and library enhancements. But there are also numerous smaller changes throughout the library that are quite useful. I pored over all @since 1.8 notes in the API documentation and grouped the changes into categories for easy reference. In this chapter, you will find what is new for strings, numbers, math, collections, files, annotations, regular expressions, and JDBC.

The key points of this chapter are:

- Joining strings with a delimiter is finally easy: `String.join(", ", a, b, c)` instead of `a + ", " + b + ", " + c`.
- Integer types now support unsigned arithmetic.
- The `Math` class has methods to detect integer overflow.
- Use `Math.floorMod(x, n)` instead of `x % n` if `x` might be negative.
- There are new mutators in `Collection.removeIf` and `List.replaceAll, sort`.
- `Files.lines` lazily reads a stream of lines.
- `Files.list` lazily lists the entries of a directory, and `Files.walk` traverses them recursively.
- There is finally official support for Base64 encoding.
- Annotations can now be repeated and applied to type uses.
- Convenient support for null parameter checks can be found in the `Objects` class.

8.1. Strings

A common task is to combine several strings, separating them with a delimiter such as `,` `"` or `"/"`. This has now been added to Java 8. The strings can come from an array or an `Iterable<? extends CharSequence>`:

[Click here to view code image](#)

```
String joined = String.join("/", "usr", "local", "bin"); // "usr/local/bin"
System.out.println(joined);
String ids = String.join(", ", ZoneId.getAvailableZoneIds());
System.out.println(ids);
// All time zone identifiers, separated by commas
```

Think of `join` as the opposite of the `String.split` instance method. This is the only method added to the `String` class in Java 8.



NOTE

As already mentioned in [Chapter 2](#), the `CharSequence` interface provides a useful instance method `codePoints` that returns a stream of Unicode values, and a less useful method `chars` that returns a stream of UTF-16 code units.

8.2. Number Classes

Ever since Java 5, each of the seven numeric primitive type wrappers (i.e., not `Boolean`) had a static `SIZE` field that gives the size of the type in bits. You will be glad to know that there is now a `BYTES` field that reports the size in bytes, for those who cannot divide by eight.

All eight primitive type wrappers now have static `hashCode` methods that return the same hash code as the instance method, but without the need for boxing.

The five types `Short`, `Integer`, `Long`, `Float`, and `Double` now have static methods `sum`, `max`, and `min`, which can be useful as reduction functions in stream operations. The `Boolean` class has static methods `logicalAnd`, `logicalOr`, and `logicalXor` for the same purpose.

Integer types now support unsigned arithmetic. For example, instead of having a `Byte` represent the range from -128 to 127, you can call the static method `Byte.toUnsignedInt(b)` and get a value between 0 and 255. In general, with unsigned numbers, you lose the negative values and get twice the range of positive values. The `Byte` and `Short` classes have methods `toUnsignedInt`, and `Byte`, `Short`, and `Integer` have methods `toUnsignedLong`.

The `Integer` and `Long` classes have methods `compareUnsigned`, `divideUnsigned`, and `remainderUnsigned` to work with unsigned values. You don't need special methods for addition, subtraction, and multiplication. The + and - operators do the right thing already for unsigned values. Integer multiplication would overflow with unsigned integers larger than `Integer.MAX_VALUE`, so you should call `toUnsignedLong` and multiply them as long values.



NOTE

In order to work with unsigned numbers, you need to have a clear understanding of base-two arithmetic and the binary representation of negative numbers. In C and C++, mixing signed and unsigned types is a common cause of subtle errors. Java has wisely decided to stay away from this area, and has managed to live with only signed numbers for many years. The primary reason to use unsigned numbers is if you work with file formats or network protocols that require them.

The `Float` and `Double` classes have static methods `isFinite`. The call `Double.isFinite(x)` returns `true` if `x` is not infinity, negative infinity, or a NaN (not a number). In the past, you had to call the instance methods `isInfinite` and `isNaN` to get the same result.

Finally, the `BigInteger` class has instance methods (`long|int|short|byte`)`valueExact` that return the value as a `long`, `int`, `short`, or `byte`, throwing an `ArithmaticException` if the value is not

within the target range.

8.3. New Mathematical Functions

The `Math` class provides several methods for “exact” arithmetic that throw an exception when a result overflows. For example, `100000 * 100000` quietly gives the wrong result `1410065408`, whereas `multiplyExact(100000, 100000)` throws an exception. The provided methods are (`add|subtract|multiply|increment|decrement|negate`)`Exact`, with `int` and `long` parameters. The `toIntExact` method converts a `long` to the equivalent `int`.

The `floorMod` and `floorDiv` methods aim to solve a long-standing problem with integer remainders. Consider the expression `n % 2`. Everyone knows that this is `0` if `n` is even and `1` if `n` is odd. Except, of course, when `n` is negative. Then it is `-1`. Why? When the first computers were built, someone had to make rules for how integer division and remainder should work for negative operands. Mathematicians had known the optimal (or “Euclidean”) rule for a few hundred years: always leave the remainder ≥ 0 . But, rather than open a math textbook, those pioneers came up with rules that seemed reasonable but are actually inconvenient.

Consider this problem. You compute the position of the hour hand of a clock. An adjustment is applied, and you want to normalize to a number between `0` and `11`. That is easy: `(position + adjustment) % 12`. But what if `adjustment` is negative? Then you might get a negative number. So you have to introduce a branch, or use `((position + adjustment) % 12 + 12) % 12`. Either way, it is a hassle.

The new `floorMod` method makes it easier: `floorMod(position + adjustment, 12)` always yields a value between `0` and `11`.



NOTE

Unfortunately, `floorMod` gives negative results for negative divisors, but that situation doesn’t often occur in practice.

The `nextDown` method, defined for both `double` and `float` parameters, gives the next smaller floating-point number for a given number. For example, if you promise to produce a number $< b$, but you happen to have computed exactly `b`, then you can return `Math.nextDown(b)`. (The corresponding `Math.nextUp` method exists since Java 6.)



NOTE

All methods described in this section also exist in the `StrictMath` class.

8.4. Collections

The big change for the collections library is, of course, support for streams which you have seen in [Chapter 2](#). There are some smaller changes as well.

8.4.1. Methods Added to Collection Classes

[Table 8–1](#) shows miscellaneous methods added to collection classes and interfaces in Java 8, other than the `stream`, `parallelStream`, and `spliterator` methods.

Class/Interface	New Methods
Iterable	<code>forEach</code>
Collection	<code>removeIf</code>
List	<code>replaceAll</code> , <code>sort</code>
Map	<code>forEach</code> , <code>replace</code> , <code>replaceAll</code> , <code>remove(key, value)</code> (removes only if key mapped to value), <code>putIfAbsent</code> , <code>compute</code> , <code>computeIfAbsent</code> <code>Present</code> , <code>merge</code>
Iterator	<code>forEachRemaining</code>
BitSet	<code>stream</code>

Table 8–1 Methods Added to Collection Classes and Interface in Java 8

You may wonder why the `Stream` interface has so many methods that accept lambda expressions but just one such method, `removeIf`, was added to the `Collection` interface. If you review the `Stream` methods, you will find that most of them return a single value or a stream of transformed values that are not present in the original stream. The exceptions are the `filter` and `distinct` methods. The `removeIf` method can be thought of as the opposite of `filter`, removing rather than producing all matches and carrying out the removal in place. The `distinct` method would be costly to provide on arbitrary collections.

The `List` interface has a `replaceAll` method, which is an in-place equivalent of `map`, and a `sort` method that is obviously useful.

The `Map` interface has a number of methods that are particularly important for maps accessed concurrently. See [Chapter 6](#) for more information on these methods.

The `Iterator` interface has a `forEachRemaining` method that exhausts the iterator by feeding the remaining iterator elements to a function.

Finally, the `BitSet` class has a method that yields all members of the set as a stream of `int` values.

8.4.2. Comparators

The `Comparator` interface has a number of useful new methods, taking advantage of the fact that interfaces can now have concrete methods.

The static `comparing` method takes a “key extractor” function that maps a type `T` to a comparable type (such as `String`). The function is applied to the objects to be compared, and the comparison is then made on the returned keys. For example, suppose you have an array of `Person` objects. Here is how you can sort them by name:

[Click here to view code image](#)

```
Arrays.sort(people, Comparator.comparing(Person::getName));
```

You can chain comparators with the `thenComparing` method for breaking ties. For example,

[Click here to view code image](#)

```
Arrays.sort(people,
    Comparator.comparing(Person::getLastName)
        .thenComparing(Person::getFirstName));
```

If two people have the same last name, then the second comparator is used.

There are a few variations of these methods. You can specify a comparator to be used for the keys that the comparing and thenComparing methods extract. For example, here we sort people by the length of their names:

[Click here to view code image](#)

```
Arrays.sort(people, Comparator.comparing(Person::getName,
    (s, t) -> Integer.compare(s.length(), t.length())));
```

Moreover, both the comparing and thenComparing methods have variants that avoid boxing of int, long, or double values. An easier way of producing the preceding operation would be

[Click here to view code image](#)

```
Arrays.sort(people, Comparator.comparingInt(p -> p.getName().length()));
```

If your key function can return null, you will like the nullsFirst and nullsLast adapters. These static methods take an existing comparator and modify it so that it doesn't throw an exception when encountering null values but ranks them as smaller or larger than regular values. For example, suppose getMiddleName returns a null when a person has no middle name. Then you can use Comparator.comparing(Person::getMiddleName(), Comparator.nullsFirst(...)).

The nullsFirst method needs a comparator—in this case, one that compares two strings. The naturalOrder method makes a comparator for any class implementing Comparable. A Comparator.<String>naturalOrder() is what we need. Here is the complete call for sorting by potentially null middle names. I use a static import of java.util.Comparator.*., to make the expression more legible. Note that the type for naturalOrder is inferred.

[Click here to view code image](#)

```
Arrays.sort(people, comparing(Person::getMiddleName,
    nullsFirst(naturalOrder())));
```

The static reverseOrder method gives the reverse of the natural order. To reverse any comparator, use the reversed instance method. For example, naturalOrder().reversed() is the same as reverseOrder().

8.4.3. The Collections Class

Java 6 introduced NavigableSet and NavigableMap classes that take advantage of the ordering of the elements or keys, providing efficient methods to locate, for any given value v, the smallest element \geq or $\geq v$, or the largest element \leq or $< v$. Now the Collections class supports these classes as it does other collections, with methods (unmodifiable|synchronized|checked|empty)Navigable(Set|Map).

A checkedQueue wrapper, that has apparently been overlooked all these years, has also been added. As a reminder, the checked wrappers have a class parameter and throw a ClassCastException when you insert an element of the wrong type. These classes are intended as debugging aids. Suppose you declare a Queue<Path>, and somewhere in your code there is a ClassCastException trying to cast a String to a Path. This could have happened because you passed the queue to a method void getMoreWork(Queue q) with no type parameter. Then, someone

somewhere inserted a `String` into `q`. (Because the generic type was suppressed, the compiler could not detect that.) Much later, you took out that `String`, thinking it was a `Path`, and the error manifested itself. If you temporarily replace the queue with a `CheckedQueue<new LinkedList<Path>, Path.class>`, then every insertion is checked at runtime, and you can locate the faulty insertion code.

Finally, there are `emptySorted(Set|Map)` methods that give lightweight instances of sorted collections, analogous to the `empty(Set|Map)` methods that have been around since Java 5.

8.5. Working with Files

Java 8 brings a small number of convenience methods that use streams for reading lines from files and for visiting directory entries. Also, there is finally an official way of performing Base64 encoding and decoding.

8.5.1. Streams of Lines

To read the lines of a file lazily, use the `Files.lines` method. It yields a stream of strings, one per line of input:

[Click here to view code image](#)

```
Stream<String> lines = Files.lines(path);
Optional<String> passwordEntry = lines.filter(s -> s.contains("password")).findFirst();
```

As soon as the first line containing `password` is found, no further lines are read from the underlying file.



NOTE

Unlike the `FileReader` class, which was a portability nightmare since it opened files in the local character encoding, the `Files.lines` method defaults to UTF-8. You can specify other encodings by supplying a `Charset` argument.

You will want to close the underlying file. Fortunately, the `Stream` interface extends `AutoCloseable`. The streams that you have seen in [Chapter 2](#) didn't need to close any resources. But the `Files.lines` method produces a stream whose `close` method closes the file. The easiest way to make sure the file is indeed closed is to use a Java 7 try-with-resources block:

[Click here to view code image](#)

```
try (Stream<String> lines = Files.lines(path)) {
    Optional<String> passwordEntry
        = lines.filter(s -> s.contains("password")).findFirst();
    ...
} // The stream, and hence the file, will be closed here
```

When a stream spawns another, the `close` methods are chained. Therefore, you can also write

[Click here to view code image](#)

```
try (Stream<String> filteredLines
    = Files.lines(path).filter(s -> s.contains("password"))) {
    Optional<String> passwordEntry = filteredLines.findFirst();
    ...
}
```



NOTE

If you want to be notified when the stream is closed, you can attach an `onClose` handler. Here is how you can verify that closing `filteredLines` actually closes the underlying stream:

[Click here to view code image](#)

```
try (Stream<String> filteredLines
    = Files.lines(path).onClose(() -> System.out.println("Closing"))
        .filter(s -> s.contains("password"))) { ... }
```

If an `IOException` occurs as the stream fetches the lines, that exception is wrapped into an `UncheckedIOException` which is thrown out of the stream operation. (This subterfuge is necessary because stream operations are not declared to throw any checked exceptions.)

If you want to read lines from a source other than a file, use the `BufferedReader.lines` method instead:

[Click here to view code image](#)

```
try (BufferedReader reader
    = new BufferedReader(new InputStreamReader(url.openStream()))) {
    Stream<String> lines = reader.lines();
    ...
}
```

With this method, closing the resulting stream does *not* close the reader. For that reason, you must place the `BufferedReader` object, and not the stream object, into the header of the `try` statement.



NOTE

Almost ten years ago, Java 5 introduced the `Scanner` class to replace the cumbersome `BufferedReader`. It is unfortunate that the Java 8 API designers decided to add the `lines` method to `BufferedReader` but not to `Scanner`.

8.5.2. Streams of Directory Entries

The static `Files.list` method returns a `Stream<Path>` that reads the entries of a directory. The directory is read lazily, making it possible to efficiently process directories with huge numbers of entries.

Since reading a directory involves a system resource that needs to be closed, you should use a `try` block:

[Click here to view code image](#)

```
try (Stream<Path> entries = Files.list(pathToDirectory)) {
    ...
}
```



NOTE

Under the hood, the stream uses a `DirectoryStream`, a construct introduced in Java 7 for efficient traversal of huge directories. That interface has nothing to do with Java 8 streams; it extends `Iterable` so that it can be used in an enhanced `for` loop.

[Click here to view code image](#)

```
try (DirectoryStream stream = Files.newDirectoryStream(pathToDirectory)) {  
    for (Path entry : stream) {  
        ...  
    }  
}
```

In Java 8, just use `Files.list`.

The `list` method does not enter subdirectories. To process all descendants of a directory, use the `Files.walk` method instead.

[Click here to view code image](#)

```
try (Stream<Path> entries = Files.walk(pathToRoot)) {  
    // Contains all descendants, visited in depth-first order  
}
```

You can limit the depth of the tree that you want to visit by calling `Files.walk(pathToRoot, depth)`. Both `walk` methods have a varargs parameter of type `FileVisitOption...`, but there is currently only one option you can supply: `FOLLOW_LINKS` to follow symbolic links.



NOTE

If you filter the paths returned by `walk` and your filter criterion involves the file attributes stored with a directory, such as size, creation time, or type (file, directory, symbolic link), then use the `find` method instead of `walk`. Call that method with a predicate function that accepts a path and a `BasicFileAttributes` object. The only advantage is efficiency. Since the directory is being read anyway, the attributes are readily available.

8.5.3. Base64 Encoding

The Base64 encoding encodes a sequence of bytes into a (longer) sequence of printable ASCII characters. It is used for binary data in email messages and “basic” HTTP authentication. For many years, the JDK had a nonpublic (and therefore unusable) class `java.util.prefs.Base64` and an undocumented class `sun.misc.BASE64Encoder`. Finally, Java 8 provides a standard encoder and decoder.

The Base64 encoding uses 64 characters to encode six bits of information:

- 26 uppercase letters A . . . Z
- 26 lowercase letters a . . . z
- 10 digits 0 . . . 9
- 2 symbols, + and / (basic) or - and _ (URL- and filename-safe variant)

Normally, an encoded string has no line breaks, but the MIME standard used for email requires a `"\r\n"` line break every 76 characters.

For encoding, request a `Base64.Encoder` with one of the static methods `getEncoder`, `getUrlEncoder`, or `getMimeEncoder` of the `Base64` class.

That class has methods to encode an array of bytes or a NIO `ByteBuffer`. For example,

[Click here to view code image](#)

```
Base64.Encoder encoder = Base64.getEncoder();
String original = username + ":" + password;
String encoded = encoder.encodeToString(original.getBytes(StandardCharsets.UTF_8));
```

Alternatively, you can “wrap” an output stream, so that all data sent to it is automatically encoded.

[Click here to view code image](#)

```
Path originalPath = ..., encodedPath = ...;
Base64.Encoder encoder = Base64.getMimeEncoder();
try (OutputStream output = Files.newOutputStream(encodedPath)) {
    Files.copy(originalPath, encoder.wrap(output));
}
```

To decode, reverse these operations:

[Click here to view code image](#)

```
Path encodedPath = ..., decodedPath = ...;
Base64.Decoder decoder = Base64.getMimeDecoder();
try (InputStream input = Files.newInputStream(encodedPath)) {
    Files.copy(decoder.wrap(input), decodedPath);
}
```

8.6. Annotations

Annotations are tags inserted into the source code that some tools can process. In Java SE annotations are used for simple purposes, such as marking deprecated features or suppressing warnings. Annotations have a much more important role in Java EE where they are used to configure just about any aspect of an application, replacing painful boilerplate code and XML customization that was the bane of older Java EE versions.

Java 8 has two enhancements to annotation processing: repeated annotations and type use annotations. Moreover, reflection has been enhanced to report method parameter names. This has the potential to simplify annotations on method parameters.

8.6.1. Repeated Annotations

When annotations were first created, they were envisioned to mark methods and fields for processing, for example,

[Click here to view code image](#)

```
@PostConstruct public void fetchData() { ... } // Call after construction
@Resource("jdbc:derby:sample") private Connection conn;
// Inject resource here
```

In this context, it made no sense to apply the same annotation twice. You can't inject a field in two ways. Of course, different annotations on the same element are fine and quite common:

[Click here to view code image](#)

```
@Stateless @Path("/service") public class Service { ... }
```

Soon, more and more uses for annotations emerged, leading to situations where one would have liked to repeat the same annotation. For example, to denote a composite key in a database, you need to specify multiple columns:

[Click here to view code image](#)

```
@Entity  
 @PrimaryKeyJoinColumn(name="ID")  
 @PrimaryKeyJoinColumn(name="REGION")  
 public class Item { ... }
```

Since that wasn't possible, the annotations were packed into a container annotation, like this:

[Click here to view code image](#)

```
@Entity  
 @PrimaryKeyJoinColumns({  
     @PrimaryKeyJoinColumn(name="ID")  
     @PrimaryKeyJoinColumn(name="REGION")  
 })  
 public class Item { ... }
```

That's pretty ugly, and it is no longer necessary in Java 8.

As an annotation user, that is all you need to know. If your framework provider has enabled repeated annotations, you can just use them.

For a framework implementor, the story is not quite as simple. After all, the `AnnotatedElement` interface has a method

[Click here to view code image](#)

```
public <T extends Annotation> T getAnnotation(Class<T> annotationClass)
```

that gets *the* annotation of type `T`, if present. What should that method do if multiple annotations of the same type are present? Return the first one only? That could have all sorts of undesirable behavior with legacy code.

To solve this problem, the inventor of a repeatable annotation must

1. Annotate the annotation as `@Repeatable`
2. Provide a container annotation

For example, for a simple unit testing framework, we might define a repeatable `@TestCase` annotation, to be used like this:

[Click here to view code image](#)

```
@TestCase(params="4", expected="24")  
 @TestCase(params="0", expected="1")  
 public static long factorial(int n) { ... }
```

Here is how the annotation can be defined:

[Click here to view code image](#)

```
@Repeatable(TestCases.class)  
 @interface TestCase {  
     String params();  
     String expected();  
 }  
  
 @interface TestCases {  
     TestCase[] value();
```

}

Whenever the user supplies two or more `@TestCase` annotations, they are automatically wrapped into a `@TestCases` annotation.

When annotation processing code calls `element.getAnnotation(TestCase.class)` on the element representing the `factorial` method, `null` is returned. This is because the element is actually annotated with the container annotation `TestCases`.

When implementing an annotation processor for your repeatable annotation, you will find it simpler to use the `getAnnotationsByType` method. The call `element.getAnnotationsByType(TestCase.class)` “looks through” any `TestCases` container and gives you an array of `TestCase` annotations.



NOTE

What I just described relates to processing runtime annotations with the reflection API. If you process source-level annotations, you use the `javax.lang.model` and `javax.annotation.processing` APIs. In those APIs, there is no support for “looking through” a container. You will need to process both the individual annotation (if it is supplied once) and the container (if the same annotation is supplied more than once).

8.6.2. Type Use Annotations

Prior to Java 8, an annotation was applied to a *declaration*. A declaration is a part of code that introduces a new name. Here are a couple of examples, with the declared name in bold:

[Click here to view code image](#)

```
@Entity public class Person { ... }  
@SuppressWarnings("unchecked") List<Person> people = query.getResultList();
```

In Java 8, you can annotate any *type use*. This can be useful in combination with tools that check for common programming errors. One common error is throwing a `NullPointerException` because the programmer didn’t anticipate that a reference might be `null`. Now suppose you annotated variables that you never want to be `null` as `@NonNull`. A tool can check that the following is correct:

[Click here to view code image](#)

```
private @NonNull List<String> names = new ArrayList<>();  
...  
names.add("Fred"); // No possibility of a NullPointerException
```

Of course, the tool should detect any statement that might cause `names` to become `null`:

[Click here to view code image](#)

```
names = null; // Null checker flags this as an error  
names = readNames(); // OK if readNames returns a @NonNull String
```

It sounds tedious to put such annotations everywhere, but in practice, some of the drudgery can be avoided by simple heuristics. The null checker in the Checker Framework (<http://types.cs.washington.edu/checker-framework>) assumes that any nonlocal variables are implicitly `@NonNull`, but that local variables might be `null` unless the code shows otherwise. If a

method may return a `null`, it needs to be annotated as `@Nullable`. That may not be any worse than documenting the nullness behavior. (The Java API documentation has over 5,000 occurrences of “`NullPointerException`.”)

In the preceding example, the `names` variable was declared as `@NonNull`. That annotation was possible before Java 8. But how can one express that the list `elements` should be non-null? Logically, that would be

[Click here to view code image](#)

```
private List<@NonNull String> names;
```

It is this kind of annotation that was not possible before Java 8 but has now become legal.



NOTE

These annotations are *not* part of standard Java. There are currently no standard annotations that are meaningful for type use. All examples in this section come from the Checker Framework or from the author’s imagination.

Type use annotations can appear in the following places:

- With generic type arguments: `List<@NonNull String>, Comparator.<@NonNull String> reverseOrder()`.
- In any position of an array: `@NonNull String[][] words` (`words[i][j]` is not `null`), `String @NonNull [][] words` (`words` is not `null`), `String[] @NonNull [] words` (`words[i]` is not `null`).
- With superclasses and implemented interfaces: `class Image implements @Rectangular Shape`.
- With constructor invocations: `new @Path String("/usr/bin")`.
- With casts and `instanceof` checks: `(@Path String) input, if (input instanceof @Path String)`. (The annotations are only for use by external tools. They have no effect on the behavior of a cast or an `instanceof` check.)
- With exception specifications: `public Person read() throws @Localized IOException`.
- With wildcards and type bounds: `List<@ReadOnly ? extends Person>, List<? extends @ReadOnly> Person`.
- With method and constructor references: `@Immutable Person::getName`.

There are a few type positions that cannot be annotated:

[Click here to view code image](#)

```
@NonNull String.class // Illegal—cannot annotate class literal  
import java.lang.@NonNull String; // Illegal—cannot annotate import
```

It is also impossible to annotate an annotation. For example, given `@NonNull String name`, you cannot annotate `@NonNull`. (You can supply a separate annotation, but it would apply to the `name` declaration.)

The practical use of these annotations hinges on the viability of the tools. If you are interested in

exploring the potential of extended type checking, a good place to start is the Checker Framework tutorial at <http://types.cs.washington.edu/checker-framework/tutorial>.

8.6.3. Method Parameter Reflection

The names of parameters are now available through reflection. That is promising because it can reduce annotation boilerplate. Consider a typical JAX-RS method

[Click here to view code image](#)

```
Person getEmployee(@PathParam("dept") Long dept, @QueryParam("id") Long id)
```

In almost all cases, the parameter names are the same as the annotation arguments, or they can be made to be the same. If the annotation processor could read the parameter names, then one could simply write

[Click here to view code image](#)

```
Person getEmployee(@PathParam Long dept, @QueryParam Long id)
```

This is possible in Java 8, with the new class `java.lang.reflect.Parameter`.

Unfortunately, for the necessary information to appear in the classfile, the source must be compiled as `javac -parameters SourceFile.java`. Let's hope annotation writers will enthusiastically embrace this mechanism, so there will be momentum to drop that compiler flag in the future.

8.7. Miscellaneous Minor Changes

We end this chapter with miscellaneous minor changes that you might find useful. This section covers the new features of the `Objects`, `Logger`, and `Locale` classes, as well as changes to regular expressions and JDBC.

8.7.1. Null Checks

The `Objects` class has static predicate methods `isNull` and `nonNull` that can be useful for streams. For example,

[Click here to view code image](#)

```
stream.anyMatch(Object::isNull)
```

checks whether a stream contains a `null`, and

[Click here to view code image](#)

```
stream.filter(Object::nonNull)
```

gets rid of all of them.

8.7.2. Lazy Messages

The `log`, `logp`, `severe`, `warning`, `info`, `config`, `fine`, `finer`, and `finest` methods of the `java.util.Logger` class now support lazily constructed messages.

For example, consider the call

[Click here to view code image](#)

```
logger.finest("x: " + x + ", y:" + y);
```

The message string is formatted even when the logging level is such that it would never be used. Instead, use

[Click here to view code image](#)

```
logger.finest(() -> "x: " + x + ", y:" + y);
```

Now the lambda expression is only evaluated at the `FINEST` logging level, when the cost of the additional lambda invocation is presumably the least of one's problems.

The `requireNonNull` of the `Objects` class (which is described in [Chapter 9](#)) also has a version that computes the message string lazily.

[Click here to view code image](#)

```
this.directions = Objects.requireNonNull(directions,
() -> "directions for " + this.goal + " must not be null");
```

In the common case that `directions` is not `null`, `this.directions` is simply set to `directions`. If `directions` is `null`, the lambda is invoked, and a `NullPointerException` is thrown whose message is the returned string.

8.7.3. Regular Expressions

Java 7 introduced named capturing groups. For example, a valid regular expression is

[Click here to view code image](#)

```
(?<city>[\p{L} ]+), \s*(?<state>[A-Z]{2})
```

In Java 8, you can use the names in the `start`, `end`, and `group` methods of `Matcher`:

[Click here to view code image](#)

```
Matcher matcher = pattern.matcher(input);
if (matcher.matches()) {
    String city = matcher.group("city");
    ...
}
```

The `Pattern` class has a `splitAsStream` method that splits a `CharSequence` along a regular expression:

[Click here to view code image](#)

```
String contents = new String(Files.readAllBytes(path), StandardCharsets.UTF_8);
Stream<String> words = Pattern.compile("[\p{L}]+").splitAsStream(contents);
```

All nonletter sequences are word separators.

The method `asPredicate` can be used to filter strings that match a regular expression:

[Click here to view code image](#)

```
Stream<String> acronyms = words.filter(Pattern.compile("[A-Z]{2,}").asPredicate());
```

8.7.4. Locales

A locale specifies everything you need to know to present information to a user with local preferences concerning language, date formats, and so on. For example, an American user prefers to see a date formatted as December 24, 2013 or 12/24/2013, whereas a German user expects 24. Dezember 2013 or 24.12.2013.

It used to be that locales were simple, consisting of location, language, and (for a few oddball cases, such as the Norwegians who have two spelling systems) variants. But those oddball cases mushroomed, and the Internet Engineering Task Force issued its “Best Current Practices” memo BC47 (<http://tools.ietf.org/html/bcp47>) to bring some order into the chaos. Nowadays, a locale is composed of up to five components.

1. A language, specified by two or three lowercase letters, such as `en` (English) or `de` (German or, in German, `Deutsch`).
2. A script, specified by four letters with an initial uppercase, such as `Latn` (Latin), `Cyril` (Cyrillic), or `Hant` (traditional Chinese characters). This is useful because some languages, such as Serbian, are written in Latin or Cyrillic, and some Chinese readers prefer the traditional over the simplified characters.
3. A country, specified by two uppercase letters or three digits, such as `US` (United States) or `CH` (Switzerland).
4. Optionally, a variant. Variants are not common any more. For example, the Nynorsk spelling of Norwegian is now expressed with a different language code, `nn`, instead of a variant `NY` of the language `no`.
5. Optionally, an extension. Extensions describe local preferences for calendars (such as the Japanese calendar), numbers (Thai digits), and so on. The Unicode standard specifies some of these extensions. Such extensions start with `u-` and a two-letter code specifying whether the extension deals with the calendar (`ca`), numbers (`nu`), and so on. For example, the extension `u-nu-thai` denotes the use of Thai numerals. Other extensions are entirely arbitrary and start with `x-`, such as `x-java`.

You can still construct a locale the old-fashioned way, such as `new Locale("en", "US")`, but since Java 7 you can simply call `Locale.forLanguageTag("en-US")`. Java 8 adds methods for finding locales that match user needs.

A *language range* is a string that denotes the locale characteristics that a user desires, with `*` for wildcards. For example, a German speaker in Switzerland might prefer anything in German, followed by anything in Switzerland. This is expressed with two `Locale.LanguageRange` objects specified with strings `"de"` and `"*-CH"`. One can optionally specify a weight between 0 and 1 when constructing a `Locale.LanguageRange`.

Given a list of weighted language ranges and a collection of locales, the `filter` method produces a list of matching locales, in descending order of match quality:

[Click here to view code image](#)

```
List<Locale.LanguageRange> ranges = Stream.of("de", "*-CH")
    .map(Locale.LanguageRange::new)
    .collect(Collectors.toList());
// A list containing the Locale.LanguageRange objects for the given strings
List<Locale> matches = Locale.filter(ranges,
    Arrays.asList(Locale.getAvailableLocales()));
// The matching locales: de, de-CH, de-AT, de-LU, de-DE, de-GR, fr-CH, it_CH
```

The static `lookup` method just finds the best locale:

[Click here to view code image](#)

```
Locale bestMatch = Locale.lookup(ranges, locales);
```

In this case, the best match is `de`, which isn't very interesting. But if `locales` contains a more restricted set of locales, such as those in which a document was available, then this mechanism can be useful.

8.7.5. JDBC

In Java 8, JDBC has been updated to version 4.2. There are a few minor changes.

The `Date`, `Time`, and `Timestamp` classes in the `java.sql` package have methods to convert from and to their `java.time` analogs `LocalDate`, `LocalTime`, and `LocalDateTime`.

The `Statement` class has a method `executeLargeUpdate` for executing an update whose row count exceeds `Integer.MAX_VALUE`.

JDBC 4.1 (which was a part of Java 7) specified a generic method `getObject(column, type)` for `Statement` and `ResultSet`, where `type` is a `Class` instance. For example, `URL url = result.getObject("link", URL.class)` retrieves a `DATALINK` as a `URL`. Now the corresponding `setObject` method is provided as well.

Exercises

1. Write a program that adds, subtracts, divides, and compares numbers between 0 and $2^{32} - 1$, using `int` values and `unsigned` operations. Show why `divideUnsigned` and `remainderUnsigned` are necessary.
2. For which integer `n` does `Math.negateExact(n)` throw an exception? (Hint: There is only one.)
3. Euclid's algorithm (which is over two thousand years old) computes the greatest common divisor of two numbers as $\gcd(a, b) = a$ if b is zero, and $\gcd(b, \text{rem}(a, b))$ otherwise, where `rem` is the remainder. Clearly, the `gcd` should not be negative, even if a or b are (since its negation would then be a greater divisor). Implement the algorithm with `%`, `floorMod`, and a `rem` function that produces the mathematical (non-negative) remainder. Which of the three gives you the least hassle with negative values?
4. The `Math.nextDown(x)` method returns the next smaller floating-point number than `x`, just in case some random process hit `x` exactly, and we promised a number $< x$. Can this really happen? Consider `double r = 1 - generator.nextDouble()`, where `generator` is an instance of `java.util.Random`. Can it ever yield 1? That is, can `generator.nextDouble()` ever yield 0? The documentation says it can yield any value between 0 inclusive and 1 exclusive. But, given that there are 2^{53} such floating-point numbers, will you ever get a zero? Indeed, you do. The random number generator computes the next seed as $\text{next}(s) = s \cdot m + a \% N$, where $m = 25214903917$, $a = 11$, and $N = 2^{48}$. The inverse of m modulo N is $v = 246154705703781$, and therefore you can compute the predecessor of a seed as $\text{prev}(s) = (s - a) \cdot v \% N$. To make a `double`, two random numbers are generated, and the top 26 and 27 bits are taken each time. When s is 0, $\text{next}(s)$ is 11, so that's what we want to hit: two consecutive numbers whose top bits are zero. Now, working backwards, let's start with $s = \text{prev}(\text{prev}(\text{prev}(0)))$. Since the `Random` constructor sets $s = (\text{initialSeed} ^ m) \% N$, offer it $s = \text{prev}(\text{prev}(\text{prev}(0))) ^ m = 164311266871034$, and you'll get a zero after two calls to `nextDouble`. But that is still too obvious. Generate a million predecessors, using a stream of course, and pick the minimum seed. Hint: You will get a zero after 376050 calls to `nextDouble`.

5. At the beginning of [Chapter 2](#), we counted long words in a list as

`words.stream().filter(w -> w.length() > 12).count()`. Do the same with a lambda expression, but without using streams. Which operation is faster for a long list?

6. Using only methods of the `Comparator` class, define a comparator for `Point2D` which is a total ordering (that is, the comparator only returns zero for equal objects). Hint: First compare the `x`-coordinates, then the `y`-coordinates. Do the same for `Rectangle2D`.

7. Express `nullsFirst(naturalOrder()).reversed()` without calling `reversed`.

8. Write a program that demonstrates the benefits of the `CheckedQueue` class.

9. Write methods that turn a `Scanner` into a stream of words, lines, integers, or double values. Hint: Look at the source code for `BufferedReader.lines`.

10. Unzip the `src.zip` file from the JDK. Using `Files.walk`, find all Java files that contain the keywords `transient` and `volatile`.

11. Write a program that gets the contents of a password-protected web page. Call `URLConnection connection = url.openConnection();`. Form the string `username:password` and encode it in Base64. Then call

`connection.setRequestProperty("Authorization", "Basic " + encoded string)`, followed by `connection.connect()` and `connection.getInputStream()`.

12. Implement the `TestCase` annotation and a program that loads a class with such annotations and invokes the annotated methods, checking whether they yield the expected values. Assume that parameters and return values are integers.

13. Repeat the preceding exercise, but build a source-level annotation processor emitting a program that, when executed, runs the tests in its `main` method. (See Horstmann and Cornell, *Core Java, 9th Edition, Volume 2*, Section 10.6 for an introduction into processing source-level annotations.)

14. Demonstrate the use of the `Objects.requireNonNull` method and show how it leads to more useful error messages.

15. Using `Files.lines` and `Pattern.asPredicate`, write a program that acts like the `grep` utility, printing all lines that contain a match for a regular expression.

16. Use a regular expression with named capturing groups to parse a line containing a city, state, and zip code. Accept both 5- and 9-digit zip codes.

Chapter 9. Java 7 Features That You May Have Missed

Topics in This Chapter

- [9.1 Exception Handling Changes](#)
- [9.2 Working with Files](#)
- [9.3 Implementing the `equals`, `hashCode`, and `compareTo` Methods](#)
- [9.4 Security Requirements](#)
- [9.5 Miscellaneous Changes](#)
- [Exercises](#)

When Java 7 was released, most reviewers focused on the new language features: strings in switch statements, binary literals, underscores in literals, improved type inference, and so on. In this chapter, I will write about some of the library changes that haven't been discussed so much and that I have found far more useful in daily work than switching on strings or binary literals. I cover one language change that is very useful in daily work—the try-with-resources statement.

The key points of this chapter are:

- Use the try-with-resources statement with any object that implements `AutoCloseable`.
- The try-with-resources statement rethrows the primary exception if closing a resource throws another exception.
- You can catch unrelated exceptions with a single `catch` clause.
- The exceptions for reflective operations now have a common superclass `ReflectiveOperationException`.
- Use the `Path` interface instead of the `File` class.
- You can read and write all characters, or all lines, of a text file with a single command.
- The `Files` class has static methods for copying, moving, and deleting files, and for creating files and directories.
- Use `Objects.equals` for null-safe equality testing.
- `Objects.hash` makes it simple to implement the `hashCode` method.
- When comparing numbers in a comparator, use the static `compare` method.
- Applets and Java Web Start applications continue to be supported in corporate environments, but they may no longer be viable for home users.
- Everyone's favorite trivial change: "`+1`" can now be converted to an integer without throwing an exception.
- Changes in `ProcessBuilder` make it simple to redirect standard input, output, and error streams.

9.1. Exception Handling Changes

I start this chapter with the Java 7 features for exception handling, since they have a major impact on writing reliable programs. I briefly review the try-with-resources statement before moving on to

more subtle changes.

9.1.1. The try-with-resources Statement

Java 7 provides a useful shortcut to the code pattern

```
open a resource
try {
    work with the resource
}
finally {
    close the resource
}
```

provided the resource belongs to a class that implements the `AutoCloseable` interface. That interface has a single method

```
void close() throws Exception
```



NOTE

There is also a `Closeable` interface. It is a subinterface of `AutoCloseable`, also with a single `close` method, but that method is declared to throw an `IOException`.

In its simplest variant, the try-with-resources statement has the form

```
try (Resource res = ...) {
    work with res
}
```

When the `try` block exits, `res.close()` is called automatically. Here is a typical example—reading all words of a file:

[Click here to view code image](#)

```
try (Scanner in = new Scanner(Paths.get("/usr/share/dict/words"))) {
    while (in.hasNext())
        System.out.println(in.next().toLowerCase());
}
```

When the block exits normally, or when there is an exception, the `in.close()` method is called, exactly as if you had used a `finally` block.

You can specify multiple resources, for example:

[Click here to view code image](#)

```
try (Scanner in = new Scanner(Paths.get("/usr/share/dict/words"));
     PrintWriter out = new PrintWriter("/tmp/out.txt")) {
    while (in.hasNext())
        out.println(in.next().toLowerCase());
}
```

No matter how the block exits, both `in` and `out` are closed if they were constructed. This was surprisingly difficult to implement correctly prior to Java 7 (see Exercise 1).



NOTE

A try-with-resources statement can itself have `catch` clauses and a `finally` clause. These are executed after closing the resources. In practice, it's probably not a good idea to pile so much onto a single `try` statement.

9.1.2. Suppressed Exceptions

Whenever you work with input or output, there is an awkward problem with closing the resource after an exception. Suppose an `IOException` occurs and then, when closing the resource, the call to `close` throws another exception.

Which exception will actually be caught? In Java, an exception thrown in a `finally` clause discards the previous exception. This sounds inconvenient, and it is. After all, the user is likely to be much more interested in the original exception.

The try-with-resources statement reverses this behavior. When an exception is thrown in a `close` method of one of the `AutoCloseable` objects, the original exception gets rethrown, and the exceptions from calling `close` are caught and attached as “suppressed” exceptions. This is a very useful mechanism that would be tedious to implement by hand (see Exercise 2).

When you catch the primary exception, you can retrieve those secondary exceptions by calling the `getSuppressed` method:

[Click here to view code image](#)

```
try {  
    ...  
} catch (IOException ex) {  
    Throwable[] secondaryExceptions = ex.getSuppressed();  
}
```

If you want to implement such a mechanism yourself in the (hopefully rare) situation when you can't use the try-with-resources statement, call

[Click here to view code image](#)

```
ex.addSuppressed(secondaryException);
```



NOTE

The classes `Throwable`, `Exception`, `RuntimeException`, and `Error` have constructors with an option for disabling suppressed exceptions and for disabling stack traces. When suppressed exceptions are disabled, calling `addSuppressed` has no effect, and `getSuppressed` returns a zero-length array. When stack traces are disabled, calls to `fillInStackTrace` have no effect, and `getStackTrace` returns a zero-length array. This can be useful for VM errors when memory is low, or for programming languages on the VM that use exceptions to break out of nested method calls.



CAUTION

Detecting secondary exceptions only works when it isn't actively sabotaged. In particular, if you use a `Scanner`, and if input fails, and then closing fails, the `Scanner` class catches the input

exception, closes the resource and catches that exception, and then throws an entirely different exception, without linking the suppressed exceptions.

9.1.3. Catching Multiple Exceptions

As of Java SE 7, you can catch multiple exception types in the same `catch` clause. For example, suppose that the action for missing files and unknown hosts is the same. Then you can combine the `catch` clauses:

[Click here to view code image](#)

```
try {  
    Code that might throw exceptions  
}  
catch (FileNotFoundException | UnknownHostException ex) {  
    Emergency action for missing files and unknown hosts  
}  
catch (IOException ex) {  
    Emergency action for all other I/O problems  
}
```

This feature is only needed when catching exception types that are not subclasses of one another.

Catching multiple exceptions doesn't just make your code look simpler but is also more efficient. The generated bytecodes contain a single block for the shared `catch` clause.



NOTE

When you catch multiple exceptions, the exception variable is implicitly final. For example, you cannot assign a new value to `ex` in the body of the clause `catch`

```
(FileNotFoundException | UnknownHostException ex) { ... }.
```

9.1.4. Easier Exception Handling for Reflective Methods

In the past, when you called a reflective method, you had to catch multiple unrelated checked exceptions. For example, suppose you construct a class and invoke its `main` method:

[Click here to view code image](#)

```
Class.forName(className).getMethod("main").invoke(null, new String[] {});
```

This statement can cause a `ClassNotFoundException`, `NoSuchMethodException`, `IllegalAccessException`, or `InvocationTargetException`.

Of course, you can use the feature described in the preceding section and combine them in a single clause:

[Click here to view code image](#)

```
catch (ClassNotFoundException | NoSuchMethodException  
| IllegalAccessException | InvocationTargetException ex) { ... }
```

However, that is still very tedious. Plainly, it is bad design not to provide a common superclass for related exceptions. That design flaw has been remedied in Java 7. A new superclass `ReflectiveOperationException` has been introduced so that you can catch all of these exceptions

in a single handler:

[Click here to view code image](#)

```
catch (ReflectiveOperationException ex) { ... }
```

9.2. Working with Files

The try-with-resources statement is my favorite feature in Java 7, but the file handling improvements are a close second. Operations that used to be tedious, such as reading a file into a string, or copying a file to another, are now as easy as they should have been all along. These are part of the “NIO2” effort, which refreshes the NIO (“new I/O”) library introduced in 2002 with Java 1.4 (It is never a good idea to include “new” in a product name—what is new today will invariably become old, and the name will look silly.)

Before you can learn how to carry out these easy file operations, you have to learn about the `Path` interface that replaces the `File` class. Next, you will see how to read and write files. Finally, we will turn to file and directory operations.

9.2.1. Paths

A `Path` is a sequence of directory names, optionally followed by a file name. The first component of a path may be a root component, such as `/` or `C:\`. The permissible root components depend on the file system. A path that starts with a root component is *absolute*. Otherwise, it is *relative*. For example, here we construct an absolute and a relative path. For the absolute path, we assume a computer running a Unix-like file system.

[Click here to view code image](#)

```
Path absolute = Paths.get("/", "home", "cay");
Path relative = Paths.get("myprog", "conf", "user.properties");
```

The static `Paths.get` method receives one or more strings, which it joins with the path separator of the default file system (`/` for a Unix-like file system, `\` for Windows). It then parses the result, throwing an `InvalidPathException` if the result is not a valid path in the given file system. The result is a `Path` object.

You can also provide a string with separators to the `Paths.get` method:

[Click here to view code image](#)

```
Path homeDirectory = Paths.get("/home/cay");
```



NOTE

Just like a `File` object, a `Path` object does not have to correspond to a file that actually exists. It is merely an abstract sequence of names. To create a file, first make a path, then call a method to create the corresponding file.

It is very common to combine or resolve paths. The call `p.resolve(q)` returns a path according to these rules:

- If `q` is absolute, then the result is `q`.
- Otherwise, the result is “`p` then `q`,” according to the rules of the file system.

For example, suppose your application needs to find its configuration file relative to the home directory. Here is how you can combine the paths:

[Click here to view code image](#)

```
Path configPath = homeDirectory.resolve("myprog/conf/user.properties");
// Same as homeDirectory.resolve(Paths.get("myprog/conf/user.properties"));
```

There is a convenience method `resolveSibling` that resolves against a path's parent, yielding a sibling path. For example, if `workPath` is `/home/cay/myprog/work`, the call

[Click here to view code image](#)

```
Path tempPath = workPath.resolveSibling("temp");
```

yields `/home/cay/myprog/temp`.

The opposite of `resolve` is `relativize`. The call `p.relativize(r)` yields the path `q` which, when resolved with `p`, yields `r`. For example,

[Click here to view code image](#)

```
Paths.get("/home/cay").relativize(Paths.get("/home/fred/myprog"))
```

yields `../fred/myprog`, assuming we have a file system that uses `..` to denote the parent directory.

The `normalize` method removes any redundant `.` and `..` components (or whatever the file system may deem redundant). For example, normalizing the path `/home/cay/.../fred/./myprog` yields `/home/fred/myprog`.

The `toAbsolutePath` method yields the absolute path of a given path. If the path is not already absolute, it is resolved against the “user directory”—that is, the directory from which the JVM was invoked. For example, if you launched a program from `/home/cay/myprog`, then `Paths.get("config").toAbsolutePath()` returns `/home/cay/myprog/config`.

The `Path` interface has many useful methods for taking paths apart and combining them with other paths. This code sample shows some of the most useful ones:

[Click here to view code image](#)

```
Path p = Paths.get("/home", "cay", "myprog.properties");
Path parent = p.getParent(); // The path /home/cay
Path file = p.getFileName(); // The last element, myprog.properties
Path root = p.getRoot(); // The initial segment / (null for a relative path)
```



NOTE

Occasionally, you may need to interoperate with legacy APIs that use the `File` class instead of the `Path` interface. The `Path` interface has a `toFile` method, and the `File` class has a `toPath` method.

9.2.2. Reading and Writing Files

The `Files` class makes quick work of common file operations. For example, you can easily read the entire contents of a file:

[Click here to view code image](#)

```
byte[] bytes = Files.readAllBytes(path);
```

If you want to read the file as a string, call `readAllBytes` followed by

[Click here to view code image](#)

```
String content = new String(bytes, StandardCharsets.UTF_8);
```

But if you want the file as a sequence of lines, call

[Click here to view code image](#)

```
List<String> lines = Files.readAllLines(path);
```

Conversely, if you want to write a string, call

[Click here to view code image](#)

```
Files.write(path, content.getBytes(StandardCharsets.UTF_8));
```

You can also write a collection of lines with

```
Files.write(path, lines);
```

To append to a given file, use

[Click here to view code image](#)

```
Files.write(path, lines, StandardOpenOption.APPEND);
```



NOTE

By default, all methods of the `Files` class that read or write characters use the UTF-8 encoding. In the (hopefully unlikely) case that you need a different encoding, you can supply a `Charset` argument. Contrast with the `String` constructor and `getBytes` method which use the platform default. Commonly used desktop operating systems still use archaic 8-bit encodings that are incompatible with UTF-8, so we must specify the encoding whenever converting between strings and bytes.

When you work with text files of moderate length, it is usually simplest to process the contents as a single string or list of strings. If your files are large or binary, you can still use the familiar streams or readers/writers:

[Click here to view code image](#)

```
InputStream in = Files.newInputStream(path);
OutputStream out = Files.newOutputStream(path);
Reader reader = Files.newBufferedReader(path);
Writer writer = Files.newBufferedWriter(path);
```

These convenience methods save you from having to deal with `FileInputStream`, `FileOutputStream`, `BufferedReader`, or `BufferedWriter`.

Occasionally, you may have an `InputStream` (for example, from a URL) and you want to save its contents to a file. Use

```
Files.copy(in, path);
```

Conversely,

```
Files.copy(path, out);
```

copies a file to an output stream.

9.2.3. Creating Files and Directories

To create a new directory, call

```
Files.createDirectory(path);
```

All but the last component in the path must already exist. To create intermediate directories as well, use

[Click here to view code image](#)

```
Files.createDirectories(path);
```

You can create an empty file with

```
Files.createFile(path);
```

The call throws an exception if the file already exists. The check for existence and the creation are atomic. If the file doesn't exist, it is created before anyone else has a chance to do the same.

The call `path.exists()` method checks whether the given file or directory exists, but of course it might cease to exist by the time the method has returned.

There are convenience methods for creating a temporary file or directory in a given or system-specific location.

[Click here to view code image](#)

```
Path newPath = Files.createTempFile(dir, prefix, suffix);
Path newPath = Files.createTempFile(prefix, suffix);
Path newPath = Files.createTempDirectory(dir, prefix);
Path newPath = Files.createTempDirectory(prefix);
```

Here, `dir` is a `Path`, and `prefix/suffix` are strings which may be null. For example, the call `Files.createTempFile(null, ".txt")` might return a path such as `/tmp/1234405522364837194.txt`.



NOTE

To read files from a directory, use the `Files.list` and `Files.walk` methods described in [Chapter 8](#).

9.2.4. Copying, Moving, and Deleting Files

To copy a file from one location to another, simply call

```
Files.copy(fromPath, toPath);
```

To move a file (that is, copy and delete the original), call

```
Files.move(fromPath, toPath);
```

You can also use this command to move an empty directory.

The copy or move will fail if the target exists. If you want to overwrite an existing target, use the `REPLACE_EXISTING` option. If you want to copy all file attributes, use the `COPY_ATTRIBUTES` option. You can supply both like this:

[Click here to view code image](#)

```
Files.copy(fromPath, toPath, StandardCopyOption.REPLACE_EXISTING,  
          StandardCopyOption.COPY_ATTRIBUTES);
```

You can specify that a move should be atomic. Then you are assured that either the move completed successfully, or the source continues to be present. Use the `ATOMIC_MOVE` option:

[Click here to view code image](#)

```
Files.move(fromPath, toPath, StandardCopyOption.ATOMIC_MOVE);
```

Finally, to delete a file, simply call

```
Files.delete(path);
```

This method throws an exception if the file doesn't exist, so instead you may want to use

[Click here to view code image](#)

```
boolean deleted = Files.deleteIfExists(path);
```

The deletion methods can also be used to remove an empty directory.



NOTE

There is no convenient method for removing or copying a nonempty directory. See the API documentation of the `FileVisitor` interface for code outlines that achieve these tasks.

9.3. Implementing the `equals`, `hashCode`, and `compareTo` Methods

Java 7 introduces several methods that make it more convenient to deal with null values in the ubiquitous `equals` and `hashCode`, and with numeric comparisons in `compareTo`.

9.3.1. Null-safe Equality Testing

Suppose you have to implement the `equals` method for this class:

```
public class Person {  
    private String first;  
    private String last;  
    ...  
}
```

First, there is the drudgery of casting the parameter to a `Person`:

[Click here to view code image](#)

```
public boolean equals(Object otherObject) {  
    if (this == otherObject) return true;  
    if (otherObject == null) return false;  
    if (getClass() != otherObject.getClass()) return false;  
    Person other = (Person) otherObject;  
    ...  
}
```

Unfortunately, that drudgery isn't simplified yet. But now it gets better. Instead of worrying that `first` or `last` might be `null`, just call

[Click here to view code image](#)

```
return Objects.equals(first, other.first) && Objects.equals(last, other.last);
```

The call `Objects.equals(a, b)` returns `true` if both `a` and `b` are `null`, `false` if only `a` is `null`, and `a.equals(b)` otherwise.



NOTE

In general, it is a good idea to call `Objects.equals(a, b)` when you would have called `a.equals(b)` before.

9.3.2. Computing Hash Codes

Consider computing a hash code for the preceding class. The `Objects.hashCode` method returns a code of `0` for a `null` argument, so you can implement the body of your `hashCode` method like this:

[Click here to view code image](#)

```
return 31 * Objects.hashCode(first) + Objects.hashCode(last);
```

But it gets better than that. The varargs method `Objects.hash`, introduced in Java 7, lets you specify any sequence of values, and their hash codes get combined:

[Click here to view code image](#)

```
return Objects.hash(first, last);
```



NOTE

`Objects.hash` simply calls `Arrays.hash`, which existed since Java 5. But it isn't a varargs method, making it less convenient.



NOTE

There has always been a null-safe way of calling `toString` as `String.valueOf(obj)`. If `obj` is `null`, the string "null" is returned. If you don't like that, you can use `Object.toString` and supply the value to be used for `null`, for example `Object.toString(obj, "")`.

9.3.3. Comparing Numeric Types

When you compare integers in a comparator, it is tempting to return the difference between them since you are allowed to return any negative or positive number—only the sign matters. For example, suppose you are implementing a `Point` class:

[Click here to view code image](#)

```
public int compareTo(Point other) {
    int diff = x - other.x; // Risk of overflow
```

```
    if (diff != 0) return diff;
    return y - other.y;
}
```

But that is problematic. If `x` is large and `other.x` is negative, the difference can overflow. That makes `compareTo` rather tedious (see Exercise 8).

As of Java 7, use the static `Integer.compare` method:

[Click here to view code image](#)

```
public int compareTo(Point other) {
    int diff = Integer.compare(x, other.x); // No risk of overflow
    if (diff != 0) return diff;
    return Integer.compare(y, other.y);
}
```

In the past, some people used `new Integer(x).compareTo(other.x)`, but that creates two boxed integers. The static method has `int` parameters.

The static `compare` method has also been added to `Long`, `Short`, `Byte`, and `Boolean`. If you need to compare two `char` values, you can safely subtract them because the result will not overflow. (The same is true for `short` or `byte`, of course.)



NOTE

The static `compare` method existed for `Double` and `Float` since Java 1.2.

9.4. Security Requirements

When Java 1.0 was introduced in 1995 to an astounded world, the feature that caught everyone's imagination were applets: remotely served code that runs inside the user's web browser. The designers of Java knew perfectly well that executing remote code is a security risk, so they designed a "sandbox" model that stopped any damaging instructions in their tracks.

Soon thereafter, academic researchers found some implementation flaws that were promptly fixed, and other academic researchers groused in general over the fact that the Java security model was rather complex and there was little assurance that its darker corners are safe from assault. At the time, I didn't take that very seriously because the vast majority of Java applet consumers used Microsoft Windows, which was far less secure and far more complex.

Applets were limited to visual effects and network connections to the originating host, which many application writers found limiting. They wanted local device access for storage, printing, and so on. In 2001, Java Web Start delivered an extension of the sandbox that was quite powerful, comparable to today's HTML 5 extensions for local device access. Unfortunately, Java Web Start was poorly understood, not integrated with applets, and not maintained with any vigor.

Instead, many application developers simply signed their web-delivered programs, which gave them full permission to do anything on the user's machine. Signing certificates from commercial entities are within reach of anyone willing to endure some cost and pain. It was also possible to apply a meaningless self-signed certificate, or have users agree to run an applet without a certificate. Warnings were toned down from one release to the next until they became background noise. This was very bad.

Meanwhile, Microsoft, with an enormous engineering effort, got better at closing Windows loopholes, and it became worthwhile for hackers to look at obscure Java vulnerabilities instead. When Oracle purchased Sun in 2010, they inherited a very limited infrastructure for dealing with such attacks and no reliable means of updating client virtual machines. Hackers became increasingly successful in exploiting Java implementation bugs. In this regard, the early researchers who warned of a large attack surface in the Java security model were entirely justified. It took Oracle until 2013 to credibly respond to attacks. Management of client VMs is still a work in progress.

As of today, Oracle signals that it is no longer focused on securing home users' Java applets and Web Start applications (collectively called rich internet applications, or RIAs). Oracle continues to close Java vulnerabilities, and develops tools that are suitable for corporate deployment, so that legacy RIAs can be deployed safely. From a commercial standpoint, this makes sense. Home users are expected to migrate away from PCs to tablets and smartphones. These devices don't support a Java VM in the browser. And business users are a plausible revenue target for maintaining legacy applications.

With successive Java 7 releases, Oracle has tightened the security rules. As of January 2014, RIAs running outside the sandbox need to be signed by a commercial certificate authority. Another requirement is designed to thwart "repurposing attacks." Currently, it is possible to grab a legitimately signed JAR file from a third party and serve it from a hacker site, exploiting some vulnerability in that third-party app. As of January 2014, all JARs *must* have a manifest entry

Permissions: sandbox

or

Permissions: all-permissions

Since the manifest entry is inside the JAR file, it is signed and cannot be modified afterwards. The Java client will not permit sandbox execution of an all-permission client, which prevents "drive-by" attacks where an applet runs without any user consent. Of course, it is still possible to attack users who are habituated to agree to any security dialogs. To make that harder, another, as yet optional, manifest entry has been added:

[Click here to view code image](#)

Codebase: `https://www.mycompany.com www.mycompany.com:8080`

only allows the application to be loaded from one of the given URLs.



NOTE

It has always been possible to call applets from JavaScript—another dubious decision from the point of view of the security minded. If you are using that feature in your application, you can minimize the repurposing risk by adding an entry `Caller-Allowable-Codebase: https://www.mycompany.com` to the manifest before signing.

Overall, these developments are very sad. Java held great promise as a universal execution platform for remote code. If Java had offered a more compelling sandbox, if nonsandbox code had been more aggressively controlled, if there had been consistent response to security breaches, and if client VMs had been reliably updated, Java might still be that universal platform. But there is no use

dwelling on what might have been. At this point, Java is no longer a viable platform for widespread distribution of client applications over the Internet.

If you maintain an applet or Java Web Start application for home users, the message is clear: Move away from it. If your application serves a specialized audience (for example, software development, image editing, or document processing), make your users install Java or bundle a JVM with your installer. If you target a general audience—such as game players—consider using another technology, perhaps HTML 5.

NOTE

If you decide to make your users install Java, you face another hurdle. If you direct Windows users to the installer at <http://java.com>, they will receive the widely reviled toolbar for Ask.com by default (see [Figure 9–1](#)). You have a couple of alternatives. You could have your users install the JDK, directing them to www.oracle.com/technetwork/java/javase/downloads and providing them with instructions for traversing that ever-changing page. Or you could bundle a JVM, which you are then obligated to update since no effective update mechanism is supplied by Oracle.



Figure 9–1 By default, the Windows JRE installer installs the Ask toolbar.

In a corporate environment, you can effectively secure Java RIAs, provided you have control over the applications and the client machines. You will need to tightly manage the application packaging and be ready to update client VMs when security updates become available.

NOTE

To more tightly manage corporate RIAs, you can provide *deployment rulesets* on end-user machines. The process—not for the faint of heart—is explained at

9.5. Miscellaneous Changes

As in the preceding chapter, this section describes a number of smaller features that you may find interesting or useful.

9.5.1. Converting Strings to Numbers

Prior to JDK 1.7, what was the result of the following code segment?

[Click here to view code image](#)

```
double x = Double.parseDouble("+1.0");
int n = Integer.parseInt("+1");
```

Pat yourself on the back if you knew the answer: +1.0 has always been a valid floating-point number, but until Java 7, +1 was not a valid integer.

This has now been fixed for all the various methods that construct `int`, `long`, `short`, `byte`, and `BigInteger` values from strings. There are more of them than you may think. In addition to `parse(Int|Long|Short|Byte)`, there are `decode` methods that work with hexadecimal and octal inputs, and `valueOf` methods that yield wrapper objects. The `BigInteger(String)` constructor is also updated.

9.5.2. The Global Logger

In order to encourage the use of logging even in simple cases, the `Logger` class has a global logger instance. It was meant to be as easy as possible to use, so that you could always add trace statements as `Logger.global.finest("x=" + x);` instead of `System.out.println("x=" + x);`.

Unfortunately, that instance variable has to be initialized somewhere, and if other logging happens in the static initialization code, it was possible to cause deadlocks. Therefore, `Logger.global` was deprecated in Java 6. Instead, you were supposed to call `Logger.getLogger(Logger.GLOBAL_LOGGER_NAME)`, which wasn't anyone's idea of quick and easy logging.

In Java 7, you can call `Logger.getGlobal()` instead, which isn't too bad.

9.5.3. Null Checks

The `Objects` class has methods `requireNonNull` for convenient null checks of parameters. Here is the simplest one:

[Click here to view code image](#)

```
public void process(String directions) {
    this.directions = Objects.requireNonNull(directions);
    ...
}
```

If `directions` is null, a `NullPointerException` is thrown, which doesn't seem like a huge improvement at first. But consider working back from a stack trace. When you see a call to `requireNonNull` as the culprit, you know right away what you did wrong.

You can also supply a message string for the exception:

[Click here to view code image](#)

```
this.directions = Objects.requireNonNull(directions,
    "directions must not be null");
```

9.5.4. ProcessBuilder

Prior to Java 5, the `Runtime.exec` method was the only way to execute an external command from within a Java application. Java 5 added the `ProcessBuilder` class that gives more control over the generated operating system process. In particular, with the `ProcessBuilder`, you can change the working directory.

Java 7 adds convenience methods to hook the standard input, output, and error streams of the process to files. For example,

[Click here to view code image](#)

```
ProcessBuilder builder = new ProcessBuilder(
    "grep", "-o", "[A-Za-z_][A-Za-z_0-9]*");
builder.redirectInput(Paths.get("Hello.java").toFile());
builder.redirectOutput(Paths.get("identifiers.txt").toFile());
Process process = builder.start();
process.waitFor();
```



NOTE

Since Java 8, the `Process` class has a `waitFor` method with timeout:

[Click here to view code image](#)

```
boolean completed = process.waitFor(1, TimeUnit.MINUTES);
```

Also new in Java 7 is the `inheritIO` method of `ProcessBuilder`. It sets the standard input, output, and error streams of the process to those of the Java program. For example, when you run

[Click here to view code image](#)

```
ProcessBuilder builder = new ProcessBuilder("ls", "-al");
builder.inheritIO();
builder.start().waitFor();
```

then the output of the `ls` command is sent to `System.out`.

9.5.5. URLClassLoader

Suppose you want to write a Java program that automates execution of JUnit tests. To load the `JUnitCore` class, you need a class loader that reads the JUnit JAR files:

[Click here to view code image](#)

```
URL[] urls = {
    new URL("file:junit-4.11.jar"),
    new URL("file:hamcrest-core-1.3.jar")
};
URLClassLoader loader = new URLClassLoader(urls);
Class<?> klass = loader.loadClass("org.junit.runner.JUnitCore");
```

Before Java 7, code such as this could lead to resource leaks. Java 7 simply adds a `close` method to close the classloader. `URLClassLoader` now implements `AutoCloseable`, so you can use a try-with-resources statement:

[Click here to view code image](#)

```
try (URLClassLoader loader = new URLClassLoader(urls)) {
    Class<?> klass = loader.loadClass("org.junit.runner.JUnitCore");
    ...
}
```



CAUTION

Don't use any classes after the classloader has been closed. If you do, and those classes need to load other classes to do their work, they will fail.

9.5.6. BitSet

A `BitSet` is a set of integers that is implemented as a sequence of bits. The i^{th} bit is set if the set contains the integer i . That makes for very efficient set operations. Union/intersection/complement are simple bitwise or/and/not.

Java 7 adds methods to construct bitsets.

[Click here to view code image](#)

```
byte[] bytes = { (byte) 0b10101100, (byte) 0b00101000 };
BitSet primes = BitSet.valueOf(bytes);
// {2, 3, 5, 7, 11, 13}
long[] longs = { 0x100010116L, 0x1L, 0x1L, 0L, 0x1L };
BitSet powersOfTwo = BitSet.valueOf(longs);
// {1, 2, 4, 8, 16, 32, 64, 128, 256}
```

The inverse methods are `toByteArray` and `toLongArray`.

[Click here to view code image](#)

```
byte[] bytes = powersOfTwo.toByteArray();
// [0b00010110, 1, 1, 0, 1, 0, 0, 0, 1, ...]
```



NOTE

As of Java 8, `BitSet` has a method `stream` that yields an `IntStream`.

Exercises

1. Implement a code segment that constructs a `Scanner` and a `PrintWriter` at the end of [Section 9.1.1, “The try-with-resources Statement,”](#) on page [180](#), without the `try-with-resources` statement. Be sure to close both objects, provided they have been properly constructed. You need to consider the following conditions:

- The `Scanner` constructor throws an exception.
- The `PrintWriter` constructor throws an exception.
- `hasNext`, `next`, or `println` throws an exception.
- `in.close()` throws an exception.
- `out.close()` throws an exception.

2. Improve on the preceding exercise by adding any exceptions thrown by `in.close()` or `out.close()` as suppressed exceptions to the original exception, if there was one.
3. When you rethrow an exception that you caught in a `multi-catch` clause, how do you declare its type in the `throws` declaration of the ambient method? For example, consider

[Click here to view code image](#)

```
public void process() throws ... {
    try {
        ...
        catch (FileNotFoundException | UnknownHostException ex) {
            logger.log(Level.SEVERE, "...", ex);
            throw ex;
        }
    }
```

4. In which other parts of the Java library did you encounter situations that would benefit from `multi-catch` or, even better, common exception superclasses? (Hint: XML parsing.)
5. Write a program that reads all characters of a file and writes them out in reverse order. Use `Files.readAllBytes` and `Files.write`.
6. Write a program that reads all lines of a file and writes them out in reverse order. Use `Files.readAllLines` and `Files.write`.
7. Write a program that reads the contents of a web page and saves it to a file. Use `URL.openStream` and `Files.copy`.
8. Implement the `compareTo` method of the `Point` class in [Section 9.3.3, “Comparing Numeric Types](#),” on page [189](#), without using `Integer.compareTo`.

9. Given a class

[Click here to view code image](#)

```
public class LabeledPoint {
    private String label;
    private int x;
    private int y;
    ...
}
```

implement the `equals` and `hashCode` methods.

10. Implement a `compareTo` method for the `LabeledPoint` class of the preceding exercise.
11. Using the `ProcessBuilder` class, write a program that calls `grep -r` to look for credit card numbers in all files in any subdirectory of the user’s home directory. Collect the numbers that you found in a file.
12. Turn the application of the preceding exercise into an applet or a Java Web Start implementation. Suppose you want to offer it to users as a security scan. Package it so that it will run on your JRE. What did you have to do? What would your users have to do to run it from your web site?

Index

Symbols

- operator, for numbers, [159](#)
- , in shell scripts, [151](#)
- >, in lambda expressions, [4–6](#)
- ; (semicolon), in JavaScript, [141](#)
- :: operator, in method references, [8](#)
- / (slash), in Unix paths, [184](#)
 - ` ... ` (back quotes), in shell scripts, [149](#)
- ^ (caret), for denoting free variables, [4](#)
- ' ... ' and " ... " (single and double quotes)
 - in JavaScript, [138](#)
 - in shell scripts, [150](#)
- [...] (square brackets), in JavaScript, [141](#), [144–145](#)
- { ... } (curly braces), in lambdas, [5](#)
- \$ (dollar sign), in JavaScript, [142](#)
- \$ { ... }, in shell scripts, [150](#)
- * (asterisk), in locales, [173](#)
- \ (backslash), in Windows paths, [184](#)
- # !, in shell scripts, [151](#)
- + operator, for numbers, [159](#)
- < operator, in JavaScript, [143](#)

A

- abstract methods, in functional interfaces, [6](#)
- acceptEither method (`CompletableFuture`), [134](#)
- accumulate method (`LongAccumulator`), [122](#)
- accumulateAndGet method (`AtomicXXX`), [121](#)
- actions, repeating, [49](#)
- add method
 - of `Bindings`, [78](#)
 - of `LongAdder`, [121](#)
- addExact method (`Math`), [159](#)
- addListener method (`JavaFX`), [72](#), [153](#)
- addSuppressed method (`Throwable`), [182](#)
- allof method (`CompletableFuture`), [134](#)
- AnchorPane class (`JavaFX`), [84](#)
- and method

of Bindings, [78–79](#)

of Predicate, [50](#)

Android, [80](#)

AnnotatedElement interface, getAnnotation, getAnnotationsByType methods, [168](#)

annotations, [167–171](#)

 container, [167](#)

 in lambdas, [5](#)

 no annotations for, [170](#)

 repeated, [167–169](#)

 type use, [169–170](#)

anyMatch method (Stream), [28](#)

anyOf method (CompletableFuture), [134](#)

Apollo 11, launch of, [104, 109](#)

applets, [190–192](#)

Application class

 init method, [153](#)

 start method, [71](#)

 stop method, [153](#)

applyToEither method (CompletableFuture), [134](#)

\$ARG, in shell scripts, [151](#)

ArithmeticException, [159](#)

arrays

 and generic types, [10, 61](#)

 computing values of, [129](#)

 from stream elements, [33](#)

 in Nashorn, [144–145](#)

 sorting, [128](#)

 type use annotations in, [170](#)

Arrays class

 parallelXXX methods, [128–129](#)

 sort method, [3, 6](#)

 stream method, [39](#)

ASCII characters, printable, [166](#)

Ask.com toolbar, [192](#)

asPredicate method (Pattern), [172](#)

asynchronous applications, [131](#)

atomic values, [120–123](#)

 and performance, [121](#)

 in concurrent hash maps, [124–126](#)

AtomicXXX classes

 accumulateAndGet method, [121](#)

`compareAndSet` method, [120](#)
`getAndXXX` methods, [121](#)
`incrementAndGet` method, [120](#)
`updateAndGet` method, [121](#)

Atwood's law, [153](#)

`atZone` method (`LocalDateTime`), [109](#)

autoboxing, reducing, [52](#)

`AutoCloseable` interface, [25](#), [163](#), [180–181](#), [195](#)

`average` method (`XXXStream`), [40](#)

AWT (Abstract Window Toolkit), [70](#)

B

`Base64`, `BASE64Encoder` classes, [166](#)

`BeanInfo` class, [73](#)

`between` method (`Duration`), [103](#)

`BiConsumer` interface, [43](#), [51](#)

`BiFunction` interface, [7](#), [43](#), [51](#)

`BigInteger` class, [159](#)

 constructor for, [193](#)

`BinaryOperator` interface, [43](#), [51](#)

`bind`, `bindBidirectional` methods (`XXXProperty`), [76](#)

`Binding` interface, [78](#)

bindings, [75–80](#)

 lambdas for, [79](#)

 with JavaScript, [140](#)

`Bindings` class, methods of, [78–79](#)

`BiPredicate` interface, [51](#)

`BitSet` class, [195](#)

 constructor for, [195](#)

`stream` method, [161](#), [196](#)

`toXXXArray` methods, [196](#)

`valueOf` method, [196](#)

books, counting words in, [22](#)

`Boolean` class, logical`XXX` methods of, [158](#)

`BooleanProperty` class, [74](#)

`BooleanSupplier` interface, [53](#)

`BorderLayout` control (Swing), [81](#)

`BorderPane` class (JavaFX), [80–81](#), [84](#)

`boxed` method (`XXXStream`), [40](#)

`BufferedReader` class, `lines` method, [164](#)

`BufferedXXX` classes, [186](#)

buttons

disabling, at the ends of a gauge, [77](#)

event handling for, [3](#), [8](#)

Byte class

compare method, [190](#)

decode method, [193](#)

parseByte method, [193](#)

toUnsignedXXX methods, [158](#)

valueOf method, [193](#)

BYTE static field, [158](#)

byteValueExact method (`BigInteger`), [159](#)

C

C++ programming language

default methods in, [15](#)

unsigned types in, [159](#)

Calendar class, [101](#)

Callable interface

call method, [8](#)

checked exceptions in, [60](#)

casts, type use annotations in, [170](#)

catch statement, [181](#)

multiple exceptions in, [182–183](#)

certificates, signing, [190](#)

ChangeListener interface, [75](#), [77](#), [153](#)

charAt method (`String`), [25](#)

CharSequence interface

chars, codePoints methods, [39](#), [158](#)

splitting by regular expressions, [24](#), [172](#)

checked exceptions, [8](#)

checkedNavigableXXX methods (`Collections`), [162](#)

checkedQueue method (`Collections`), [162](#)

Checker Framework, [169–170](#)

Church, Alonzo, [4](#), [104](#)

“class wins” rule, [16](#)

ClassCastException, [162](#)

classes

and classloader, [195](#)

companion, [16](#)

extending, in JavaScript, [146–148](#)

classifier functions, [36](#)

`clone` method (`Object`), [6](#)
`close` method (`AutoCloseable`), [163](#), [180–181](#)
`Closeable` interface, [180](#)
closures, [11](#)
code units, [39](#), [158](#)
`codePoints` method (`CharSequence`), [39](#), [158](#)
`collect` method (`Stream`), [33–34](#)
Collection interface, [160–163](#)

- `parallelStream` method, [23](#), [40](#)
- `removeI` methods, [160–161](#)
- `stream` method, [22–24](#)
- `toArray` method, [61](#)

collections, [160–163](#)

- and lambda expressions, [160](#)
- processing, [22–23](#)
- sorting, [27](#)
- threadsafe, [119](#)
- vs. streams, [22](#)

Collections class, [17](#), [162–163](#)

- `checkedQueue` method, [162](#)
- `emptySortedXXX` methods, [163](#)
- `sort` method, [27](#)
- `xxxNavigableXXX` methods, [162](#)

collections library

- adding `forEach` method to, [14](#)
- and function expressions, [1](#)

Collector interface, [33](#)
Collectors class, [33](#)

- `counting` method, [37](#)
- `groupingBy` method, [36–39](#)
- `groupingByConcurrent` method, [41](#)
- `joining` method, [34](#)
- `mapping` method, [38](#)
- `maxBy`, `minBy` methods, [37](#)
- `partitioningBy` method, [36–37](#), [39](#)
- `reducing` method, [38](#)
- `summarizingXXX` methods, [34](#)
- `summingXXX` methods, [37](#)
- `toCollection` method, [33](#)
- `toConcurrentMap` method, [36](#)
- `toMap` method, [34–36](#)

`toSet` method, [33](#), [37](#)
collectors, downstream, [37–39](#)
`com` global object (JavaScript), [141](#)
Comparator interface, [2](#), [161–162](#)
 and lambdas, [6](#)
 `compare` method, [17](#)
 comparing method, [17](#), [161–162](#)
 `naturalOrder` method, [162](#)
 `nullXXX` methods, [162](#)
 `reverseOrder`, reversed methods, [162](#)
 `thenComparing` method, [161–162](#)
comparators, [49](#)
 chaining, [161](#)
 comparing integers in, [189–190](#)
 customizing, [54](#)
`compare` method (integer types), [3–6](#), [189–190](#)
`compareAndSet` method (`AtomicXXX`), [120](#)
`compareUnsigned` method (`Integer`, `Long`), [159](#)
CompletableFuture class, [130–131](#)
 `acceptEither`, `applyToEither` methods, [134](#)
 `allof`, `anyOf` methods, [134](#)
 exceptions in, [133](#)
 `handle` method, [133](#)
 `runAfterXXX` methods, [134](#)
 `runAsync` method, [131](#)
 `supplyAsync` method, [131–132](#)
 `thenAccept` method, [132–133](#)
 `thenAcceptBoth` method, [134](#)
 `thenApply` method, [63](#), [130–133](#)
 `thenApplyAsync` method, [131–133](#)
 `thenCombine` method, [134](#)
 `thenCompose` method, [132–133](#)
 `thenRun` method, [133](#)
 `whenComplete` method, [133](#)
CompletionStage interface, [134](#)
`compose` method (`UnaryOperator`), [55–56](#)
composition pipeline, [131–132](#)
`compute`, `computeIfXXX` methods (`Map`), [161](#)
concat method
 of `Bindings`, [79](#)
 of `Stream`, [26](#)

concurrent programming, [1](#), [119–135](#)
ConcurrentHashMap class, [123–128](#)
 atomic updates in, [124–126](#)
 compute, computeIfXXX methods, [125–126](#)
 forEach, forEachXXX methods, [126–128](#)
 get method, [124](#)
 mappingCount method, [123](#)
 merge method, [125–126](#)
 newKeySet, keySet methods, [128](#)
 organizing buckets as trees in, [124](#)
 put method, [124](#)
 putIfAbsent method, [125](#)
 reduce, reduceXXX methods, [126–128](#)
 replace method, [124](#)
 search, searchXXX methods, [126–128](#)
config method (Logger), [171](#)
constructor references, [9–10](#)
 for arrays, [10](#)
 type use annotations in, [170](#)
Consumer interface, [43](#), [51](#)
convert method (Bindings), [79](#)
copy method (Files), [186–187](#)
count method (Stream), [22–23](#), [28](#)
counting method (Collectors), [37](#)
createBindings method (ScriptEngine), [140](#)
createXXX methods (Files), [186–187](#)
createXXXBindings methods (Bindings), [79](#)
CSS (Cascading Style Sheets), [80](#)
 using with JavaFX, [90–91](#)

D

Date class, [115](#), [174](#)
Date and Time API, [101–117](#)
 and legacy code, [115–116](#)
dates
 computing, [107–108](#)
 difference between, [104–106](#)
 formatting, [112–115](#)
 local, [104–106](#)
 local preferences for, [172](#)
 parsing, [115](#)

`DateTimeFormatter` class, [112–115](#)

and legacy classes, [116](#)

`format` method, [112](#)

`ofLocalizedXXX` methods, [112](#)

`ofPattern` method, [114](#)

`parse` method, [115](#)

`toFormat` method, [114](#)

`withLocale` method, [112](#)

`DayOfWeek` class, [106](#)

`dayOfWeekInMonth` method (`TemporalAdjusters`), [107](#)

deadlocks, [119](#)

in loggers, [193](#)

debugging

layouts, [84, 91](#)

streams, [27](#)

with checked wrappers, [162](#)

`decrementExact` method (`Math`), [159](#)

default methods, [14–16](#)

adding to interfaces, [16](#)

resolving ambiguities in, [15](#)

deferred execution, [2–4, 48–49](#)

`delete`, `deleteIfExists` methods (`Files`), [187](#)

deployment rulesets, [193](#)

directories

checking existence of, [187](#)

creating, [186](#)

deleting, [188](#)

paths for, [184](#)

streams of, [165](#)

temporary, [187](#)

working, changing, [194](#)

`DirectoryStream` interface, [165](#)

`disableProperty` method (`JavaFX`), [77](#)

`distinct` method (`Stream`), [27, 41, 160](#)

`divide` method (`Bindings`), [76, 78](#)

`dividedBy` method (`Instant, Duration`), [103](#)

`divideUnsigned` method (`Integer, Long`), [159](#)

`Double` class

`compare` method, [190](#)

`decode` method, [193](#)

`isXXX` methods, [159](#)

`parseDouble` method, [193](#)
`sum, max, min` methods, [158](#)
`valueOf` method, [193](#)

`DoubleAccumulator`, `DoubleAdder` classes, [122](#)

`DoubleProperty` class, [74–75](#)

`doubles` method (`Random`), [40](#)

`DoubleStream` class, [39–40](#)

boxed method, [40](#)

mapToDouble method, [39](#)

range, rangeClosed methods, [39](#)

sum, average, max, min methods, [40](#)

summaryStatistics method, [40](#)

toArray method, [40](#)

`DoubleSummaryStatistics` class, [34, 40](#)

`DoubleXXX` interfaces, [43, 53](#)

downstream collectors, [37–39](#)

`DropShadow` class (JavaFX), [93](#)

`Duration` class

arithmetic operations, [103](#)

between method, [103](#)

immutable, [104](#)

toXXX methods, [103](#)

dynamically typed languages, [143](#)

E

ECMAScript standard, [137, 146](#)

`edu` global object (JavaScript), [141](#)

Emacs text editor, running `jjs` inside, [139](#)

emails, binary data in, [166](#)

`empty` method (`Optional`), [30](#)

`emptyNavigableXXX` methods (`Collections`), [162](#)

`emptySortedXXX` methods (`Collections`), [163](#)

`<<END`, in shell scripts, [150](#)

`$ENV`, in shell scripts, [151](#)

environment variables, [151](#)

epoch, definition of, [102](#)

`equal, equalIgnoreCase` methods (`Bindings`), [78](#)

`equals` method (`Object`), [16, 188](#)

`$ERR`, in shell scripts, [149](#)

Error, Exception classes, disabling suppressed exceptions in, [182](#)

`eval` method (`ScriptEngine`), [140](#)

event handlers

- deferred execution in, [3](#)
- for asynchronous actions, [131](#)
- passing methods to, [8](#)
- event-driven programming, [1](#)
- exception specifications, type use annotations in, [170](#)
- exceptions, [58–61](#)
 - catching multiple, [182–183](#)
 - checked, [7–8](#)
 - in functional interfaces, [60–61](#)
 - in reflective methods, [183](#)
 - suppressed, [181–182](#)
- `exec` method (`Runtime`), [194](#)
- `executeLargeUpdate` method (`Statement`), [174](#)
- `ExecutionException`, [133](#)
- `exists` method (`Files`), [187](#)
- `exit` function (shell scripts), [152](#)
- `$EXIT`, in shell scripts, [149](#)
- expression closure, [146](#)
- `extends` keyword, for function types, [62](#)

F

- `FadeTransition` class (JavaFX), [92](#)
- fat clients, [70](#)
- `File` class, `toPath` method, [185](#)
- `FileReader` class, [163](#)
- files
 - checking existense of, [187](#)
 - closing, [163](#)
 - copying/moving/deleting, [187](#)
 - creating, [184](#), [186](#)
 - processing, [50](#)
 - reading, [185](#)
 - all words of, [181](#)
 - lazily, [163–164](#)
 - redirecting standard I/O streams to, [194](#)
 - saving streams into, [186](#)
 - specifying encoding for, [163](#)
 - temporary, [187](#)
 - working with, [183–188](#)
 - writing, [185](#)

Files class, [185–188](#)

copy method, [186–187](#)

createXXX methods, [186–187](#)

delete, deleteIfExists methods, [187](#)

encodings in, [186](#)

exists method, [187](#)

lines method, [25, 163](#)

list method, [165](#)

move method, [187](#)

newBufferedXXX, newXXXStream methods, [186](#)

readAllXXX methods, [185](#)

walk method, [165](#)

write method, [185](#)

FileTime class, and legacy classes, [116](#)

FileVisitor interface, [188](#)

FileXXXStream classes, [186](#)

fillInStackTrace method (Throwable), [182](#)

filter method

of Locale, [173](#)

of Stream, [22–23, 25, 28, 42–43, 160](#)

final modifier, in lambdas, [5](#)

finally statement, [181](#)

findXXX methods (Stream), [28](#)

fine, finer, finest methods (Logger), [171](#)

firstDayOfXXX methods (TemporalAdjusters), [107](#)

Flash, [70](#)

flatMap method

of Optional, [30–31, 64](#)

of Stream, [26](#)

Float class

compare method, [190](#)

isXXX methods, [159](#)

sum, max, min methods, [158](#)

FloatProperty class, [74](#)

floorXXX methods (Math), [159–160](#)

FlowPane class (JavaFX), [84](#)

for loop, enhanced, [165](#)

forEach method

adding to collection library, [14](#)

of ConcurrentHashMap, [126–128](#)

of Iterable, [14, 161](#)

of `Map`, [161](#)
of `Stream`, [34](#)

`forEachOrdered` method (`Stream`), [34](#)

`forEachRemaining` method (`Iterator`), [161](#)

`forEachXXX` methods (`ConcurrentHashMap`), [126–128](#)

`forLanguageTag` method (`Locale`), [173](#)

`format` method

- of `Bindings`, [79](#)
- of `DateTimeFormatter`, [112](#)

formatters, for date/time values

- custom, [114](#)
- predefined, [112–113](#)

`from` method (`Instant`, `ZonedDateTime`), [115](#)

Function interface, [43](#), [51](#)

- identity method, [35](#)

function keyword (JavaScript), [146](#)

function types

- generic, [50](#)
- using wildcards for, [62](#)

functional interfaces, [6–8](#), [42–43](#)

- annotating, [7](#)
- as return type, [53–54](#)
- choosing, [48](#), [50–53](#)
- composing, [54](#), [63](#)
- conversion to, [6](#)
- defining, [52](#)
- exceptions in, [60–61](#)
- generic, [7](#)
- methods in abstract, [6](#)
- methods in non abstract, [50](#)
- parallelizing, [57–58](#)
- processed lazily, [56–57](#)

functional programming, [1](#)

`@FunctionalInterface` annotation, [7](#), [52](#)

Future interface, [130](#)

futures

- combining multiple, [133–134](#)
- completable, [130–134](#)
- composing, [132–134](#)

`fx:id` attribute (FXML), [89](#)

FXML, [86–90](#)

constructing elements in, [87](#)

initialization in, [89](#)

writing files in, [87](#)

@FXML annotation, [88](#)

G

GaussianBlur class (JavaFX), [94](#)

generate method (Stream), [24](#), [39](#)

generic types

 and arrays, [10](#)

 and lambdas, [61–62](#)

 type use annotations in, [170](#)

generic wrappers, [60](#)

get method

 of ConcurrentHashMap, [124](#)

 of LongAccumulator, [122](#)

 of ObservableXXXValue, [78](#)

 of Path, [184–185](#)

 of property classes, [75](#)

getAndXXX methods (AtomicXXX), [121](#)

getAnnotation, getAnnotationsByType methods (AnnotatedElement), [168](#)

getAsXXX methods (OptionalXXX classes), [40](#)

getAverage method (XXXSummaryStatistics), [34](#)

getBytes method (String), [185–186](#)

getEncoder, getXXXEncoder methods (Base64), [166](#)

getFileName method (Path), [185](#)

getGlobal, getLogger methods (Logger), [193](#)

getMax method (XXXSummaryStatistics), [34](#)

getObject method (ResultSet, Statement), [174](#)

getParent, getRoot (Path), [185](#)

getStackTrace method (Throwable), [182](#)

getSuppressed method (Throwable), [181–182](#)

getters/setters

 in JavaFX, [73–75](#)

 in Nashorn, [141](#)

getValue method (property classes), [75](#), [78](#)

getXXX methods (Date and Time API), [105–106](#), [108](#), [111–112](#)

GlassFish administration tool, [150](#)

Glow class (JavaFX), [94](#)

greaterThan, greaterThanOrEqual methods (Bindings), [78](#)

GregorianCalendar class, [115](#)

`toZonedDateTime` method, [115](#)
`GridBagLayout` control (Swing), [82](#)
`GridPane` class (JavaFX), [82–84](#), [87](#)
 alignment in, [83](#)
 using CSS with, [90–91](#)

Groovy programming language
 executing scripts in, [140](#)
 JavaFX bindings in, [86](#)

`groupingBy` method (`Collectors`), [36–39](#)
`groupingByConcurrent` method (`Collectors`), [41](#)
GStreamer framework, [95–97](#)

H

`handle` method (`CompletableFuture`), [133](#)
`hash` method (`Arrays`, `Objects`), [189](#)
hash tables, [123](#)
`hashCode` method
 of `Objects`, [189](#)
 of primitive types, [158](#)
`hasNext` method (JavaScript), [146–147](#)
`HBx` class (JavaFX), [81–82](#), [84](#), [87](#)
 alignment and padding in, [83](#)
 using CSS with, [91](#)
here documents, [150](#)
HTML (HyperText Markup Language), [80](#)
 HTML 5, [190](#), [192](#)
HTTP authentication, [166](#)

I

IANA (Internet Assigned Numbers Authority), [109](#)
`identity` method (`Function`), [35](#)
identity values, [32](#)
`ifPresent` method (`Optional`), [29](#)
`IllegalStateException`, [35](#)
images, transforming, [49–57](#)
 parallel, [57–58](#)
implements specification, type use annotations in, [170](#)
in-car displays, user interfaces for, [71](#)
`increment` method (`LongAdder`), [121–122](#)
`incrementAndGet` method (`AtomicXXX`), [120](#)
`incrementExact` method (`Math`), [159](#)

`info` method (`Logger`), [49](#), [171](#)
`inheritIO` method (`ProcessBuilder`), [194](#)

`init` method (`Application`), [153](#)

`Initializable` interface, [88](#)

inner classes

 capturing values in, [9](#), [12](#)

 vs. lambdas, [6](#)

`InputStream` class, [186](#)

`instanceof` keyword, and type use annotations, [170](#)

`Instant` class, [102](#)

 and legacy classes, [116](#)

 arithmetic operations, [103](#)–[104](#)

`from` method, [115](#)

 immutable, [104](#)

`now` method, [102](#)

`Integer` class

`compare` method, [3](#)–[6](#), [189](#)–[190](#)

`decode` method, [193](#)

`parseInt` method, [193](#)

`sum`, `max`, `min` methods, [158](#)

`toUnsignedLong` method, [158](#)

`valueOf` method, [193](#)

`xxxUnsigned` methods, [159](#)

integer ranges, [39](#)

integer remainders, [159](#)–[160](#)

`IntegerProperty` class, [74](#)–[75](#)

interfaces

 functional, [42](#)–[43](#), [48](#), [50](#)–[53](#)

 implemented in JavaScript, [146](#)–[148](#)

 methods in, [16](#)–[17](#)

 default, [14](#)–[16](#)

 name clashes between, [15](#)

 nonabstract, [6](#)

`Introspector` class, [73](#)

`ints` method (`Random`), [40](#)

`IntStream` class, [39](#)–[40](#)

`boxed` method, [40](#)

`mapToInt` method, [39](#)–[40](#)

`of` method, [39](#)

`range`, `rangeClosed` methods, [39](#)

`sum`, `average`, `max`, `min` methods, [40](#)

summaryStatistics method, [40](#)
toArray method, [40](#)
IntSummaryStatistics class, [34](#), [40](#)
intValueExact method (`BigInteger`), [159](#)
IntXXX interfaces, [43](#), [53](#)
InvalidationListener interface, [75](#), [77](#), [153](#)
InvalidPathException, [184](#)
IOException, [164](#)
isEmpty, isNotEmpty,isNull, isNotNull methods (`Bindings`), [78](#)
isEqual method (`Predicate`), [50](#)
isFinite, isInfinite, isNaN methods (`Double`, `Float`), [159](#)
isLoggable method (`Logger`), [49](#)
isNull method (objects), [171](#)
isPresent method (`Optional`), [28–29](#)
isXXX methods (Date and Time API), [105](#), [108](#), [112](#)
isZero, isNegative methods (`Instant`, `Duration`), [103](#)
Iterable interface, [165](#)
 forEach method, [14](#), [161](#)
iterate method (`Stream`), [24](#), [27](#), [39](#)
Iterator interface, forEachRemaining method, [161](#)
iterators, [33](#)
 for random numbers, [146–147](#)

J

Java Media Framework, [95](#)
Java programming language
 executing external commands from, [194](#)
 implementation bugs in, [191](#)
 simplicity and consistency of, [4](#)
Java Web Start, [190–192](#)
java, javax, javafx global objects (JavaScript), [141](#)
Java.extend function (JavaScript), [146–147](#)
Java.from function (JavaScript), [145](#)
Java.super function (JavaScript), [148](#)
Java.to function (JavaScript), [144–145](#)
Java.type function (JavaScript), [141–142](#)
java.util.concurrent package, [119](#), [130](#)
java.util.concurrent.atomic package, [120](#)
java.util.function package, [7](#)
JavaBeans, [73](#)
javadoc comments, redeclaring `Object` methods for, [6](#)

JavaFX, [69–98](#)

- controls in, [94–97](#)
- debugging in, [84, 91](#)
- dimensions in, [82](#)
- event handling in, [72–73](#)
- getters/setters in, [73–75](#)
- labels in, [71](#)
- launching, [72](#)
- from Nashorn, [152–154](#)
- layouts in, [80–86](#)
- alignment, [83](#)
- cell styling, [84, 91](#)
- markup, [86–90](#)
- padding property, [82](#)
- panes, [80](#)
- properties in, [72–75, 153](#)
- scenes in, [71](#)
- setting fonts in, [71](#)
- sliders in, [72–73](#)
- special effects in, [91–94](#)
- stages in, [71, 140](#)
- transitions in, [92](#)
- using CSS in, [90–91](#)
- versions of, [70](#)

JavaFX Script programming language, [85](#)

JavaScript programming language

- accessing Java applications from, [153](#)
- anonymous functions in, [146](#)
- anonymous subclasses in, [147](#)
- bracket notation in, [141, 144–145](#)
- calling applets from, [191](#)
- catching Java exceptions in, [148](#)
- constructing objects in, [141–142](#)
- delimiters in, [138](#)
- extending Java classes in, [146–148](#)
- implementing Java interfaces in, [146–148](#)
- inner classes in, [142](#)
- instance variables in, [147](#)
- invoking:
 - Java methods in, [140–141](#)
 - superclasses in, [148](#)

making JavaFX stages visible in, [140](#)

Mozilla implementation of, [146](#)

no method overloading in, [141](#)

numbers in, [143](#)

objects vs. strings in, [143](#)

REPL in, [138–139](#)

semicolons in, [141](#)

static methods in, [142](#)

using with Nashorn, [137–155](#)

`javax.annotation.processing` package, [169](#)

`javax.lang.model` package, [169](#)

JDBC (Java Database Connectivity), [174](#)

JDK (Java Development Kit), installed by users, [192](#)

`JEditorPane` control (Swing), [95](#)

`jjs` tool, [138–139](#)

command-line arguments in, [151](#)

executing commands in, [149](#)

`-fx` option, [152](#)

`join` method (`String`), [158](#)

`joining` method (`Collectors`), [34](#)

JRuby programming language, [140](#)

`jrunscript` script shell, [149, 151](#)

JUnit test, automated execution of, [195](#)

`JUnitCore` class, [195](#)

JVM (Java Virtual Machine), installed by users, [192](#)

Jython programming language, [140](#)

K

`keySet` method (`ConcurrentHashMap`), [128](#)

kiosks, user interfaces for, [71](#)

L

`Label` class, `setFont` method, [71](#)

lambda expressions, [1–17, 48–49](#)

accessing variables in, [10–13](#)

and collections, [160](#)

and computed bindings, [79](#)

and functional interfaces, [6](#)

and generics, [61–62](#)

and JavaScript, [146](#)

and method references, [8](#)

annotations in, [5](#)
capturing values by, [11](#)
event handling with, [72](#)
modifiers in, [5](#)
no assigning to a variable of type `Object`, [7](#)
no-arg, [48](#)
parameter types in, [5](#)
parameters of, [49–50](#)
result type of, [6](#)
scope of, [13](#)
syntax of, [4–5](#)
`this` keyword in, [13](#)
throwing exceptions in, [58–61](#)
updating counters with, [13](#)
using with `map` method, [25](#)
vs. inner classes, [6](#)

language range, [173](#)

`lastXXX` methods (`TemporalAdjusters`), [107](#)

leap seconds, [102](#)

leap years, [105](#)

`length` method (`Bindings`), [78](#)

`lessThan`, `lessThanOrEqual` methods (`Bindings`), [78](#)

`limit` method (`Stream`), [26](#), [41](#)

`lines` method

 of `BufferedReader`, [164](#)

 of `Files`, [25](#), [163](#)

`lines`, reading, [25](#), [163–164](#), [185](#)

Lisp programming language, [1](#)

`list` method (`Files`), [165](#)

`List` interface, [17](#)

`replaceAll`, `sort` methods, [160–161](#)

`ListProperty` class, [74](#)

lists

 declaring non-null elements of, [169](#)

 in Nashorn, [145](#)

`LocalDate` class, [174](#)

 and legacy classes, [116](#)

 methods of, [105–106](#)

`LocalDateTime` class, [109](#), [174](#)

 and legacy classes, [116](#)

`atZone` method, [109](#)

`Locale` class

`filter` method, [173](#)

`forLanguageTag` method, [173](#)

`lookup` method, [173](#)

`locales`, [36](#), [172–174](#)

`default`, [112](#)

`finding`, [173](#)

 formatting styles for, [114](#)

`LocalTime` class, [108–109](#), [174](#)

 and legacy classes, [116](#)

 methods of, [108](#)

`locks`, [122](#)

`Logger` class

`getGlobal`, `getLogger` methods, [193](#)

`isLoggable` method, [49](#)

`log`, `logp`, `severe`, `warning`, `info`, `config`, `fine`, `finer`, `finest` methods, [171](#)

`Logger.global` instance, [193](#)

`logging`, lazily, [48–49](#), [171–172](#)

`logicalXXX` methods (`Boolean`), [158](#)

`Long` class

`compare` method, [190](#)

`decode` method, [193](#)

`parseLong` method, [193](#)

`sum`, `max`, `min` methods, [158](#)

`valueOf` method, [193](#)

`xxxUnsigned` methods, [159](#)

`LongAccumulator` class, [121](#)

`accumulate`, `get` methods, [122](#)

`LongAdder` class, [121](#), [125](#)

`add`, `sum` methods, [121](#)

`increment` method, [121–122](#)

`LongProperty` class, [74](#)

`longs` method (`Random`), [40](#)

`LongStream` class, [39–40](#)

`boxed` method, [40](#)

`mapToLong` method, [39](#)

`range`, `rangeClosed` methods, [39](#)

`sum`, `average`, `max`, `min` methods, [40](#)

`summaryStatistics` method, [40](#)

`toArray` method, [40](#)

`LongSummaryStatistics` class, [34](#), [40](#)

`longValueExact` method (`BigInteger`), [159](#)

`LongXXX` interfaces, [43](#), [53](#)

M

`map` method

 of `Optional`, [29](#), [63](#)

 of `Stream`, [25](#), [63](#)

`Map` interface, methods of, [161](#)

`mapping` method (`Collectors`), [38](#)

`mappingCount` method (`ConcurrentHashMap`), [123](#)

`MapProperty` class, [74](#)

maps

 concurrent, [36](#)

 in Nashorn, [145](#)

 merging, [34–36](#), [41](#)

`mapToInt` method (`Stream`), [32](#)

`mapToXXX` methods (`XXXStream`), [39–40](#)

`Math` class, [159–160](#)

`max` method

 of `Bindings`, [78](#)

 of integer types, [158](#)

 of streams, [28](#), [40](#)

`maxBy` method (`Collectors`), [37](#)

`Media`, `MediaXXX` classes (JavaFX), [95–96](#)

`merge` method (`ConcurrentHashMap`), [125–126](#)

messages, constructed lazily, [171–172](#)

method references, [8–9](#)

`this`, `super` parameters in, [9](#)

 type use annotations in, [170](#)

methods

 abstract, in functional interfaces, [6](#)

 customizing functions passed to, [54](#)

 default, [14–16](#)

 adding to interfaces, [16](#)

 parameters of, available through reflection, [170–171](#)

 reflective, exceptions in, [183](#)

 resolving ambiguities in, [15–16](#)

 static, adding to interfaces, [16–17](#)

Microsoft Office, [139](#)

`min` method

 of `Bindings`, [78](#)

of integer types, [158](#)

of streams, [28](#), [40](#)

minus, minus XXX methods (Date and Time API), [103](#), [105–106](#), [108](#), [111](#)

monads, [26](#), [63–64](#)

MonthDay class, [106](#)

move method (`Files`), [187](#)

Mozilla JavaScript implementation, [146](#)

multipliedBy method (`Instant, Duration`), [103](#)

multiply method (`Bindings`), [78](#)

multiplyExact method (`Math`), [159](#)

N

named capturing groups, [172](#)

Nashorn engine, [137–155](#)

anonymous subclasses in, [147](#)

arrays in, [144–145](#)

catching Java exceptions in, [148](#)

class objects in, [142](#)

extending Java classes in, [146–148](#)

getters/setters in, [141](#)

implementing Java interfaces in, [146–148](#)

instance variables in, [147](#)

invoking:

Java methods in, [140–141](#)

superclasses in, [148](#)

launching JavaFX from, [152–154](#)

lists and maps in, [145](#)

numbers in, [143](#)

running from:

command line, [138–139](#)

Java, [139–140](#)

shell scripting in, [148–152](#)

strings in, [142–143](#)

naturalOrder method (`Comparator`), [162](#)

Navigable XXX classes, [162](#)

negate method

of `Bindings`, [78](#)

of `Predicate`, [50](#)

negated method (`Instant, Duration`), [103](#)

negateExact method (`Math`), [159](#)

new keyword, in constructor references, [9](#)

`new` operator (JavaScript), [142](#), [144](#), [147](#)
`newBufferedXXX`, `newXXXStream` methods (`Files`), [186](#)
`newKeySet` method (`ConcurrentHashMap`), [128](#)
`next` method (JavaScript), [146–147](#)
`next`, `nextOrSame` methods (`TemporalAdjusters`), [107](#)
`nextXXX` methods (`Math`), [160](#)
NIO (New I/O) library, [183](#)
nominal typing, [50](#)
`noneMatch` method (`Stream`), [28](#)
noninterference, of stream operations, [42](#)
`@NonNull` annotation, [169](#)
`nonNull` method (`Objects`), [171](#)
`normalize` method (`Path`), [185](#)
`NoSuchElementException`, [29](#)
`not` method (`Bindings`), [78](#)
`notEqual`, `notEqualIgnoreCase` methods (`Bindings`), [78](#)
`now` method (Date and Time API), [102–103](#), [105](#), [108](#), [111](#)
`@Nullable` annotation, [169](#)
`NullPointerException`, [28](#), [169](#), [194](#)
null-safe equality testing, [188](#)
`nullXXX` methods (`Comparator`), [162](#)
Number type (JavaScript), [143](#)
numbers, [158–159](#)

- arithmetic operations on, [158](#)
- comparing, [162](#), [189–190](#)
- converting from strings, [193](#)
- unsigned, [158–159](#)

O

`Object` class

- `clone` method, [6](#)
- `equals` method, [16](#)
- no redefining for methods of, [16](#)
- `toString` method, [6](#), [16](#), [189](#)

`object-oriented` programming, [1](#)
`ObjectProperty` class, [74](#)
`Objects` class

- `equals` method, [188](#)
- `hash` method, [189](#)
- `hashCode` method, [189](#)
- `isNull`, `nonNull` methods, [171](#)

`requireNonNull` method, [172](#), [194](#)

`ObjXXXConsumer` interfaces, [53](#)

`Observable`, `ObservableValue` interfaces, [77](#)

`ObservableXXXValue` interfaces, [78](#)

`of` method

 of Date and Time API, [105](#), [108–109–111](#)

 of `IntStream`, [39](#)

 of `Optional`, [30](#)

 of `Stream`, [24](#)

`ofDateAdjuster` method (`TemporalAdjusters`), [107](#)

`OffsetDateTime` class, [112](#)

`ofInstant` method (`ZonedDateTime`), [111](#)

`ofLocalizedXXX` methods (`DateTimeFormatter`), [112](#)

`ofNullable` method (`Optional`), [30](#)

`ofPattern` method (`DateTimeFormatter`), [114](#)

`Optional` class, [28–31](#)

 creating values of, [30](#)

 empty method, [30](#)

 flatMap method, [30–31](#), [64](#)

 ifPresent method, [29](#)

 isPresent method, [28–29](#)

 map method, [29](#), [63](#)

 of, `ofNullable` methods, [30](#)

`OptionalXXX` classes, [40](#)

`or` method

 of `Bindings`, [78](#)

 of `Predicate`, [50](#)

`org` global object (JavaScript), [141](#)

`$OUT`, in shell scripts, [149](#)

P

`Package` object (JavaScript), [141](#)

`parallel` method (`Stream`), [40](#)

parallelism threshold, [126](#)

`parallelStream` method (`Collection`), [23](#), [40](#), [160](#)

`ParallelTransition` class (JavaFX), [93](#)

`parallelXXX` methods (`Arrays`), [128–129](#)

`Parameter` class, [171](#)

`parse` method (`DateTimeFormatter`), [115](#)

`parseXXX` methods (integer types), [193](#)

`partitioningBy` method (`Collectors`), [36–37](#), [39](#)

Path interface, [16–17](#), [184–185](#)

get, getXXX methods, [184–185](#)

normalize method, [185](#)

relativize method, [184](#)

resolve, resolveSibling methods, [184](#)

toAbsolutePath, toFile methods, [185](#)

paths

absolute, [185](#)

combining, [185](#)

for directories, [184](#)

resolving, [184](#)

Paths class, [16–17](#)

Pattern class

asPredicate method, [172](#)

splitAsStream method, [24](#), [172](#)

peek method (Stream), [27](#), [34](#)

performance, and atomic values, [121](#)

Period class, [106](#)

PHP programming language, [140](#)

plus, plusXXX methods (Date and Time API), [103](#), [105–106](#), [108](#), [110–111](#)

Predicate interface, [42–43](#), [50–51](#)

and, or, negate, isEqual methods, [50](#)

previous, previousOrSame methods (TemporalAdjusters), [107](#)

primitive types

comparing, [162](#)

specializations for, [52](#)

streams of, [39–40](#), [161](#)

transforming hash map values to, [128](#)

wrappers for, [158](#)

println method (System.out), [8](#)

Process class, waitFor method, [194](#)

ProcessBuilder class, [194–195](#)

inheritIO method, [194](#)

redirectXXX methods, [194](#)

Programmer's Day, [105](#)

properties (JavaFX), [72–80](#)

bound, [73](#)

computed, [76](#)

enumerating, [73](#)

final, [74](#)

implementing, [74](#)

listeners for, [72](#), [74](#), [153](#)

numeric, using `ChangeListener` for, [75](#)

updating automatically, [75–80](#)

`Property` interface, [74](#)

`put` method (`ConcurrentHashMap`), [124](#)

`putIfAbsent` method

of `ConcurrentHashMap`, [125](#)

of `Map`, [161](#)

R

race conditions, [41](#), [119–120](#)

`Random` class, methods of, [40](#)

random numbers, [40](#), [146–147](#)

range, `rangeClosed` methods (`XXXStream`), [39](#)

`readAllXXX` methods (`Files`), [185](#)

`readLine` function (shell scripts), [151](#)

`redirectXXX` methods (`ProcessBuilder`), [194](#)

`reduce`, `reduceXXX` methods (`ConcurrentHashMap`), [31–33](#), [126–128](#)

reducing method (`Collectors`), [38](#)

reductions, [28](#), [31–32](#)

reflection, [170–171](#)

reflective methods, [183](#)

`ReflectiveOperationException`, [183](#)

regular expressions, [172](#)

`relativize` method (`Path`), [184](#)

rem units, [82](#)

`remainderUnsigned` method (`Integer`, `Long`), [159](#)

`remove` method (`Map`), [161](#)

`removeIf` method (`Collection`), [160–161](#)

`@Repeatable` annotation, [168](#)

REPL (“read-eval-print” loop), [138–139](#)

`replace` method

of `ConcurrentHashMap`, [124](#)

of `Map`, [161](#)

`replaceAll` method

of `List`, [160–161](#)

of `Map`, [161](#)

repurposing attacks, [191](#)

`requireNonNull` method (`Objects`), [172](#), [194](#)

`resolve`, `resolveSibling` methods (`Path`), [184](#)

`ResultSet` class, `get`/`setObject` methods, [174](#)

return statement, in lambdas, [5](#)
reverseOrder, reversed methods (`Comparator`), [162](#)
Rhino engine, [137](#)
rlwrap tool, [139](#)
RotateTransition class (JavaFX), [92–93](#)
runAfterXXX methods (`CompletableFuture`), [134](#)
runAsync method (`CompletableFuture`), [131](#)
Runnable interface, [51](#)
 and lambdas, [6](#)
 run method, [2](#)
Runtime class, exec method, [194](#)
RuntimeException class, disabling suppressed exceptions in, [182](#)

S

sandbox, [190–191](#)
Scala programming language
 covariant type parameters in, [61](#)
 default methods in, [15](#)
 JavaFX bindings in, [86](#)
 REPL in, [139](#)
ScaleTransition class (JavaFX), [92](#)
Scanner class, [164](#), [182](#)
SceneBuilder program, [80](#), [87](#)
scheduling applications
 and time zones, [104](#), [109](#)
 computing dates for, [107–108](#)
Scheme programming language, [1](#)
 executing scripts in, [140](#)
ScriptEngine interface, createBindings, eval methods, [140](#)
search, searchXXX methods (`ConcurrentHashMap`), [126–128](#)
seconds, leap, [102](#)
security, [190–193](#)
select, selectXXX methods (`Bindings`), [79](#)
SequentialTransition class (JavaFX), [93](#)
set, setValue methods (property classes), [75](#)
setFont method (`Label`), [71](#)
setObject method (`ResultSet`, `Statement`), [174](#)
SetProperty class, [74](#)
sets
 flattening, [26](#), [63](#)
 operations on, for integers, [195](#)

`threadsafe`, [128](#)

`severe` method (`Logger`), [171](#)

`shebang`, [151](#)

`shell scripts`, [148–152](#)

- command-line arguments in, [151](#)

- environment variables in, [151](#)

- string interpolation in, [150](#)

`Short` class

- `compare` method, [190](#)

- `decode` method, [193](#)

- `parseShort` method, [193](#)

- `sum`, `max`, `min` methods, [158](#)

- `toUnsignedXXX` methods, [158](#)

- `valueOf` method, [193](#)

`shortValueExact` method (`BigInteger`), [159](#)

`SimpleXXXProperty` classes, [74](#)

`size` method (`Bindings`), [78](#)

`SIZE` static field, [158](#)

`skip` method (`Stream`), [26](#)

`sleep` method (`Thread`), [8](#)

`slice` method (`JavaScript`), [142](#)

`sort` method

- `of Arrays`, [3](#), [6](#)

- `of Collections`, [27](#)

- `of List`, [160–161](#)

`sorted` method (`Stream`), [27](#)

sorting

- people, by name, [161–162](#)

- strings by length, [2–5](#)

`split` method (`String`), [158](#)

`splitAsStream` method (`Pattern`), [24](#), [172](#)

`spliterator` method (`Collection`), [160](#)

square root, computing, [31](#)

stack traces

- disabling, [182](#)

- working back from, [194](#)

`StackPane` class (`JavaFX`), [84](#)

`$STAGE`, in shell scripts, [152](#)

`StampedLock` class, [122–123](#)

`start` method

- `of Application`, [71](#)

of Thread, [2](#)

statement class, methods of, [174](#)

static methods, adding to interfaces, [16–17](#)

stop method (Application), [153](#)

stream method

of Arrays, [39](#)

of BitSet, [161, 196](#)

of Collection, [22–24, 160](#)

Stream interface

collect method, [33](#)

concat method, [26](#)

count method, [22–23, 28](#)

distinct method, [27, 41, 160](#)

filter method, [22–23, 25, 28, 42–43, 160](#)

findXXX methods, [28](#)

flatMap method, [26](#)

generate method, [24, 39](#)

iterate method, [24, 27, 39](#)

limit method, [26, 41](#)

map method, [25, 63](#)

mapToInt method, [32](#)

max, min methods, [28](#)

of method, [24](#)

parallel method, [40](#)

peek method, [27, 34](#)

skip method, [26](#)

sorted method, [27](#)

toArray method, [10, 33](#)

unordered method, [41](#)

xxxMatch methods, [28](#)

streams, [21–43](#)

closing, [25, 164](#)

combining, [26](#)

converting:

between objects and primitive types of, [39–40](#)

to arrays, [33](#)

creating, [24–25](#)

debugging, [27](#)

empty, [32](#)

extracting substreams from, [26](#)

flattening, [26](#)

infinite, [23–24](#), [27](#)
cutting, [26](#)
intermediate operations for, [23](#)
noninterference of, [42](#)
null checks for, [171](#)
of directory entries, [165](#)
of primitive type values, [39–40](#), [161](#)
of random numbers, [40](#)
ordered, [41](#)
parallel, [23](#), [28](#), [34](#), [40–42](#)
pipeline of, [27](#)
processed lazily, [23](#), [27](#), [42](#)
reductions of, [28](#)
sorting, [27](#)
standard I/O, redirecting to files, [194](#)
terminal operation for, [23](#)
threadsafe operations on, [41](#)
transformations of, [25–26](#)
stateful, [27](#)
stateless, [26–27](#)
vs. collections, [22](#)
with no elements, [24](#)
`StrictMath` class, [160](#)
`String` class
 `charAt` method, [25](#)
 `getBytes` method, [185–186](#)
 `join`, `split` methods, [158](#)
 `toLowerCase` method, [25](#)
 `valueOf` method, [189](#)
string interpolation, [150](#)
`StringProperty` class, [74–75](#)
strings
 combining, [158](#)
 converting to numbers, [193](#)
 filtering by regular expressions, [172](#)
 sorting by length, [2–5](#)
 splitting, [24](#), [158](#), [172](#)
 transforming to lowercase, [25](#)
 `subtract` method (`Bindings`), [78](#)
 `subtractExact` method (`Math`), [159](#)
 `sum` method

of integer types, [158](#)

of LongAdder, [121](#)

of XXXStream, [40](#)

summarizingXXX methods (Collectors), [34](#)

summaryStatistics method (XXXStream), [40](#)

summingXXX methods (Collectors), [37](#)

super keyword

capturing in method references, [9](#)

for function types, [62](#)

superclasses

for related exceptions, [183](#)

type use annotations in, [170](#)

Supplier interface, [43, 48, 51](#)

supplyAsync method (CompletableFuture), [131–132](#)

Swing, [70, 80](#)

naming controls in, [71](#)

showing HTML in, [95](#)

synchronizedNavigableXXX methods (Collections), [162](#)

T

Temporal interface, with method, [107](#)

TemporalAdjuster interface, [107](#)

TemporalAdjusters class, [107](#)

thenAccept method (CompletableFuture), [132–133](#)

thenAcceptBoth method (CompletableFuture), [134](#)

thenApply method (CompletableFuture), [63, 130–133](#)

thenApplyAsync method (CompletableFuture), [131–133](#)

thenCombine method (CompletableFuture), [134](#)

thenComparing method (Comparator), [161–162](#)

thenCompose method (CompletableFuture), [132–133](#)

thenRun method (CompletableFuture), [133](#)

this keyword

capturing in method references, [9](#)

in lambda expressions, [13](#)

Thread class

constructor for, [147](#)

sleep method, [8](#)

start method, [2](#)

threads

atomic mutations in, [120–123](#)

concurrency enhancements for, [119–135](#)

executing:
code in, [2](#)
increments concurrently, [12–13](#)
locking, [120–123](#)
race conditions in, [41](#)
reading web pages in, [130](#)
starting new, [2](#), [9](#)
terminating upon an exception, [59](#)
updating hash tables in, [123–128](#)

Throwable class

addSuppressed method, [182](#)
getStackTrace, fillInStackTrace methods, [182](#)
getSuppressed method, [181–182](#)

TilePane class (JavaFX), [84](#)

time

between two instants, [103](#)
current, [102](#)
daylight savings, [109–112](#)
formatting, [112–115](#)
local, [108–109](#)
measuring, [103](#)
parsing, [115](#)
zoned, [109–112](#)

Time class, [115](#), [174](#)

Timestamp class, [115](#), [174](#)

timestamps, [112](#)

using instants as, [103](#)

TimeZone class, and legacy classes, [116](#)

toAbsolutePath method (Path), [185](#)

toArray method

of Collection, [61](#)
of Stream, [10](#), [33](#)
of XXXStream, [40](#)

toCollection method (Collectors), [33](#)

toConcurrentMap method (Collectors), [36](#)

toFile method (Path), [185](#)

toFormat method (DateTimeFormatter), [114](#)

toInstant method

of Date, [115](#)
of ZonedDateTime, [109](#), [112](#)

toIntExact method (Math), [159](#)

`toLocalXXX` methods (`ZonedDateTime`), [112](#)
`toLowerCase` method (`String`), [25](#)
`toMap` method (`Collectors`), [34–36](#)
`toPath` method (`File`), [185](#)
`toSet` method (`Collectors`), [33, 37](#)
`toString` method (`Object`), [16](#)
 null-safe calling, [189](#)
 redeclaring, [6](#)
`toUnsignedXXX` methods (integer types), [158](#)
`toXXX` methods (`Duration`), [103](#)
`toXXXArray` methods (`BitSet`), [196](#)
`ToXXXBiFunction` interfaces, [53](#)
`ToXXXFunction` interfaces, [43, 53](#)
`toXXXofDay` methods (`LocalTime`), [108](#)
`toZonedDateTime` method (`GregorianCalendar`), [115](#)
`tryOptimisticRead` method (`StampedLock`), [122–123](#)
`try-with-resources` statement, [180–181](#)
 closing:
 files with, [163–165](#)
 streams with, [25, 164](#)
 for JUnit tests, [195](#)
 suppressed exceptions in, [181–182](#)
`type parameters`, [61](#)
`type use annotations`, [169–170](#)

U

`UnaryOperator` interface, [43, 51–52](#)
 compose method, [55–56](#)
`unbind`, `unbindBidirectional` methods (`XXXProperty`), [76](#)
`UncheckedIOException`, [164](#)
`unmodifiableNavigableXXX` methods (`Collections`), [162](#)
`unordered` method (`Stream`), [41](#)
`until` method (`LocalDate`), [105–106](#)
`updateAndGet` method (`AtomicXXX`), [121](#)
`URLClassLoader` class, [195](#)
`use-site variance`. *See* [wildcards](#)
`UTC` (coordinated universal time), [110](#)

V

`valueAt`, `XXXValueAt` methods (`Bindings`), [79](#)
`valueOf` method

of `BitSet`, [196](#)

of integer types, [193](#)

of `String`, [189](#)

`valueProperty` method (JavaFX), [72](#)

values

captured:

by inner classes, [12](#)

by lambda expressions, [11](#)

grouping, [36–38](#)

partitioning, [36–37](#)

variables

accessing in lambdas, [10–13](#)

atomic mutations of, [120–123](#)

effectively final, [12](#)

VB Script programming language, [139](#)

`VBox` class (JavaFX), [82](#), [84](#)

vendor lock, [139](#)

videos, playing, [95–97](#)

W

`waitFor` method (`Process`), [194](#)

`walk` method (`Files`), [165](#)

`warning` method (`Logger`), [171](#)

web pages

layout of, [80](#)

reading:

from URL, [63](#), [132](#)

in a separate thread, [130](#)

WebKit engine, [95](#)

`WebView` class (JavaFX), [95](#)

`whenComplete` method (`CompletableFuture`), [133](#)

wildcards, [61](#)

type use annotations in, [170](#)

`with` method (`Temporal`), [107](#)

`withLocale` method (`DateTimeFormatter`), [112](#)

`withXXX` methods (Date and Time API), [105](#), [108](#), [111](#)

`write` method (`Files`), [185](#)

Y


`Year`, `YearMonth` classes, [106](#)

years, leap, [105](#)

Z

`ZonedDateTime` class
and legacy classes, [115–116](#)
methods of, [109–112](#), [115](#)

Get Started Quickly with Scala



ISBN-13: 978-0-321-77409-5

Scala for the Impatient concisely shows developers what Scala can do and how to do it. In this guide, Cay Horstmann offers a rapid, code-based introduction that's completely practical. Horstmann introduces Scala concepts and techniques in blog-sized chunks that you can quickly master and apply. Hands-on activities guide you through well-defined stages of competency, from basic to expert.

Safari
Books Online

Available in print and eBook formats

informIT

For more information and sample content visit
informit.com/title/9780321774095

REGISTER



THIS PRODUCT

informit.com/register

Register the Addison-Wesley, Exam Cram, Prentice Hall, Que, and Sams products you own to unlock great benefits.

To begin the registration process, simply go to **informit.com/register** to sign in or create an account.

You will then be prompted to enter the 10- or 13-digit ISBN that appears on the back cover of your product.

Registering your products can unlock the following benefits:

- Access to supplemental content, including bonus chapters, source code, or project files.
- A coupon to be used on your next purchase.

Registration benefits vary by product. Benefits will be listed on your Account page under Registered Products.

About InformIT — THE TRUSTED TECHNOLOGY LEARNING SOURCE

INFORMIT IS HOME TO THE LEADING TECHNOLOGY PUBLISHING IMPRINTS Addison-Wesley Professional, Cisco Press, Exam Cram, IBM Press, Prentice Hall Professional, Que, and Sams. Here you will gain access to quality and trusted content and resources from the authors, creators, innovators, and leaders of technology. Whether you're looking for a book on a new technology, a helpful article, timely newsletters, or access to the Safari Books Online digital library, InformIT has a solution for you.

informIT.com

THE TRUSTED TECHNOLOGY LEARNING SOURCE

Addison-Wesley | Cisco Press | Exam Cram
IBM Press | Que | Prentice Hall | Sams

SAFARI BOOKS ONLINE

PEARSON

InformIT is a brand of Pearson and the online presence for the world's leading technology publishers. It's your source for reliable and qualified content and knowledge, providing access to the top brands, authors, and contributors from the tech community.

▲Addison-Wesley

Cisco Press

EXAM/CRAM

IBM
Press..

QUE'

PRENTICE
HALL

SAMS

Safari[®]
Books Online

LearnIT at **InformIT**

Looking for a book, eBook, or training video on a new technology? Seeking timely and relevant information and tutorials? Looking for expert opinions, advice, and tips? **InformIT has the solution.**

- Learn about new releases and special promotions by subscribing to a wide variety of newsletters.
Visit informit.com/newsletters.
- Access FREE podcasts from experts at informit.com/podcasts.
- Read the latest author articles and sample chapters at informit.com/articles.
- Access thousands of books and videos in the Safari Books Online digital library at safari.informit.com.
- Get tips from expert blogs at informit.com/blogs.

Visit informit.com/learn to discover all the ways you can access the hottest technology content.

Are You Part of the **IT** Crowd?

Connect with Pearson authors and editors via RSS feeds, Facebook, Twitter, YouTube, and more! Visit informit.com/socialconnect.



```
class Worker implements Runnable {  
    public void run() {  
        for (int i = 0; i < 1000; i++)  
            doWork();  
    }  
    ...  
}
```

```
class LengthComparator implements Comparator<String> {  
    public int compare(String first, String second) {  
        return Integer.compare(first.length(), second.length());  
    }  
}
```

```
Arrays.sort(strings, new LengthComparator());
```

```
button.setOnAction(new EventHandler<ActionEvent>() {  
    public void handle(ActionEvent event) {  
        System.out.println("Thanks for clicking!");  
    }  
});
```

```
Integer.compare(first.length(), second.length())
```

```
(String first, String second)
-> Integer.compare(first.length(), second.length())
```

```
lambda first, second: Integer.compare(first.length(), second.length())
```

```
(String first, String second) -> {  
    if (first.length() < second.length()) return -1;  
    else if (first.length() > second.length()) return 1;  
    else return 0;  
}
```

```
() -> { for (int i = 0; i < 1000; i++) doWork(); }
```

```
Comparator<String> comp
    = (first, second) // Same as (String first, String second)
        -> Integer.compare(first.length(), second.length());
```

```
EventHandler<ActionEvent> listener = event ->
    System.out.println("Thanks for clicking!");
    // Instead of (event) -> or (ActionEvent event) ->
```

```
(String first, String second) -> Integer.compare(first.length(), second.length())
```

```
Arrays.sort(words,  
        (first, second) -> Integer.compare(first.length(), second.length()));
```

```
button.setOnAction(event ->
    System.out.println("Thanks for clicking!));
```

```
BiFunction<String, String, Integer> comp  
= (first, second) -> Integer.compare(first.length(), second.length());
```

```
Runnable sleeper = () -> { System.out.println("Zzz"); Thread.sleep(1000); };  
// Error: Thread.sleep can throw a checked InterruptedException
```

```
button.setOnAction(event -> System.out.println(event));
```

```
button.setOnAction(System.out::println);
```

```
Arrays.sort(strings, String::compareToIgnoreCase)
```

```
class Greeter {  
    public void greet() {  
        System.out.println("Hello, world!");  
    }  
}  
  
class ConcurrentGreeter extends Greeter {  
    public void greet() {  
        Thread t = new Thread(super::greet);  
        t.start();  
    }  
}
```

```
List<String> labels = ...;  
Stream<Button> stream = labels.stream().map(Button::new);  
List<Button> buttons = stream.collect(Collectors.toList());
```

```
Object[] buttons = stream.toArray();
```

```
Button[] buttons = stream.toArray(Button[]::new);
```

```
public static void repeatMessage(String text, int count) {  
    Runnable r = () -> {  
        for (int i = 0; i < count; i++) {  
            System.out.println(text);  
            Thread.yield();  
        }  
    };  
    new Thread(r).start();  
}
```

```
public static void repeatMessage(String text, int count) {  
    Runnable r = () -> {  
        while (count > 0) {  
            count--; // Error: Can't mutate captured variable  
            System.out.println(text);  
            Thread.yield();  
        }  
    };  
    new Thread(r).start();  
}
```

```
int matches = 0;
for (Path p : files)
    new Thread(() -> { if (p has some property) matches++; }).start();
    // Illegal to mutate matches
```

```
List<Path> matches = new ArrayList<>();  
for (Path p : files)  
    new Thread(() -> { if (p has some property) matches.add(p); }).start();  
    // Legal to mutate matches, but unsafe
```

```
int[] counter = new int[1];
button.setOnAction(event -> counter[0]++);
```

```
Path first = Paths.get("/usr/bin");
Comparator<String> comp =
    (first, second) -> Integer.compare(first.length(), second.length());
// Error: Variable first already defined
```

```
public class Application() {  
    public void doWork() {  
        Runnable runner = () -> { ...; System.out.println(this.toString()); ... };  
        ...  
    }  
}
```

```
for (int i = 0; i < list.size(); i++)
    System.out.println(list.get(i));
```

```
list.forEach(System.out::println);
```

```
interface Person {  
    long getId();  
    default String getName() { return "John Q. Public"; }  
}
```

```
interface Named {  
    default String getName() { return getClass().getName() + "_" + hashCode(); }  
}
```

```
class Student implements Person, Named {  
    ...  
}
```

```
class Student implements Person, Named {  
    public String getName() { return Person.super.getName(); }  
    ...  
}
```

```
class Student extends Person implements Named { ... }
```

```
public interface Path {  
    public static Path get(String first, String... more) {  
        return FileSystems.getDefault().getPath(first, more);  
    }  
    ...  
}
```

```
public static void shuffle(List<?> list)
```

```
public static <T> List<T> nCopies(int n, T o)
    // Constructs a list of n instances of o
```

```
new Thread(uncheck(  
() -> { System.out.println("Zzz"); Thread.sleep(1000); })).start();  
// Look, no catch (InterruptedException)!
```

```
String[] names = { "Peter", "Paul", "Mary" };
List<Runnable> runners = new ArrayList<>();
for (String name : names)
    runners.add(() -> System.out.println(name));
```

```
String contents = new String(Files.readAllBytes(  
    Paths.get("alice.txt")), StandardCharsets.UTF_8); // Read file into string  
List<String> words = Arrays.asList(contents.split("[\\P{L}]+"));  
// Split into words; nonletters are delimiters
```

```
int count = 0;
for (String w : words) {
    if (w.length() > 12) count++;
}
```

```
long count = words.stream().filter(w -> w.length() > 12).count();
```

```
long count = words.parallelStream().filter(w -> w.length() > 12).count();
```

```
Stream<String> words = Stream.of(contents.split("\\P{L}+"));  
// split returns a String[] array
```

```
Stream<String> song = Stream.of("gently", "down", "the", "stream");
```

```
Stream<String> silence = Stream.empty();
// Generic type <String> is inferred; same as Stream.<String>empty()
```

```
Stream<String> echos = Stream.generate(() -> "Echo");
```

```
Stream<Double> randoms = Stream.generate(Math::random);
```

```
Stream<BigInteger> integers  
= Stream.iterate(BigInteger.ZERO, n -> n.add(BigInteger.ONE));
```

```
Stream<String> words  
= Pattern.compile("[\\P{L}]+").splitAsStream(contents);
```

```
try (Stream<String> lines = Files.lines(path)) {  
    Do something with lines  
}
```

```
List<String> wordList = ...;  
Stream<String> words = wordList.stream();  
Stream<String> longWords = words.filter(w -> w.length() > 12);
```

```
Stream<String> lowercaseWords = words.map(String::toLowerCase);
```

```
Stream<Character> firstChars = words.map(s -> s.charAt(0));
```

```
public static Stream<Character> characterStream(String s) {  
    List<Character> result = new ArrayList<>();  
    for (char c : s.toCharArray()) result.add(c);  
    return result.stream();  
}
```

```
Stream<Stream<Character>> result = words.map(w -> characterStream(w));
```

```
Stream<Character> letters = words.flatMap(w -> characterStream(w))  
// Calls characterStream on each word and flattens the results
```

```
Stream<Double> randoms = Stream.generate(Math::random).limit(100);
```

```
Stream<String> words = Stream.of(contents.split("\\\\P{L}]+")).skip(1);
```

```
Stream<Character> combined = Stream.concat(  
    characterStream("Hello"), characterStream("World"));  
// Yields the stream ['H', 'e', 'l', 'l', 'o', 'W', 'o', 'r', 'l', 'd']
```

```
Object[] powers = Stream.iterate(1.0, p -> p * 2)
    .peek(e -> System.out.println("Fetching " + e))
    .limit(20).toArray();
```

```
Stream<String> uniqueWords  
= Stream.of("merrily", "merrily", "merrily", "gently").distinct();  
// Only one "merrily" is retained
```

```
Stream<String> longestFirst =  
    words.sorted(Comparator.comparing(String::length).reversed());
```

```
Optional<String> largest = words.max(String::compareToIgnoreCase);
if (largest.isPresent())
    System.out.println("largest: " + largest.get());
```

```
Optional<String> startsWithQ  
= words.filter(s -> s.startsWith("Q")).findFirst();
```

```
Optional<String> startsWithQ  
= words.parallel().filter(s -> s.startsWith("Q")).findAny();
```

```
boolean aWordStartsWithQ  
= words.parallel().anyMatch(s -> s.startsWith("Q"));
```

```
Optional<T> optionalValue = ...;  
optionalValue.get().someMethod()
```

```
if (optionalValue.isPresent()) optionalValue.get().someMethod();
```

```
if (value != null) value.someMethod();
```

```
optionalValue.isPresent(v -> Process v);
```

```
optionalValue.ifPresent(v -> results.add(v));
```

```
optionalValue.ifPresent(results::add);
```

```
Optional<Boolean> added = optionalValue.map(results::add);
```

```
String result = optionalString.orElse("");
// The wrapped string, or "" if none
```

```
String result = optionalString.orElseGet(() -> System.getProperty("user.dir"));
// The function is only called when needed
```

```
String result = optionalString.orElseThrow(NoSuchElementException::new);  
// Supply a method that yields an exception object
```

```
public static Optional<Double> inverse(Double x) {  
    return x == 0 ? Optional.empty() : Optional.of(1 / x);  
}
```

```
Optional<U> = s.f().flatMap(T::g);
```

```
public static Optional<Double> squareRoot(Double x) {  
    return x < 0 ? Optional.empty() : Optional.of(Math.sqrt(x));  
}
```

```
Double result = inverse(x).flatMap(MyMath::squareRoot);
```

```
Double result = Optional.of(-4.0).flatMap(Test::inverse).flatMap(Test::squareRoot);
```

```
Stream<Integer> values = ...;  
Optional<Integer> sum = values.reduce((x, y) -> x + y)
```

```
Stream<Integer> values = ...;  
Integer sum = values.reduce(0, (x, y) -> x + y)  
    // Computes  $0 + v_0 + v_1 + v_2 + \dots$ 
```

```
int result = words.reduce(0,  
    (total, word) -> total + word.length(),  
    (total1, total2) -> total1 + total2);
```

```
String[] result = words.toArray(String[]::new);
// words.toArray() has type Object[]
```

```
HashSet<String> result = stream.collect(HashSet::new, HashSet::add, HashSet::addAll);
```

```
List<String> result = stream.collect(Collectors.toList());
```

```
Set<String> result = stream.collect(Collectors.toSet());
```

```
TreeSet<String> result = stream.collect(Collectors.toCollection(TreeSet::new));
```

```
String result = stream.collect(Collectors.joining());
```

```
String result = stream.collect(Collectors.joining(", "));
```

```
String result = stream.map(Object::toString).collect(Collectors.joining(", "));
```

```
IntSummaryStatistics summary = words.collect(  
    Collectors.summarizingInt(String::length));  
double averageWordLength = summary.getAverage();  
double maxWordLength = summary.getMax();
```

```
stream.forEach(System.out::println);
```

```
Map<Integer, String> idToName = people.collect(  
    Collectors.toMap(Person::getId, Person::getName));
```

```
Map<Integer, Person> idToPerson = people.collect(  
    Collectors.toMap(Person::getId, Function.identity()));
```

```
Stream<Locale> locales = Stream.of(Locale.getAvailableLocales());
Map<String, String> languageNames = locales.collect(
    Collectors.toMap(
        l -> l.getDisplayLanguage(),
        l -> l.getDisplayLanguage(l),
        (existingValue, newValue) -> existingValue));
```

```
Map<String, Set<String>> countryLanguageSets = locales.collect(
    Collectors.toMap(
        l -> l.getDisplayCountry(),
        l -> Collections.singleton(l.getDisplayLanguage()),
        (a, b) -> { // Union of a and b
            Set<String> r = new HashSet<>(a);
            r.addAll(b);
            return r; }));
```

```
Map<Integer, Person> idToPerson = people.collect(  
    Collectors.toMap(  
        Person::getId,  
        Function.identity(),  
        (existingValue, newValue) -> { throw new IllegalStateException(); },  
        TreeMap::new));
```

```
Map<String, List<Locale>> countryToLocales = locales.collect(  
    Collectors.groupingBy(Locale::getCountry));
```

```
List<Locale> swissLocales = countryToLocales.get("CH");  
// Yields locales [it_CH, de_CH, fr_CH]
```

```
Map<Boolean, List<Locale>> englishAndOtherLocales = locales.collect(  
    Collectors.partitioningBy(l -> l.getLanguage().equals("en")));  
List<Locale>> englishLocales = englishAndOtherLocales.get(true);
```

```
Map<String, Set<Locale>> countryToLocaleSet = locales.collect(  
    groupingBy(Locale::getCountry, toSet()));
```

```
Map<String, Long> countryToLocaleCounts = locales.collect(  
    groupingBy(Locale::getCountry, counting()));
```

```
Map<String, Integer> stateToCityPopulation = cities.collect(  
    groupingBy(City::getState, summingInt(City::getPopulation)));
```

```
Map<String, City> stateToLargestCity = cities.collect(  
    groupingBy(City::getState,  
        maxBy(Comparator.comparing(City::getPopulation))));
```

```
Map<String, Optional<String>> stateToLongestCityName = cities.collect(  
    groupingBy(City::getState,  
               mapping(City::getName,  
                      maxBy(Comparator.comparing(String::length)))));
```

```
Map<String, Set<String>> countryToLanguages = locales.collect(  
    groupingBy(l -> l.getDisplayCountry(),  
              mapping(l -> l.getDisplayLanguage(),  
                      toSet())));
```

```
Map<String, IntSummaryStatistics> stateToCityPopulationSummary = cities.collect(  
    groupingBy(City::getState,  
    summarizingInt(City::getPopulation)));
```

```
Map<String, String> stateToCityNames = cities.collect(  
    groupingBy(City::getState,  
    reducing("", City::getName,  
        (s, t) -> s.length() == 0 ? t : s + ", " + t)));
```

```
Map<String, String> stateToCityNames = cities.collect(  
    groupingBy(City::getState,  
        mapping(City::getName,  
            joining(", "))));
```

```
IntStream stream = IntStream.of(1, 1, 2, 3, 5);
stream = Arrays.stream(values, from, to); // values is an int[] array
```

```
IntStream zeroToNinetyNine = IntStream.range(0, 100); // Upper bound is excluded  
IntStream zeroToHundred = IntStream.rangeClosed(0, 100); // Upper bound is included
```

```
String sentence = "\uD835\uDD46 is the set of octonions.";  
// \uD835\uDD46 is the UTF-16 encoding of the letter Ø, unicode U+1D546
```

```
IntStream codes = sentence.codePoints();  
// The stream with hex values 1D546 20 69 73 20 ...
```

```
Stream<String> words = ...;  
IntStream lengths = words.mapToInt(String::length);
```

```
Stream<Integer> integers = Integer.range(0, 100).boxed();
```

```
Stream<String> parallelWords = Stream.of(wordArray).parallel();
```

```
int[] shortWords = new int[12];
words.parallel().forEach(
    s -> { if (s.length() < 12) shortWords[s.length()]++; });
// Error—race condition!
System.out.println(Arrays.toString(shortWords));
```

```
Stream<T> sample = stream.parallel().unordered().limit(n);
```

```
Map<String, List<String>> result = cities.parallel().collect(  
    Collectors.groupingByConcurrent(City::getState));  
    // Values aren't collected in stream order
```

```
List<String> wordList = ...;
Stream<String> words = wordList.stream();
wordList.add("END"); // Ok
long n = words.distinct().count();
```

```
Stream<String> words = wordList.stream();
words.forEach(s -> if (s.length() < 12) wordList.remove(s));
// Error—interference
```

```
Stream<String> longWords = words.filter(s -> s.length() >= 12);
```

```
Stream<T> filter(Predicate<? super T> predicate)
```

```
public interface Predicate {  
    boolean test(T argument);  
}
```

```
logger.info("x: " + x + ", y: " + y);
```

```
public static void info(Logger logger, Supplier<String> message) {  
    if (logger.isLoggable(Level.INFO))  
        logger.info(message.get());  
}
```

```
Arrays.sort(names,  
           (s, t) -> Integer.compare(s.length(), t.length())); // Compare strings s and t
```

```
public static void repeat(int n, IntConsumer action) {  
    for (int i = 0; i < n; i++) action.accept(i);  
}
```

```
repeat(10, i -> System.out.println("Countdown: " + (9 - i)));
```

```
button.setOnAction(event -> action);
```

```
public static void repeat(int n, Runnable action) {  
    for (int i = 0; i < n; i++) action.run();  
}
```

```
repeat(10, () -> System.out.println("Hello, World!"));
```

```
Image brightenedImage = transform(image, Color::brighter);
```

```
public static Image transform(Image in, UnaryOperator<Color> f) {  
    int width = (int) in.getWidth();  
    int height = (int) in.getHeight();  
    WritableImage out = new WritableImage(width, height);  
    for (int x = 0; x < width; x++)  
        for (int y = 0; y < height; y++)  
            out.getPixelWriter().setColor(x, y,  
                f.apply(in.getPixelReader().getColor(x, y)));  
    return out;  
}
```

```
@FunctionalInterface  
public interface ColorTransformer {  
    Color apply(int x, int y, Color colorAtXY);  
}
```

```
Image brightenedImage = transform(image, Color::brighter);
```

```
Image brightenedImage = transform(image,  
    (c, factor) -> c.deriveColor(0, 1, factor, 1), // Brighten c by factor  
    1.2); // Use a factor of 1.2
```

```
public static <T> Image transform(Image in, BiFunction<Color, T> f, T arg)
```

```
public static UnaryOperator<Color> brighten(double factor) {  
    return c -> c.deriveColor(0, 1, factor, 1);  
}
```

```
Image brightenedImage = transform(image, brighten(1.2));
```

```
Image image = new Image("eiffel-tower.jpg");
Image image2 = transform(image, Color::brighter);
Image finalImage = transform(image2, Color::grayscale);
```

```
public static <T> UnaryOperator<T> compose(UnaryOperator<T> op1,  
    UnaryOperator<T> op2) {  
    return t -> op2.apply(op1.apply(t));  
}
```

```
Image finalImage = transform(image, compose(Color::brighter, Color::grayscale));
```

```
LatentImage latent = transform(image, Color::brighter);
```

```
public class LatentImage {  
    private Image in;  
    private List<UnaryOperator<Color>> pendingOperations;  
    ...  
}
```

```
LatentImage transform(UnaryOperator<Color> f) {  
    pendingOperations.add(f);  
    return this;  
}
```

```
LatentImage latent = LatentImage.from(image)
    .transform(Color::brighter).transform(Color::grayscale);
```

```
Image finalImage = LatentImage.from(image)
    .transform(Color::brighter).transform(Color::grayscale)
    .toImage();
```

```
public Image toImage() {
    int width = (int) in.getWidth();
    int height = (int) in.getHeight();
    WritableImage out = new WritableImage(width, height);
    for (int x = 0; x < width; x++)
        for (int y = 0; y < height; y++) {
            Color c = in.getPixelReader().getColor(x, y);
            for (UnaryOperator<Color> f : pendingOperations) c = f.apply(c);
            out.getPixelWriter().setColor(x, y, c);
        }
    return out;
}
```

```
public static Color[][][] parallelTransform(Color[][][] in, UnaryOperator<Color> f) {
    int n = Runtime.getRuntime().availableProcessors();
    int height = in.length;
    int width = in[0].length;
    Color[][][] out = new Color[height][width];
    try {
        ExecutorService pool = Executors.newCachedThreadPool();
        for (int i = 0; i < n; i++) {
            int fromY = i * height / n;
            int toY = (i + 1) * height / n;
            pool.submit(() -> {
                for (int x = 0; x < width; x++)
                    for (int y = fromY; y < toY; y++)
                        out[y][x] = f.apply(in[y][x]);
            });
        }
        pool.shutdown();
        pool.awaitTermination(1, TimeUnit.HOURS);
    }
    catch (InterruptedException ex) {
        ex.printStackTrace();
    }
    return out;
}
```

```
public static void doInOrder(Runnable first, Runnable second) {  
    first.run();  
    second.run();  
}
```

```
public static void doInOrderAsync(Runnable first, Runnable second) {  
    Thread t = new Thread() {  
        public void run() {  
            first.run();  
            second.run();  
        }  
    };  
    t.start();  
}
```

```
public static void doInOrderAsync(Runnable first, Runnable second,
    Consumer<Throwable> handler) {
    Thread t = new Thread() {
        public void run() {
            try {
                first.run();
                second.run();
            } catch (Throwable t) {
                handler.accept(t);
            }
        }
    };
    t.start();
}
```

```
public static <T> void doInOrderAsync(Supplier<T> first, Consumer<T> second,
    Consumer<Throwable> handler) {
    Thread t = new Thread() {
        public void run() {
            try {
                T result = first.get();
                second.accept(result);
            } catch (Throwable t) {
                handler.accept(t);
            }
        }
    };
    t.start();
}
```

```
public static <T> Supplier<T> unchecked(Callable<T> f) {  
    return () -> {  
        try {  
            return f.call();  
        }  
        catch (Exception e) {  
            throw new RuntimeException(e);  
        }  
        catch (Throwable t) {  
            throw t;  
        }  
    };  
}
```

```
unchecked(() -> new String(Files.readAllBytes(  
    Paths.get("/etc/passwd")), StandardCharsets.UTF_8))
```

```
String[] result = words.toArray(String[]::new);
```

```
List<Employee> staff = ...;  
List<Person> tenants = staff; // Not legal, but suppose it was  
tenants.add(new Person("John Q. Public")); // Adds Person to staff!
```

```
void forEach(Consumer<? super T> action)
Stream<T> filter(Predicate<? super T> predicate)
<R> Stream<R> map(Function<? super T, ? extends R> mapper)
```

```
T reduce(T identity, BinaryOperator<T> accumulator)
```

```
public static <T> void doInOrderAsync(Supplier<T> first,  
                                     Consumer<T> second, Consumer<Throwable> handler)
```

```
public static <T> void doInOrderAsync(Supplier<? extends T> first,  
    Consumer<? super T> second, Consumer<? super Throwable> handler)
```

```
withLock(myLock, () -> { some action })
```

```
public static <T> Image transform(Image in, BiFunction<Color, T> f, T arg)
```

```
UnaryOperator op = Color::brighter;
Image finalImage = transform(image, op.compose(Color::grayscale));
```

```
Label message = new Label("Hello, JavaFX!");
```

```
public class HelloWorld extends Application {  
    public void start(Stage stage) {  
        Label message = new Label("Hello, JavaFX!");  
        message.setFont(new Font(100));  
        stage.setScene(new Scene(message));  
        stage.setTitle("Hello");  
        stage.show();  
    }  
}
```

```
public class MyApp extends Application {  
    public static void main(String[] args) {  
        launch(args);  
    }  
    ...  
}
```

```
Button red = new Button("Red");
red.setOnAction(event -> message.setTextFill(Color.RED));
```

```
slider.valueProperty().addListener(property  
-> message.setFont(new Font(slider.getValue())));
```

```
value = obj.property;  
    // In many languages (but not Java), this calls the property getter  
obj.property = value; // And this calls the property setter
```

```
public class Greeting {  
    private StringProperty text = new SimpleStringProperty("");  
    public final StringProperty textProperty() { return text; }  
    public final void setText(String newValue) { text.set(newValue); }  
    public final String getText() { return text.get(); }  
}
```

```
slider.valueProperty().addListener((property, oldValue, newValue)
-> message.setFont(new Font(newValue)));
```

```
slider.valueProperty().addListener((property, oldValue, newValue)
-> message.setFont(new Font(newValue.doubleValue())));
```

```
billing.textProperty().bindBidirectional(shipping.textProperty());
```

```
billing.textProperty().bindBidirectional(shipping.textProperty());
```

```
circle.centerXProperty().bind(Bindings.divide(scene.widthProperty(), 2));
```

```
import static javafx.beans.binding.Bindings.*;
```

```
smaller.disableProperty().bind(Bindings.lessThanOrEqualTo(gauge.widthProperty(), 0));  
larger.disableProperty().bind(Bindings.greaterThanOrEqualTo(gauge.widthProperty(), 100));
```

```
larger.disableProperty().bind(  
    createBooleanBinding(  
        () -> gauge.getWidth() >= 100, // This expression is computed ...  
        gauge.widthProperty())); // ... when this property changes
```

```
BorderPane pane = new BorderPane();
pane.setTop(new Button("Top"));
pane.setLeft(new Button("Left"));
pane.setCenter(new Button("Center"));
pane.setRight(new Button("Right"));
pane.setBottom(new Button("Bottom"));
stage.setScene(new Scene(pane));
```

```
HBox box = new HBox(10); // ten pixels between controls  
box.getChildren().addAll(yesButton, noButton, maybeButton);
```

```
final double rem = new Text("").getLayoutBounds().getHeight();  
pane.setPadding(new Insets(0.8 * rem));
```

```
GridPane.setAlignment(usernameLabel, HPos.RIGHT);
```

```
pane.setHgap(0.8 * em);
pane.setVgap(0.8 * em);
pane.setPadding(new Insets(0.8 * em));
```

```
pane.setGridLinesVisible(true);
```

```
buttons.setStyle("-fx-border-color: red;");
```

```
GridPane pane = GridPaneBuilder.create()
    .hgap(10)
    .vgap(10)
    .padding(new Insets(10))
    .children(
        usernameLabel = LabelBuilder.create()
            .text("User name:")
            .build(),
        passwordLabel = LabelBuilder.create()
            .text("Password:")
            .build(),
        username = TextFieldBuilder.create().build(),
        password = PasswordFieldBuilder.create().build(),
        buttons = HBoxBuilder.create()
            .spacing(10)
            .alignment(Pos.CENTER)
            .children(
                okButton = ButtonBuilder.create()
                    .text("Ok")
                    .build(),
                cancelButton = ButtonBuilder.create()
                    .text("Cancel")
                    .build())
            .build())
    .build();
```

```
<?xml version="1.0" encoding="UTF-8"?>

<?import java.lang.*?>
<?import java.util.*?>
<?import javafx.scene.control.*?>
<?import javafx.scene.layout.*?>

<GridPane hgap="10" vgap="10">
    <padding>
        <Insets top="10" right="10" bottom="10" left="10"/>
    </padding>
    <children>
        <Label text="User name:" GridPane.columnIndex="0" GridPane.rowIndex="0"
               GridPane.halignment="RIGHT" />
        <Label text="Password: " GridPane.columnIndex="0" GridPane.rowIndex="1"
               GridPane.halignment="RIGHT" />
        <TextField GridPane.columnIndex="1" GridPane.rowIndex="0"/>
        <PasswordField GridPane.columnIndex="1" GridPane.rowIndex="1" />
        <HBox GridPane.columnIndex="0" GridPane.rowIndex="2"
              GridPane.columnSpan="2" alignment="CENTER" spacing="10">
            <children>
                <Button text="Ok" />
                <Button text="Cancel" />
            </children>
        </HBox>
    </children>
</GridPane>
```

```
<TextField GridPane.columnIndex="1" GridPane.rowIndex="0"/>
```

```
<GridPane hgap="10" vgap="10">
  <padding>
    <Insets top="10" right="10" bottom="10" left="10"/>
  </padding>
  ...

```

```
<HBox ...>
  <children>
    <Button text="Ok" />
    <Button text="Cancel" />
  </children>
</HBox>
```

```
public void start(Stage stage) {  
    try {  
        Parent root = FXMLLoader.load(getClass().getResource("dialog.fxml"));  
        stage.setScene(new Scene(root));  
        stage.show();  
    } catch (IOException ex) {  
        ex.printStackTrace();  
        System.exit(0);  
    }  
}
```

```
<TextField id="username" GridPane.columnIndex="1" GridPane.rowIndex="0"/>
```

```
TextField username = (TextField) root.lookup("#username");
```

```
public class LoginDialogController implements Initializable {  
    @FXML private TextField username;  
    @FXML private PasswordField password;  
    @FXML private Button okButton;  
  
    public void initialize(URL url, ResourceBundle rb) {  
        okButton.disableProperty().bind(  
            Bindings.createBooleanBinding(  
                () -> username.getText().length() == 0  
                    || password.getText().length() == 0,  
                username.textProperty(),  
                password.textProperty()));  
        okButton.setOnAction(event ->  
            System.out.println("Verifying " + username.getText()  
                + ":" + password.getText()));  
    }  
}
```

```
<TextField fx:id="username" GridPane.columnIndex="1" GridPane.rowIndex="0"/>
<PasswordField fx:id="password" GridPane.columnIndex="1" GridPane.rowIndex="1" />
<Button fx:id="okButton" text="Ok" />
```

```
<GridPane xmlns:fx="http://javafx.com/fxml" hgap="10" vgap="10"  
fx:controller="LoginDialogController">
```

```
FXMLLoader loader = new FXMLLoader(getClass().getResource(...));  
loader.setController(new Controller(service));  
Parent root = (Parent) loader.load();
```

```
FXMLLoader loader = new FXMLLoader();
loader.setController(...);
Parent root = (Parent) loader.load(getClass().getResource(...));
// Error—calls static method
```

```
Scene scene = new Scene(pane);
scene.getStylesheets().add("scene.css");
```

```
GridPane pane = new GridPane();
pane.setId("pane");
```

```
#pane {  
    -fx-padding: 0.5em;  
    -fx-hgap: 0.5em;  
    -fx-vgap: 0.5em;  
    -fx-background-image: url("metal.jpg")  
}
```

```
HBox buttons = new HBox();
buttons.getStyleClass().add("buttonrow");
```

```
.label {  
    -fx-font-family: "Comic Sans MS";  
}
```

```
<GridPane id="pane" stylesheets="scene.css">
```

```
buttons.setStyle("-fx-border-color: red;");
```

```
ScaleTransition st = new ScaleTransition(Duration.millis(3000));
st.setByX(1.5);
st.setByY(1.5);
st.setNode(yesButton);
st.play();
```

```
st.setCycleCount(Animation.INDEFINITE);  
st.setAutoReverse(true);
```

```
FadeTransition ft = new FadeTransition(Duration.millis(3000));  
ft.setFromValue(1.0);  
ft.setToValue(0);  
ft.setNode(noButton);  
ft.play();
```

```
RotateTransition rt = new RotateTransition(Duration.millis(3000));
rt.setByAngle(180);
rt.setCycleCount(Animation.INDEFINITE);
rt.setAutoReverse(true);
rt.setNode(maybeButton);
rt.play();
```

```
DropShadow dropShadow = new DropShadow();
dropShadow.setRadius(5.0);
dropShadow.setOffsetX(3.0);
dropShadow.setOffsetY(3.0);
dropShadow.setColor(Color.GRAY);

Text text = new Text();
text.setFill(Color.RED);
text.setText("Drop shadow");
text.setFont(Font.font("sans", FontWeight.BOLD, 40));
text.setEffect(dropShadow);
```

```
text2.setEffect(new Glow(0.8));
text3.setEffect(new GaussianBlur());
```

```
ObservableList<PieChart.Data> pieChartData =  
    FXCollections.observableArrayList(  
        new PieChart.Data("Asia", 4298723000.0),  
        new PieChart.Data("North America", 355361000.0),  
        new PieChart.Data("South America", 616644000.0),  
        new PieChart.Data("Europe", 742452000.0),  
        new PieChart.Data("Africa", 1110635000.0),  
        new PieChart.Data("Oceania", 38304000.0));  
final PieChart chart = new PieChart(pieChartData);  
chart.setTitle("Population of the Continents");
```

```
String location = "http://horstmann.com";
WebView browser = new WebView();
WebEngine engine = browser.getEngine();
engine.load(location);
```

```
Path path = Paths.get("moonlanding.mp4");
String location = path.toUri().toString();
Media media = new Media(location);
MediaPlayer player = new MediaPlayer(media);
player.setAutoPlay(true);
MediaView view = new MediaView(player);
view.setOnError(e -> System.out.println(e));
```

```
public static <T, R> ObservableValue<R> observe(  
    Function<T, R> f, ObservableValue<T> t)  
public static <T, U, R> ObservableValue<R> observe(  
    BiFunction<T, U, R> f, ObservableValue<T> t, ObservableValue<U> u)
```

```
target.disableProperty().bind(observe(  
    t -> t >= 100, gauge.widthProperty()));
```

```
Instant start = Instant.now();
runAlgorithm();
Instant end = Instant.now();
Duration timeElapsed = Duration.between(start, end);
long millis = timeElapsed.toMillis();
```

```
Duration timeElapsed2 = Duration.between(start2, end2);
boolean overTenTimesFaster =
    timeElapsed.multipliedBy(10).minus(timeElapsed2).isNegative();
// Or timeElapsed.toNanos() * 10 < timeElapsed2.toNanos()
```

```
LocalDate today = LocalDate.now(); // Today's date
LocalDate alonzosBirthday = LocalDate.of(1903, 6, 14);
alonzosBirthday = LocalDate.of(1903, Month.JUNE, 14);
// Uses the Month enumeration
```

```
LocalDate programmersDay = LocalDate.of(2014, 1, 1).plusDays(255);  
// September 13, but in a leap year it would be September 12
```

```
independenceDay.until(christmas)
```

```
independenceDay.until(christmas, ChronoUnit.DAYS) // 174 days
```

```
LocalDate.of(2016, 1, 31).plusMonths(1)
```

```
LocalDate.of(2016, 3, 31).minusMonths(1)
```

```
LocalDate.of(1900, 1, 1).getDayOfWeek().getValue()
```

```
LocalDate firstTuesday = LocalDate.of(year, month, 1).with(  
    TemporalAdjusters.nextOrSame(DayOfWeek.TUESDAY));
```

```
TemporalAdjuster NEXT_WORKDAY = w -> {
    LocalDate result = (LocalDate) w;
    do {
        result = result.plusDays(1);
    } while (result.getDayOfWeek().getValue() >= 6);
    return result;
};

LocalDate backToWork = today.with(NEXT_WORKDAY);
```

```
TemporalAdjuster NEXT_WORKDAY = TemporalAdjusters.ofDateAdjuster(w -> {
    LocalDate result = w; // No cast
    do {
        result = result.plusDays(1);
    } while (result.getDayOfWeek().getValue() >= 6);
    return result;
});
```

```
LocalTime rightNow = LocalTime.now();
LocalTime bedtime = LocalTime.of(22, 30); // or LocalTime.of(22, 30, 0)
```

```
LocalTime wakeup = bedtime.plusHours(8); // wakeup is 6:30:00
```

```
ZonedDateTime apollo11launch = ZonedDateTime.of(1969, 7, 16, 9, 32, 0, 0,  
ZoneId.of("America/New_York"));  
// 1969-07-16T09:32-04:00[America/New_York]
```

```
ZonedDateTime skipped = ZonedDateTime.of(  
    LocalDate.of(2013, 3, 31),  
    LocalTime.of(2, 30),  
    ZoneId.of("Europe/Berlin"));  
// Constructs March 31 3:30
```

```
ZonedDateTime ambiguous = ZonedDateTime.of(  
    LocalDate.of(2013, 10, 27), // End of daylight savings time  
    LocalTime.of(2, 30),  
    ZoneId.of("Europe/Berlin"));  
// 2013-10-27T02:30+02:00[Europe/Berlin]  
ZonedDateTime anHourLater = ambiguous.plusHours(1);  
// 2013-10-27T02:30+01:00[Europe/Berlin]
```

```
ZonedDateTime nextMeeting = meeting.plus(Duration.ofDays(7));  
// Caution! Won't work with daylight savings time
```

```
ZonedDateTime nextMeeting = meeting.plus(Period.ofDays(7)); // OK
```

```
String formatted = DateTimeFormatter.ISO_DATE_TIME.format(apollo11launch);
// 1969-07-16T09:32:00-05:00[America/New_York]
```

```
DateTimeFormatter formatter = DateTimeFormatter.ofLocalizedDateTime(FormatStyle.LONG);
String formatted = formatter.format(apollo11Launch);
// July 16, 1969 9:32:00 AM EDT
```

```
formatted = formatter.withLocale(Locale.FRENCH).format(apollo11Launch);  
// 16 juillet 1969 09:32:00 EDT
```

```
formatter = DateTimeFormatter.ofPattern("E yyyy-MM-dd HH:mm");
```

```
LocalDate churchsBirthday = LocalDate.parse("1903-06-14");
ZonedDateTime apollo11Launch =
    ZonedDateTime.parse("1969-07-16 03:32:00-0400",
        DateTimeFormatter.ofPattern("yyyy-MM-dd HH:mm:ssxx"));
```

```
today.with(next(w -> getDayOfWeek().getValue() < 6))
```

```
public static AtomicLong nextNumber = new AtomicLong();
// In some thread...
long id = nextNumber.incrementAndGet();
```

```
public static AtomicLong largest = new AtomicLong();
// In some thread ...
largest.set(Math.max(largest.get(), observed)); // Error—race condition!
```

```
do {  
    oldValue = largest.get();  
    newValue = Math.max(oldValue, observed);  
} while (!largest.compareAndSet(oldValue, newValue));
```

```
largest.updateAndGet(x -> Math.max(x, observed));
```

```
largest.accumulateAndGet(observed, Math::max);
```

```
final LongAdder adder = new LongAdder();
for (...) {
    pool.submit(() -> {
        while (...) {
            ...
            if (...) adder.increment();
        }
    });
...
long total = adder.sum());
```

```
LongAccumulator adder = new LongAccumulator(Long::sum, 0);
// In some thread ...
adder.accumulate(value);
```

```
public class Vector {  
    private int size;  
    private Object[] elements;  
    private StampedLock lock = new StampedLock();  
  
    public Object get(int n) {  
        long stamp = lock.tryOptimisticRead();  
        Object[] currentElements = elements;  
        int currentSize = size;  
        if (!lock.validate(stamp)) { // Someone else had a write lock  
            stamp = lock.readLock(); // Get a pessimistic lock  
            currentElements = elements;  
            currentSize = size;  
            lock.unlockRead(stamp);  
        }  
        return n < currentSize ? currentElements[n] : null;  
    }  
    ...  
}
```

```
Long oldValue = map.get(word);
Long newValue = oldValue == null ? 1 : oldValue + 1;
map.put(word, newValue); // Error—might not replace oldValue
```

```
do {  
    oldValue = map.get(word);  
    newValue = oldValue == null ? 1 : oldValue + 1;  
} while (!map.replace(word, oldValue, newValue));
```

```
map.putIfAbsent(word, new LongAdder());  
map.get(word).increment();
```

```
map.putIfAbsent(word, new LongAdder()).increment();
```

```
map.compute(word, (k, v) -> v == null ? 1 : v + 1);
```

```
map.computeIfAbsent(word, k -> new LongAdder()).increment();
```

```
map.merge(word, 1L, (existingValue, newValue) -> existingValue + newValue);
```

```
map.merge(word, 1L, Long::sum);
```

```
U searchKeys(long threshold, BiFunction<? super K, ? extends U> f)
U searchValues(long threshold, BiFunction<? super V, ? extends U> f)
U search(long threshold, BiFunction<? super K, ? super V,? extends U> f)
U searchEntries(long threshold, BiFunction<Map.Entry<K, V>, ? extends U> f)
```

```
String result = map.search(threshold, (k, v) -> v > 1000 ? k : null);
```

```
map.forEach(threshold,  
    (k, v) -> System.out.println(k + " -> " + v));
```

```
map.forEach(threshold,  
    (k, v) -> k + " -> " + v, // Transformer  
    System.out::println); // Consumer
```

```
map.forEach(threshold,  
    (k, v) -> v > 1000 ? k + " -> " + v : null, // Filter and transformer  
    System.out::println); // The nulls are not passed to the consumer
```

```
Long sum = map.reduceValues(threshold, Long::sum);
```

```
Integer maxlen = map.reduceKeys(threshold,  
    String::length, // Transformer  
    Integer::max); // Accumulator
```

```
Long count = map.reduceValues(threshold,  
    v -> v > 1000 ? 1L : null,  
    Long::sum);
```

```
long sum = map.reduceValuesToLong(threshold,  
    Long::longValue, // Transformer to primitive type  
    0, // Default value for empty map  
    Long::sum); // Primitive type accumulator
```

```
Set<String> words = ConcurrentHashMap.<String>newKeySet();
```

```
Set<String> words = map.keySet(1L);  
words.add("Java");
```

```
String contents = new String(Files.readAllBytes(  
    Paths.get("alice.txt")), StandardCharsets.UTF_8); // Read file into string  
String[] words = contents.split("[\\P{L}]+"); // Split along nonletters  
Arrays.parallelSort(words);
```

```
values.parallelSort(values.length / 2, values.length); // Sort the upper half
```

```
Arrays.parallelSetAll(values, i -> i % 10);
// Fills values with 0 1 2 3 4 5 6 7 8 9 0 1 2 ...
```

[1, 1 × 2, 1 × 2 × 3, 1 × 2 × 3 × 4, ...]

[1, 1 × 2, 3, 3 × 4, 5, 5 × 6, 7, 7 × 8]

[1, 1 × 2, 1 × 2 × 3, 1 × 2 × 3 × 4, 5, 5 × 6, 5 × 6 × 7, 5 × 6 × 7 × 8]

```
public void Future<String> readPage(URL url)
```

```
Future<String> contents = readPage(url);
```

```
public static List<URL> getLinks(String page)
```

```
String page = contents.get();
List<URL> links = Parser.getLinks(page);
```

```
CompletableFuture<String> contents = readPage(url);  
CompletableFuture<List<String>> links = contents.thenApply(Parser::getLinks);
```

```
CompletableFuture<String> contents  
    = CompletableFuture.supplyAsync(() -> blockingReadPage(url));
```

```
CompletableFuture<List<String>> links  
= CompletableFuture.supplyAsync(() -> blockingReadPage(url))  
.thenApply(Parser::getLinks);
```

```
CompletableFuture<Void> links
    = CompletableFuture.supplyAsync(() -> blockingReadPage(url))
        .thenApply(Parser::getLinks)
        .thenAccept(System.out::println);
```

```
CompletableFuture<U> future.thenApply(f);  
CompletableFuture<U> future.thenApplyAsync(f);
```

```
public String blockingReadPage(URL url)
```

```
public CompletableFuture<String> readPage(URL url)
```

```
public CompletableFuture<URL> getURLInput(String prompt)
```

```
ForkJoinPool.commonPool().awaitQuiescence(10, TimeUnit.SECONDS);
```

```
public static <T> CompletableFuture<T> repeat(  
    Supplier<T> action, Predicate<T> until)
```

```
jjs> function factorial(n) { return n <= 1 ? 1 : n * factorial(n - 1) }
function factorial(n) { return n <= 1 ? 1 : n * factorial(n - 1) }
jjs> factorial(10)
3628800
```

```
var input = new java.util.Scanner(  
    new java.net.URL('http://horstmann.com').openStream())  
input.useDelimiter('$')  
var contents = input.next()
```

```
ScriptEngineManager manager = new ScriptEngineManager();
ScriptEngine engine = manager.getEngineByName("nashorn");
Object result = engine.eval("'Hello, World!'.length");
System.out.println(result);
```

```
Object result = engine.eval(Files.newBufferedReader(path));
```

```
public void start(Stage stage) {  
    engine.put("stage", stage);  
    engine.eval(script); // Script code can access the object as stage  
}
```

```
Bindings scope = engine.createBindings();
scope.put("stage", stage);
engine.eval(script, scope);
```

```
var javaNetPackage = java.net // A JavaPackage object  
var URL = java.net.URL // A JavaClass object
```

```
var URL = Java.type('java.net.URL')
```

```
var URL = Java.type('java.net.URL')
var JMath = Java.type('java.lang.Math')
// Avoids conflict with JavaScript Math object
```

```
var URL = java.net.URL  
var url = new URL('http://horstmann.com')
```

```
var url = new java.net.URL('http://horstmann.com')
```

```
var url = new (Java.type('java.net.URL'))('http://horstmann.com')
```

```
var entry = new java.util.AbstractMap.SimpleEntry('hello', 42)
```

```
var Entry = Java.type('java.util.AbstractMap$SimpleEntry')
```

```
'Hello'.slice(-2) // Yields 'lo'
```

```
var path = java.nio.file.Paths.get(/home/)  
// A JavaScript RegExp is converted to a Java String!
```

```
var price = 10
java.lang.String.format('Price: %.2f', price)
// Error: f format not valid for java.lang.Integer
```

```
java.lang.String.format('Unit price: %.2f', Number(price))
```

```
var intArray = Java.type('int[]')
var StringArray = Java.type('java.lang.String[]')
```

```
var numbers = new intArray(10) // A primitive int[] array  
var names = new StringArray(10) // An array of String references
```

for each (var elem in names)
Do something with elem

```
for (var i in names)
  Do something with i and names[i]
```

```
var javaNames = Java.to(names, StringArray) // An array of type String[]
```

```
var jsNumbers = Java.from(numbers)
jsNumbers[-1] = 42
```

```
java.util.Arrays.toString([1, 2, 3])
```

```
java.util.Arrays.toString(Java.to([1, 2, 3], Java.type('int[]')))
```

```
java.util.Arrays.toString(Java.to([1, 2, 3], 'int[]'))
```

```
var names = java.util.Arrays.asList('Fred', 'Wilma', 'Barney')
var first = names[0]
names[0] = 'Duke'
```

```
var scores = new java.util.HashMap  
scores['Fred'] = 10 // Calls scores.put('Fred', 10)
```

```
for (var key in scores) ...  
for each (var value in scores) ...
```

```
for each (var e in scores.entrySet())
    Process e.key and e.value
```

```
var square = function(x) { return x * x }
// The right-hand side is an anonymous function
var result = square(2)
// The () operator invokes the function
```

```
java.util.Arrays.sort(words,  
    function(a, b) { return java.lang.Integer.compare(a.length, b.length) })  
// Sorts the array by increasing length
```

```
java.util.Arrays.sort(words,  
    function(a, b) java.lang.Integer.compare(a.length, b.length))
```

```
var RandomIterator = Java.extend(java.util.Iterator, {
    next: function() Math.random(),
    hasNext: function() true
}) // RandomIterator is a class object
var iter = new RandomIterator() // Use it to construct an instance
```

```
var iter = new java.util.Iterator {  
    next: function() Math.random(),  
    hasNext: function() true  
}
```

```
var task = new java.lang.Runnable(function() { print('Hello') })  
// task is an object of an anonymous class implementing Runnable
```

```
var iter = new java.util.Iterator {  
    count: 10,  
    next: function() { this.count--; return Math.random() },  
    hasNext: function() this.count > 0  
}
```

```
var arr = new (Java.extend(java.util.ArrayList)) {
    add: function(x) {
        print('Adding ' + x);
        return Java.super(arr).add(x)
    }
}
```

```
try {
    var first = list.get(0)
    ...
} catch (e) {
    if (e instanceof java.lang.IndexOutOfBoundsException)
        print('list is empty')
}
```

```
$EXEC('grep -v class', `ls -al`)
```

```
var cmd = "javac -classpath ${classpath} ${mainclass}.java"  
$EXEC(cmd)
```

```
'javac -classpath ${classpath} ${mainclass}.java'
```

```
var message = "The current time is ${java.time.Instant.now()}"  
// Sets message to a string such as The current time is 2013-10-12T21:48:58.545Z
```

```
var message = 'The current time is ${java.time.Instant.now()}'  
// Sets message to The current time is ${java.time.Instant.now()}
```

```
jjs script1.js script2.js -- arg1 arg2 arg3
```

```
jrunscript -f script.js arg1 arg2 arg3
```

```
var deployCommand = "deploy ${arguments[0]} ${arguments[1]}"
```

```
var deployCommand = "deploy ${$ARG[0]} ${$ARG[1]}"
```

```
var javaHome = $ENV.JAVA_HOME
```

```
var username = readLine('Username: ')
```

```
var password = java.lang.System.console().readPassword('Password: ')
```

```
if (username.length == 0) exit(1)
```

```
var message = new javafx.scene.control.Label("Hello, JavaFX!");
message.font = new javafx.scene.text.Font(100);
$STAGE.scene = new javafx.scene.Scene(message);
$STAGE.title = "Hello";
```

```
message.setFont(new Font(100))
```

```
slider.valueProperty().addListener(function(property)
    message.font = new Font(slider.value))
// Error—Nashorn can't determine which listener type to add
```

```
slider.valueProperty().addListener(  
    new javafx.beans.InvalidationListener(function(property)  
        message.font = new Font(slider.value)))
```

```
Frame {  
    title: "Hello"  
    content: Label {  
        text: "Hello, World!"  
    }  
}
```

```
var b = new java.math.BigInteger('1234567890987654321')
```

```
String joined = String.join("/", "usr", "local", "bin"); // "usr/local/bin"
System.out.println(joined);
String ids = String.join(", ", ZoneId.getAvailableZoneIds());
System.out.println(ids);
// All time zone identifiers, separated by commas
```

```
Arrays.sort(people, Comparator.comparing(Person::getName));
```

```
Arrays.sort(people,  
    Comparator.comparing(Person::getLastName)  
        .thenComparing(Person::getFirstName));
```

```
Arrays.sort(people, Comparator.comparing(Person::getName,  
        (s, t) -> Integer.compare(s.length(), t.length())));
```

```
Arrays.sort(people, Comparator.comparingInt(p -> p.getName().length()));
```

```
Arrays.sort(people, comparing(Person::getMiddleName,  
    nullsFirst(naturalOrder())));
```

```
Stream<String> lines = Files.lines(path);
Optional<String> passwordEntry = lines.filter(s -> s.contains("password")).findFirst();
```

```
try (Stream<String> lines = Files.lines(path)) {
    Optional<String> passwordEntry
        = lines.filter(s -> s.contains("password")).findFirst();
    ...
} // The stream, and hence the file, will be closed here
```

```
try (Stream<String> filteredLines
    = Files.lines(path).filter(s -> s.contains("password"))) {
    Optional<String> passwordEntry = filteredLines.findFirst();
    ...
}
```

```
try (Stream<String> filteredLines
    = Files.lines(path).onClose(() -> System.out.println("Closing"))
        .filter(s -> s.contains("password")))) { ... }
```

```
try (BufferedReader reader
    = new BufferedReader(new InputStreamReader(url.openStream()))) {
    Stream<String> lines = reader.lines();
    ...
}
```

```
try (Stream<Path> entries = Files.list(pathToDirectory)) {  
    ...  
}
```

```
try (DirectoryStream stream = Files.newDirectoryStream(pathToDirectory)) {  
    for (Path entry : stream) {  
        ...  
    }  
}
```

```
try (Stream<Path> entries = Files.walk(pathToRoot)) {  
    // Contains all descendants, visited in depth-first order  
}
```

```
Base64.Encoder encoder = Base64.getEncoder();
String original = username + ":" + password;
String encoded = encoder.encodeToString(original.getBytes(StandardCharsets.UTF_8));
```

```
Path originalPath = ..., encodedPath = ...;
Base64.Encoder encoder = Base64.getMimeEncoder();
try (OutputStream output = Files.newOutputStream(encodedPath)) {
    Files.copy(originalPath, encoder.wrap(output));
}
```

```
Path encodedPath = ..., decodedPath = ...;
Base64.Decoder decoder = Base64.getMimeDecoder();
try (InputStream input = Files.newInputStream(encodedPath)) {
    Files.copy(decoder.wrap(input), decodedPath);
}
```

```
@PostConstruct public void fetchData() { ... } // Call after construction  
@Resource("jdbc:derby:sample") private Connection conn;  
// Inject resource here
```

```
@Stateless @Path("/service") public class Service { ... }
```

```
@Entity  
@PrimaryKeyJoinColumn(name="ID")  
@PrimaryKeyJoinColumn(name="REGION")  
public class Item { ... }
```

```
@Entity  
 @PrimaryKeyJoinColumns({  
     @PrimaryKeyJoinColumn(name="ID")  
     @PrimaryKeyJoinColumn(name="REGION")  
 })  
 public class Item { ... }
```

```
public <T extends Annotation> T getAnnotation(Class<T> annotationClass)
```

```
@TestCase(params="4", expected="24")
@TestCase(params="0", expected="1")
public static long factorial(int n) { ... }
```

```
@Repeatable(TestCases.class)
@interface TestCase {
    String params();
    String expected();
}

@interface TestCases {
    TestCase[] value();
}
```

```
@Entity public class Person { ... }  
@SuppressWarnings("unchecked") List<Person> people = query.getResultList();
```

```
private @NotNull List<String> names = new ArrayList<>();  
...  
names.add("Fred"); // No possibility of a NullPointerException
```

```
names = null; // Null checker flags this as an error  
names = readNames(); // OK if readNames returns a @NotNull String
```

```
private List<@NotNull String> names;
```

```
@NotNull String.class // Illegal—cannot annotate class literal  
import java.lang.@NotNull String; // Illegal—cannot annotate import
```

```
Person getEmployee(@PathParam("dept") Long dept, @QueryParam("id") Long id)
```

Person getEmployee(@PathParam Long dept, @QueryParam Long id)

```
stream.anyMatch(Object::isNull)
```

```
stream.filter(Object::nonNull)
```

```
logger.finest("x: " + x + ", y:" + y);
```

```
logger.finest(() -> "x: " + x + ", y:" + y);
```

```
this.directions = Objects.requireNonNull(directions,  
() -> "directions for " + this.goal + " must not be null");
```

(?<city>[\p{L}]+),\s*(?<state>[A-Z]{2})

```
Matcher matcher = pattern.matcher(input);
if (matcher.matches()) {
    String city = matcher.group("city");
    ...
}
```

```
String contents = new String(Files.readAllBytes(path), StandardCharsets.UTF_8);
Stream<String> words = Pattern.compile("[\\P{L}]").splitAsStream(contents);
```

```
Stream<String> acronyms = words.filter(Pattern.compile("[A-Z]{2,}").asPredicate());
```

```
List<Locale.LanguageRange> ranges = Stream.of("de", "-CH")
    .map(Locale.LanguageRange::new)
    .collect(Collectors.toList());
// A list containing the Locale.LanguageRange objects for the given strings
List<Locale> matches = Locale.filter(ranges,
    Arrays.asList(Locale.getAvailableLocales()));
// The matching locales: de, de-CH, de-AT, de-LU, de-DE, de-GR, fr-CH, it_CH
```

```
Locale bestMatch = Locale.lookup(ranges, locales);
```

```
try (Scanner in = new Scanner(Paths.get("/usr/share/dict/words"))){  
    while (in.hasNext())  
        System.out.println(in.next().toLowerCase());  
}
```

```
try (Scanner in = new Scanner(Paths.get("/usr/share/dict/words"));
    PrintWriter out = new PrintWriter("/tmp/out.txt")) {
    while (in.hasNext())
        out.println(in.next().toLowerCase());
}
```

```
try {  
    ...  
} catch (IOException ex) {  
    Throwable[] secondaryExceptions = ex.getSuppressed();  
}
```

```
ex.addSuppressed(secondaryException);
```

```
try {  
    Code that might throw exceptions  
}  
catch (FileNotFoundException | UnknownHostException ex) {  
    Emergency action for missing files and unknown hosts  
}  
catch (IOException ex) {  
    Emergency action for all other I/O problems  
}
```

```
Class.forName(className).getMethod("main").invoke(null, new String[] {});
```

```
catch (ClassNotFoundException | NoSuchMethodException  
| IllegalAccessException | InvocationTargetException ex) { ... }
```

```
catch (ReflectiveOperationException ex) { ... }
```

```
Path absolute = Paths.get("/", "home", "cay");
Path relative = Paths.get("myprog", "conf", "user.properties");
```

```
Path homeDirectory = Paths.get("/home/cay");
```

```
Path configPath = homeDirectory.resolve("myprog/conf/user.properties");
// Same as homeDirectory.resolve(Paths.get("myprog/conf/user.properties"));
```

```
Path tempPath = workPath.resolveSibling("temp");
```

```
Paths.get("/home/cay").relativize(Paths.get("/home/fred/myprog"))
```

```
Path p = Paths.get("/home", "cay", "myprog.properties");
Path parent = p.getParent(); // The path /home/cay
Path file = p.getFileName(); // The last element, myprog.properties
Path root = p.getRoot(); // The initial segment / (null for a relative path)
```

```
byte[] bytes = Files.readAllBytes(path);
```

```
String content = new String(bytes, StandardCharsets.UTF_8);
```

```
List<String> lines = Files.readAllLines(path);
```

```
Files.write(path, content.getBytes(StandardCharsets.UTF_8));
```

```
Files.write(path, lines, StandardOpenOption.APPEND);
```

```
InputStream in = Files.newInputStream(path);
OutputStream out = Files.newOutputStream(path);
Reader reader = Files.newBufferedReader(path);
Writer writer = Files.newBufferedWriter(path);
```

```
Files.createDirectories(path);
```

```
Path newPath = Files.createTempFile(dir, prefix, suffix);
Path newPath = Files.createTempFile(prefix, suffix);
Path newPath = Files.createTempDirectory(dir, prefix);
Path newPath = Files.createTempDirectory(prefix);
```

```
Files.copy(fromPath, toPath, StandardCopyOption.REPLACE_EXISTING,  
StandardCopyOption.COPY_ATTRIBUTES);
```

```
Files.move(fromPath, toPath, StandardCopyOption.ATOMIC_MOVE);
```

```
boolean deleted = Files.deleteIfExists(path);
```

```
public boolean equals(Object otherObject) {  
    if (this == otherObject) return true;  
    if (otherObject == null) return false;  
    if (getClass() != otherObject.getClass()) return false;  
    Person other = (Person) otherObject;  
    ...  
}
```

```
return Objects.equals(first, other.first) && Objects.equals(last, other.last);
```

```
return 31 * Objects.hashCode(first) + Objects.hashCode(last);
```

```
return Objects.hash(first, last);
```

```
public int compareTo(Point other) {  
    int diff = x - other.x; // Risk of overflow  
    if (diff != 0) return diff;  
    return y - other.y;  
}
```

```
public int compareTo(Point other) {  
    int diff = Integer.compare(x, other.x); // No risk of overflow  
    if (diff != 0) return diff;  
    return Integer.compare(y, other.y);  
}
```

Codebase: <https://www.mycompany.com> www.mycompany.com:8080

```
double x = Double.parseDouble("+1.0");
int n = Integer.parseInt("+1");
```

```
public void process(String directions) {  
    this.directions = Objects.requireNonNull(directions);  
    ...  
}
```

```
this.directions = Objects.requireNonNull(directions,  
        "directions must not be null");
```

```
ProcessBuilder builder = new ProcessBuilder(  
    "grep", "-o", "[A-Za-z_][A-Za-z_0-9]*");  
builder.redirectInput(Paths.get("Hello.java").toFile());  
builder.redirectOutput(Paths.get("identifiers.txt").toFile());  
Process process = builder.start();  
process.waitFor();
```

```
boolean completed = process.waitFor(1, TimeUnit.MINUTES);
```

```
ProcessBuilder builder = new ProcessBuilder("ls", "-al");
builder.inheritIO();
builder.start().waitFor();
```

```
URL[] urls = {  
    new URL("file:junit-4.11.jar"),  
    new URL("file:hamcrest-core-1.3.jar")  
};  
URLClassLoader loader = new URLClassLoader(urls);  
Class<?> klass = loader.loadClass("org.junit.runner.JUnitCore");
```

```
try (URLClassLoader loader = new URLClassLoader(urls)) {
    Class<?> klass = loader.loadClass("org.junit.runner.JUnitCore");
    ...
}
```

```
byte[] bytes = { (byte) 0b10101100, (byte) 0b00101000 };
BitSet primes = BitSet.valueOf(bytes);
// {2, 3, 5, 7, 11, 13}
long[] longs = { 0x100010116L, 0x1L, 0x1L, 0L, 0x1L };
BitSet powersOfTwo = BitSet.valueOf(longs);
// {1, 2, 4, 8, 16, 32, 64, 128, 256}
```

```
byte[] bytes = powersOfTwo.toByteArray();
// [0b00010110, 1, 1, 0, 1, 0, 0, 0, 1, ...]
```

```
public void process() throws ... {
    try {
        ...
        catch (FileNotFoundException | UnknownHostException ex) {
            logger.log(Level.SEVERE, "...", ex);
            throw ex;
        }
    }
}
```

```
public class LabeledPoint {  
    private String label;  
    private int x;  
    private int y;  
    ...  
}
```

Table of Contents

[About This eBook](#)

[Title Page](#)

[Copyright Page](#)

[Dedication Page](#)

[Contents](#)

[Preface](#)

[About the Author](#)

[Chapter 1. Lambda Expressions](#)

[1.1. Why Lambdas?](#)

[1.2. The Syntax of Lambda Expressions](#)

[1.3. Functional Interfaces](#)

[1.4. Method References](#)

[1.5. Constructor References](#)

[1.6. Variable Scope](#)

[1.7. Default Methods](#)

[1.8. Static Methods in Interfaces](#)

[Exercises](#)

[Chapter 2. The Stream API](#)

[2.1. From Iteration to Stream Operations](#)

[2.2. Stream Creation](#)

[2.3. The filter, map, and flatMap Methods](#)

[2.4. Extracting Substreams and Combining Streams](#)

[2.5. Stateful Transformations](#)

[2.6. Simple Reductions](#)

[2.7. The Optional Type](#)

[2.8. Reduction Operations](#)

[2.9. Collecting Results](#)

[2.10. Collecting into Maps](#)

[2.11. Grouping and Partitioning](#)

[2.12. Primitive Type Streams](#)

[2.13. Parallel Streams](#)

[2.14. Functional Interfaces](#)

[Exercises](#)

[Chapter 3. Programming with Lambdas](#)

[3.1. Deferred Execution](#)

[3.2. Parameters of Lambda Expressions](#)

[3.3. Choosing a Functional Interface](#)

[3.4. Returning Functions](#)

[3.5. Composition](#)

[3.6. Laziness](#)

[3.7. Parallelizing Operations](#)

[3.8. Dealing with Exceptions](#)

[3.9. Lambdas and Generics](#)

[3.10. Monadic Operations](#)

[Exercises](#)

[Chapter 4. JavaFX](#)

[4.1. A Brief History of Java GUI Programming](#)

[4.2. Hello, JavaFX!](#)

[4.3. Event Handling](#)

[4.4. JavaFX Properties](#)

[4.5. Bindings](#)

[4.6. Layout](#)

[4.7. FXML](#)

[4.8. CSS](#)

[4.9. Animations and Special Effects](#)

[4.10. Fancy Controls](#)

[Exercises](#)

[Chapter 5. The New Date and Time API](#)

[5.1. The Time Line](#)

[5.2. Local Dates](#)

[5.3. Date Adjusters](#)

[5.4. Local Time](#)

[5.5. Zoned Time](#)

[5.6. Formatting and Parsing](#)

[5.7. Interoperating with Legacy Code](#)

[Exercises](#)

[Chapter 6. Concurrency Enhancements](#)

[6.1. Atomic Values](#)

[6.2. ConcurrentHashMap Improvements](#)

[6.3. Parallel Array Operations](#)

[6.4. Completable Futures](#)

[Exercises](#)

[Chapter 7. The Nashorn JavaScript Engine](#)

[7.1. Running Nashorn from the Command Line](#)

[7.2. Running Nashorn from Java](#)

[7.3. Invoking Methods](#)

[7.4. Constructing Objects](#)

[7.5. Strings](#)

[7.6. Numbers](#)

[7.7. Working with Arrays](#)

[7.8. Lists and Maps](#)

[7.9. Lambdas](#)

[7.10. Extending Java Classes and Implementing Java Interfaces](#)

[7.11. Exceptions](#)

[7.12. Shell Scripting](#)

[7.13. Nashorn and JavaFX](#)

[Exercises](#)

[Chapter 8. Miscellaneous Goodies](#)

- [8.1. Strings](#)
- [8.2. Number Classes](#)
- [8.3. New Mathematical Functions](#)
- [8.4. Collections](#)
- [8.5. Working with Files](#)
- [8.6. Annotations](#)
- [8.7. Miscellaneous Minor Changes](#)

[Exercises](#)

[Chapter 9. Java 7 Features That You May Have Missed](#)

- [9.1. Exception Handling Changes](#)
- [9.2. Working with Files](#)
- [9.3. Implementing the equals, hashCode, and compareTo Methods](#)
- [9.4. Security Requirements](#)
- [9.5. Miscellaneous Changes](#)

[Exercises](#)

[Index](#)