

SPARSER

version 2.3b

USER DOCUMENTATION

Preliminary edition

January 1995

Copyright © 1992-1996, 2010-2014 David D. McDonald

David D. McDonald, Ph.D.
davidmcdonald@alum.mit.edu

1. Introduction	1
1.1 Capabilities	1
1.2 Overview	1
2. Running Sparser	2
2.1 Calling Sparser	2
2.1.1 Managing file input	3
2.1.2 Terminating early	3
2.2 Installation	4
2.2.1 Directory Structure	4
2.2.2 Loading	4
2.2.3 Creating an image	5
2.3 Lisp Packages	5
3. Labels	7
3.1 Words	7
3.1.1 Case-sensitivity	7
3.1.2 Defining words	8
3.1.3 Accessing words	9
3.1.4 The components of the “word” object	9
3.1.5 Predefined words	10
3.1.5.1 Punctuation	10
3.1.5.2 “Meaningless” characters	11
3.1.5.3 Reserved words	11
3.1.5.4 Spaces	12
3.1.6 Whitespace	12
3.1.7 Deleting words	13
3.1.8 Limits on the length of words	14
3.2 Polywords	14
3.2.1 The appearance of polywords in the chart	15
3.2.2 The fields in a polyword	16
3.2.3 Managing polywords	16
3.3 Categories	17
3.3.1 The components of the category object	17
4. Phrase Structure Rules	18
4.1 Context-free phrase structure rules	18
4.1.1 Terminology	18
4.1.2 “CFR” Objects	19
4.1.3 Defining context-free rules	20
4.1.4 More than two terms on a righthand side	22
4.2 “Referents” in phrase structure rules	25
4.2.1 Referent fields	25
4.2.2 Supplying referents directly with the rule	26
4.2.3 Instructions for calculating referents	27

4.2.4 Global variables for referent calculation	29
4.3 Context-sensitive rules	30
4.3.1 Defining context-sensitive rules	31
4.4 Keeping track of rules	32
4.5 Deleting rules	32
4.6 Rule-sets	33
5. The Chart	35
5.1 The data structure for the chart	36
5.1.1 Extracting information from the chart.....	36
5.2 Positions	37
5.2.1 The fields in a position object	38
5.2.2 Operations over positions	39
5.3 Edge-vectors	40
5.3.1 The fields of an edge-vector	41
5.4 Edges	42
5.4.1 The fields on an edge	43
5.4.2 Constructing an edge	45
5.5 Chart objects as reusable resources	45
6. Analyzing a text	48
6.0.1 The Analysis Core	48
6.0.2 After-Analysis actions	48
6.1 Initializations	49
6.1.1 Initializing sessions	50
6.1.1.1 Switch settings.....	50
6.1.2 Initializing runs	51
6.2 The Character buffer	52
6.2.1 State information	52
6.2.2 Special control characters.....	53
6.2.3 References to character buffer positions	54
6.2.4 Modifying characters' interpretations	54
6.3 The Tokenizer	55
6.3.1 What is a token	55
6.3.1.1 'meaningless' characters	55
6.3.1.2 spaces	56
6.3.1.3 punctuation	56
6.3.2 The data structure for 'tokens'	56
6.3.2.1 Known words	57
6.3.2.2 Digit sequences	57
6.3.2.3 Unknown words	57
6.3.3 Calling the Tokenizer	58
6.4 Populating the chart with terminals.....	58
6.4.1 "Terminals"	59

6.4.2	The standard procedure	60
6.4.3	The Newline hook	62
6.5	Coordinating word-level actions	63
6.6	Introducing edges over words	65
6.6.1	Dependence on how a word appears in a rule	65
6.6.2	Capitalized words	66
6.6.3	Unknown words	67
6.6.4	Digits	69
6.7	Chart-driven processing	69
6.7.1	Just process terminals	70
6.7.2	The ‘All-Edges’ parsing protocol.....	70
6.7.3	The ‘top-edges only’ protocol	72
7.	Hooks for User Code	73
7.1	The “Completion” hook	73
7.2	Special-purpose, word-level parsing	75
7.2.1	Initiating a word-level routine	76
7.2.2	Return values	77
7.2.3	Coordinating the scan	77
8.	Tracing Sparser’s Operations	79
8.1	Run-time traces	79

1. Introduction

1.1 Capabilities

Sparser is a software system written in the language Common Lisp, consisting of a directory of files for loading into the user's Lisp image, a pre-loaded image that may be launched on its own, or some combination of the two.

At its heart, Sparser is a bottom-up, phrase-structure-based chart parser, optimized for semantic grammars and partial parsing. It has a highly efficient implementation based on resources of reused data structures and the option of an indelible, deterministic parsing algorithm.

Included with Sparser is a notation for constructing a grammar of context free and limited context-sensitive rewrite rules (§4). Phrase structure rules may incorporate user-defined objects and operations over them to be used as the referents of the phrases that the rules construct (§4.2).

Since real texts can pose problems for analysis that are not readily or best analyzed using phrase structure techniques, Sparser provides a high-level, task-oriented programming language for defining grammars using a whole range of techniques. A Lisp application programmer's interface (API) for user-defined parsing networks over terminals and initial non-terminals is provided (§7). User-defined code may be executed upon the completion of rules or words (§7.1). The interpretation of input characters is table-driven (§6.2.4). The definition of what constitutes a terminal can be modified (§6.4.1). Special routines may be executed at newlines (§6.4.3).

Sparser takes a string or file of ascii characters as input, and supplies a populated chart as output. An API for examining this chart is supplied (§5), as are trace routines (§8).

1.2 Overview

Before Sparser can be used you must load its files into Lisp or activate a stored Lisp image that already includes them. You must also load the grammar you intend to use, which will typically be a set of files of rule definition forms that you created earlier. At that point you can have Sparser analyze files of text or individual strings by calling the appropriate function (§2.5). You can also embed calls to run Sparser in your own functions, along with code for examining the results of the its analysis.

To write a phrase structure grammar for Sparser you have to understand the conventions of the rule notation (§4); you will also want to look at the trace routines that have been provided (§8). To write routines of your own for examining Sparser's analysis you have to understand the data structures that make up Sparser's representations (§3, §5). To write more advanced routines to take advantage of the user-code hooks within Sparser you also need to understand

something of Sparser's algorithms so that you will know when the hooks are called and what is available for your routines to examine at those points (§6).