1) git log

2) git checkout main
   git checkout -b feature-xyz

3) git checkout main
   git merge feature-xyz

4) git restore nom_de_fichier

5) git status

MINGW64:/c/Users/lenovo/depot_test

```
lenovo@4phtt MINGW64 ~
$ mkdir depot_local
mkdir: cannot create directory ‘depot_local’: File exists

lenovo@4phtt MINGW64 ~
$ cd depot_local

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git init
Reinitialized existing Git repository in C:/Users/lenovo/depot_local/.git/

lenovo@4phtt MINGW64 ~/depot_local (master)
$ ggit remote add origin https://github.com/4phtt/depot_local.git
bash: $'\302\223git': command not found

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote add origin https://github.com/4phtt/depot_local.git
error: remote origin already exists.

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote -v
origin  https://github.com/4phtt/depot_local.git~ (fetch)
origin  https://github.com/4phtt/depot_local.git~ (push)

lenovo@4phtt MINGW64 ~/depot_local (master)
$ ^[[200~git remote set-url origin https://github.com/4phtt/depot_local.git~
bash: $'\E[200~git': command not found

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote set-url origin https://github.com/4phtt/depot_local.git

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote -v
origin  https://github.com/4phtt/depot_local.git (fetch)
origin  https://github.com/4phtt/depot_local.git (push)

lenovo@4phtt MINGW64 ~/depot_local (master)
$ touch produit.html style.css script.js

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git status
On branch master
nothing to commit, working tree clean

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git add produit.html style.css script.js

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git commit -m "Ajout des fichiers"
On branch master
nothing to commit, working tree clean

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git config --global user.name "houssam"

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git config --global user.email "marmoudhoussam.123@gmail.com"

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git checkout -b "Gestion produits"
```

```
MINGW64:/c/Users/lenovo/depot_test
$ git config --global user.email "marmoudhoussam.123@gmail.com"

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git checkout -b "Gestion produits"
fatal: 'Gestion produits' is not a valid branch name
hint: See 'git help check-ref-format'
hint: Disable this message with "git config set advice.refSyntax false"

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git log --oneline
34cb30f (HEAD -> master, Gestion-produits) Modification des fichier
e077a77 Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git ls-files
produit.html
script.js
style.css

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git checkout -b Gestion_produits
Switched to a new branch 'Gestion_produits'

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git branch
  Gestion-produits
* Gestion_produits
  master

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ echo "<h1>Produits</h1>" > produit.html

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ echo "body { margin: 0; }" > style.css

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ echo "console.log('ok');" > script.js

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git status
On branch Gestion_produits
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   produit.html
        modified:   script.js
        modified:   style.css

no changes added to commit (use "git add" and/or "git commit -a")

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git add .
warning: in the working copy of 'produit.html', LF will be replaced by CRLF the next time Git touche
s it
warning: in the working copy of 'script.js', LF will be replaced by CRLF the next time Git touches i
t
warning: in the working copy of 'style.css', LF will be replaced by CRLF the next time Git touches i
t

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git commit -m "Modification des trois fichiers"
```

MINGW64:/c/Users/lenovo/depot_test

```
lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git commit -m "Modification des trois fichiers"
On branch Gestion_produits
nothing to commit, working tree clean

lenovo@4phtt MINGW64 ~/depot_local (Gestion_produits)
$ git checkout master
Switched to branch 'master'

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git merge Gestion_produits
Already up to date.

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote set-url origin https://github.com/4phtt/depot_local.git

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote -v
origin  https://github.com/4phtt/depot_local.git (fetch)
origin  https://github.com/4phtt/depot_local.git (push)

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git log --oneline
34cb30f (HEAD -> master, Gestion_produits, Gestion-produits) Modification des fichier
e077a77 Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git remote show origin
* remote origin
  Fetch URL: https://github.com/4phtt/depot_local.git
  Push  URL: https://github.com/4phtt/depot_local.git
  HEAD branch: (unknown)

lenovo@4phtt MINGW64 ~/depot_local (master)
$ git push -u origin master
Enumerating objects: 8, done.
Counting objects: 100% (8/8), done.
Delta compression using up to 8 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (8/8), 608 bytes | 67.00 KiB/s, done.
Total 8 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/4phtt/depot_local.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

lenovo@4phtt MINGW64 ~/depot_local (master)
$ cd ~

lenovo@4phtt MINGW64 ~
$ cp -r depot_local depot_test

lenovo@4phtt MINGW64 ~
$ cd depot_test

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git log --oneline
34cb30f (HEAD -> master, origin/master, Gestion_produits, Gestion-produits) Modification des fichier
e077a77 Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_test (master)
```

MINGW64:/c/Users/lenovo/depot_test

```
Delta compression using up to 8 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (8/8), 608 bytes | 67.00 KiB/s, done.
Total 8 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/4phtt/depot_local.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

lenovo@4phtt MINGW64 ~/depot_local (master)
$ cd ~

lenovo@4phtt MINGW64 ~
$ cp -r depot_local depot_test

lenovo@4phtt MINGW64 ~
$ cd depot_test

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git log --oneline
34cb30f (HEAD -> master, origin/master, Gestion_produits, Gestion-produits) Modification des fichier
e077a77 Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git reset --hard <id_du_premier_commit>
bash: syntax error near unexpected token `newline'

lenovo@4phtt MINGW64 ~/depot_test (master)
$ rm -rf .git

lenovo@4phtt MINGW64 ~/depot_test
$ git init
Initialized empty Git repository in C:/Users/lenovo/depot_test/.git/

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git reset --hard e077a77
fatal: ambiguous argument 'e077a77': unknown revision or path not in the working tree.
Use '--' to separate paths from revisions, like this:
'git <command> [<revision>...] -- [<file>...]'

lenovo@4phtt MINGW64 ~/depot_test (master)
$ cd ~

lenovo@4phtt MINGW64 ~
$ rm -rf depot_test

lenovo@4phtt MINGW64 ~
$ cp -r depot_local depot_test

lenovo@4phtt MINGW64 ~
$ cd depot_test

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git reset --hard e077a77
HEAD is now at e077a77 Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_test (master)
$ git log --oneline
e077a77 (HEAD -> master) Ajout des fichiers initiaux

lenovo@4phtt MINGW64 ~/depot_test (master)
$
```