

SYMBOL	PARAMETER	MIN	TYP ⁽¹⁾	MAX	UNIT	CONDITIONS
V _C	Input Clamp Voltage (All Input Pins)		-0.8	-1.2	V	I _C = -5 mA
I _F	Input Load Current:					
	CLK Input		-75	-750	μA	V _F = 0.45V
	EN Input		-50	-500	μA	
	All Other Inputs		-25	-250	μA	
I _R	Input Leakage Current:					
	CLK			120	μA	V _R = 5.5V
	EN Input			80	μA	
	All Other Inputs			40	μA	
V _{IL}	Input Low Voltage			0.8	V	V _{CC} = 5.0V
V _{IH}	Input High Voltage	2.0			V	
I _{CC}	Power Supply Current ⁽²⁾		170	250	mA	
V _{OL}	Output Low Voltage (All Output Pins)		0.35	0.45	V	I _{OL} = 10 mA
V _{OH}	Output High Voltage (MA ₀ -MA ₈ , ISE, FO)	2.4	3.0		V	I _{OH} = -1 mA
I _{OS}	Output Short Circuit Current (MA ₀ -MA ₈ , ISE, FO)	-15	-28	-60	mA	V _{CC} = 5.0V
I _{O (off)}	Off-State Output Current:					
	MA ₀ -MA ₈ , FO			-100	μA	V _O = 0.45V
	MA ₀ -MA ₈ , FO, PR ₀ -PR ₂			100	μA	V _O = 5.5V