

CloudForensiX

A forensic-ready monitoring and incident-response framework for multi-tenant clouds

Aditya Sharma · **Atithi Jaiman** · **Ashish Singh** · **Chiranthan**

Cloud and SRE Security — Monitoring and Incident Response

Base paper: Manral et al., "A Systematic Survey on Cloud Forensics", ACM Computing Surveys, 2019

github.com/4uashish2628/cloudsre

Why investigating a cloud incident is hard

Aditya



Unknown evidence location

Data is virtualised and spread across data centres and jurisdictions. No physical seizure.



Shared, multi-tenant resources

One host, one hypervisor log, one memory dump can hold many customers' data.



Scattered logs and clocks

User, tenant and provider each keep different log formats, time zones and drifting clocks.



Trust in the provider

The provider controls the logs. A malicious insider could edit them.

Base paper: a survey of cloud forensics

Aditya

Manral, Somani, Choo, Conti, Gaur

ACM Computing Surveys 52(6), 2019

- 80 papers (2009–2019) classified into a taxonomy
- Table 14: which artifacts each stakeholder holds
- 5 investigation guidelines (Sec. 8.2)

Incident-driven
continuous / post-incident

Provider-driven
log- and agent-based

Consumer-driven
physical / management plane

Resource-driven
VM, storage, network



Gaps the survey points out

Most proposals "lack implementation and model evaluation", and there are no metrics to compare forensic solutions.

Our idea: guidelines into one working system

Aditya


Requirement (survey section)	SecLaaS	BlockSLaaS	FROST	FMP	CLOSER	Ours
R1 Tamper-evident logs, safe from a malicious provider (3.1, 8.2.3)	◐	◐	–	◐	–	✓
R2 Aggregate logs, fix time zones (8.2.2)	–	–	–	–	◐	✓
R3 Live detection, few false alerts (8.2.1, 7.2)	–	–	–	◐	–	✓
R4 Correlation and timeline reconstruction (4.1)	–	–	–	–	✓	✓
R5 Privacy and evidence isolation (8.2.4)	–	–	◐	–	–	✓
R6 Integrity, custody, metrics (5, 7.2, 8.2.5)	◐	◐	◐	◐	–	✓

✓ addressed ◐ partially – not addressed

Six requirements → six components, each tested against the methods the survey reviews.

Architecture of CloudForensiX

Atithi



Stages follow the survey's five-step investigation process. Orange = what the investigator receives.

Who we defend against

Atithi



External attacker

Steals credentials or breaks into VMs; runs one of five attack campaigns.

Detect fast, rebuild the full story



Malicious cloud insider

Full write access to the log store. Can edit, delete, reorder or truncate records and recompute every hash.

Cannot forge the tenant's key or rewrite published anchors



Curious co-tenant

Should never see another customer's data in the evidence.

Isolate and pseudonymise

FRSL: a log the provider cannot quietly rewrite

Atithi

1 

Hash chain
Each entry includes the hash of the previous one, so order and deletions are protected.

2 

Merkle-sealed batches
Every B entries are sealed under one Merkle root; one record proves itself with 10 hashes.

3 

Proof of Past Log, signed by the tenant
Root, count and last hash are MAC'd with a key only the tenant holds.

4 

Published outside the provider
Proofs go to an append-only anchor. A Bloom filter answers "did this record exist?"




The provider can rewrite its own disk, but not the tenant's anchor.


Fixes the weakness the survey lists for SecLaaS and BlockSLaaS: no protection against a malicious provider, and high cost.

FRSL results: tamper detection and cost

Atithi



Detection rate over 100 trials per attack. Only FRSL and blockchain catch an insider who recomputes hashes.



100%

of insider attacks detected, even with recomputed hashes

7.2×

faster ingest than blockchain logging

8 µs

to verify one record (5,300× faster than a full audit)

Caveat: records not yet sealed can be cut off undetected → seal on a timer.

Test setup: a simulated multi-tenant cloud

Ashish

20

attack campaigns per 24-hour run

5

random seeds, results averaged

37k

raw log records per run (4 tenants)

5 attack types

- Password brute force → data theft
- Privilege escalation to admin
- Cryptomining on stolen GPUs
- SSH break-in → lateral movement
- Anti-forensics: logging switched off, logs shredded


Harmless look-alikes

- Forgotten passwords, travelling users
- Nightly backups with bulk downloads
- Disaster-recovery drill from a new site
- Real admin grants, GPU batch jobs
- Internet SSH scanners

Why simulated: researchers cannot instrument real providers' back-ends (the survey says so too). Logs use real formats; hidden ground truth is used only for scoring.

Hybrid detection: 67% fewer false alerts

Ashish



100%

of campaigns detected (Isolation Forest alone: 26%)

83 s

mean time to detect

0.49 → 0.78

event precision, rules vs hybrid

How: rules fire, then alerts matching learnt normal behaviour (known user + known IP) are suppressed, and strong anomalies are added.


Rebuilding the full attack timeline

Ashish

34% → **100%**

of each attack's events: alerts alone vs. after entity-graph reconstruction

Entity graph (ours)
Links alerts sharing an attacker IP, user or host. Best grouping score (ARI 0.9996) vs. Leader-Follower [CLOSER] and a time window; splits campaigns least (1.19 incidents each vs 1.39–1.85).



Live demo

Ashish

```
$ cd cloudsre
$ .venv/bin/python -m pytest -q
28 passed

$ .venv/bin/python -m cloudforensix.cli \
      investigate --seed 7 --out cases
alerts 116 · incidents 24 · campaigns 20/20
store_verified: true
```

Open an incident report and point at:

Timeline
failed SSH logins → success → dropper → lateral movement

Integrity
50/50 records verified by Merkle proof


Privacy
residual foreign identifiers = 0

Acquisition plan
who holds each piece of evidence (Table 14)

Backup: screen recording + examples/CASE-tenant-a-020 in the repo

Evidence isolation: no other customer's data

Chiranthan



51 → 0

foreign-tenant identifiers per incident (119 incidents)

100%

of the attack's own records kept

7,150 → 2,030

records per evidence set: smaller and focused


Other tenants' records are dropped; shared host logs keep only our VMs, with the rest replaced by keyed pseudonyms a court can unlock.

Provider dependency and scalability

Chiranthan

Attack	Needs provider	Wait today*
Data theft	storage logs	≈80 h
Cryptomining	hypervisor logs	≈92 h
Privilege escalation	–	≈5 h
SSH lateral	–	≈8 h
Anti-forensics	–	≈8 h

Using the survey's Table 14. With our pipeline, owner-side evidence is ready in seconds; only a provider forensics-as-a-service API removes the long wait for provider-held logs.



* *modelled median, assumed delays (owner ≈4 h, legal request to provider ≈72 h)*

≈52k records/s

linear scaling on one laptop core

What we contributed, and its limits

Chiranthan

Contributions

- 6 requirements derived from the survey
- Open-source framework: ~2,300 lines, 28 tests
- FRSL: secure log safe from a malicious provider
- Reproducible simulator with ground truth
- Forensic metric suite + 8 experiments

Limitations

- Simulated data, not a real provider
- Rules written knowing the attack types
- Tenant MAC, not public signatures
- Unsealed records can be truncated
- Acquisition delays are modelled

Three takeaways



External anchoring

Defeats a malicious insider at a fraction of blockchain's cost.



Context beats raw rules

Learnt behaviour cuts false alerts by two thirds, no campaign missed.



Correlate with correct time

Turns a third of the evidence into all of it.

Future work: real cloud log datasets · public signatures with TPM keys · streaming on OpenSearch · container and SDN logs

Thank you — questions?

github.com/4uashish2628/cloudsre