APRX Software Requirement Specification

Table of Contents

1 APRX Software Requirement Specification 2
1.1 Purpose: 2
1.2 Usage Environments: 3
2 Treatment rules: 4
2.1 Basic IGate rules: 4
2.2 Low-Level Transmission Rules: 5
2.3 Low-Level Receiving Rules: 6
2.4 Additional Tx-IGate rules: 6
2.5 Digipeater Rules: 7
2.6 Radio Interface Statistics Telemetry 8
2.7 Individual Call-Signs for Each Receiver, or Not? 8
2.8 Beaconing 9
2.8.1 Radio Beaconing 9
2.8.2 Network beaconing 9

1 APRX Software Requirement Specification

This is *Requirement Specification* for a software serving in Amateur Radio APRS service.

Reader is assumed to be proficient with used terminology, and they are not usually explained here.

1.1 Purpose:

This describes algorithmic, IO-, and environmental requirements for a software doing any combination of following three tasks related to APRS service:

1. Listen on messages with a radio, and pass them to APRSIS network service
2. Listen on messages with a radio, and selectively re-send them on radio
3. Listen on messages with a radio, and selectively re-send them on radios on other frequencies
4. Receive messages from APRSIS network, and after selective filtering, send some of them on radio

Existing *aprx* software implements Receive-Only (Rx) IGate functionality, and the purpose of this paper is to map new things that it will need for extending functionality further.

1.2 Usage Environments:

The *aprx* software can be used in several kinds of environments to handle multiple tasks associated with local APRS network infrastructure tasks.

On following one should remember that amateur radio transmitters need a licensed owner/operator/license themselves, but receivers do not:

1. License-free Receive-Only (RX) IGate, to add more “ears” to hear packets, and to pipe them to APRSIS
2. Licensed bidirectional IGate, selectively passing messages from radio channels to APRSIS, and from APRSIS to radio channels, but not repeating packets heard on a radio channel back to a radio channel.
3. Licensed bidirectional IGate plus selectively re-sending of packets heard on radio channels back to radio channels
4. Licensed system for selectively re-sending of packets heard on radio channels back to other radio channels, and this without bidirectional IGate service.
5. Licensed system for selectively re-sending of packets heard on radio channels back to radio channels, and doing with with “receive only” IGate, so passing information heard on radio channel to APRSIS, and not the other way at all.

In more common case, there is single radio and single TNC attached to digipeating (re-sending), in more challenging cases there are multiple receivers all around, and very few transmitters. Truly challenging systems operate on multiple radio channels. As single-TNC and single-radio systems are just simple special cases of these complex systems, and for the purpose of this software requirements we consider the complex ones:

1. 3 different frequencies in use, traffic is being relayed in between them, and the APRSIS network.
2. On each frequency there are multiple receivers, and one well placed transmitter.
3. Relaying from one frequency to other frequency may end up having different rules, than when re-sending on same frequency: Incoming packet retains traced paths, and gets WIDEn-N/TRACEn-N requests replaced with whatever sysop wants.

2 Treatment rules:

Generally: All receivers report what they hear straight to APRSIS, after small amount of filtering of junk messages, and things which explicitly state that they should not be sent to APRSIS.

2.1 Basic IGate rules:

General rules for these receiving filters are described here:

http://www.aprs-is.net/IGateDetails.aspx

Gate all packets heard on RF to the Internet (Rx-IGate) EXCEPT

1. 3rd party packets (data type '}') should have all before and including the data type stripped and then the packet should be processed again starting with step 1 again. There are cases like D-STAR gateway to APRS of D-STAR associated operator (radio) positions.
2. generic queries (data type '?').
3. packets with TCPIP, TCPXX, NOGATE, or RFONLY in the header, especially in those opened up from a 3rd party packets.

Gate message packets and associated posits to RF (Tx-IGate) if

1. the receiving station has been heard within range within a predefined time period (range defined as digi hops, distance, or both).
2. the sending station has not been heard via RF within a predefined time period (packets gated from the Internet by other stations are excluded from this test).
3. the sending station does not have TCPXX, NOGATE, or RFONLY in the header.
4. the receiving station has not been heard via the Internet within a predefined time period.
   A station is said to be heard via the Internet if packets from the station contain TCPIP* or TCPXX* in the header or if gated (3rd party) packets are seen on RF gated by the station and containing TCPIP or TCPXX in the 3rd party header (in other words, the station is seen on RF as being an IGate).

Gate all packets to RF based on criteria set by the sysop (such as call sign, object name, etc.).

With more advanced looking inside frames to be relayed, both the digipeater and Tx-IGate can use filtering rules, like “packet reports a position that is within my service area.”

From multiple receivers + single (or fewer) transmitter(s) follows, than when a more usual system does not hear what it sent out itself, this one will hear, and its receivers must have a way to ignore a frame it sent out itself a moment ago.

Without explicit “ignore what I just sent” filtering, an APRS packet will get reported twice to APRSIS:

rx ⟹ igate-to-aprsis + digi ⟹ tx ⟹ rx ⟹ igate-to-aprsis + digi (dupe filter stops)

Digipeating will use common packet duplication testing to sent similar frame out only once per given time interval (normally 30 seconds.)

2.2 Low-Level Transmission Rules:

These rules control repeated transmissions of data that was sent a moment ago, and other basic transmitter control issues, like persistence. In particular the persistence is fine example of how to efficiently use radio channel, by sending multiple small frames in quick succession with same preamble and then be silent for longer time.

1. Normal digipeater duplicate packet detection compares message source, destination, and payload data against another expiring storage called “duplicate detector”. Digipeater and Tx-IGate will ignore packets finding a hit in this storage.
2. A candidate packet is then subjected to a number of filters, and if approved for it, the packet will be put on duplicate packet detection database (one for each transmitter.) See Digipeater Rules, below.
3. Because the system will hear the packets it sends out itself, there must be a global expiring storage for recently sent packets, which the receivers can then compare against. (Around 100 packets of 80-120 bytes each.) This storage gets a full copy of packet being sent out – a full AX.25 frame.

Also, transmitters should be kept in limited leash: Transmission queue is less than N seconds (< 5 ?), which needs some smart scheduling coding, when link from computer to TNC is considerably faster.

Original KISS interface is defined as “best effort”: if TNC is busy while host sends a frame, the frame will be discarded, and “upper layers” will resend. In APRS Digipeating, the upper layer sends the packet once, and then declares circa 30 second moratorium on packets with same payload.

2.3 Low-Level Receiving Rules:

1. Received AX.25 packet is compared against “my freshly sent packets” storage, and matched ones are dropped. (Case of one/few transmitters, and multiple receivers hearing them.)
2. Received packet is validated against AX.25 basic structure, invalid ones are dropped.
3. Received packet is validated against Rx-IGate rules, forbidden ones are dropped (like when a VIA-field contains invalid data.)
4. Packet may be rejected for Rx-IGate, but it may still be valid for digipeating! For example a 3rd party frame is OK to digipeat, but not to Rx-IGate to APRSIS! Also some D-STAR to APRS gateways output 3rd party frames, while the original frame is quite close to an APRS frame.

Divide packet rejection filters to common, and destination specific ones.

2.4 Additional Tx-IGate rules:

The Tx-IGate can have additional rules for control:

1. Multiple filters look inside the message, and can enforce a rule of “repeat only packets within my service area,” or to “limit passing message responses only to destinations within my service area”
2. Basic gate filtering rules:
    1. the receiving station has been heard within range within a predefined time period (range defined as digi hops, distance, or both).
    2. the sending station has not been heard via RF within a predefined time period (packets gated from the Internet by other stations are excluded from this test).
    3. the sending station does not have TCPXX, NOGATE, or RFONLY in the header.
    4. the receiving station has not been heard via the Internet within a predefined time period.

    A station is said to be heard via the Internet if packets from the station contain TCPIP* or TCPXX* in the header or if gated (3rd-party) packets are seen on RF gated by the station and containing TCPIP or TCPXX in the 3rd-party header (in other words, the station is seen on RF as being an IGate).
3. More rules ?

2.5 Digipeater Rules:

Digipeater will do following for each transmitter:

1. Compare candidate packet against duplicate filter, if found, then drop it. (Low-level transmission rules, number 1)
2. Count number of hops the message has so far done, and...
3. Figure out the number of hops the message has been requested to do (e.g. “OH2XYZ-1>APRS,OH2RDU*,WIDE7-5: ...” will report that there was request of 7 hops, so far 2 have been executed – one is shown on trace path.)
4. If either of previous ones are over any of configured limits, the packet is dropped.
5. FIXME: WIDEn-N/TRACEn-N treatment rules: By default treat both as TRACE, have an option to disable TRACE mode. Possibly additional keywords for cross-band digipeating?
6. Multiple filters look inside the message, and can enforce a rule of “repeat only packets within my service area.”
7. FIXME: Cross frequency digipeating? Treat much like Tx-IGate?
   Relaying from one frequency to other frequency may end up having different rules, than when re-sending on same frequency: Incoming packet retains traced paths, and gets WIDEn-N/TRACEn-N requests replaced with whatever sysop wants.
8. Cross band relaying may need to add both an indication of “received on 2m”, and transmitter identifier: “sent on 6m”:
   “OH2XYZ-1>APRS,RX2M*,OH2RDK-6*,WIDE3-2: ...”

   This “source indication” may not have anything to do with real receiver identifier, which is always shown on packets passed to APRSIS.

2.6 Radio Interface Statistics Telemetry

Current *aprx* software offers telemetry data on radio interfaces. It consists of following four things. Telemetry is reported to APRS-IS every 10 minutes:

1. Channel occupancy average in Erlangs over 1 minute interval, and presented as busiest 1 minute within the report interval. Where real measure of carrier presence on radio channel is not available, the value is derived from number of received AX.25 frame bytes plus a fixed Stetson-Harrison constant added per each packet for overheads. That is then divided by presumed channel modulation speed, and thus derived a figure somewhere in between 0.0 and 1.0.
2. Channel occupancy average in Erlangs over 10 minute interval. Same data source as above.
3. Count of received packets over 10 minutes.
4. Count of packets dropped for some reason during that 10 minute period.

Additional telemetry data points could be:

1. Number of transmitted packets over 10 minute interval
2. Number of packets IGate:d from APRSIS over 10 minute interval
3. Number of packets digipeated for this radio interface over 10 minute interval
4. Erlang calculations could include both Rx and Tx, but could also be separate.

2.7 Individual Call-Signs for Each Receiver, or Not?

Opinions are mixed on the question of having separate call-signs for each receiver (and transmitter), or not. Even the idea to use all 16 available SSIDs for a call-sign for something does get some opposition.

- There is no license fee in most countries for receivers, and there is no need to limit used call signs only on those used for the site transmitters.
- There is apparently some format rule on APRSIS about what a “call-sign” can be, but it is rather lax: 6 alphanumerics + optional tail of: “-” (minus sign) and one or two alphanumerics. For example OH2XYZ-R1 style call-sign can have 36 different values before running out of variations on last character alone (A to Z, 0 to 9.)
- Transmitter call-signs are important, and there valid AX.25 format call-signs are mandatory.

Transmitters should have positional beacons for them sent on correct position, and auxiliary elements like receivers could have their positions either real (when elsewhere), or actually placed near the primary Tx location so that they are separate on close enough zoomed map plot.

Using individual receiver identities (and associated net-beaconed positions near the real location) can give an idea of where the packet was heard, and possibly on which band. At least the *aprs.fi* is able to show the path along which the position was heard.

2.8 Beaconing

Smallest time interval available to position viewing at aprs.fi site is 15 minutes. A beacon interval longer than that will at times disappear from that view. Default view interval is 60 minutes.

Beacon transmission time **must not** be manually configured to fixed exact minute. There are large peaks in APRSIS traffic because of people are beaconing out every 5 minutes, and every 10 minutes, at exact 5/10 minutes. Beaconing algorithm must be able to spread the requests over the entire cycle time (10 to 30 minutes) evenly. Even altering the total cycle time by up to 10% at random at the start of each cycle should be considered (and associated re-scheduling of all beacon events at every cycle start). All this to avoid multiple non-coordinated systems running at same rhythm.

The Bresenham's line plotting algorithm can be used to find smooth integer time intervals – or the programmer can resort of floating point. Related algorithm is known as “Digital Differential Analyser”. Both can be implemented using integer arithmetic, which may be of interest on some cases.

Beaconing at quicker repetition rates is also possible by inserting same item multiple times into the cycle.

Receiver location beacons need only to be on APRSIS, transmitter locations could be also on radio.

2.8.1 Radio Beaconing

“Tactical situation awareness” beaconing frequency could be 5-10 minutes, WB4APR does suggest 10 minutes interval. Actively moving systems will send positions more often. Transmit time spread algorithm must be used.

Minimum interval of beacon transmissions to radio should be 30 seconds. If more beacons need to be sent in this time period, use of Persistence parameter on TNCs (and KISS) should help: Send the beacons one after the other (up to 3?) during same transmitter activation, and without prolonged buffer times in between them.

2.8.2 Network beaconing

Network beaconing cycle time can be up to 30 minutes.

Network beaconing can also transmit positions and objects at much higher rate, than radio beaconing. Transmit time spread algorithm must be used.

Beacons could also be bursting similar to radio beacon Persistence – within a reason.