# Does DVOL add information beyond HAR?

A retrospective BTC variance forecast study | Yuvraj Singh | 24 October 2026

**Abstract.** I test whether Bitcoin (BTC) DVOL, Deribit's option-implied volatility index, adds information beyond a heterogeneous autoregressive (HAR) model for direct 30-day variance forecasts, using 1,357 daily origins from 2023 to 2026. Raw DVOL's advantage over HAR + DVOL is concentrated in 2025–2026; 2025 accounts for 76.93% of its net quasi-likelihood (QLIKE) loss advantage. Rolling rescaling barely changes raw DVOL's mean loss, while a fixed 50/50 HAR–DVOL variance blend trails raw DVOL and has lower mean loss than HAR + DVOL. Every new paired interval includes zero. HAR + DVOL lowers HAR's mean QLIKE by 11.35%, but the original paired intervals also include zero and their effective sample sizes (ESS), 53.44 and 51.71, are below the preset reporting rule of 60. The variance-budget diagnostic shows no clear gain; the prospective year remains evidence collection without a formal significance test.





Figure 1. Mean QLIKE loss for the five matched forecasts, descriptive 95% paired intervals, and the original cumulative paired differences over 1,357 daily origins. Negative differences favour the first forecast named. Raw-DVOL, rescaling and fixed-blend comparisons are exploratory additions made after inspection.

## 1 Introduction

Does option-implied variance add forecasting information beyond daily, weekly and monthly realised variance? I compare a direct 30-day HAR forecast with HAR + DVOL, which adds the previous completed daily DVOL variance. Raw DVOL and trailing variance provide reference forecasts.

Among the original forecasts, raw DVOL has lower mean QLIKE than HAR + DVOL, with an interval including zero. Rolling rescaling changes little; the equal blend narrows the regression's mean-loss gap but trails raw DVOL.

Prior work asks whether option-implied volatility adds information beyond historical volatility. Christensen and Prabhala (1998) find incremental information in implied volatility for the S&P 100 index using non-overlapping observations; their setting differs from the overlapping BTC targets here. Corsi (2009) combines realised-volatility components across time horizons in the HAR model, which I adapt to a direct variance target. Patton (2011) studies how imperfect volatility proxies affect forecast rankings and motivates care in choosing the loss function.

Using Deribit option trades, Hoang and Baur (2020) compare implied volatility with time-series forecasts, including HAR. They find horizon-dependent accuracy and gains from combining implied volatility with model forecasts. Their option-derived measure and shorter forecast horizons differ from the direct 30-day DVOL comparison here.

## 2 Data and method

The retained inputs contain 48,626 hourly BTC-PERPETUAL candles and 1,996 daily DVOL candles, downloaded on 19 October 2026. Evaluation uses daily midnight forecast origins from 1 January 2023 through 18 September 2026. Each target is the next 720 hourly log-return squares, annualised by 8,760; that window requires 721 completed closes.

Both regressions use exactly the latest 365 labels whose full 30-day targets have ended. Prior 1-, 7- and 30-day annualised variances form the HAR features. HAR + DVOL adds the previous completed daily DVOL close divided by 100 and then squared. Level ordinary least squares includes an intercept, with features centred and scaled using training rows only. An annual-variance floor of 1e-6 applies to forecasts; raw predictions and every floor hit are retained. Neither regression reaches that floor in this sample. Level OLS minimises squared variance errors, while evaluation uses QLIKE. These are different objectives within the restricted HAR specifications, although both losses target conditional mean variance when forecasts are unrestricted (Patton, 2011).

With $r_t$ denoting an hourly log return and $t$ the forecast origin, the future target and completed-return features are

$$V_t^{(30\mathrm{d})} = \frac{8760}{720}\sum_{h=1}^{720} r_{t+h}^2,$$

$$RV_t^{(k)} = \frac{8760}{24\,k}\sum_{h=1}^{24\,k} r_{t-h+1}^2, \quad k \in \{1, 7, 30\}.$$

The two direct forecasts are

$$\widehat{V}_t^{(30\mathrm{d}),\mathrm{HAR}} = \widehat{\beta}_{0,t} + \widehat{\beta}_{d,t} RV_t^{(1)} + \widehat{\beta}_{w,t} RV_t^{(7)} + \widehat{\beta}_{m,t} RV_t^{(30)},$$

$$\widehat{V}_t^{(30\mathrm{d}),\mathrm{HAR+DVOL}} = \widehat{\gamma}_{0,t} + \widehat{\gamma}_{d,t} RV_t^{(1)} + \widehat{\gamma}_{w,t} RV_t^{(7)} + \widehat{\gamma}_{m,t} RV_t^{(30)} + \widehat{\gamma}_{D,t}\left(\frac{\mathrm{DVOL}_t^{\mathrm{prev.close}}}{100}\right)^2.$$

All comparisons use identical origins. Smaller values of the QLIKE loss indicate more accurate variance forecasts:

$$\mathrm{QLIKE} = \frac{\text{realised}}{\text{forecast}} - \log\left(\frac{\text{realised}}{\text{forecast}}\right) - 1.$$

## 3 Testing scale and fixed-weight alternatives

The original HAR + DVOL minus HAR mean QLIKE difference is -0.01424, with descriptive interval [-0.03490, +0.00505] and ESS 51.71. Raw DVOL minus (HAR + DVOL) has mean -0.01513, interval [-0.03939, +0.00817] and ESS 53.44.

I declared the added specifications in public commit `6a6b59b` before evaluating these additions, after inspecting the original ranking. Rescaled DVOL uses exactly the same latest 365 fully completed labels as each HAR fit. With $D_t$ denoting raw DVOL variance, $V_s$ the realised target and $\mathcal{T}_t$ that training set, the added forecasts are

$$c_t = \frac{1}{365}\sum_{s\in\mathcal{T}_t}\frac{V_s}{D_s}, \qquad \widehat{V}_t^{\mathrm{rescaled}} = c_t D_t, \qquad \widehat{V}_t^{\mathrm{equal}} = 0.5\widehat{V}_t^{\mathrm{HAR}} + 0.5 D_t.$$

The multiplier is positive and unclipped. The blend averages variances and has no fitted combination weight; HAR's coefficients remain estimated. The scalar rule also appeared in the earlier DVOL reference comparison; this table matches it to HAR. All rows use the same origins, bootstrap draws and ESS machinery, while the locked prospective primary comparison stays unchanged.

Table 1. Matched exploratory comparisons against HAR + DVOL. Lower mean QLIKE is better. Negative paired differences favour the row forecast. All intervals are descriptive; the reference row has no paired interval or ESS.

| Forecast | Mean QLIKE | Paired mean difference | 95% interval | ESS |
|---|---|---|---|---|
| Raw DVOL | 0.09611 | -0.01513 | [-0.03939, +0.00817] | 53.44 |
| Rescaled DVOL | 0.09582 | -0.01541 | [-0.03732, +0.00577] | 70.63 |
| 50/50 HAR–DVOL | 0.09937 | -0.01186 | [-0.02929, +0.00339] | 58.57 |
| HAR + DVOL | 0.11123 | — | — | — |
| HAR | 0.12548 | +0.01424 | [-0.00505, +0.03490] | 51.71 |

Rescaled DVOL minus raw DVOL has mean -0.00028 and interval [-0.01600, +0.01550]. The equal blend minus raw DVOL has mean +0.00327 and interval [-0.01125, +0.01952]. Rescaling barely changes the mean loss; the blend has lower mean loss than HAR + DVOL but higher mean loss than raw DVOL. All four new paired intervals include zero. The simpler rules therefore leave the cause of the original ranking unresolved.

Mean realised-to-forecast variance ratios are 1.1689 for trailing variance, 0.8920 for raw DVOL, 0.9499 for HAR and 1.0072 for HAR + DVOL. Each averages individual $V_t/\widehat{V}_t$ ratios, rather than dividing sample means. A single scalar equal to that mean minimises in-sample QLIKE. It lowers raw DVOL's in-sample mean to 0.08981 and HAR + DVOL's to 0.11121. This algebraic diagnostic leans against helpful constant upward scaling as the explanation for raw DVOL's advantage. It uses the full sample and is separate from the completed-label rolling forecast; it establishes neither conditional calibration nor a causal explanation. QLIKE penalises a forecast too low by a factor $k > 1$ more than one too high by the same factor. Trailing variance's mean QLIKE is 0.16670.

## 3.1 Extreme differences pull against the mean

The largest 1% and 5% of absolute HAR + DVOL minus HAR QLIKE differences account for 8.6% and 27.8% of total absolute differences. Their aggregate signed contributions are positive, so these groups hurt HAR + DVOL relative to HAR even though the full-sample mean is negative. This pattern runs against a simple explanation in which HAR + DVOL wins by avoiding the most extreme losses.

Table 2. Mean paired QLIKE differences within each year. Negative values favour the first forecast named. The final year ends on 18 September; these are descriptive episode summaries.

| Year | Origins | HAR + DVOL minus HAR | Raw DVOL minus (HAR + DVOL) |
|---|---|---|---|
| 2023 | 365 | -0.01943 | +0.00386 |
| 2024 | 366 | -0.01870 | +0.00072 |
| 2025 | 365 | -0.02382 | -0.04327 |
| 2026 (partial) | 261 | +0.01265 | -0.02455 |

Raw DVOL's advantage over HAR + DVOL is concentrated in 2025–2026. The 2025 signed loss sum accounts for 76.93% of the full-sample net advantage; the small positive differences in 2023–2024 partly offset later gains. HAR + DVOL lowers annual mean QLIKE relative to HAR in 2023–2025 and raises it in the partial 2026 sample. Leave-one-year-out diagnostics remain in the results JSON.

The retained diagnostics cover every fixed calendar quarter, extreme-origin dates and all 30 non-overlapping starting phases. Each phase contains 45 or 46 outcomes. These displays describe concentration; their interpretation is set out in the limitations below.

## 3.2 Lower mean QLIKE loss brings no clear budget gain

I use a variance-budget diagnostic with an illustrative annual variance target of 0.04, equivalent to 20% annual volatility. The rule scales assumed fractional exposure; its capped weight and squared variance-budget error are

$$w = \min\left(1, \frac{0.20}{\sqrt{\text{forecast variance}}}\right), \qquad \left(w^2 \times \text{realised variance} - 0.04\right)^2.$$

Table 3. The variance-budget diagnostic. Budget exceeded is the share of origins above the target variance budget.

| Forecast | Mean weight | Mean squared variance-budget error | Budget exceeded |
|---|---|---|---|
| trailing variance | 0.469 | 0.0008186 | 46.7% |
| Raw DVOL | 0.418 | 0.0002872 | 29.6% |
| HAR | 0.420 | 0.0004014 | 36.3% |
| HAR + DVOL | 0.437 | 0.0004196 | 41.7% |

HAR + DVOL has a higher mean squared variance-budget error than HAR: the paired difference is +0.0000182, with interval [-0.0000818, +0.0001221]. The interval includes zero, so this diagnostic leaves the benefit uncertain.

# 4 Inference limits

Paired stationary-bootstrap inference uses 5,000 draws, a fixed seed and expected blocks of 60 days, with a 59-lag heteroskedasticity- and autocorrelation-consistent (HAC) cross-check. Block sensitivities use 30, 90, 180 and 365 days. Overlapping targets and rolling fits can create dependence beyond the 30-day horizon. For each paired QLIKE difference series, ESS is the minimum of the observation count, an estimate from positive autocorrelation pairs constrained to decrease, and a variance-ratio estimate using the 59-lag Newey–West long-run variance; the pair sequence stops at its first nonpositive pair. The existing plan fixes 60 as a minimum reporting rule to withhold confirmatory results when estimated information is limited; I retain it without tuning it to these results, but the study provides no size or power derivation that makes this cutoff sufficient for valid inference.

Each declared synthetic scenario has 200 independent replications at sample sizes 365 and 1,357, with 2,000 bootstrap draws per replication. The population null has exactly zero mean, without centring each realised sample. The scenarios use a 30-day moving-average loss component alone, add a stationary slow component of persistence $\exp(-1/365)$, or add symmetric rare shocks spread across overlapping windows. The alternative shifts the mean by -0.25 marginal standard deviations, rather than -0.25 QLIKE.

Table 4. Synthetic null rejection rates before the ESS rule. Monte Carlo (MC) intervals describe simulation uncertainty; the last column is the share of replications passing the rule.

| $n$ | Synthetic loss process | Ungated rejection | 95% MC interval | ESS rule passes |
|---|---|---|---|---|
| 365 | 30-day overlap | 19.0% | 14.2% to 25.0% | 0.0% |
| 365 | 30-day overlap plus slow component | 49.0% | 42.2% to 55.9% | 0.0% |
| 365 | 30-day overlap plus clustered tail shocks | 16.0% | 11.6% to 21.7% | 0.0% |
| 1,357 | 30-day overlap | 10.0% | 6.6% to 14.9% | 1.5% |
| 1,357 | 30-day overlap plus slow component | 45.0% | 38.3% to 51.9% | 0.0% |
| 1,357 | 30-day overlap plus clustered tail shocks | 8.5% | 5.4% to 13.2% | 1.5% |

At $n = 365$, ungated null rejection ranges from 16% to 49%, against nominal 5%. The ESS rule passes zero of 200 replications under every one-year null and alternative. The Wilson 95% upper bound is around 1.9% for the probability of passing the rule in those scenarios. The rule therefore prevents a formal significance test in every declared one-year replication. At $n = 1{,}357$, some conditional estimates use only one to four passing replications, with wide Monte Carlo intervals.

# 5 Limitations

**Research choices.** I added the historical comparisons after inspecting the data. Chronological training does not remove that exposure to research choices. All historical findings and generated-forecast diagnostics are exploratory; the intervals are descriptive, and additional diagnostics are not primary discoveries. The mean QLIKE ranking establishes no formal superiority. Raw-DVOL, rescaling and fixed-blend comparisons all follow inspection. A one-parameter rolling fit still has estimation risk because its overlapping labels are dependent. The added intervals do not turn these mechanism checks into confirmatory tests.

**Data.** The original source check compares open, high, low and close (OHLC) fields. It fails because one unused DVOL open differs. All three audited DVOL closes match, but those dates cover little of the full history. I cannot verify the original unrevised data vintages from these historical downloads. One perpetual contract supplies a proxy for spot-index returns, so the study covers one asset and venue.

**Scope.** I evaluate variance forecasts and a variance-budget diagnostic. The diagnostic assumes constant fractional exposure; it does not model a fixed-unit portfolio, rebalancing, funding or profit. I have not established that the rule minimises squared variance-budget error. I make no claims about net trading returns, a causal variance premium or an executable edge. The cumulative figure tracks QLIKE differences, rather than portfolio returns.

**Inference.** The non-overlapping phase samples can still be dependent because volatility and rolling parameter estimates persist. These samples show concentration; they do not select a crisis window or identify an ex-ante regime rule. ESS estimates dependence-adjusted information rather than counting independent episodes. The synthetic stress tests approximate loss dependence, not the full rolling HAR estimation pipeline. None of the declared one-year replications passes the ESS rule, but zero observed passes does not mean the true probability is zero; the Wilson bound quantifies that uncertainty.

# 6 Prospective protocol

The primary prospective contrast remains HAR + DVOL minus HAR. Under the inference-validation amendment, I treat the planned year as timestamped evidence collection without a formal significance test. I fix the cohort and terminal date in advance, even if the result is inconclusive; a later inference design needs a separate prospective declaration.

The HAR cohort contains 365 scheduled origins from 21 October 2026 through 20 October 2027, each at 01:00 UTC. Features end at midnight, forecasts freeze between 00:10 and 00:50, and outcomes begin at 01:00. Training uses the correspondingly shifted historical 30-day targets completed by midnight, a different alignment from the retrospective midnight targets. Final maturity is 19 November 2027, with terminal analysis fixed at 21 November 2027, 01:00 UTC.

Each new forecast requires matching hourly and daily DVOL closes and completion of fitting and the durable write before the freeze deadline. Missed scheduled days count as missed and stay unfilled. Terminal intervals require all 365 planned pairs and source checks; the fixed analysis cutoff excludes later-arriving scores.

# A Reproduction

The numerical results rebuild offline from the retained public recordings with Python 3.12; the README lists the pinned dependencies:

```
python scripts/build_research.py
```

The output retains matched forecasts, coefficients, training cutoffs, diagnostics, simulation rates and plan hashes. The manuscript compiles separately from its checked LaTeX source, bibliography and figure PDF. Collection details, provenance and operational limits are documented in the DVOL methods note.

# References.


Christensen and Prabhala (1998), The relation between implied and realized volatility, doi:10.1016/S0304-405X(98)00034-8.

Corsi (2009), A Simple Approximate Long-Memory Model of Realized Volatility, doi:10.1093/jjfinec/nbp001.

Patton (2011), Volatility Forecast Comparison Using Imperfect Volatility Proxies, doi:10.1016/j.jeconom.2010.03.034.

Hoang and Baur (2020), Forecasting bitcoin volatility: Evidence from the options market, doi:10.1002/fut.22144.

Politis and Romano (1994), The Stationary Bootstrap, doi:10.1080/01621459.1994.10476870.

Deribit, DVOL methodology, `https://insights.deribit.com/exchange-updates/dvol-deribit-implied-volatility-index/`; accessed 21 October 2026.