```
% Effect of addition on closed loop poles
sys = tf([1], [1 3 6])
p = [-1 -5 -10 -20]
for i=1:4
    sys_new = tf([1], [1 -p(i)])*sys
    subplot(2, 2, i)
    step(sys_new)
    stepinfo(sys_new)
end
sys =
  s^2 + 3 s + 6
Continuous-time transfer function.
p =
   -1 -5 -10 -20
sys_new =
          1
  s^3 + 4 s^2 + 9 s + 6
Continuous-time transfer function.
ans =
  struct with fields:
        RiseTime: 2.0388
    SettlingTime: 4.3619
     SettlingMin: 0.1503
     SettlingMax: 0.1667
       Overshoot: 0
      Undershoot: 0
            Peak: 0.1667
        PeakTime: 12.8484
sys_new =
             1
```

s^3 + 8 s^2 + 21 s + 30 Continuous-time transfer function. ans = struct with fields: RiseTime: 0.8705 SettlingTime: 2.6518 SettlingMin: 0.0301 SettlingMax: 0.0358 Overshoot: 7.4106 Undershoot: 0 Peak: 0.0358 PeakTime: 1.8789 sys\_new = 1 s^3 + 13 s^2 + 36 s + 60 Continuous-time transfer function. ans = struct with fields: RiseTime: 0.7990 SettlingTime: 2.5417 SettlingMin: 0.0152 SettlingMax: 0.0181 Overshoot: 8.4569 Undershoot: 0 Peak: 0.0181 PeakTime: 1.7500 sys\_new =

1 s^3 + 23 s^2 + 66 s + 120


Continuous-time transfer function.

ans =

struct with fields:

RiseTime: 0.7770 SettlingTime: 2.4869 SettlingMin: 0.0076 SettlingMax: 0.0091 Overshoot: 8.6970 Undershoot: 0 Peak: 0.0091

PeakTime: 1.6886



Published with MATLAB® R2020a