


Neural Architecture Search

Yu Cao

NAS search space


1. Architecture space

Every layer (even an activation) in a model is involved



2. Cell space

Multiple layers compose a single cell and cells are involved as search space (smaller size)



NAS Search Strategy

Traditionally, the search procedure is not differentiable

1. **Random Search:** random select a series of models and test their performance
2. **Evolutionary method:** shrink the search space step by step via filtering low-performance models using fewer training steps.
3. **Bayesian Optimization:** Assuming the performance of a model follows the Gaussian distribution, maximize the acquisition function based on the performance observation of models.
4. **Reinforcement Learning:** regard a the generation of a model as an action of the agent and the reward is the performance of current generation.
5. **Gradient-based method:** transfer the procedure as a differentiable operation using soft weights to combine different candidate ops for a node. (**Most popular approach now**)

NAS Performance Estimation Strategy (Speed up)

1. **Lower Fidelity Estimates:** training using fewer epochs, subset of the data, downscaled models, etc.
2. **Learning Curve Extrapolation:** training stops when the performance can be extrapolated after few epochs.
3. **Weight Inheritance:** model can be trained from a parent model.
4. **One-shot model:** only the one-shot model is trained while its weight is shared across different architectures.

DARTS: Differentiable Architecture Search

Hanxiao Liu (CMU), Karen Simonyan (DeepMind), Yiming Yang (CMU)

ICLR 2019

Contribution


1. It transforms the NAS problem into differentiable one using soft weighting on the possible operations of nodes in a complex topologies, which can be used on both convolutional and recurrent networks.
2. Such method can also achieve efficiency improvement, as it uses gradient-based optimization to find the best architecture among all possible ones jointly instead of one by one.

Search Space

It is a cell-level search, in which each cell is a **directed acyclic graph (DAG)**, in which each node x^i is a representation and edge (i, j) is the operation $o^{i,j}$ on x^i .

The final representation of node j is the combination of results from all input edges

$$x^{(j)} = \sum_{i < j} o^{(i,j)}(x^{(i)})$$



Optimization Procedure

Given a set of operation \mathcal{O} , the output of an operation is weighted using softmax on a weight vector $\alpha^{(i,j)}$ in dimension $|\mathcal{O}|$.

$$\bar{o}^{(i,j)}(x) = \sum_{o \in \mathcal{O}} \frac{\exp(\alpha_o^{(i,j)})}{\sum_{o' \in \mathcal{O}} \exp(\alpha_{o'}^{(i,j)})} o(x)$$

Thus the goal is jointly learn the architecture α and layer weight w within all mixed operations, given the training loss \mathcal{L}_{train} and validation loss \mathcal{L}_{val}

$$\begin{aligned} \min_{\alpha} \quad & \mathcal{L}_{val}(w^*(\alpha), \alpha) \\ \text{s.t.} \quad & w^*(\alpha) = \operatorname{argmin}_w \mathcal{L}_{train}(w, \alpha) \end{aligned}$$

Gradient Approximation

Directly optimize the objective is too resource-consuming with complexity $O(|\alpha||w|)$

An approximation is

$$\begin{aligned} & \nabla_{\alpha} \mathcal{L}_{val}(w^*(\alpha), \alpha) \\ & \approx \nabla_{\alpha} \mathcal{L}_{val}(w - \xi \nabla_w \mathcal{L}_{train}(w, \alpha), \alpha) \end{aligned}$$

Applying chain rule yields $\nabla_{\alpha} \mathcal{L}_{val}(w', \alpha) - \xi \nabla_{\alpha, w}^2 \mathcal{L}_{train}(w, \alpha) \nabla_{w'} \mathcal{L}_{val}(w', \alpha)$

Where $w' = w - \xi \nabla_w \mathcal{L}_{train}(w, \alpha)$ is a one-step forward model.

The second item is approximated using finite difference approximation

$$\nabla_{\alpha, w}^2 \mathcal{L}_{train}(w, \alpha) \nabla_{w'} \mathcal{L}_{val}(w', \alpha) \approx \frac{\nabla_{\alpha} \mathcal{L}_{train}(w^+, \alpha) - \nabla_{\alpha} \mathcal{L}_{train}(w^-, \alpha)}{2\epsilon} \quad w^{\pm} = w \pm \epsilon \nabla_{w'} \mathcal{L}_{val}(w', \alpha)$$

DARTS Algorithm

The final optimization on α turns to be following, with complexity $O(|\alpha| + |w|)$

$$\nabla_{\alpha} L_{val}(w', \alpha) - \xi \frac{\nabla_{\alpha} L_{train}(w + \epsilon \nabla_{w'} L_{val}(w', \alpha), \alpha) - \nabla_{\alpha} L_{train}(w - \epsilon \nabla_{w'} L_{val}(w', \alpha), \alpha)}{2\epsilon}$$

The algorithm will optimize α and w iteratively, in which the optimization of α is described as above

Algorithm 1: DARTS – Differentiable Architecture Search

Create a mixed operation $\bar{o}^{(i,j)}$ parametrized by $\alpha^{(i,j)}$ for each edge (i, j)

while not converged do

- 1. Update architecture α by descending $\nabla_{\alpha} \mathcal{L}_{val}(w - \xi \nabla_w \mathcal{L}_{train}(w, \alpha), \alpha)$
($\xi = 0$ if using first-order approximation)
- 2. Update weights w by descending $\nabla_w \mathcal{L}_{train}(w, \alpha)$

Derive the final architecture based on the learned α .

max value in α for each node indicates the selected operation

Experiments

DARTS is tested on CIFAR-10 (conv net) and PTB (RNN)

CIFAR-10

| Architecture | Test Error (%) | Params (M) | Search Cost (GPU days) | #ops | Search Method |
|---|-----------------|------------|------------------------|------|----------------|
| DenseNet-BC (Huang et al., 2017) | 3.46 | 25.6 | – | – | manual |
| NASNet-A + cutout (Zoph et al., 2018) | 2.65 | 3.3 | 2000 | 13 | RL |
| NASNet-A + cutout (Zoph et al., 2018) [†] | 2.83 | 3.1 | 2000 | 13 | RL |
| BlockQNN (Zhong et al., 2018) | 3.54 | 39.8 | 96 | 8 | RL |
| AmoebaNet-A (Real et al., 2018) | 3.34 ± 0.06 | 3.2 | 3150 | 19 | evolution |
| AmoebaNet-A + cutout (Real et al., 2018) [†] | 3.12 | 3.1 | 3150 | 19 | evolution |
| AmoebaNet-B + cutout (Real et al., 2018) | 2.55 ± 0.05 | 2.8 | 3150 | 19 | evolution |
| Hierarchical evolution (Liu et al., 2018b) | 3.75 ± 0.12 | 15.7 | 300 | 6 | evolution |
| PNAS (Liu et al., 2018a) | 3.41 ± 0.09 | 3.2 | 225 | 8 | SMBO |
| ENAS + cutout (Pham et al., 2018b) | 2.89 | 4.6 | 0.5 | 6 | RL |
| ENAS + cutout (Pham et al., 2018b) [*] | 2.91 | 4.2 | 4 | 6 | RL |
| Random search baseline [‡] + cutout | 3.29 ± 0.15 | 3.2 | 4 | 7 | random |
| DARTS (first order) + cutout | 3.00 ± 0.14 | 3.3 | 1.5 | 7 | gradient-based |
| DARTS (second order) + cutout | 2.76 ± 0.09 | 3.3 | 4 | 7 | gradient-based |

Experiments

DARTS is tested on CIFAR-10 (conv net) and PTB (RNN)

PTB

| Architecture | Perplexity | | Params (M) | Search Cost (GPU days) | #ops | Search Method |
|---|------------|------|---------------|---------------------------|------|------------------|
| | valid | test | | | | |
| Variational RHN (Zilly et al., 2016) | 67.9 | 65.4 | 23 | – | – | manual |
| LSTM (Merity et al., 2018) | 60.7 | 58.8 | 24 | – | – | manual |
| LSTM + skip connections (Melis et al., 2018) | 60.9 | 58.3 | 24 | – | – | manual |
| LSTM + 15 softmax experts (Yang et al., 2018) | 58.1 | 56.0 | 22 | – | – | manual |
| NAS (Zoph & Le, 2017) | – | 64.0 | 25 | 1e4 CPU days | 4 | RL |
| ENAS (Pham et al., 2018b)* | 68.3 | 63.1 | 24 | 0.5 | 4 | RL |
| ENAS (Pham et al., 2018b)† | 60.8 | 58.6 | 24 | 0.5 | 4 | RL |
| Random search baseline‡ | 61.8 | 59.4 | 23 | 2 | 4 | random |
| DARTS (first order) | 60.2 | 57.6 | 23 | 0.5 | 4 | gradient-based |
| DARTS (second order) | 58.1 | 55.7 | 23 | 1 | 4 | gradient-based |

Conclusion

DARTS significantly reduces the resource consumption of NAS while provides comparable performance compared to RL or Evolution approaches, which makes it followed by many related works (690 citations in past 2 years).

Gradient-based NAS has also become the main trend, 80% of last related papers use gradient-based optimization.

NAS in NLP


1. [The Evolved Transformer](#) (ICML 2019, Google, Quoc V.Le)
2. [Continual and Multi-Task Architecture Search](#) (ACL 2019, UNC Chapel Hill)
3. [Improved Differentiable Architecture Search for Language Modeling and Named Entity Recognition](#) (EMNLP 2019 (short), NEU China)
4. [Learning Architectures from an Extended Search Space for Language Modeling](#) (ACL 2020, NEU China)
5. [Improving Transformer Models by Reordering their Sublayers](#) (ACL 2020, UW and Allen AI)

1. The Evolved Transformer

So, David, Quoc Le, and Chen Liang. "The Evolved Transformer." *International Conference on Machine Learning*. 2019.


This paper utilizes **evolution algorithm** to search **a better architecture of Transformer** for MT task.

The search space is 14 blocks (6 for encoder and 8 for decoder), each block contains left and right branch (input, normalization, layer, output dimension and activation in each of them) and combination function



Evolution algorithm

1. Random sampling architecture as the initial child models, build a set of small training step number set $\langle s, s_1, s_2, \dots \rangle$
2. Train each model with a small step s and evaluate their fitness (performance)
3. Set the hurdle as the mean fitness of all models. Models with lower fitness than hurdle will be filtered.
4. Rest models will be trained for further step s_i and repeat 2,3,4 until all step numbers in a set are used or no model left.



y-axis is the fitness while the x-axis is the order of the generating of candidate models. Solid lines are hurdles.

Experiment and results

It uses WMT datasets, initial model number $m=5000$, and step numbers set are $\langle 60k, 60k, 120k \rangle$, $\sim 50,000$ TPU hour ($\sim 1,000,000$ GPU hour) to find 20 best architecture and find the best one with full training.

| TASK | SIZE | TRAN PARAMS | ET PARAMS | TRAN PERP | ET PERP | TRAN BLEU | ET BLEU |
|--------------|------|----------------|--------------|------------------|------------------------------------|----------------|----------------------------------|
| WMT'14 EN-DE | BASE | 61.1M | 64.1M | 4.24 ± 0.03 | 4.03 ± 0.02 | 28.2 ± 0.2 | 28.4 ± 0.2 |
| WMT'14 EN-DE | BIG | 210.4M | 221.7M | 3.87 ± 0.02 | 3.77 ± 0.02 | 29.1 ± 0.1 | 29.3 ± 0.1 |
| WMT'14 EN-DE | DEEP | 224.0M | 218.1M | 3.86 ± 0.02 | 3.69 ± 0.01 | 29.2 ± 0.1 | 29.5 ± 0.1 |
| WMT'14 EN-FR | BASE | 60.8 | 63.8M | 3.61 ± 0.01 | 3.42 ± 0.01 | 40.0 ± 0.1 | 40.6 ± 0.1 |
| WMT'14 EN-FR | BIG | 209.8M | 221.2M | 3.26 ± 0.01 | 3.13 ± 0.01 | 41.2 ± 0.1 | 41.3 ± 0.1 |
| WMT'14 EN-Cs | BASE | 59.8M | 62.7M | 4.98 ± 0.04 | 4.42 ± 0.01 | 27.0 ± 0.1 | 27.6 ± 0.2 |
| WMT'14 EN-Cs | BIG | 207.6M | 218.9M | 4.43 ± 0.01 | 4.38 ± 0.03 | 28.1 ± 0.1 | 28.2 ± 0.1 |
| LM1B | BIG | 141.1M | 151.8M | 30.44 ± 0.04 | 28.60 ± 0.03 | - | - |

| Model | Embedding Size | Parameters | Perplexity | BLEU | Δ BLEU |
|-------------|-------------------|------------|-----------------------------------|----------------------------------|---------------|
| Transformer | 128 | 7.0M | 8.62 ± 0.03 | 21.3 ± 0.1 | - |
| ET | 128 | 7.2M | 7.62 ± 0.02 | 22.0 ± 0.1 | + 0.7 |
| Transformer | 432 | 45.8M | 4.65 ± 0.01 | 27.3 ± 0.1 | - |
| ET | 432 | 47.9M | 4.36 ± 0.01 | 27.7 ± 0.1 | + 0.4 |
| Transformer | 512 | 61.1M | 4.46 ± 0.01 | 27.7 ± 0.1 | - |
| ET | 512 | 64.1M | 4.22 ± 0.01 | 28.2 ± 0.1 | + 0.5 |
| Transformer | 768 | 124.8M | 4.18 ± 0.01 | 28.5 ± 0.1 | - |
| ET | 768 | 131.2M | 4.00 ± 0.01 | 28.9 ± 0.1 | + 0.4 |
| Transformer | 1024 | 210.4M | 4.05 ± 0.01 | 28.8 ± 0.2 | - |
| ET | 1024 | 221.7M | 3.94 ± 0.01 | 29.0 ± 0.1 | + 0.2 |

Conclusion

ET only provides 0.2 BLEU value promotion compared to large transformer, and a bit more obvious improvement on small transformer with BLEU value 0.7, which are minor for MT task.

The experiment cannot be reproduced due to huge computation resource requirements. Thus using traditional algorithm including evolution algorithm as well as large models in NAS is not an ideal direction.



2. Continual and Multi-task Search

Pasunuru, Ramakanth, and Mohit Bansal. "Continual and Multi-Task Architecture Search." Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics. 2019.

This paper utilizes **ENAS** (Efficient Neural Architecture Search) with some modifications in sequential or combined multi-task tasks to **enhance the generalization** as well as performance of obtained model architectures.

ENAS: Using a RNN as a controller to determine the network structure. Two steps:


- 1) controller sampler a architecture and optimize its parameters.
- 2) controller sampler a architecture and use its validation performance as the loss to optimize the parameters of itself.



Continual architecture search (CAS)

Given several datasets sequentially

- 1) The model on the first dataset d_1 trained using ENAS and obtaining parameters $\theta_{1,k}$ with sparse constraint $\sum_{i=1}^m |(\|\theta_{1,k}[i, :]\|_2)|_1$ and corresponding architecture dag1
- 2) In next dataset d_2 run ENAS but with parameters initialized from $\theta_{1,k}$, obtaining architecture dag2 and parameters $\theta_{2,k}$ with extra loss item $L_p(\theta_{2,k}) = \|\theta_{1,k}^T \cdot \psi_{2,k}\|_2^2$, where $\psi_{2,k}$ is current parameter change compared to $\theta_{1,k}$
- 3) Continue 2) for following datasets, using the final parameters but corresponding architecture in evaluating




Multi-task architecture search (MAS)

Given several datasets at the same time.

All datasets will use the shared model, but the loss for training the controller will become the joint loss for current model on all datasets $r_c = \frac{1}{n} \sum_{i=1}^n r_i$

Such obtained architecture can obtain a higher generalization on all datasets.



Experiments

Both CAS and MAS are tested on text classification tasks (QNLI, RTE, WNLI) and video captioning tasks (MSR-VTT, MSVD, DiDeMo)

The generalization performance indeed shows promotion due to more data is involved in the training.

Performance on RTE by raw LSTM, ENAS on each dataset and MAS

| Cell Structure | Performance on RTE |
|-----------------|--------------------|
| LSTM cell | 52.3 |
| QNLI cell | 52.4 |
| WNLI cell | 52.2 |
| RTE cell | 52.9 |
| Multi-Task cell | 53.9 |

Performance on DiDeMo by raw LSTM, ENAS on each dataset and MAS

| Cell Structure | Performance on DiDeMo | | | |
|-----------------|-----------------------|------|-----|------|
| | M | C | B | R |
| LSTM cell | 12.7 | 26.7 | 7.6 | 30.6 |
| MSR-VTT cell | 12.9 | 25.7 | 7.4 | 30.3 |
| MSVD cell | 12.1 | 25.2 | 7.9 | 30.6 |
| DiDeMo cell | 13.1 | 27.1 | 7.9 | 30.9 |
| Multi-Task cell | 13.4 | 27.5 | 8.1 | 30.8 |

Performance on video captioning by CAS compared to baselines

| Models | MSR-VTT | | | | | MSVD | | | | |
|---------------------------------------|---------|------|------|------|------|------|------|------|------|------|
| | C | B | R | M | AVG | C | B | R | M | AVG |
| Baseline (Pasunuru and Bansal, 2017b) | 48.2 | 40.8 | 60.7 | 28.1 | 44.5 | 85.8 | 52.5 | 71.2 | 35.0 | 61.1 |
| ENAS | 48.9 | 41.3 | 61.2 | 28.1 | 44.9 | 87.2 | 52.9 | 71.7 | 35.2 | 61.8 |
| CAS Step-1 (MSR-VTT training) | 48.9 | 41.1 | 60.5 | 27.5 | 44.5 | N/A | N/A | N/A | N/A | N/A |
| CAS Step-2 (MSVD training) | 48.4 | 40.1 | 59.9 | 27.1 | 43.9 | 88.1 | 52.4 | 71.3 | 35.1 | 61.7 |

Performance on text classification by CAS compared to baselines

| Models | QNLI | RTE | WNLI |
|----------------------------|------|------|------|
| PREVIOUS WORK | | | |
| BiLSTM+ELMo (2018) | 69.4 | 50.1 | 65.1 |
| BiLSTM+ELMo+Attn (2018) | 61.1 | 50.3 | 65.1 |
| BASELINES | | | |
| Baseline (with ELMo) | 73.2 | 52.3 | 65.1 |
| ENAS (Architecture Search) | 74.5 | 52.9 | 65.1 |
| CAS RESULTS | | | |
| CAS Step-1 (QNLI training) | 73.8 | N/A | N/A |
| CAS Step-2 (RTE training) | 73.6 | 54.1 | N/A |
| CAS Step-3 (WNLI training) | 73.3 | 54.0 | 64.4 |

3. Using DARTS in LM and NER

Jiang, Yufan, et al. "Improved differentiable architecture search for language modeling and named entity recognition." Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). 2019.


This paper tries to improve the performance of searched architecture by **modifying the raw DARTS** method.

Raw DARTS: softmax weight is calculated independently on the edge node(cell) to node(cell).

$$\alpha_k^{i,j} = \frac{\exp(w_k^{i,j})}{\sum_{k'} \exp(w_{k'}^{i,j})}$$

Modified DARTS: the weight of all edges imported to a node will be calculated together

$$\alpha_k^{i,j} = \frac{\exp(w_k^{i,j})}{\sum_{j < i} \sum_{k'} \exp(w_{k'}^{i,j})}$$



Experiment

Such approach is substantially a additional pruning compared to raw one.


It is tested on PTB LM task and CoNLL-2003 NER task, showing a very slight promotion on performance and search cost compared to DARTS.

CoNLL-2003 NER

| Model | F1 |
|--|-------|
| <i>best published</i> | |
| BiLSTM-CRF (Lample et al., 2016) | 90.94 |
| BiLSTM-CRF+ELMo (Peters et al., 2018) | 92.22 |
| BERT Base (Devlin et al., 2018) | 92.40 |
| BERT Large (Devlin et al., 2018) | 92.80 |
| BiLSTM-CRF+PCE (Akbik et al., 2019) | 93.18 |
| Random RNNs w/o pre-trained LM | 90.64 |
| DARTS w/o pre-trained LM | 91.05 |
| I-DARTS ($n = 2$) w/o pre-trained LM | 90.96 |
| I-DARTS ($n = 1$) w/o pre-trained LM | 91.23 |
| Random RNNs | 92.89 |
| DARTS | 93.13 |
| I-DARTS ($n = 2$) | 93.14 |
| I-DARTS ($n = 1$) | 93.47 |

PTB

| Architecture | Perplexity | | Search Cost (GPU days) |
|---------------------|------------|------|------------------------|
| | val | test | |
| V-RHN | 67.9 | 65.4 | - |
| LSTM | 60.7 | 58.8 | - |
| LSTM + SC | 60.9 | 58.3 | - |
| LSTM + SE | 58.1 | 56.0 | - |
| ENAS | 60.8 | 58.6 | 0.50 |
| DARTS | 58.3 | 56.1 | 0.25 |
| Random RNNs | 63.7 | 61.2 | - |
| I-DARTS ($n = 1$) | 58.0 | 56.0 | 0.17 |
| I-DARTS ($n = 2$) | - | - | - |




4. Further extend DARTS on LM and NER

Li, Yingqiao, et al. "Learning Architectures from an Extended Search Space for Language Modeling." Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics. 2020.

This paper is an extend of previous paper, who uses both intra-cell level DARTS (the same as original DARTS) and **inter-cell level DARTS** (new parts, substantially adding attention to RNN) on LM and NER tasks.

For a RNN, inter-cell learns the way how current cell connecting with previous cells and the input vectors. While intra-cell learns the intra architecture of a cell.



Combine inter-cell and intra-cell search

It splits RNN into 3 functions, $f(\cdot)$ that generates \hat{h}_{t-1} , $g(\cdot)$ that generates \hat{x}_t and $\pi(\cdot)$ takes the output from former two functions and generate h_t . Since each function has two input vectors, DAGs can be created on them separately and the final output is the element-wise product of the last node from them $F(\alpha; \beta) = s^\alpha \odot s^\beta$

The original claimed two input sources for each function are

| Function | α | β |
|--------------|--------------------------------|---------------|
| $\pi(\cdot)$ | $\{\hat{h}_{t-1}, \hat{x}_t\}$ | 1 |
| $f(\cdot)$ | $h_{[0,t-1]}$ | $x_{[1,t-1]}$ |
| $g(\cdot)$ | $x_{[1,t]}$ | $h_{[0,t-1]}$ |

But in the real implementation, **they are simplified**(???) as

$$f(h_{[0,t-1]}; x_{[1,t-1]}) = f'(h_{t-1}; x_{[t-m,t-1]})$$

$$g(x_{[1,t]}; h_{[0,t-1]}) = g'(x_t; h_{[t-m,t-1]})$$


Only one DAG is remained in each function so the function F is totally unused?.

In fact it is just a refined version of DARTS with two intermediate state \hat{h}_{t-1} and \hat{x}_t , more previous state rather than last step are considered, just like RNN with attention.

Experiments

It is also tested on LM tasks (PTB and WikiText-103) and NER tasks (CoNLL-2003, WNUT-2017, CoNLL-2000, same architecture transferred from WikiText-103). There is no doubt that this method is obviously better than DARTS (it is substantially RNN with attention compared to raw RNN).

| Dataset | Method | Search Space | | Params | Perplexity | | Search Cost (GPU days) |
|---------|--------------------------------------|--------------|------------|--------|-------------|-------------|---------------------------|
| | | intra-cell | inter-cell | | valid | test | |
| PTB | AWD-LSTM (Merity et al., 2018c) | - | - | 24M | 61.2 | 58.8 | - |
| | Transformer-XL (Dai et al., 2019) | - | - | 24M | 56.7 | 54.5 | - |
| | Mogriifier LSTM (Melis et al., 2019) | - | - | 23M | 51.4 | 50.1 | - |
| | ENAS (Pham et al., 2018) | ✓ | - | 24M | 60.8 | 58.6 | 0.50 |
| | RS (Li and Talwalkar, 2019) | ✓ | - | 23M | 57.8 | 55.5 | 2 |
| | DARTS [†] | ✓ | - | 23M | 55.2 | 53.0 | 0.25 |
| | ESS | - | ✓ | 23M | 54.1 | 52.3 | 0.5 |
| | ESS | ✓ | ✓ | 23M | 47.9 | 45.6 | 0.5 |
| WT-103 | QRNN (Merity et al., 2018a) | - | - | 151M | 32.0 | 33.0 | - |
| | Hebbian + Cache (Rae et al., 2018) | - | - | - | 29.9 | 29.7 | - |
| | Transformer-XL (Dai et al., 2019) | - | - | 151M | 23.1 | 24.0 | - |
| | DARTS [†] | ✓ | - | 151M | 31.4 | 31.6 | 1 |
| | ESS | ✓ | ✓ | 156M | 28.8 | 29.2 | 1.5 |



5. Sandwich architecture for Transformer

Press, Ofir, Noah A. Smith, and Omer Levy. "Improving Transformer Models by Reordering their Sublayers." Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics. 2020.

This paper split a transformer layer into self-attention sublayer **s** and feedforward sublayer **f** and a raw transformer can be represented by

s f s f s f s f s f s f s f s f s f s f s f s f

They reorder these sublayers randomly to form a new transformer, trying to promote its performance. And based on their analysis, they proposes a **sandwich transformer** in which multiple redundant **s** are stacked in the lower layers while multiple redundant **f** are stacked in the higher layers.

s s s s s s s f s f s f s f s f s f s f f f f f f f

This paper can be regarded as a **simplified cell-level NAS** in which there is only one input edge and one output edge in the DAG for each cell.

Random search























































































































































































































































































































































































































































































s and **f** can be defined as the corresponding layer and residual connection after it.

$$\mathbf{X}_1 = \text{self-attention}(\mathbf{X}_0) + \mathbf{X}_0$$

$$\mathbf{X}_2 = \text{feedforward}(\mathbf{X}_1) + \mathbf{X}_1$$

Taking a 16-layer 16-head transformer with $d=1024$ as the baseline, each **s** contains $4d^2$ parameters and each contains $8d^2$ parameters (omitting bias).

First 20 unbalance transformers with 16 **s** and 16 **f** randomly ordered to test their PPL on WikiText-103, with raw transformer bold. It can be found most random architectures are worse than the raw one.

| Model | PPL |
|---|--------------|
|                                        | 20.74 |
|                                        | 20.64 |
|                                        | 20.33 |
|                                        | 20.27 |
|                                        | 19.98 |
|                                        | 19.92 |
|                                        | 19.69 |
|                                        | 19.54 |
|                                        | 19.13 |
|                                        | 19.08 |
|                                        | 18.90 |
|                                        | 18.83 |
|    | |


Random search

Then it randomly samples 20 architectures with the equivalent parameter numbers as the raw transformer but different layer numbers (may contains different numbers of **s** and **f**), the model depth ranges from 24 layer (all **f**) to 48 layers (all **s**), also found general worse performance than the raw one.

| Model | PPL |
|---|-------|
| s f f f s s f s f s f s s f f f s f s f s f f f f f f | 22.80 |
| s f f s s f s s s s s s s s s s s s s f s s s s f s f s s s f s s s f s | 21.02 |
| s s s s s s f f s f f f f s s f f f f s s s f s f s s s s s s s | 20.98 |
| f f f f f f f f s f s s f s f f s s s s f s f s s s f | 20.75 |
| f s s f s s s f f f f f s s f s s s f s f f s s s s f s f s s | 20.43 |
| s f f s f f f f f s f s f s s f s s s f s f s f s s f s s f s | 20.28 |
| s f f s s f s f f f s f s f s s s f f f f f s s s s f f | 20.02 |
| f s f f s f s s f f f s f s f f f s f f f s s f f f s s s | 19.93 |
| s f f s f f s s f f s f s f f s s f s s s s f s s s f f f s s s | 19.85 |
| s s f f f f f f f s s f f f s s f s s f f s f s f s f f s f | 19.82 |
| s f s f s f f f s f f f s s f s f f f s f s s f s f s f s s | 19.77 |
| s f s f f s s s f f s f f s s s f s s f f f f f s s s s f s s s f | 19.55 |
| s f f s f s s f f f s f f s f s s s s f s f s f f f f s f s s s | 19.49 |
| s f f f f s f f s s s s f s s s f s s f f s s s f s s s s f s f s | 19.47 |
| f s s s f f s s s s s s f s f s f s f f s f f f f s s f s f s s s | 19.25 |
| s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f | 19.13 |
| f s s s s s s f s f s f s f f f s f s s s f s s f f s s s s f s f f | 18.86 |
| s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f | 18.83 |
| s s f s f s s s f s s s s f f s f s f s s s f s s f s s s s s s s f | 18.62 |
| s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f | 18.54 |
| s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f | 18.49 |
| s s s f s f s f s s f s s s f f s f f f f f s s s f s f f f | 18.34 |
| s s s f s f s f f s s s f s f f f f f s f s f f f s s s f f | 18.31 |
| s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f s f | 18.25 |
| s s s s s s f s s s f f f s f s f f f f f f f f f s f | 18.12 |

Sandwich Transformer

However, they find that better models usually have more **s** at first and more **f** at the last of the model according to their analysis



Therefore they propose sandwich transformer, with first k layers as **s**, last k layers as **f** and $n-k$ **sf** in the middle, which can be represented as $\mathbf{s}^k (\mathbf{sf})^{n-k} \mathbf{f}^k$

$n=16$, k ranges from 0 to 15, the best k is determined by the best performance on a specific task acrossing all enumerations.

Experiments


The sandwich model is tested on LM tasks (WikiText-103, Toronto Book Corpus, performance is measured by PPL), and character-level LM (text8 and enwik8) which shows slight promotion compared to transformer baselines.

Character-level LM

| Model | text8 (BPC) | enwik8 (BPC) |
|---|---------------------|---------------------|
| Transformer-XL (Dai et al., 2019) | 1.08 | 0.99 |
| Adaptive Span (Sukhbaatar et al., 2019) | 1.07 | 0.98 |
| Compressive (Rae et al., 2020) | — | 0.97 |
| Baseline (Adaptive Span; 5 Runs) | 1.0802 ± 0.0103 | 0.9752 ± 0.0008 |
| Sandwich ₃ ²⁴ | 1.076 | — |
| Sandwich ₅ ²⁴ | — | 0.968 |

WikiText-103

| Model | Test |
|-------------------------------------|------------------|
| Baseline (Baevski and Auli, 2019) | 18.70 |
| Transformer XL (Dai et al., 2019) | 18.30 |
| kNN-LM (Khandelwal et al., 2019) | 15.79 |
| Baseline (5 Runs) | 18.63 ± 0.26 |
| Sandwich ₆ ¹⁶ | 17.96 |



Book Corpus

| Model | PPL |
|-------------------------------------|------------------|
| Baseline (5 runs) | 11.89 ± 0.35 |
| kNN-LM (Khandelwal et al., 2019) | 10.89 |
| Sandwich ₇ ¹⁶ | 10.83 |

Experiments

It is also tested on MT tasks (WMT2014 En-de) using encoder-decoder architecture with additional cross-attention sublayer **c** involved in decoder.

$$\mathbf{Y}_2 = \text{cross-attention}(\mathbf{Y}_1, \mathbf{X}) + \mathbf{Y}_1$$

The concatenation of self-attention and cross-attention **sc** is used to replace **s** in the original sandwich. Using 6 layers in both encoder and decoder, with k varies from 0 to 5 with sandwich applied to encoder or decoder, it only achieves very slight promotion in BLEU under specific configurations.

| Sandwich Coefficient | Encoder Sandwich | Decoder Sandwich |
|-----------------------------|-------------------------|-------------------------|
| 0 (Baseline) | 28.74 \pm 0.15 | |
| 1 | 28.71 | 28.64 |
| 2 | 28.71 | 28.56 |
| 3 | 28.81 | 28.67 |
| 4 | 28.48 | 28.66 |
| 5 | 28.45 | 28.76 |

Conclusion

- NAS in traditional NLP tasks usually cannot obtain as significant promotion as CV, as most popular models (e.g. transformers, pre-trained models) are already carefully designed.
- Gradient-based optimization for NAS is becoming a main direction instead of Evolution Algorithm or Reinforcement Learning due to the much less computing resource requirement (considering the 1M GPU hours in Evolved Transformer)
- Trying to simplifying or redesign the NAS problem for current NLP models is a possible direction (e.g. sandwich transformer), but I don't think fine-grained NAS on NLP models is a good idea.
- Maybe NAS can be applied to some special setting of NLP tasks, e.g. few-shot learning, UDA, generalization across different datasets.

Thank you!