(1) Task 1

```
hsh@hsh-virtual-machine:~$ touch c1.c
hsh@hsh-virtual-machine:~$ vim c1.c
```

```
hsh@hsh-virtual-machine:~$ vim Makefile
hsh@hsh-virtual-machine:~$ make
gcc      -c      c1.c
gcc      -o      hello1  c1.o
hsh@hsh-virtual-machine:~$ ./hello1 example.txt
open source example.txt failed
hsh@hsh-virtual-machine:~$ vim example.txt
hsh@hsh-virtual-machine:~$ ./hello1 example.txt
hello world!


hsh@hsh-virtual-machine:~$ make clean
rm       -rf     *.o
```

(2) Task 2

```
hsh@hsh-virtual-machine:~/桌面$ vim Makefile
hsh@hsh-virtual-machine:~/桌面$ vim c2.c
hsh@hsh-virtual-machine:~/桌面$ make
gcc -c c2.c
gcc -o hello2 c2.o
```

```
hsh@hsh-virtual-machine:~/桌面$ ./hello2
..
fifo_page_replacement.sh
新建文件夹
page_table2.txt
hello2
c2.o
4.1.sh
Makefile
lru_page_replacement.sh
4.3.sh
4.5.sh
4.2.sh
page_table.txt
4.4.sh
address_translation.sh
.
c2.c
hsh@hsh-virtual-machine:~/桌面$ make clean
rm -rf *.o hello2
```

(3) Task 3

```
hsh@hsh-virtual-machine:~/桌面$ vim c3.c
hsh@hsh-virtual-machine:~/桌面$ vim Makefile
hsh@hsh-virtual-machine:~/桌面$ make
Makefile:2: *** 缺失分隔符。 停止。
hsh@hsh-virtual-machine:~/桌面$ vim Makefile
hsh@hsh-virtual-machine:~/桌面$ make
gcc -c c3.c
gcc -o hello3 c3.o
hsh@hsh-virtual-machine:~/桌面$ ./hello3
/home/hsh/桌面
success
/home
hsh@hsh-virtual-machine:~/桌面$ make clean
rm -rf *.o
hsh@hsh-virtual-machine:~/桌面$
```