Regular expressions

Patterns for searching, validating and replacing text

Yarrowpine Developer Cheatsheets

CHARACTERS

`.`	any character except a line break
`\d \w \s`	digit, word character, whitespace
`\D \W \S`	the opposite of each of the above
`[abc] [a-z] [^0-9]`	one of a set, a range, anything but
`\. \* \?`	escape a special character to match it

ANCHORS

`^ $`	start and end of the line or string
`\b`	word boundary: \bcat\b skips "concat"
`\A \z`	absolute start and end (most engines)

QUANTIFIERS

`a* a+ a?`	zero or more, one or more, optional
`a{3} a{2,} a{2,4}`	exactly 3, at least 2, between 2 and 4
`a+? a*?`	lazy: match as little as possible

GROUPS

`(abc)`	capture group, reused as \1 or $1
`(?:abc)`	group without capturing
`(?<year>\d{4})`	named group
`cat|dog`	either alternative

LOOKAROUND

`x(?=y)`	x only if followed by y
`x(?!y)`	x only if not followed by y
`(?<=y)x`	x only if preceded by y
`(?<!y)x`	x only if not preceded by y

FLAGS

`i`	ignore case
`m`	^ and $ match at every line
`s`	. also matches line breaks
`g`	find all matches, not just the first
`x`	allow spaces and comments in the pattern

RECIPES

`^\d{4}-\d{2}-\d{2}$`	date shaped like 2026-11-04
`^\S+@\S+\.\S+$`	rough email shape check
`^#?[0-9a-fA-F]{6}$`	six-digit hex colour
`\b(\w+)\s+\1\b`	a word typed twice in a row
`^\s+|\s+$`	leading or trailing spaces (to trim)
`(?<=order-)\d+`	the number in "order-1042"

GOOD HABITS

- Engines differ: test patterns in the language you will use.
- Shape checks are not full validation; confirm emails by sending a link.
- Avoid nested quantifiers like (a+)+ on user input; they can be very slow.

© 2026 Yarrowpine Studio · CC BY 4.0 · creativecommons.org/licenses/by/4.0 · v1.0.1

HTTP and REST APIs

Methods, status codes and headers for designing and debugging web APIs

Yarrowpine Developer Cheatsheets

METHODS

`GET /orders`	read; safe and repeatable
`POST /orders`	create; not repeatable by default
`PUT /orders/42`	replace the whole resource
`PATCH /orders/42`	change some fields
`DELETE /orders/42`	remove; repeating it is harmless

SUCCESS AND REDIRECTS

`200 OK`	request worked, body has the result
`201 Created`	new resource; Location header points to it
`204 No Content`	worked, nothing to return
`301 / 308`	moved for good (308 keeps the method)
`302 / 307`	moved for now (307 keeps the method)
`304 Not Modified`	cached copy is still current

CLIENT ERRORS (4XX)

`400 Bad Request`	malformed or invalid input
`401 Unauthorized`	missing or bad credentials
`403 Forbidden`	known caller, not allowed
`404 Not Found`	no such resource
`409 Conflict`	clashes with current state
`422 Unprocessable Content`	well-formed but fails validation
`429 Too Many Requests`	slow down; see Retry-After

SERVER ERRORS (5XX)

`500 Internal Server Error`	unexpected failure on the server
`502 Bad Gateway`	an upstream server answered badly
`503 Service Unavailable`	overloaded or in maintenance
`504 Gateway Timeout`	an upstream server took too long

USEFUL HEADERS

`Content-Type: application/json`	format of the body sent
`Accept: application/json`	format the client wants back
`Authorization: Bearer <token>`	credentials for the request
`Cache-Control: no-store`	do not keep a copy
`ETag / If-None-Match`	cheap check whether data changed
`Idempotency-Key: <uuid>`	make a retried POST safe (if supported)

REST DESIGN HABITS

`/customers/7/orders`	plural nouns, nesting for ownership
`?status=paid&limit=20`	filter and page with query params
`?sort=-created_at`	sort; a leading minus means descending
`{"error": {"code": "...", "message": "..."}}`	one consistent error shape
`/v1/...`	version the API before the first breaking change

GOOD HABITS

- Use HTTPS everywhere; never put secrets in URLs.
- Return the most specific status code that is true.
- Document every endpoint's success and error responses.

© 2026 Yarrowpine Studio · CC BY 4.0 · creativecommons.org/licenses/by/4.0 · v1.0.1