## SyDEVS Library Framework Overview

Autodesk Research April 2018

#### Classic Theory (1970s)



Main page Contents Featured content Current events Random article Donate to Wikipedia Wikipedia store

Interaction

Help

About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wikidata item Cite this page

Not logged in Talk Contributions Create account Log in

Article Talk

Read Edit View history

Search Wikipedia

Q

#### **DEVS**

From Wikipedia, the free encyclopedia

DEVS abbreviating Discrete Event System Specification is a modular and hierarchical formalism for modeling and analyzing general systems

#### Atomic DEVS [edit]


An atomic DEVS model is defined as a 7-tuple


$$M = \langle X, Y, S, ta, \delta_{ext}, \delta_{int}, \lambda \rangle$$


where


- X is the set of input events;
- Y is the set of output events;
- S is the set of sequential states (or also called the set of partial states);
- $s_0 \in S$  is the initial state:
- $ta: S \to \mathbb{T}^{\infty}$  is the time advance function which is used to determine the lifespan of a state;
- $\delta_{ext}: Q \times X \to S$  is the external transition function which defines how an input event changes a state of the system, where  $Q = \{(s, t_e) | s \in S, t_e \in (\mathbb{T} \cap [0, ta(s)])\}$  is the set of total states, and  $t_e$  is the elapsed time since the last event,
- ullet  $\delta_{int}:S o S$  is the internal transition function which defines how a state of the system changes internally (when the elapsed time reaches to the lifetime of the state);
- $\lambda: S \to Y^{\phi}$  is the output function where  $Y^{\phi} = Y \cup \{\phi\}$  and  $\phi \notin Y$  is a silent event or an unobserved event. This function defines how a state of the system generates an output event (when the elapsed time reaches to the lifetime of the state);




























https://autodeskresearch.com/publications/designingdevs





#### **DEVS**

From Wikipedia, the free encyclopedia

DEVS abbreviating Discrete Event System Specification is a modular and hierarchical formalism for m

...


#### Atomic DEVS [edit]

An atomic DEVS model is defined as a 7-tuple

$$M = \langle X, Y, S, ta, \delta_{ext}, \delta_{int}, \lambda \rangle$$

where

- X is the set of input events;
- Y is the set of output events;
- S is the set of sequential states (or also called the set of partial states);
- $s_0 \in S$  is the initial state;
- $ta:S \to \mathbb{T}^\infty$  is the time advance function which is used to determine the lifespan of a state;
- $\delta_{ext}: Q \times X \to S$  is the external transition function which defines how an input event change  $Q = \{(s,t_e) | s \in S, t_e \in (\mathbb{T} \cap [0,ta(s)])\}$  is the set of total states, and  $t_e$  is the elapsed the
- δ<sub>int</sub>: S → S is the internal transition function which defines how a state of the system change time reaches to the lifetime of the state);
- $\lambda: S \to Y^{\phi}$  is the output function where  $Y^{\phi} = Y \cup \{\phi\}$  and  $\phi \notin Y$  is a silent event or an  $\iota$  defines how a state of the system generates an output event (when the elapsed time reaches  $\mathfrak{t}$



#### **DEVS**

From Wikipedia, the free encyclopedia

DEVS abbreviating Discrete Event System Specification is a modular and hierarchical formalism for m

...


#### Atomic DEVS [edit]


An atomic DEVS model is defined as a 7-tuple

$$M = \langle X, Y, S, ta, \delta_{ext}, \delta_{int}, \lambda \rangle$$

where

- X is the set of input events;
- Y is the set of output events;
- S is the set of sequential states (or also called the set of partial states);
- s<sub>0</sub> ∈ S is the initial state;
- $ta: S \to \mathbb{T}^{\infty}$  is the time advance function which is used to determine the lifespan of a state;
- $\delta_{ext}: Q \times X \to S$  is the external transition function which defines how an input event change  $Q = \{(s,t_e)|s \in S, t_e \in (\mathbb{T} \cap [0,ta(s)])\}$  is the set of total states, and  $t_e$  is the elapsed the
- δ<sub>int</sub>: S → S is the internal transition function which defines how a state of the system change time reaches to the lifetime of the state);
- $\lambda: S \to Y^{\phi}$  is the output function where  $Y^{\phi} = Y \cup \{\phi\}$  and  $\phi \notin Y$  is a silent event or an  $\iota$  defines how a state of the system generates an output event (when the elapsed time reaches to







## Example – Function Nodes




#### Example – Function Nodes







## Example – Simulation Nodes




#### Example – Simulation Nodes




## Example – Atomic Nodes




#### Example – Composite Nodes




## Example – Flow Links




## Example – Message Links




## Example – Inward Links





## Example – Inner Links



## Example – Outward Links







**}**;

#### Node class thermodynamics node : public atomic node public: port<flow, input, thermodynamic\_temperature> initial\_temperature\_input; port<flow, input, std::pair<array2d<int64>, distance>> building layout input; port<flow, input, float64> wall resistance input; port<message, input, thermodynamic temperature> outdoor temperature input; port<message, output, array2d<thermodynamic temperature>> temperature field output; protected: // building layout array2d<int64> L; // number of cells in the x dimension int64 nx; // number of cells in the y dimension int64 ny; float64 wall R; // wall resistance array2d<thermodynamic temperature> TF; // temperature field duration step dt; // time step duration planned dt; // planned duration

virtual duration initialization event();

virtual duration unplanned\_event(duration elapsed\_dt);
virtual duration planned\_event(duration elapsed\_dt);
virtual void finalization event(duration elapsed dt);

## Types of Nodes

```
class thermodynamics_node : public atomic node
public:
    port<flow, input, thermodynamic temperature> initial temperature input;
    port<flow, input, std::pair<array2d<int64>, distance>> building layout input;
    port<flow, input, float64> wall resistance input;
    port<message, input, thermodynamic temperature> outdoor temperature input;
    port<message, output, array2d<thermodynamic temperature>> temperature field output;
protected:
                                            // building layout
    array2d<int64> L;
                                            // number of cells in the x dimension
    int64 nx;
                                            // number of cells in the y dimension
    int64 ny;
    float64 wall R;
                                            // wall resistance
    array2d<thermodynamic temperature> TF; // temperature field
    duration step dt;
                                            // time step
    duration planned dt;
                                            // planned duration
    virtual duration initialization event();
    virtual duration unplanned event(duration elapsed dt);
    virtual duration planned event(duration elapsed dt);
    virtual void finalization event(duration elapsed dt);
};
```

```
class system node
                                  Types of Nodes
class atomic node: public system node
   virtual duration initialization_event() = 0;
   virtual duration unplanned_event(duration elapsed_dt) = 0;
   virtual duration planned_event(duration elapsed_dt) = 0;
   virtual void finalization event(duration elapsed dt) = 0;
};
class composite node : public system node
   void inward_link(port<dmode, input, T>& src_port, port<dmode, input, T>& dst_port);
   void inner_link(port<dmode, output, T>& src_port, port<dmode, input, T>& dst_port);
   void outward_link(port<dmode, output, T>& src_port, port<dmode, output, T>& dst_port);
class function node : public system node
   virtual void flow event() = 0;
                                                                // Also...
                                                                class collection node ...
};
```

```
class system node
class atomic node: public system node
   virtual duration initialization event() = 0;
    virtual duration unplanned_event(duration elapsed_dt) = 0;
    virtual duration planned_event(duration elapsed_dt) = 0;
    virtual void finalization event(duration elapsed dt) = 0;
};
                                                       Event Handlers
class composite node : public system node
    void inward link(port<dmode, input, T>& src port, port<dmode, input, T>& dst port);
    void inner_link(port<dmode, output, T>& src_port, port<dmode, input, T>& dst_port);
    void outward_link(port<dmode, output, T>& src_port, port<dmode, output, T>& dst_port);
class function node : public system node
   virtual void flow event() = 0;
                                                                // Also...
                                                                class collection node ...
};
```

#### Visual Interface

#### **DEVS**

From Wikipedia, the free encyclopedia

DEVS abbreviating Discrete Event System Specification is a modular and hierarchical formalism for m

...


#### Atomic DEVS [edit]

An atomic DEVS model is defined as a 7-tuple

$$M = \langle X, Y, S, ta, \delta_{ext}, \delta_{int}, \lambda \rangle$$


where

- X is the set of input events;
- Y is the set of output events;
- S is the set of sequential states (or also called the set of partial states);
- $s_0 \in S$  is the initial state;
- $ta:S \to \mathbb{T}^\infty$  is the time advance function which is used to determine the lifespan of a state;
- $\delta_{ext}: Q \times X \to S$  is the external transition function which defines how an input event change  $Q = \{(s,t_e)|s \in S, t_e \in (\mathbb{T} \cap [0,ta(s)])\}$  is the set of total states, and  $t_e$  is the elapsed the
- δ<sub>int</sub>: S → S is the internal transition function which defines how a state of the system change time reaches to the lifetime of the state);
- $\lambda: S \to Y^{\phi}$  is the output function where  $Y^{\phi} = Y \cup \{\phi\}$  and  $\phi \notin Y$  is a silent event or an  $\iota$  defines how a state of the system generates an output event (when the elapsed time reaches t



#### **Event Handlers**

#### Example



#### **Ports**

```
class thermodynamics_node : public atomic_node
public:
    port<flow, input, thermodynamic temperature> initial temperature_input;
    port(<flow, input, std::pair<array2d<int64>, distance>> building layout input;
    port<flow, input float64> wall_resistance_input;
    port<message, input) thermodynamic temperature> outdoor temperature input;
    port<message, output) array2d<thermodynamic temperature>> temperature field output;
protected:
                                            // building layout
    array2d<int64> L;
                                            // number of cells in the x dimension
    int64 nx;
                                            // number of cells in the y dimension
    int64 ny;
    float64 wall R;
                                            // wall resistance
    array2d<thermodynamic temperature> TF; // temperature field
    duration step dt;
                                            // time step
    duration planned dt;
                                            // planned duration
    virtual duration initialization event();
    virtual duration unplanned event(duration elapsed dt);
    virtual duration planned event(duration elapsed dt);
    virtual void finalization event(duration elapsed dt);
};
```

Example

```
class thermodynamics node : public atomic node
                                                  Data types
public:
    port<flow, input; thermodynamic_temperature> initial_temperature_input;
    port<flow, input, std::pair<array2d<int64>, distance>> building_layout_input;
    port<flow, input, float64> wall resistance input;
    port<message, input, thermodynamic temperature> outdoor temperature input;
    port<message, output, array2d<thermodynamic temperature>> temperature field output;
protected:
                                           // building layout
    array2d<int64> L;
                                           // number of cells in the x dimension
    int64 nx;
                                           // number of cells in the y dimension
    int64 ny;
    float64 wall R;
                                           // wall resistance
    array2d<thermodynamic temperature> TF; // temperature field
    duration step dt;
                                           // time step
    duration planned dt;
                                           // planned duration
    virtual duration initialization event();
    virtual duration unplanned event(duration elapsed dt);
    virtual duration planned event(duration elapsed dt);
    virtual void finalization event(duration elapsed dt);
};
```

```
// Core Types
pointer // not sortable; encapsulates std::shared_ptr<void>
bool // sortable
                           Data types
int64 // sortable
float64 // sortable
std::string // sortable
quantity<U> // sortable; includes e.g. distance, duration, quantity<decltype( kg* m/ s/ s)>
arraynd<T, ndims> // valid if T is valid; not sortable
std::pair<T1, T2> // valid if T1, T2 are valid; sortable if T1, T2 are sortable
std::tuple<T> // valid if T is valid; sortable if T is sortable
std::tuple<T, Ts...> // valid if T, Ts... are valid; sortable if T, Ts... are sortable
std::vector<T> // valid if T is valid; sortable if T is sortable
// sortable if T is sortable
std::shared ptr<T> // not sortable
T default value<T>() // create a default value of core type T
tostring(const T&) // convert the value of core type T to a string
```

```
#include <my_cpp_libraries/my_CFD_solver.h>
class CFD node : public atomic node
public:
    port<message, output, array3d<float>> velocities;
protected:
    my CFD solver state CFD state;
    virtual duration initialization event()
        CFD_state = initialize_my_CFD_solver();
        return 5_s; // planned_dt
    virtual duration planned_event(duration elapsed_dt)
        advance_one_time_step_using_my_CFD_solver(CFD_state);
        velocities.send(CFD_state.get_velocities);
        return 5 s; // planned dt
```

```
#include <my_cpp_libraries/my_CFD_solver.h>
class CFD_node : public atomic_node
public:
    port<message, output, array3d<float>> velocities;
protected:
    my CFD solver state CFD state;
    virtual duration initialization event()
        CFD_state =(initialize_my_CFD_solver();)
        return 5_s; // planned dt
    virtual duration planned_event(duration elapsed_dt/
        advance_one_time_step_using_my_CFD_solver(CFD_state);
        velocities.send(CFD_state.get_velocities);
        return 5_s; // planned_dt
```

Possible to wrap existing simulation libraries (eg. CFD)

```
#include <my cpp libraries/my CFD solver.h>
class CFD node : public atomic node
public:
    port<message, output, array3d<float>> velocities;
protected:
    my CFD solver state CFD state;
    virtual duration initialization event()
        CFD state = initialize my CFD solver();
        return 5 s; // planned dt
    virtual duration planned event(duration elapsed dt)
        advance_one_time_step_using_my_CFD_solver(CFD_state);
        velocities.send(CFD_state.get_velocities);
        return 5 s; // planned dt
```

# The library includes multidimensional arrays


```
#include <my_cpp_libraries/my_CFD_solver.h>
class CFD_node : public atomic_node
public:
    port<message, output, array3d<float>> velocities;
protected:
    my CFD solver state CFD state;
    virtual duration initialization event()
        CFD_state = initialize mv CFD_solver();
        return 5_s; // planned_dt
    virtual duration planned_event(duration elapsed_dt)
        advance_one_time_step_using_my_CFD_solver(CFD_state);
        velocities.send(CFD state.get_velocities);
        return 5_s; // planned_dt
```

# Elapsed durations and planned durations are important concepts

```
#include <my cpp libraries/my CFD solver.h>
class CFD_node : public atomic_node
public:
    port<message, output, array3d<float>> velocities;
protected:
    my CFD solver state CFD state;
    virtual duration initialization event()
        CFD state = initialize my CFD solver();
        return 5_s; // planned_dt
    virtual duration planned_event(duration elapsed_dt)
        advance_one_time_step_using_my_CFD_solver(CFD_state);
        velocities.send(CFD_state.get_velocities);
        return 5_s; // planned_dt
};
```

SI units are represented explicitly and checked at compile-time


#### Review




#### Review – Function Nodes




#### Review – Function Nodes




#### Review – Function Nodes





#### Review







#### Review – Simulation Nodes






#### Review – Simulation Nodes













#### Review – Atomic Nodes







# Review – Composite Nodes







#### Review – Flow Links







## Review – Message Links







#### Review – Inward Links





#### Review – Inner Links





#### Review – Outward Links

