

RFC-218 Configurer

Draft

23 Pages

Abstract

10 point Arial Centered.

OSGi Configuration Admin is a slightly pedantic but highly effective flexible standardized model to configure applications. This RFC seeks a solution to carry configuration information in a bundle.



0 Document Information

0.1 License

DISTRIBUTION AND FEEDBACK LICENSE, Version 2.0

The OSGi Alliance hereby grants you a limited copyright license to copy and display this document (the "Distribution") in any medium without fee or royalty. This Distribution license is exclusively for the purpose of reviewing and providing feedback to the OSGi Alliance. You agree not to modify the Distribution in any way and further agree to not participate in any way in the making of derivative works thereof, other than as a necessary result of reviewing and providing feedback to the Distribution. You also agree to cause this notice, along with the accompanying consent, to be included on all copies (or portions thereof) of the Distribution. The OSGi Alliance also grants you a perpetual, non-exclusive, worldwide, fully paid-up, royalty free, limited license (without the right to sublicense) under any applicable copyrights, to create and/or distribute an implementation of the Distribution that: (i) fully implements the Distribution including all its required interfaces and functionality; (ii) does not modify, subset, superset or otherwise extend the OSGi Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the OSGi Name Space other than those required and authorized by the Distribution. An implementation that does not satisfy limitations (i)-(ii) is not considered an implementation of the Distribution, does not receive the benefits of this license, and must not be described as an implementation of the Distribution. "OSGi Name Space" shall mean the public class or interface declarations whose names begin with "org.osgi" or any recognized successors or replacements thereof. The OSGi Alliance expressly reserves all rights not granted pursuant to these limited copyright licenses including termination of the license at will at any time.

EXCEPT FOR THE LIMITED COPYRIGHT LICENSES GRANTED ABOVE, THE OSGI ALLIANCE DOES NOT GRANT, EITHER EXPRESSLY OR IMPLIEDLY, A LICENSE TO ANY INTELLECTUAL PROPERTY IT, OR ANY THIRD PARTIES, OWN OR CONTROL. Title to the copyright in the Distribution will at all times remain with the OSGI Alliance. The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted therein are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

THE DISTRIBUTION IS PROVIDED "AS IS," AND THE OSGI ALLIANCE (INCLUDING ANY THIRD PARTIES THAT HAVE CONTRIBUTED TO THE DISTRIBUTION) MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DISTRIBUTION ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

NEITHER THE OSGI ALLIANCE NOR ANY THIRD PARTY WILL BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THE DISTRIBUTION.

Implementation of certain elements of this Distribution may be subject to third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a member of the OSGi Alliance). The OSGi Alliance is not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

The Distribution is a draft. As a result, the final product may change substantially by the time of final publication, and you are cautioned against relying on the content of this Distribution. You are encouraged to update any implementation of the Distribution if and when such Distribution becomes a final specification.

The OSGi Alliance is willing to receive input, suggestions and other feedback ("Feedback") on the Distribution. By providing such Feedback to the OSGi Alliance, you grant to the OSGi Alliance and all its Members a non-exclusive, non-transferable,

Draft

April 22, 2016

worldwide, perpetual, irrevocable, royalty-free copyright license to copy, publish, license, modify, sublicense or otherwise distribute and exploit your Feedback for any purpose. Likewise, if incorporation of your Feedback would cause an implementation of the Distribution, including as it may be modified, amended, or published at any point in the future ("Future Specification"), to necessarily infringe a patent or patent application that you own or control, you hereby commit to grant to all implementers of such Distribution or Future Specification an irrevocable, worldwide, sublicenseable, royalty free license under such patent or patent application to make, have made, use, sell, offer for sale, import and export products or services that implement such Distribution or Future Specification. You warrant that (a) to the best of your knowledge you have the right to provide this Feedback, and if you are providing Feedback on behalf of a company, you have the rights to provide Feedback on behalf of your company; (b) the Feedback is not confidential to you and does not violate the copyright or trade secret interests of another; and (c) to the best of your knowledge, use of the Feedback would not cause an implementation of the Distribution or a Future Specification to necessarily infringe any third-party patent or patent application known to you. You also acknowledge that the OSGi Alliance is not required to incorporate your Feedback into any version of the Distribution or a Future Specification.

I HEREBY ACKNOWLEDGE AND AGREE TO THE TERMS AND CONDITIONS DELINEATED ABOVE.

0.2 Trademarks

OSGi™ is a trademark, registered trademark, or service mark of the OSGi Alliance in the US and other countries. Java is a trademark, registered trademark, or service mark of Oracle Corporation in the US and other countries. All other trademarks, registered trademarks, or service marks used in this document are the property of their respective owners and are hereby recognized.

0.3 Feedback

This document can be downloaded from the OSGi Alliance design repository at https://github.com/osgi/design The public can provide feedback about this document by opening a bug at https://www.osgi.org/bugzilla/.

0.4 Table of Contents

0 Document Information	2
0.1 License	
0.2 Trademarks	3
0.3 Feedback	
0.4 Table of Contents	
0.5 Terminology and Document Conventions	
0.6 Revision History	
1 Introduction	5
2 Application Domain	5
2.1 Coordination	6
2.2 Logical PIDs	
2.3 Delivery	
2.4 OSGi Application Model	
2.5 OSGi enRoute Configurer	
3 Problem Description	7
4 Requirements	8
4.1 General	
4.2 Configuration Admin	9
5 Technical Solution	9
5.1 Configuration Admin Enhancements	



5.1.1 PID Handling of Factory Configurations	9
5.1.2 Locking Configuration Records	10
5.1.3 Improving Configuration Updates	11
5.1.4 Capabilities	12
5.2 Configurations	12
5.2.1 osgi.implementation Capability	12
5.2.2 Configurations in a Bundle	12
5.2.3 Configuration File Format	13
5.2.4 Binaries	
5.2.5 Environments	15
5.2.6 Configuration Ranking5.2.7 Configurations from the Runtime Environment	16
5.2.7 Configurations from the Runtime Environment	
5.2.8 Overwrite policies	
5.3 Processing Bundles	17
5.3.1 Applying Configurations from a Bundle	
5.3.2 Coordinator Support	
5.4 Standalone Configurations	18
5.4.1 Configuration capabilities	
6 Data Transfer Objects	20
7 Javadoc	20
8 Considered Alternatives	21
8.1 Placeholders	
8.2 Merging Configurations	
0.2 Weighig Configurations	
9 Security Considerations	22
3 Security Considerations	
10 Document Support	20
10.1 Deferences	
10.1 References	22
10.2 Author's Address	22 22

0.5 Terminology and Document Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in 1.

Source code is shown in this typeface.

0.6 Revision History

The last named individual in this history is currently responsible for this document.

Revision	Date	Comments
Initial	DEC 04 2015	Initial Version
		Carsten Ziegeler, Adobe < <u>cziegele@adobe.com</u> >

April 22, 2016



Revision **Comments Date** DEC 17 2015 Update Updated based on EEG call Rewrote most parts Carsten Ziegeler, Adobe < cziegele@adobe.com > 0.2 January, 2016 David Bosschaert, updates from F2F meeting in Madrid FEB-02-2016 Updates from F2F meeting in Madrid, move to YAML 0.3 Carsten Ziegeler, Adobe < cziegele@adobe.com > 0.4 MAR-02-2016 Improved configuration update handling Carsten Ziegeler, Adobe < cziegele@adobe.com > 0.5 APR-22-2016 Updates from F2F meeting in Chicago Carsten Ziegeler, Adobe <cziegele@adobe.com>

1 Introduction

This RFC originates from the OSGi enRoute work. In this project, a number of services were identified, designed and implemented based on their needs for web based applications. This document analyzes the application domain and defines the problem that needs to be solved.

This RFC discusses the Configurer, an extender that allows the storage of configuration data in a bundle.

2 Application Domain

OSGi provides a standardized model to provide bundles with configurations. This is specified in the Configuration Admin specification. In this specification, A configuration is identified by a persistent identity (PID). A PID is a unique token, recommended to be conforming to the symbolic name syntax. A configuration consists of a set of properties, where a property consists of a string key and a corresponding value. The type of the value is limited to the primitive types and their wrappers, Strings, or Java Arrays/List/Vector of these.



Sometimes it is necessary to store binary large objects (BLOB) in configuration. For example, a keystore with certificates. Since configuration admin is not suitable for this, these BLOBs are often stored on the files system. The application developers then must manage the life cycles of these files.

Configurations can be grouped with a factory PID. Configurations with a factory PID are called *factory* configurations and without it they are called *singleton* configurations.

The original specification specified that the configurations were sent to a Managed Service for the singletons and Managed Service Factory services for the factory instances. However, over time *component models* became popular and a component can rely on configuration. For example, Declarative Services is tightly integrated with Configuration Admin. For these heavy users of configurations a *Configuration Listener* whiteboard service was added. Configuration update, delete, and bundle location change events are forwarded to this whiteboard service on a background thread.

2.1 Coordination

In OSGi, the *management agent* creates and deletes configurations through the Configuration Admin service. Appropriate Create/Read/Update/Delete (CRUD) methods for singletons and factories are available on this service. If the management agent performs a number of sequential updates then it can group these updates within a Coordination from the Coordinator service. Clients can then register a Synchronous Configuration Listener and delay the application of the properties until the Coordination has ended.

2.2 Logical PIDs

One popular management agent from the early days was File Install [3]. File install watched a directory and configurations stored in that directory were configured in the local Configuration Admin. This is straightforward for singletons since the file name of the configuration file can be used to calculate the PID. However, for factories, the PID for the instance is calculated by Configuration Admin and is not predictable. Therefore, File Install needed to manage the number of instances since the operations to create them were not idempotent. To prevent a restart from creating an every growing number of instances it was necessary to create a link between the instance and the file. Therefore, File Install created a logical (instance) PID based on the file name. If this instance was detected, File Install first looks in Configuration Admin if there is any instance that has this logical PID as value in a specially designated key. Only if no such instance was found, a new one was created. This made the operation idempotent.

2.3 Delivery

The Deployment Admin specification developed for OSGi Mobile provided the means to carry configuration information inside a JAR via the means of *resource processors*. The Auto Configuration specification defined how an Autoconf resource processor could get an XML file from a Deployment Package. Since the Deployment Package could not define the instance PID for a factory it used an alias in the XML file. When a configuration was found, the alias was looked up to see to what instance PID it was mapped to. If no mapping was found, a new instance was created. Since Deployment Packages had a well defined life cycle, they basically are like bundles, Deployment Admin could therefore also delete stale aliases.

2.4 OSGi Application Model


The Require-Capability model was designed to create applications from one or more *initial requirements*, generally identity requirements, to so called *root bundles*. From these initial requirements a *resolver*, generally with some human help, can then create a *deployable artifact*. For example an executable JAR which includes all dependencies including configuration, a subsystem specification, an Eclipse or subsystem features, etc.

April 22, 2016



2.5 OSGi enRoute Configurer

The enRoute project defined a *Configurer extender* [4].. Bundles can store configuration data in a "magic" resource at configuration/configuration.json. This is a JSON file containing an array of configurations. When a bundle is installed, the Configurer detects the magic resource and installs the corresponding configuration. It does not remove the configuration when the bundle is uninstalled. The Configurer uses logical PIDs to manage factories.



Before the JSON file is interpreted, the Configurer will first run it through a macro pre-processor, this is the bndlib [5]. macro preprocessor. The macro sequence is @ { . . . } to not clash with build time processing.

The Configurer also supports BLOBs. A special macro <code>@{resource:<resource>}</code> points to a resource in the bundle. The Configurer will then extract this resource to the file system and replace the macro with the actual file path. The Configurer stores this data by default in the bundle's file area.

Additionally, the Configurer also read a standard system property and interpreted the content as a JSON configuration file.

3 Problem Description

The trend in OSGi is to use the Require-Capability model to construct applications out of a set of initial requirements. This means there is no applicable container like Deployment Admin to contain configurations. However, enRout shows that it is actually quite easy to store configuration data in a bundle which can then be part of the resolve process. This configuration bundle can be a root bundle representing the application or a special configuration bundle. Having everything as bundles without artificial grouping will leverage the existing specifications for life cycle management instead of introducing a new layer since interacting life cycles are notoriously hard to make reliable and usually force one to redo the same functionality slightly different.


BLOBs are awkward to handle in configurations. If they are delivered in a bundle then the developer must extract it somewhere on the file system and set the configuration to point to that file.



4 Requirements

4.1 General

- G0010 A solution that makes it possible to store configurations, either singleton or factory, in a bundle that are installed in Configuration Admin when that bundle is installed.
- G0020 It must be possible to specify configurations in a system property
- G0030 Factory configurations must be idempotent.
- G0040 If the bundle that originated a configuration gets uninstalled then all its configurations must be deleted
- G0050 If a bundle with configurations is updated then configurations that are already on the system must not be updated.
- G0060 Developers must be able to indicate that a configuration must be forced updated, even if it already exists.
- G0065 G0040-G0060 imply the need for configurations to have an update policy. The update policy must define how it interacts with the lifecycle of the bundle containing the configuration.
- G0070 It must be possible to prevent the updating of a configuration by the runtime even the developer forced it.
- G0080 It must be possible to include BLOBs in the configuration that are stored in the bundle but extracted to the file system.
- G0085 BLOBs must always be updated on the file system to a different location than the previous version. This is too avoid open file lock issues on Windows file systems.
- G0090 It must be possible to load configuration from the host bundle as well as all its fragments
- G0100 If configurations are duplicated, the specification must define a proper order
- G0120 The format used to store the configuration must be a human readable text file. It should be easy to read.
- G0125 The format must allow configuration keys to be typed. For example: "foo:Integer":"1".
- G0130 The configurations must by default be usable by any bundle. That is the bundle location must be
 "?"
- G0150 It must be possible to coordinate the settings of configurations, but use of the OSGi Coordinator service must be optional.





- G0160 If the Configurer starts up, it must set all configurations that are in installed bundles at that
 moment in a single coordination, if the Coordinator is present. The configurations must be applied even if
 the coordination is failed.
- G0170 The solution should group settings inside a coordination as much as possible. A participant must
 use the topmost coordination on the coordinations stack and apply configurations regardless whether the
 coordination failed or succeeded.
- G0180 The solution must be able to purge configurations from uninstalled bundles even if it had not been active while they were uninstalled.
- G0190 It must be possible in runtime to disable specific configurations.
- G0220 Any errors must be logged
- G0230 It must be possible to specify the configuration in multiple bundle resources. The specification must define how to resolve conflicting configurations.
- G0240 It must be possible to specify a profile system property that can select a part of a configuration file. This will allow the same bundle to be used in different settings.

4.2 Configuration Admin

• C0010 – It must be possible to specify the service.pid value when creating a factory configuration. This implies the need for a get or create factory configuration method in ConfigurationAdmin.

5 Technical Solution

5.1 Configuration Admin Enhancements

This chapter contains enhancements to the Configuration Admin Service Specification.

5.1.1 PID Handling of Factory Configurations

The current Configuration Admin Service Specification provides no control over the PID of a factory configuration: a new factory configuration gets assigned a PID generated by the *Configuration Admin*. This makes it hard for any (provisioning) tool to manage such a configuration as it needs to store this generated PID in order to later on update or delete the factory configuration.

Configuration Admin specifies that a "PID should follow the symbolic-name syntax", however in the examples in table 104.1 non symbolic-names are used. For targeted PIDs it's already defined that the pipe character '|' is used to separate the PID part from the target information which in fact means that a PID must not use this character. This should be more precisely specified in section 104.3.1. In the same way as the pipe character has been

introduced as a special character we could introduce a new special character as outlined below. We pick '#' for now.the character '#' is introduced as another special character for the PID handling of factory configurations.

By introducing two new methods on the *Configuration Admin* service, a client of the service can specify an alias for the PID of the factory configuration by providing the factory PID and a name:

```
public Configuration getFactoryConfiguration(String factoryPid, String
    aliasname, String location) throws IOException;
```

```
public Configuration getFactoryConfiguration(String factoryPid, String
    aliasname) throws IOException;
```

These methods require a factoryPID and an alias name argument. The method still generates a PID however the generated PID has the form: factoryPid#aliasname. This ensures that the Configuration Admin can still guarantee uniqueness of the PID. If a configuration with the given combination of factoryPID and aliasname already exists, this is returned, otherwise a new factory configuration is returned. The returned configuration has the factoryPID and a generated PID as mentioned above. Location handling and permission checks works as defined for getConfiguration.

The aliasname can be used to find a factory configuration using listConfigurations:

```
ConfigurationAdmin ca = ...;
ca.listConfigurations("(service.pid=my.factory.pid#myaliasmyname)");
```

5.1.2 Locking Configuration Records

The Configuration interface is enhanced with the following methods:

If the configuration is locked using setLocked(true) this state is persisted and the configuration remains locked until it is explicitly unlocked calling setLocked(false). If the configuration is locked and Configuration.update(), Configuration.update() is called, a LockedConfigurationException (subclass of IOException) is thrown.



5.1.2.1 Security impacts

A new action, LOCK, is added to the configuration permission. In order to lock or unlock a configuration, the caller needs the permission to do so. The verification of the permission is handled in the same way as for the CONFIGURE action as outline in section 104.11.1.

5.1.3 Improving Configuration Updates

Currently, any call of the update method on the Configuration object assumes that the configuration actually changed. The change count is increased, listeners and managed service (factories) are informed.

Configuration Admin should actually check whether the updated configuration is the same as the previous configuration, and if so ignore this operation. This allows all (provisioning) clients to simply update a configuration without reimplementing a complicated change check, Doing it once in Configuration Admin is more efficient and improves the handling for every client.

As configurations should only contain a limited set of types, equals can be called on the property values to find out whether the values are the same. For arrays, equals need to be called on each member of the array.

/**
* Update the properties of this {@code Configuration} object if the
* provided properties are different than the currently stored set
*
* If the properties are the same, no operation is performed, otherwise it
* stores the properties in persistent storage after adding or overwriting
* the following properties:
*
* "service.pid": is set to be the PID of this configuration.
* "service.factoryPid": if this is a factory configuration it is set
* to the factory PID else it is not set.
*
* These system properties are all of type {@code String}.
* *
<u>* </u>
* If the corresponding Managed Service/Managed Service Factory is
* registered, its updated method must be called asynchronously. Else, this
* callback is delayed until aforementioned registration occurs.
<u>*</u>
<u>* </u>
* Also notifies all Configuration Listeners with a
* {@link ConfigurationEvent#CM_UPDATED} event.
* @param properties the new set of properties for this configuration
* @throws LockedConfigurationException If the configuration is locked
* @throws IOException if update cannot be made persistent
* @throws IllegalArgumentException if the {@code Dictionary} object
<u>* contains invalid configuration types or contains case variants of</u>
* the same key name.
* @throws IllegalStateException If this configuration has been deleted.
*/
<pre>public void setProperties(Dictionary<string, ?=""> properties) throws IOException;</string,></pre>



5.1.4 Capabilities

The Configuration Admin implementation bundle must provide the osgi.implementation capability with name osgi.cm. This capability can be used by provisioning tools and during resolution to ensure that a Configuration Admin implementation is present to manage configurations. The capability must also declare a uses constraint for the org.osgi.service.cm package and provide the version of this specification:

```
Provide-Capability: osgi.implementation;
osgi.implementation="osgi.cm";
uses:="org.osgi.service.cm";
version:Version="1.6"
```

This capability must follow the rules defined for the osgi.implementation Namespace.

The bundle providing the Configuration Admin service must provide a capability in the osgi.service namespace representing this service. This capability must also declare a uses constraint for the org.osgi.service.cm package:

```
Provide-Capability: osgi.service;
objectClass:List<String>="org.osgi.service.cm.ConfigurationAdmin";
uses:="org.osgi.service.cm"
```

This capability must follow the rules defined for the osgi.service Namespace.

5.2 Configurations

The Configurer service is a service defined by this specification to process configurations stored in a bundle.

5.2.1 osgi.implementation Capability

The Configurer implementation bundle must provide the osgi.implementation capability with name osgi.configurer. This capability can be used by provisioning tools and during resolution to ensure that a Configurer implementation is present to process the configurations. The capability must also provide the version of this specification:

```
Provide-Capability: osgi.implementation;
osgi.implementation="osgi.configurer";
version:Version="1.0"
```

This capability must follow the rules defined for the osgi.implementation Namespace.

5.2.2 Configurations in a Bundle

If a bundle contains configurations to be managed by the Configurer service, it must require the above mentioned capability.

The Configurer uses <code>Bundle.findEntries</code> on the bundle requiring the above capability to find all files ending in <code>.yaml</code> in the configured paths. Files with other endings in the configured paths are ignored. Subdirectories are not followed either. The default configured path is <code>OSGI-INF/configurer</code>. If the bundle

wants to store its configurations at a different location within the bundle it can specify the attribute configurations on the require capability clause. The value of that attribute must be of type String or List of Strings. Each value represents a path. The path is always relative to the root of the bundle and may begin with a slash. A path value of slash indicates the root of the bundle. If a path is configured several times, it is only processed once.

If a configured path does not exist, an error should be logged with the log service if available. The found YAML files from all configured paths are processed in lexicographical order based on the full path.

5.2.3 Configuration File Format

Each configuration file processed by the Configurer is in YAML format [7]. <u>UTF-8 encoded</u>. If the contents of the file is invalid YAML, the file is ignored and an error should be logged with the log service if available.

Configuration files should declare the Configurer version they are compliant with via the ":configurer:version" key. If this key is omitted then version 1 is assumed. If the specified version is invalid or is not supported by the implementation, the file is ignored and an error should be logged with the log service if available. This specification defines version 1 of the YAML file format.

The overall structure of the YAML file is as follows:

The YAML configuration section is a list of configurations. The name of each configuration map is the PID of the configuration. The value is a map with the configuration properties:

configurations:

- my.component:
 - # configuration properties
- my.factory#foo:
 - # configuration properties
- my.factory#bar:
 - # configuration properties

Addition objects in the YAML are ignored.

Properties starting with the prefix ":configurer:" are reserved properties by the Configurer specification and might influence the processing of the configuration. These properties are filtered out by the Configurer before the



properties are passed to *Configuration Admin*. All other properties of the configuration map will be used for the dictionary passed to *Configuration Admin*:

```
email: something@somewhere.com
port: 300
:configurer:ranking: 12
```

The value of a configuration property for *Configuration Admin* must be the same type as the set of Primary Property Types specified in the chapter "Filter Syntax" in the OSGi Core. On the other hand, YAML only supports a basic set of scalar types (String, Float, Integer, and Boolean), arrays and maps. Without any further type information for the Java type, the mapping between the YAML type and the Java type is as follows:

YAML Type	Java Type
String	String
Integer	Long
Float	Double
Boolean	Boolean
Array of String	String[]
Array of Integer	Integer[]
Array of Float	Float[]
Array of Boolean	Boolean[]
Anything else	String containing the YAML

The Java type of a property for the configuration object can be specified as part of the property name by appending a colon followed by the Java type. The allowed types are: the scalar types (String, Integer, Long, Float, Double, Byte, Short, Character, and Boolean), the primitive types (int, long, float, double, byte, short, char, boolean), arrays of a scalar or a primitive type and collections of the scalar types. If any other type is specified, the configuration is ignored and this should be logged as an error with the log service if available. For collections, the Configurer picks a suitable implementation which preserves the order.

```
port:Integer: 300
an.int.array:int[]: [2, 3, 4]
an.Integer.collection:Collection<Integer>: [2,3,4]
complex:
    a : 1
    b : two
```

For the actual type conversion, the conversion follows the rules as outlined in RFC 215 Object Conversion.

5.2.4 Binaries

A configuration property can reference a binary. The property is declared with the type binary, the value is a path to a file. The path is always relative to the root of the bundle and may begin with a slash. The file contents is get using getEntry on the bundle containing the configuration.

```
configurations:
   - my.config:
```



a.file:binary: /OSGI-INF/files/myfile.cfg

If a configuration with a binary is added to Configuration Admin, the file is extracted from the bundle and copied to the local file system. The value of the property is replaced with the full path to the file. Each time a file is extracted to the file system, a new file name is used to avoid open file lock issues on Windows.

The type of such a property might also be an array of binaries (binary[]). In this case the value of the property will be an array of paths. All files are extracted to the file system and the value of the property will be an array of strings containing the full paths of the files in the same order.

If extracting of a file to the file system fails, this is logged as an error with the log service if available. The configuration is ignored.

If a bundle with a binary is updated, in general there is no way for the Configurer to detect whether the contents of the referenced binary is different other than extracting it and comparing it to the existing binary.

5.2.5 Environments

In some cases it is handy to have different configurations based on the environment the instance is running in. Typical scenarios are different configurations during development, for testing and in production. The Configurer gets the active environments by calling BundleContext#getProperty("configurer.environment") on the bundle context of the Configurer bundle.

The value must be a comma separated string of the active environments. An identifier of an environment must follow the *token* definition from the OSGi Core chapter. To support environments from multiple parties reverse DNS should be used to define environment names. If the property contains invalid characters, it will be ignored and logged as an error with the log service if available. Whitespace characters before and after each environment in the property value are ignored. Duplicate entries are removed, building a set of active environments. Configurations can specify the environments that they are active in using the :configurer:environments key. If a configuration does not specify the :configurer:environments key it is always applied. The value of this property is converted to a String array (as explained above). Each value in the array represents an environment name. If at least one of the mentioned environments is active, the configuration is applied.

To support different configurations depending on the environment, a configuration for the same PID might appear several times in the list of configurations

```
configurations:
    - my.service.pid:
        foo: 1
            :configurer:environments: test
        - my.service.pid:
        foo: 2
            :configurer:environments: prod
        - my.service.pid:
        foo: 100
```

If more than one configuration for a PID can be applied, the one with the highest configuration ranking (see below) is applied. All others are ignored for this PID. If two configurations have the same ranking, the first one found is used. In the example above all configurations have the same ranking. If the environment "test" is active, the first configuration is used, if "prod" is active, the second configuration is used and if neither "test" nor "prod"

April 22, 2016



are active, the third configuration is used. If both "test" and "prod" are active, again the first configuration is used.

5.2.6 Configuration Ranking

Bundles are processed sequentially by the Configurer. It is undefined in which order the bundles are processed by the Configurer. To better control the situation where more than one bundle provides a configuration for the same PID and ensure a predictable and reproducible system configuration, configurations have a configuration ranking.

The configuration ranking is modeled after the service ranking: it is an integer which defaults to 0. If two bundles have a configuration with the same PID, the configuration with the higher ranking is preferred (see below). If these two configurations have the same ranking, the configuration from the bundle with the lower bundle id is ranked higher.

The configuration ranking can be set through the property :configurer:ranking. The type of the property is converted to an Integer (as defined by the Object Converter specification). If the value can't be converted, it is set to 0. This case should be logged as a warning with the log service if available.

5.2.7 Configurations from the Runtime Environment

When the Configurer service starts, it calls <code>BundleContext#getProperty("configurer.initial")</code> on the bundle context of the Configurer implementation to get a configuration from the environment. If a value for this property is available and consists of several lines, ignoring leading spaces, it is interpreted as literal YAML, otherwise it is interpreted as a comma-separated list of URLs. The Configurer will try to resolve the URLs and read a YAML object from each URL. If a URL can't be resolved or any error occurs during reading from that URL, an error should be logged with the log service if available and this URL is ignored. The YAML files are processed in the order of the URLs.

If the read YAML is valid as defined in this specification, this configuration is applied by the Configurer. If the YAML is invalid, an error should be logged with the log service if available. The encoding of the YAML files read through the URLs is assumed to be UTF-8.

The ranking of these configurations can be set in the YAML as outlined above, the bundle id for the configurations from the environment is set to -1. The list of configurations is treated like any other bundle configuration and accordingly applied on startup of the Configurer.

If the framework is restarted, the Configurer needs to check whether the provided configuration from the environment is different than on the previous startup. The implementation is free to use whatever is appropriate to perform this check, like comparing last modified for the URL based YAML or a hash etc. If the provided configuration is different than on a previous startup, this is treated like a bundle update with a different configuration. If on a follow up start of the framework a different configuration is provided, this is treated like a bundle update with a different configuration.

5.2.8 Overwrite policies

Each configuration is processed according to its configuration ranking and policy. The policy can be defined with the property :configurer:policy. Allowed values are default and force. If no property is specified or an invalid value is specified, default is used. If the value is invalid, an error should be logged.

The configuration is applied according to the following table:

	Policy default	Policy force
No configuration in config admin	Configuration is added	Configuration is added
Configuration added by Configurer:		
- with higher ranking	No action	No action



Draft

April 22, 2016

lower rankinglower ranking					Configuration is added Configuration is added
Configuration Configurer	not	added	by	No action	Configuration is added

(*) If the Configurer adds a configuration to *Configuration Admin*, it keeps track of the change count. Comparing the current change count with the stored change count allows to find out, whether the configuration has been changed from outside of the Configurer.

If a configuration is added to the *Configuration Admin*, it replaces a potentially existing configuration with the same PID. If the configuration is locked, the configuration is ignored and this situation should be logged as a warning with the log service if available. If the Configurer gets an IllegalStateException while trying to update an existing configuration, this means the configuration has been removed in the meantime. In this case the Configurer tries to create the configuration. If that fails, the configuration is ignored and this is logged as an error with the log service if available. If any other exception occurs while creating, updating or deleting a configuration, this is logged as an error with the log service if available.

If a new configuration is added, the bundle location is set to "?". The bundle location of existing configurations is not altered.

The Configurer keeps the set of configurations together with the last modified time of the bundle and the change count of added configurations.

5.2.8.1 Removing Configurations

When the Configurer removes configurations for a bundle, the Configurer uses the calculated set of configurations. Each configuration is processed according to its policy:

	Policy default	Policy force
Configuration added by Configurer - unchanged (*)	Remove, add configuration with lower ranking if available	Remove, add configuration with lower ranking if available
- changed (*)	No action	Remove, add configuration with lower ranking if available

The Configurer removes all internal state for that bundle.

5.3 Processing Bundles

The Configurer service is active if the implementation bundle is running and the implementation has access to a *Configuration Admin* service. Therefore the Configurer should require the *Configuration Admin* service through a service capability.

When the Configurer service is started, it processes all resolvedinstalled bundles and applies the configurations. The Configurer also checks whether an activated processed bundle from a previous run has been uninstalled. In that case it removes the configurations installed from this bundle according to the policy. The check can be done by simply checking if a bundle with a given bundle id is not present in the framework anymore.

While the service is running, when a bundle transitions from thegets installed into the resolved state, the Configurer applies the contained configurations. This covers both cases, installing and updating a bundle is updated, the Configurer will process the updated bundle as well. If a bundle gets uninstalled, the Configurer removes the configurations installed from this bundle according to the policy.



Draft

April 22, 2016

Although the Configurer operates sequentially (no parallel bundle operations, no parallel configuration operations), the Configurer might first compute the actions based on the available set of bundles and perform an optimized set of operations.

5.3.1 Applying Configurations from a Bundle

The Configurer should attempt to process as many bundles providing configurations as possible in a single pass. A set of configurations to be applied by the Configurer is built from the contents of each bundle.

If the Configurer did previously process this bundle and the set of active environments is the same as at the time when the bundle has been processed previously, it compares the last modified of the bundle with the last modified of the previous run. If it is the same, the bundle is already processed and no further step is performed.

The set of configurations defined within the bundle is calculated by respecting the current set of active environments. As defined above, all YAML files from a single bundle are processed in lexicographical order based on their full path. The files are read one after the other and a set of configurations is built up.

The PIDs are processed for active environments only. PIDs without a specified environment are always processed. If multiple configurations for a single Pid exists, the definition with the highest configuration ranking is used. In case of a tie within the same bundle, the first encountered configuration wins. Multiple configurations are not merged. The winning definition defines the entire configuration for this Pid.

Once the set of configurations for a bundle is defined, the Configurer checks whether this bundle has been processed previously. In this case, the Configurer compares the set from the old run with the new calculated set. If the old set contains configurations with a PID which is not in the new set, these old configurations are removed according to their policy. All configurations from the new set are applied. For each configuration in the resulting set the following is checked:

- 1. If this PID was set before by the Configurer, the Configurer checks whether the change count is still the same as when it was previously set. If the change count is different and the policy is not set to force this PID is not set in *Configuration Admin*.
- 2. The remaining set of configurations is set in *Configuration Admin* in alphabetical order.

5.3.2 Coordinator Support

If a Coordinator service is available, the Configurer shouldmust make use of it. In this case, the Configurer checks whether there is an implicit coordination available. If it exists, the Configurer adds itself as a participant to this coordination. If there is no implicit coordinationne, the coordinator starts a new coordination and ends it, whenonce the Configurer is done with the currently available set of bundles containing configurations for the Configurer. If the coordination fails, the Configurer does not revert its actions.

5.4 Standalone Configurations

The configuration file format in section 5.2.3 defines a portable representation of configurations in *Configuration Admin*. Whilst the Configurer extender implementation is necessary to process these configurations when they are packaged inside a bundle, these files can also offer significant value to other tools for deployment and management when standalone.

For example:

 A deployer wishes to install an OSGi Application subsystem, which requires configuration to run. Currently the deployer would have to provide configuration as a separate step, in some provider specific way. With the addition of a standard configuration format the configuration(s) can be included inside the ESA, or referenced from an external repository. The subsystems implementation can then deploy the configuration into the scope of the Application Subsystem at the same time as deploying the application bundles.



- April 22, 2016
- 2. A runtime assembly tool wishes to package and deploy an OSGi framework, a set of bundles, and one or more configurations into a single executable JAR file. The bundles to be packaged are located in an OSGi repository. In order for the tool to successfully resolve and assemble the runtime it needs to know:
 - a) Does a bundle require configuration for a particular PID?
 - b) What PIDs are offered by the other resources in the repository?

5.4.1 Configuration capabilities

In order to support the various configuration use cases it is necessary to define requirements and capabilities for the Configurer, the configurations, and the configuration bundles.

For configuration bundles the requirements and capabilities must be provided using the standard Require-Capability and Provide-Capability headers in the manifest file. Configuration files do not have a location to add requirement and capability metadata, therefore the metadata must be automatically generated by the repository if a standalone configuration file is added.

5.4.1.1 Common Requirements and Capabilities

Both configuration files and configuration bundles offer configuration for one or more PIDS. This capability is modeled using the osgi.configuration namespace. Configuration files and bundles should define Capabilities for each configuration that they define, and each capability should have resolve time effectiveness.

The osgi.configuration namespace:

Attribute	Required	Default Value	Purpose
service.pid	No	N/A	Defines the PID of the configuration
service.factoryPid	No	N/A	Defines the factory PID if this is a factory configuration

Note that at least one of service.pid and service.factorypid must be defined. If the configuration is a standard configuration then only the service pid is used. If the configuration is a factory configuration with an automatically generated identity then only the service.factoryPid is used. If the configuration is a factory configuration with a specified identity then both the service.pid and service.factoryPid are used.

In order for configurations to be deployed it is necessary for there to be an active ConfigurationAdmin implementation. It is therefore important that the configuration files specify the following requirement:

```
Require-Capability:
osqi.implementation;filter:="(&(osgi.implementation=osgi.cm)
(version>=1.6)(!(version>=2)))";effective:="active"
```

The version range used in this requirement may be expanded downward if the configuration does not require features from a more recent Configuration Admin.

This require capability is not necessary if this is a configuration bundle which requires the Configurer as the Configurer in turn requires the Configuration Admin.

5.4.1.2 Standalone Configuration Capabilities

In addition to the common requirements and capabilities a standalone configuration needs to provide two other capabilities when in a repository:





- April 22, 2016
- 1. An osgi.content capability. The OSGi content namespace is easy to automatically generate for a configuration file. The one missing value is the mime type of the configuration file, which will be defined as application/vnd.osgi.configuration
- 2. An osgi.identity capability. The osgi.identity capability requires that each resource define a symbolic name and version. Currently this metadata cannot be automatically derived from the contents of the configuration file, and would have to be based on the file name.

6 Data Transfer Objects

RFC 185 defines Data Transfer Objects as a generic means for management solutions to interact with runtime entities in an OSGi Framework. DTOs provides a common, easily serializable representation of the technology.

For all new functionality added to the OSGi Framework the question should be asked: would this feature benefit from a DTO? The expectation is that in most cases it would.

The DTOs for the design in this RFC should be described here and if there are no DTOs being defined an explanation should be given explaining why this is not applicable in this case.

This section is optional and could also be provided in a separate RFC.

7 Javadoc

Please include Javadoc of any new APIs here, once the design has matured. Instructions on how to export Javadoc for inclusion in the RFC can be found here: https://www.osgi.org/members/RFC/Javadoc



8 Considered Alternatives

8.1 Placeholders

The following idea of placeholders for framework properties was dropped as the value gets replaced at the time of processing through the Configurer. For example on a restart with a different value, the configuration is not updated and still points to the value from the previous start. The only way to solve this in a useful way is to add support for placeholders directly into *Configuration Admin*.

Placeholders can be used in any of the values for a property. The JSON type of the property needs to be string. A placeholder is identified by the start token "\${" and the end token "}". A start token without an end token is considered an error, and the configuration will be ignored and the error logged with the Log Service. If a string value should contain the literal "\${" it needs to escape it with a single \$, like "\$\${". The value between the tokens is the property key. The key must follow the definition of a symbolic name, whitespace characters before and after the key are ignored. A default value can be specified by appending the pipe character after the key followed by the default value. It is allowed to specify the empty value as the default value after the pipe character – in this case the end token is directly following the pipe character.

The key is used to get the corresponding framework property. If a value for this key exists, this value is used as the value for the property. If no value exists for that key but a default value is specified, the default value is used. If no value exists and no default value is specified this is considered an error and this configuration is skipped and the error is logged with the Log Service.

As the value needs to be specified as a JSON string in order to use placeholders, the type of the Java property for the configuration should be provided as part of the property key if the type is different from String.

8.2 Merging Configurations

The above described approach overwrites configurations instead of merging them. The idea behind this is that a new bundle version contains a new version of a configuration. Example:

Bundle Version 1 contains a configuration for PID A with properties a=1, b=1, and c=2 - configuration ranking is 1

Bundle Version 2 contains a configuration for PID A with properties a=2, c=2, and d=2 - configuration ranking is 2

With overwriting configurations, regardless of the order in which the bundles are installed, the final configuration will be the one from bundle version 2 without the property b.





If a merging approach would be used and version 1 is installed first, and version 2 is merged into version 1, handling the removal of property b is tricky. A pure merge would not remove property b. Therefore, depending on the order, either property b is available in *Configuration Admin* or is not.

Using overwriting makes the processing predictable and cleaner.

9 Security Considerations

Description of all known vulnerabilities this may either introduce or address as well as scenarios of how the weaknesses could be circumvented.

10 Document Support

10.1 References

- [1]. Bradner, S., Key words for use in RFCs to Indicate Requirement Levels, RFC2119, March 1997.
- [2]. Software Requirements & Specifications. Michael Jackson. ISBN 0-201-87712-0
- [3]. http://felix.apache.org/site/apache-felix-file-install.html
- [4]. http://enroute.osgi.org/services/osgi.enroute.configurer.api.html
- [5]. http://jpm4j.org/#!/p/osgi/biz.aQute.bndlib
- [6]. https://angularjs.org/
- [7]. http://yaml.org

10.2 Author's Address





Name

Company

Address

Voice

e-mail

April 22, 2016		

10.3 Acronyms and Abbreviations

cziegele@adobe.com

Carsten Ziegeler

+41 61 226 55 0

Adobe Systems Incorporated

Barfüsserplatz 6, 4055 Basel, Switzerland

10.4 End of Document