



OSGiTM Alliance

RFC 193 - CDI Integration

Draft

52 Pages

Abstract

While OSGi services are very powerful, some still find it challenging to use them effectively. This RFC looks at how CDI can be used to interact with the OSGi service layer. The intent is to bring the popular CDI programming model to OSGi as a way to interact with OSGi services. It will provide the convenience of CDI and allows developers familiar with the CDI technology to reuse their skills in an OSGi context.

0 Document Information

0.1 License

DISTRIBUTION AND FEEDBACK LICENSE, Version 2.0

The OSGi Alliance hereby grants you a limited copyright license to copy and display this document (the "Distribution") in any medium without fee or royalty. This Distribution license is exclusively for the purpose of reviewing and providing feedback to the OSGi Alliance. You agree not to modify the Distribution in any way and further agree to not participate in any way in the making of derivative works thereof, other than as a necessary result of reviewing and providing feedback to the Distribution. You also agree to cause this notice, along with the accompanying consent, to be included on all copies (or portions thereof) of the Distribution. The OSGi Alliance also grants you a perpetual, non-exclusive, worldwide, fully paid-up, royalty free, limited license (without the right to sublicense) under any applicable copyrights, to create and/or distribute an implementation of the Distribution that: (i) fully implements the Distribution including all its required interfaces and functionality; (ii) does not modify, subset, superset or otherwise extend the OSGi Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the OSGi Name Space other than those required and authorized by the Distribution. An implementation that does not satisfy limitations (i)-(ii) is not considered an implementation of the Distribution, does not receive the benefits of this license, and must not be described as an implementation of the Distribution. "OSGi Name Space" shall mean the public class or interface declarations whose names begin with "org.osgi" or any recognized successors or replacements thereof. The OSGi Alliance expressly reserves all rights not granted pursuant to these limited copyright licenses including termination of the license at will at any time.

EXCEPT FOR THE LIMITED COPYRIGHT LICENSES GRANTED ABOVE, THE OSGi ALLIANCE DOES NOT GRANT, EITHER EXPRESSLY OR IMPLIEDLY, A LICENSE TO ANY INTELLECTUAL PROPERTY IT, OR ANY THIRD PARTIES, OWN OR CONTROL. Title to the copyright in the Distribution will at all times remain with the OSGi Alliance. The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted therein are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

THE DISTRIBUTION IS PROVIDED "AS IS," AND THE OSGi ALLIANCE (INCLUDING ANY THIRD PARTIES THAT HAVE CONTRIBUTED TO THE DISTRIBUTION) MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DISTRIBUTION ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

NEITHER THE OSGi ALLIANCE NOR ANY THIRD PARTY WILL BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THE DISTRIBUTION.

Implementation of certain elements of this Distribution may be subject to third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a member of the OSGi Alliance). The OSGi Alliance is not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

The Distribution is a draft. As a result, the final product may change substantially by the time of final publication, and you are cautioned against relying on the content of this Distribution. You are encouraged to update any implementation of the Distribution if and when such Distribution becomes a final specification.

The OSGi Alliance is willing to receive input, suggestions and other feedback ("Feedback") on the Distribution. By providing such Feedback to the OSGi Alliance, you grant to the OSGi Alliance and all its Members a non-exclusive, non-transferable,

worldwide, perpetual, irrevocable, royalty-free copyright license to copy, publish, license, modify, sublicense or otherwise distribute and exploit your Feedback for any purpose. Likewise, if incorporation of your Feedback would cause an implementation of the Distribution, including as it may be modified, amended, or published at any point in the future (“Future Specification”), to necessarily infringe a patent or patent application that you own or control, you hereby commit to grant to all implementers of such Distribution or Future Specification an irrevocable, worldwide, sublicenseable, royalty free license under such patent or patent application to make, have made, use, sell, offer for sale, import and export products or services that implement such Distribution or Future Specification. You warrant that (a) to the best of your knowledge you have the right to provide this Feedback, and if you are providing Feedback on behalf of a company, you have the rights to provide Feedback on behalf of your company; (b) the Feedback is not confidential to you and does not violate the copyright or trade secret interests of another; and (c) to the best of your knowledge, use of the Feedback would not cause an implementation of the Distribution or a Future Specification to necessarily infringe any third-party patent or patent application known to you. You also acknowledge that the OSGi Alliance is not required to incorporate your Feedback into any version of the Distribution or a Future Specification.

I HEREBY ACKNOWLEDGE AND AGREE TO THE TERMS AND CONDITIONS DELINEATED ABOVE.

0.2 Trademarks

OSGi™ is a trademark, registered trademark, or service mark of the OSGi Alliance in the US and other countries. Java is a trademark, registered trademark, or service mark of Oracle Corporation in the US and other countries. All other trademarks, registered trademarks, or service marks used in this document are the property of their respective owners and are hereby recognized.

0.3 Feedback

This document can be downloaded from the OSGi Alliance design repository at <https://github.com/osgi/design> The public can provide feedback about this document by opening a bug at <https://www.osgi.org/bugzilla/>.

0.4 Table of Contents

0 Document Information.....	2
0.1 License.....	2
0.2 Trademarks.....	3
0.3 Feedback.....	3
0.4 Table of Contents.....	3
0.5 Terminology and Document Conventions.....	4
0.6 Revision History.....	4
1 Introduction.....	6
2 Application Domain.....	6
2.1 CDI.....	7
2.1.1 Example.....	7
2.2 Weld-OSGi.....	8
2.2.1 Weld-OSGi example.....	8
2.3 Declarative Services, Blueprint and CDI.....	8
2.4 Terminology + Abbreviations.....	9
3 Problem Description.....	9
4 Requirements.....	9
4.1 Functional Requirements.....	9
4.2 Non-functional Requirements.....	11
4.3 Requirements from RFP 98 (OSGi/Java EE umbrella RFP).....	12

5 Technical Solution.....	12
5.1 Entities.....	12
5.2 CDI Container Life-Cycle.....	13
5.2.1 Initialization of a CDI Container.....	13
5.3 Requirements and Capabilities.....	16
5.4 Managed Beans and OSGi Services.....	18
5.4.1 Publishing plain CDI providers in the Service Registry.....	19
5.5 Scopes for beans annotated as @Component@Service.....	19
5.6 Life-Cycle.....	20
5.6.1 Required dependencies (@Component@Service only).....	21
5.6.2 Optional dependencies	22
5.6.3 Allowing Service Injections in vanilla CDI injection points.....	22
5.6.4 Service and bundle registration observers.....	23
5.6.5 Service Filters.....	23
5.7 BundleContext injection	25
5.8 BeanManager service.....	25
5.9 osgi.extender Capability.....	25
5.10 osgi.contract Capability.....	26
5.11 Events.....	26
5.11.1 CDI Event.....	26
5.11.2 Replay.....	27
6 Data Transfer Objects.....	27
7 Javadoc.....	27
8 Considered Alternatives.....	28
8.1 EventAdmin integration.....	28
9 Security Considerations.....	30
10 Document Support.....	30
10.1 References.....	30
10.2 Author's Address.....	31
10.3 Acronyms and Abbreviations.....	31
10.4 End of Document.....	31

0.5 Terminology and Document Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in 1.

Source code is shown in this typeface.

0.6 Revision History

The last named individual in this history is currently responsible for this document.

Revision	Date	Comments
Initial	16/10/12	Initial version of the draf. David Bosschaert <david@redhat.com>
2 nd draft	26/10/12	First draft of chapter 5 Paul Bakker <paul.bakker@luminis.eu>
3 rd draft	30/10/12	Life-cycle callbacks Paul Bakker < paul.bakker@luminis.eu >
4 th draft	27/01/13	Details on service dynamics Paul Bakker <paul.bakker@luminis.eu>
5 th draft	27/02/13	Comments after EEG call 2/20/2013
7 th draft	09.04.13	New sections Entities, CDI container lifecycle, Requirements and Capabilities. A number of comments on existing sections. Harald Wellmann/ Rebaze < harald.wellmann@rebaze.com >
8 th draft	October, 2013	David Bosschaert, some cleanup and additions: <ul style="list-style-type: none"> • Removed OSGi prefix from classnames • Replaced API described in the text with actual Javadoc generated from classes in OSGi git • Tentatively added sections about support for scopes and support for 'bare' @Inject injection points • Tentatively added section about support for declaring @Component via manifest headers • Added section on the CdiContainer service • Added section on osgi.capability portable Java contracts
9 th draft	07/11/13	David Bosschaert, process input from call 6 th November 2013.
10 th draft	14/11/13	David Bosschaert, process input from the virtual F2F November 13, 2013.
11 th draft	05/11/14	Emily Jiang, update to CDI 1.2
12 th draft	20/11/14	Emily Jiang more update based on the comments from F2F in Los Angeles
13 th draft	17/01/15	Emily Jiang. Add lifecycle and Event
14 th draft	15/02/15	Emily Jiang, update based on the call 11 th March 2015
15 th draft	09/09/15	Emily Jiang, updated based on the call in June F2F
16 th draft	18/12/15	Emily Jiang, updated based on F2F in November

1 Introduction

While OSGi services are very powerful, consuming them has been a challenge for many OSGi users. There have been a number of solutions to this problem both in OSGi specifications as well as in non-standardized technologies. OSGi Declarative Services and Blueprint are popular specifications in this area, however they provide new programming models that users need to learn. As of JavaEE 6, CDI (JSR 299) is included as a standard injection technology for JavaEE components. CDI becomes a core aspect of JavaEE platform. The JavaEE7 specification has further integrated CDI with many JavaEE components such as EJB, JSF, Bean Validation, JAX RS etc. It is enabled by default. The CDI programming model seems suitable for interaction with the OSGi service layer as well and has the benefit that developers who are familiar with CDI don't need to learn a new technology in order to interact with the OSGi service registry.

This document proposes that OSGi will support CDI with the goal of creating a specification that describes how the CDI programming model can be used to interact with OSGi services.

2 Application Domain

Software developers often need to build loosely coupled applications. The need for this stems from a number of factors:

- Developing reusable services for consumption outside of the team
- Allowing those services to be easily consumed
- Unit testing of applications and services
- Allowing larger teams to work effectively together by isolating areas of development

Software developers also wish to using a standardized programming model. This promotes:

- Transferability of skill sets
- Ease of sourcing new developers and low initial overhead

- Clear understanding of correct behavior when unexpected behavior is encountered
- Consistency of programming model across the technological strata to provide a uniformity of approach to aid understanding

Finally, software developers require an environment in which the focus can be on solving business issues rather than technological issues. This allows a more responsive development process.

2.1 CDI

CDI, Contexts and Dependency Injection is first specified by JSR 299 and then CDI 1.1 by JSR346. CDI 1.2 is the maintenance release of JSR346. It defines a clean, mostly annotations-based injection model which has recently become very popular. CDI is part of JavaEE 6/7 but can also be used standalone in a JavaSE context.

Weld (<http://weld.cdi-spec.org/>) is the Reference Implementation of JSR 299 and JSR 346.

2.1.1 Example

Although many advanced features are available, the most basic annotation used in CDI is `javax.inject.Inject` which declares the injection points for CDI.

For example the following Servlet class uses CDI injection to obtain an implementation of the `WeatherBean` interface.

```
public class CDIServlet extends HttpServlet {
    @Inject
    WeatherBean weatherBean;

    @Override
    protected void doGet(HttpServletRequest req, HttpServletResponse resp)
        throws ServletException, IOException {
        PrintWriter writer = resp.getWriter();
        writer.print("The Weather in Amsterdam: " +
            weatherBean.getDescription("Amsterdam"));

        writer.flush();
        writer.close();
    }
}
```

While for the most basic use a CDI provider does not need to be annotated, CDI will attempt to find an implementor class and instantiate it using a no-arg constructor. Other mechanisms to publish a bean into CDI can be defined by using the `javax.enterprise.inject.Produces` annotation. Additionally, a number of scopes are defined that can be used to declare the lifecycle of a CDI bean.

For example, the `WeatherBean` above can be scoped to the application lifecycle by adding the `javax.enterprise.context.ApplicationScoped` annotation, as in this example:

```
@ApplicationScoped
public class WeatherBeanProducer {
    @Produces @ApplicationScoped
    public WeatherBean newWeatherBean() {
        WeatherBean wb = new WeatherBeanImpl();
        wb.initialize();
        return wb;
    }
}
```

```
    public void disposeWeatherBean(@Disposes WeatherBean wb) {  
        wb.cleanup();  
    }  
}
```

For more information see the CDI specification at JSR 299 [3].Error: Reference source not found and JSR 346 [4].

2.2 Weld-OSGi

The Weld-OSGi project (<http://mathieuancelin.github.com/weld-osgi/>) has created an integration between CDI and OSGi. It allows CDI beans to be exposed as OSGi services and CDI injections to be satisfied by OSGi services. Weld-OSGi takes additional OSGi features into account such as service registration properties and the dynamic aspects of the Service Registry.

Furthermore, Weld-OSGi provides annotation based injection for the Bundle, BundleContext, Bundle Headers and the private bundle storage facility.

Additionally Weld-OSGi provides annotations-based integration with Service and Bundle events.

2.2.1 Weld-OSGi example

Many examples can be found in the weld-osgi documentation [5].

Weld-OSGi typically uses additional annotations to interact with the OSGi service Registry. For example, the `org.osgi.cdi.api.extension.annotation.Publish` annotation publishes the CDI bean in the OSGi Service Registry:

```
@Publish  
@ApplicationScoped  
public class MyServiceImpl implements MyService {  
    @Override  
    public void doSomething() { ... }  
}
```

To have a CDI injection come from the OSGi Service Registry, use the `OSGiService` annotation:

```
@Inject @OSGiService MyService service;
```

OSGi Services can also be selected by using LDAP filters:

```
@Inject @OSGiService @Filter("&(lang=EN)(country=US)") MyService service;
```

For more examples, see the weld-osgi documentation.

2.3 Declarative Services, Blueprint and CDI

In Java EE, the EJB and CDI containers are able to collaborate such that EJB manages an EJB component's life-cycle, whilst CDI manages its runtime dependencies. For example, when a new EJB is created it can be handed over to the CDI container for it to process the injections (`@Inject`) before finally being made available for use. This relationship helps ensure a complementary positioning between the different component models and reduces runtime duplication (EJB is not required to handle `@Inject` processing itself).

OSGi has two existing component models in the form of Declarative Services and Blueprint. Each has its own mechanism for injection of services and Blueprint also supports bean injection within a bundle. Neither has standards support for runtime annotations for injection, although there is some Blueprint prototype work in Apache Aries. In addressing any requirements for runtime annotations support, serious consideration should be given to the use of existing annotations, such as `@Inject`. It also makes sense to consider creating similar complementary

relationship between their containers and the CDI container for runtime injection processing, thus reducing duplication between various component model containers.

2.4 Terminology + Abbreviations

CDI – Context and Dependency Injection for JavaEE. Specified in JSR 299 and JSR 346.

3 Problem Description

CDI provides a standardized, type-safe, loosely coupled programming model for Java EE 6 and above. Furthermore, it introduces powerful extensibility into the Java EE programming model, and promotes an ecosystem of “portable extensions”.

CDI is declarative, with metadata provided via annotations. This allows developers to locate all logic and metadata in a single location, allowing easier comprehension of the application.

CDI does not specify any modularity or inter-application communication, relying instead on the Java EE platform to provide this.

OSGi provides the de facto standard within Java for modular, service orientated programming.

Use of CDI in the context of OSGi provides a very compelling programming model. However, today there is no standard way to achieve this. A standard for leveraging CDI in OSGi will provide a migration path between JavaEE and OSGi where developers familiar with CDI can reuse their skills in both contexts without being locked in to a particular implementation.

4 Requirements

4.1 Functional Requirements

CDI001 – The specification MUST make it possible to use the CDI annotations and XML descriptor in an OSGi bundle to expose and consume CDI beans.

CDI003 – The specification MUST make it possible to consume OSGi services in CDI @Inject injection points in an OSGi bundle.

CDI004 – The specification **MUST** make it possible to select OSGi services used in CDI beans based on OSGi filters.

CDI005 – The specification **MUST** make it possible to consider CDI qualifiers when looking up CDI beans in the OSGi Service Registry.

CDI014 – The specification **MUST** provide a mechanism to specify additional OSGi service registration properties for CDI beans.

CDI006 – The specification **MUST** make it possible to write a portable CDI jar that runs both in JavaEE as well as in OSGi.

CDI007 – The specification **MUST** consider the thread-safety issues that can arise when migrating CDI beans from JavaEE to OSGi.

CDI008 – The specification **MUST** consider the issues that can arise in relation to the dynamic bundle lifecycle in OSGi.

CDI015 – The specification **MUST** consider the issues that can arise with OSGi service dynamism when these services are injected into a CDI bean.

CDI009 – The specification **MUST** make it possible to take advantage of the dynamic service capabilities of OSGi.

CDI016 – The specification **MUST** extend the life-cycle dependency model as provided in CDI, to support the dynamic life-cycle provided by OSGi. For example, it **MUST NOT** be fatal to deploy a CDI bean that does not have all its dependencies initially satisfied and it **MUST** be possible to change bean dependencies without requiring the CDI application to be redeployed or restarted.

CDI031 – The specification **MUST** extend the life-cycle dependency model of CDI to include dynamic OSGi service dependencies.

CDI017 – The specification **MUST** make it possible to declare a CDI injection point to an OSGi service as optional.

CDI018 – The specification **MUST** provide a mechanism to consume multiple matching services/beans of a given type in an injection point. For example via the `@Inject Instance<T>` mechanism.

CDI019 – The specification **MUST** support CDI events as defined by the CDI specification.

CDI021 – The specification **MAY** provide a deep integration between CDI events and OSGi events or other OSGi mechanism.

CDI020 – The specification **MUST** support CDI extensions as defined by the CDI specification but the extension should not be required to contain the file of `META-INF/services/javax.enterprise.inject.spi.Extension`. It should discover the extension via the service registry service of `javax.enterprise.inject.spi.Extension`.

CDI022 – the specification **MAY** provide a deep integration between CDI extensions and OSGi services or other OSGi mechanism.

CDI010 – The specification **MAY** introduce additional annotations.

CDI011 – The specification **MUST** define the behavior in case of incorrect CDI metadata.

CDI012 – The specification MUST NOT prevent the use of `@Inject` (and other common java annotations) in other component models/technologies present in the OSGi Framework.

CDI013 – The specification MUST define an opt-in mechanism. Bundles not opting in MUST not be considered by the CDI-OSGi integration layer.

CDI023 – All the inter-bundle interaction between CDI beans MUST go through the OSGi Service Registry.

CDI024 – The specification MUST make it possible to access the `BundleContext` from inside a CDI bean in an OSGi Framework.

CDI025 – The specification MUST provide support for `@PostConstruct` and `@PreDestroy` activation and de-activation callbacks.

CDI026 – The specification SHOULD consider defining behavior for relevant CDI scopes.

CDI027 – The solution MAY define new scopes for use with CDI inside an OSGi Framework.

CDI028 – The specification MUST define an opt-in mechanism for CDI extensions.

CDI029 – The specification MUST consider the issues that arise from dynamically adding CDI extensions to the system.

CDI030 – The specification MUST support the inclusion of CDI beans and descriptors in a Web Application Bundle in the same way they can be included in a WAR -.

CDI032 – The specification MUST support the OSGi Service Permission security model when publishing OSGi services from CDI beans and injecting services into CDI beans. It needs to take into account that the CDI extender acts on behalf of other bundles and uses the permissions associated with those.

CDI033 – The specification implementation MUST support CDI 1,2 but may support CDI 1,0.

CDI034 – The specification MUST comply with CDI specification bean defining annotation for honoring a CDI bean not requiring the existence of `beans.xml`.

CDI034 – The specification SHOULD choose a service when multiple services are available for a particular instead of throwing `AmbiguousResolutionException` specified by CDI specification

CDI035 – The specification MUST exclude the classes from considering to be CDI beans if the classes are listed in the `beans.xml` under `excludes` elements.

4.2 Non-functional Requirements

CDI050 – The specification MUST NOT prevent an implementation from injecting OSGi services into CDI beans which are not deployed as OSGi bundles.

CDI052 – The specification MUST NOT prevent and implementation from CDI050 – The specification MUST NOT prevent an implementation from injecting OSGi services into CDI beans which are not deployed as OSGi bundles.

CDI051 – The specification SHOULD adhere to the current CDI programming model as much as possible.

4.3 Requirements from RFP 98 (OSGi/Java EE umbrella RFP)

JEE001 – A Java EE/OSGi system SHOULD enable the standard Java EE application artifacts (e.g. web application) to remain installed when a supporting Java EE runtime element (e.g. web container) is dynamically replaced.

JEE002 – RFCs that refer to one or more Java EE technologies MUST NOT impede the ability of an OSGi-compliant implementation to also be compliant with the Java EE specification.

JEE003 – RFCs that refer to one or more Java EE technologies MAY define the additional aspects of the technology that are required for the technology to be properly integrated in an OSGi framework but MUST NOT make any syntactic changes to the Java interfaces defined by those Java EE specifications.

JEE004 – RFCs whose primary purpose is integration with Java EE technologies MUST NOT require an OSGi Execution Environment greater than that which satisfies only the signatures of those Java EE technologies.

5 Technical Solution

5.1 Entities

- CDI – Contexts and Dependency Injection 1.0 (JSR-299), Contexts and Dependency Injection 1.1/1.2 (JSR346).
- CDI Provider – An implementation of the CDI 1.2 specification.
- CDI OSGi adapter – Adapts a given CDI Provider to the OSGi environment. This entity is implementation dependent and may or may not be separate from the CDI provider.
- CDI Bundle – A CDI-enabled OSGi bundle.
- CDI Container – A container for managed beans in a CDI Bundle. Each CDI Bundle has its own CDI container.
- CDI Extender – An application of the extender pattern to discover CDI Bundles and to manage the CDI container life-cycle on behalf of CDI Bundles.
- CDI Extension – A portable extension as defined in CDI 1.2.
- Extension Bundle – A bundle providing one or more CDI extensions. An extension bundle may or may not be a CDI Bundle at the same time.

- OSGi CDI Extension – A specific CDI extension for publishing and consuming OSGi services to or from managed beans by means of annotations. This is a mandatory part of this specification.

5.2 CDI Container Life-Cycle

The CDI Extender tracks all bundles becoming ACTIVE. When a tracked bundle is identified as a CDI Bundle, the CDI Extender creates a CDI Container for this bundle. When a tracked CDI Bundle is stopped, the CDI Extender stops the CDI Container for the given bundle.

Starting a CDI container requires scanning the CDI Bundle for managed bean candidate classes. Class loading scenarios are far more complex in OSGi than in Java EE or Java SE, due to the modular and dynamic nature of the OSGi environment.

The bean scanner needs to consider all classes on the bundle classpath of the CDI Bundle, including any embedded archives or directories and fragments. This maps to the resources returned via the `BundleWiring.listResources("/", "*.class", 0)` method call. The imported classes will not be included as beans.

The set of candidate bean classes determined by the bean scanner is *not* equal to the set of managed beans in the bean container: The CDI Provider discards all candidate classes that do not satisfy the requirements for managed beans. The set of managed beans may be further extended or modified by CDI extensions.

5.2.1 Initialization of a CDI Container

A CDI extender manages the life cycle of a CDI bundle based on:

- The CDI bundle state
- The injection state
- The CDI extender's bundle statement

All activities on behalf of the CDI bundle must use the Bundle Context of the CDI bundle. All dynamic class loads must use the CDI bundle's `Bundle.loadClass` method.

In the following description of the initialization steps, The CDI Container will update its state. State changes are broadcast as events [5.11.1]

If any failures occur during initialization, or the CDI bundle or CDI extender bundle is stopped, the CDI container must be destroyed.

5.2.1.1 Initialization steps

The initialization process of a CDI Container is defined in the following steps:

1. Wait until a CDI bundle is ready. A CDI bundle is ready when it is in the ACTIVE state, and for CDI bundles that have a lazy activation policy, also in the STARTING state.
2. State = CREATING and fire 'Creating' event
3. Processing injection points


4. If all mandatory service references are satisfied, the CDI Container is ready to provide component instances. Otherwise, it enters state=WAITING and fire 'Waiting' event.
5. When the mandatory services references are satisfied, the CDI Container is now ready to provide component instances.
6. State= CREATED and fire 'Created' event
7. Register the CDI Container.
8. The components are now active and perform their function until the CDI bundle or the CDI extender bundle are stopped
9. When the CDI bundle is stopped, the CDI container will go to destroying state. State = DESTROYING and fire 'Destroying' event
10. perform the Destroy phase
11. State=DESTROYED and fire 'Destroyed' event

5.2.1.2 Failure

If at any time there is a failure, the CDI Container must perform the following steps:

1. State= FAILURE
2. Unregister the CDI Container service
3. Destroy the CDI Container
4. Wait for the CDI bundle to be stopped

5.2.1.3 Diagram



5.2.1.4 Runtime Phase

The CDI Container must be registered as a service with the following service properties:

`osgi.cdi.container.symbolicname` – The bundle symbolic name of the CDI bundle

`osgi.cdi.container.version` – The version of the CDI bundle

The CDI container service must only be available during the runtime phase when initialization has succeeded.

As long as the CDI extender and the CDI bundle is active, the application is in the runtime phase.

5.2.1.5 Destroy the CDI Container

The CDI Container must be destroyed when any of the following condition becomes true:

- The CDI bundle is stopped.
- The CDI extender is stopped
- One of the initialization phases failed.

Destroying the CDI Container means:

- Unregistering the CDI Container service
- Destroying all component instances in reverse dependency order

A CDI Container must continue to follow the destruction even when component instances throw exceptions or other problems occur. These errors should be logged.

If the CDI extender is stopped, then all its active CDI Containers must be destroyed in an orderly fashion, synchronously with the stopping of the CDI extender bundle. The CDI Containers must be destroyed, using the the following algorithm:

1. Destroy CDI Containers that do not have any services registered that are in use by other bundles.
2. The previous step can have released services, therefore, repeat step 1 until on more CDI Containers can be destroyed.
3. If there are still CDI Containers that are not destroyed, then destroy the CDI Containers with:
 - The registered service that is in user with the lowest ranking number.
 - The highest registered service id

If there there still CDI Containers to be destroyed, retry step 1

During the shutting down of an OSGi framework, it is likely that many bundles are stopped near simultaneously. The CDI extender should be to handle this case, without deadlock, when the stop of a CDI Bundle overlaps with the stop of the CDI extender bundle.

5.2.1.6 Failure

If a failure occurs during the initialization of the CDI bundle, then first a FAILURE event must be posted. Then the CDI Container should be destroyed, ensuring that no uninitialized or half initialized objects are destroyed.

5.3 Requirements and Capabilities

Bean deployment archives according to CDI 1.0 are required to opt in to OSGi enrichment by the CDI Extender. However, opting in may have no effect at all if a would-be CDI Bundle is installed and started in a system where no CDI Extender is available.

This kind of dependency can be made explicit using capabilities (introduced in OSGi Core 4.3). Capabilities are also useful to express a loose dependency on a given CDI extension. This covers the following use case:

CDI Bundle A works with a CDI extension with an annotation API defined in bundle B and an extension implementation in bundle C. A has a package dependency on B, but not on C. There is only an implicit runtime dependency on C. C needs to be resolved when the CDI container for A is constructed, so that the extension can modify the set of managed beans, but C may not be available at all.

Extension capabilities are a means to declare a dependency on a given extension *by name* and not by implementation.

For these reasons, this specification defines the following capabilities.

- An OSGi extender capability named `osgi.cdi`.
- A capability `osgi.cdi.extension` with a mandatory attribute `extension = <name>`, where `<name>` is a logical name for the given extension. The name `osgi.cdi` is reserved for the OSGi CDI extension defined in this specification.

A CDI Bundle MUST require the OSGi extender capability named `osgi.cdi`, e.g.

```
Require-Capability: osgi.extender; filter:="(osgi.extender=osgi.cdi) "
```

(Note that this is not a *sufficient* condition for a bundle to be a CDI Bundle. A CDI Bundle must also be a bean deployment archive as defined in CDI 1.2, i.e. it contains a `beans.xml` descriptor in one of the defined locations with a version number of 1.1 or later and the `bean-discovery-mode` of 'all' or with no version number or that is an empty file. Alternatively, it contains one or more bean classes with a bean defining annotation as defined by the JSR346,.)

A CDI bundle can define a list of bean classes, where the classes must be defined in this bundle not imported classes.

```
Provide-Capability: ...;beans:List<String>="foo.A,foo.B".
```

The bean classes will be filtered based on the `beans.xml`. e.g. If `foo.A` is excluded by `beans.xml`, `foo.A` will not be included. If there is no `beans.xml`, the above defined list will be the bean classes of the bundle and a scan will not be performed. If no list is provided and no `beans.xml` exists, a scan will be performed to find bean classes.

A CDI Bundle MAY require additional `osgi.cdi.extension` capabilities with other filter attributes for other CDI extensions.

A CDI Extender implementation MUST provide the `osgi.extender` capability named `osgi.cdi` with version 1.0, e.g.

```
Provide-Capability = osgi.extender; osgi.extender=osgi.cdi; version=1.0
```


Future versions of this specification will require higher version numbers.

An OSGi-enabled CDI extension MUST provide an `osgi.cdi.extension` capability with a distinctive name, e.g.

```
Provide-Capability = osgi.cdi.extension; extension=frobnicator
```

5.4 Managed Beans and OSGi Services

Publishing a service in OSGi



```

@Service(properties = {@ServiceProperty(key = "key",
value = "value"), @ServiceProperty(key = "key2",
value = "42", type = "long")})
public class ExampleComponent {}
  
```

A class can be published to the OSGi service registry using the `@org.osgi.service.cdi.Service` annotation. Note that classes that are already CDI beans, are not automatically published to the service registry; the `@Service` annotation or metadata as described in section 5.4.1 is always required for this. The requirement to explicitly annotate a bean to be an OSGi component is necessary for the following reasons:

1. In CDI 1.2 every class is a potential CDI bean, no annotations are required for this. The container scans injection points at container startup time to calculate which classes should be registered as beans. A CDI container in OSGi is scoped to a single bundle, and will only know about injection points in that bundle. OSGi services however can be used by other bundles as well. Although it is technically possible to find injection points in all bundles, this would be very hard to reason about for end users.
2. Not each CDI bean should be registered to the service registry. CDI is often used to inject tightly coupled classes into each other. This is fine for internal bundle usage, but should not be reflected in the service registry.

3. Not all CDI beans might be exported. It's useless to publish services of types that other bundles can't have access to.

This behavior is different then the behavior described in the EJB integration specification, where all EJBs are published as OSGi services by default. Although technically EJBs and CDI beans are very similar, their usage in practice is often very different. EJBs tend to be used in a similar granularity as OSGi services, while CDI beans are not.

An example `@Service` annotation:

```
@Service(interfaces={A.class})
public class MyComponent implements A,B {}
```

The `interfaces` annotation element is optional. If not specified the component is registered in the OSGi Service Registry under all the interfaces it directly implements. If the component does not implement any interfaces it will be registered under its implementation class.

Service properties can be defined in the `@Service` annotation using the “properties” argument. The properties argument takes an array of `@ServiceProperty` annotations. The `@ServiceProperty` annotations requires a key and value to be set, both of type String. An optional type element can be used to specify the data type of the property value. Supported data types are: service property values may only be one of the following types:

- Scalar – String, Integer, Long, Float, Double, Byte, Short, Character, Boolean.
- Array – An array of the allowable scalar types, declared using the following syntax: `String[]` or `Float[]`.
- Collection – A list or set that contains scalar types declared using the following syntax: `List<String>` or `Set<Short>`.

```
@Service(properties = {@ServiceProperty(key = "key", value = "value"), @ServiceProperty(key = "key2", value = "42", type = "long")})
public class ExampleComponent {}
```

5.4.1 Publishing plain CDI providers in the Service Registry

To support integration of existing CDI provider classes with OSGi an alternative to the `@Service` annotation is available via the OSGi bundle manifest. This allows beans that act as providers in plain CDI environments to participate in the OSGi integration as services without having to change and recompile these components. A class can be declared as a component in the manifest through the `component` directive on the `osgi.extender=osgi.cdi` requirement:

```
Require-Capability: osgi.extender;
    filter:="(osgi.extender=osgi.cdi)";
    components:="org.acme.MyComponent,org.acme.ExampleComponent"
```

5.5 Scopes for beans annotated as `@Service`

The following table outlines the CDI scopes and their support by this specification:

<code>@ApplicationScoped</code>	Same as <code>@Singleton</code> .
<code>@ConversationScoped</code>	Web request specific
<code>@Dependent</code>	Default, map to <code>@Singleton</code>
<code>@SessionScoped</code>	Web request specific
<code>@Singleton</code>	Same as <code>@SingletonScoped</code>


@RequestScoped	web request specific
----------------	----------------------

The following table lists OSGi-defined scopes and associated behavior. These scopes are only relevant for CDI beans registered in the OSGi Service Registry:

@BundleScoped	Maps to OSGi Service Factory
@PrototypeScoped	Maps to OSGi Prototype Service Factory
@SingletonScoped	Maps to normal OSGi singleton service

5.6 Life-Cycle

Inject OSGi services in CDI beans



The life-cycle of an `@Service` is different from a normal CDI bean, because it has to deal with service dynamics. An `@Service` may have dependencies on other OSGi services which can influence the life-cycle of the `@Service` as described in the next section.

An OSGi service can be injected into another OSGi Service or a CDI bean using the standard `@Inject` annotation. The life-cycle of an OSGi service is different than a plain CDI bean however. By default, a CDI bean has the *Dependent* scope; it's life-cycle is bound to the life-cycle of the consuming bean, or alternatively it's scope is defined using annotations. For a mapping of CDI scope to OSGi behaviour, see section 5.5, however not all CDI scopes are supported in an OSGi environment. Another difference is that there may be multiple OSGi services publishing the same interface, a client may or may not choose a specific instance using service properties and ordering.


Because of the differences between the CDI BeanManager and OSGi service registry and to remove ambiguity we must always use `@Reference` CDI qualifier to instruct the CDI container (and the developer) that we are dealing with a specific type of bean, where different rules may apply. When the `@Reference` annotation is used, the CDI container will lookup the OSGi service in the service registry and inject it's instance into the CDI bean.

Any OSGi service registered in the service registry can be injected using CDI, even if the service was not registered using CDI but with the low level service API or DS for example.

5.6.1 Required dependencies (@Service only)

Require a dependency; the component will not be registered when a required dependency is not available. This is the default behavior. When all dependencies becomes available, the component will be registered. If at some point during runtime a required dependency becomes unavailable, the component will be deregistered again. This model handles service dynamics correctly, while the code doesn't have to handle the case where dependencies are not available.

As an example we have the dependency structure:




When C becomes unavailable, B will become unavailable as well, and so will A. When C becomes available again, so will be B, and so will A.

5.6.2 Optional dependencies

To deal with service dynamics a proxy is injected instead of the real reference to the service. The proxy is by default a null-object, every method invocation should return null. The code that uses an optional dependency must deal with the possibility that the service is not available and handle null values properly.

Alternatively the `@Reference` supports a configuration parameter “proxyType” that can be used to configure the proxy to throw a `org.osgi.cdi.ServiceNotAvailableException` when the proxy is invoked while the service is not available. This way clients can handle null values returned by the real service differently than the situation where the service is not available.

Optional and required dependencies can be mixed in a single component and in the dependency graph of a component. Take the following example again, note that the dependency on C is now optional.



When C becomes unavailable, B should still be available, and therefore A as well. When B becomes unavailable, A should still become unavailable as well. Because the dependency on C is now optional, the code of B should be handling the fact that method invocations on C might return null or throw exceptions.

CDI does not support dynamic dependencies. All beans must be registered and all dependencies must be resolved at container startup. For normal CDI beans the container should resolve `@Inject` `@Reference` injection points immediately with proxies as described for optional dependencies. Required dependencies are not required to be implemented by the container for normal CDI beans; the container may throw an exception to inform the developer that the required attribute is not supported. A CDI container may implement required dependencies for normal CDI beans as well too however.

For components registered with the `@Service` annotation, required dependencies must be supported. An `@Service` with unavailable dependencies must not be registered to the OSGi service registry, and it's `@PostConstruct` method must not be invoked. If the component was active before the dependency became unavailable, the `@PreDestroy` method must be called and the service must be de-registered from the service registry.

Because OSGi services are dynamic, a developer should make the explicit choice to inject beans using the OSGi service registry by using the `@Reference` qualifier. If the `@Reference` qualifier is not used, the container should not query the service registry. `@Reference` can be used on fields or method parameters.

5.6.3 Allowing Service Injections in vanilla CDI injection points

As described in previous sections, the life-cycle and dynamics of OSGi makes this a fundamentally different environment to the JavaEE container for which CDI was originally designed. This is one of the key reasons for introducing the `@Reference` annotation to go with the `@Inject` annotation.

However in certain scenarios it may be desirable allow injections from the OSGi service registry into plain `@Inject` injection points. This is to allow migration paths from pure JavaEE to configurations where unmodified CDI beans are injected with services from the OSGi service registry. Clearly such a situations introduce risks and

analysis of the system is necessary beforehand to ensure that no fatal situations can occur by the introduced dynamics.

Once satisfied that the system can cope in the OSGi environment, injection into pure `@Inject` points can be enabled by setting a directive on the extender requirement in the CDI Bundle:

```
Require-Capability: osgi.extender;  
    filter:="(osgi.extender=osgi.cdi)";  
    at-service:="optional"
```

5.6.4 Service and bundle registration observers

In most situations service dependencies are injected directly into a field. Sometimes some extra code needs to be executed however. This can be done using callback methods. There is a callback method for service registration and a callback for service deregistration. The parameters of the observer method should be the type of the service.

Only events fired while the bundle containing the observer methods are delivered. Events fired while the bundle was not active are ignored.

```
void serviceAdded(@Observes @ServiceAdded SomeService) ;  
void serviceRemoved(@Observes @ServiceRemoved SomeService) ;  
void serviceModified(@Observes @ServiceModified SomeService) ;
```

In some cases it's useful to also have access to the `ServiceReference` representing a service. For this case a special event type is introduced:

```
public class ServiceCdiEvent<T> {  
    private ServiceReference<T> reference;  
    private T service;  
    // constructor and getters etc.  
}
```

```
void serviceAdded(@Observes @ServiceAdded ServiceCdiEvent<SomeService> event)  
void serviceRemoved(@Observes @ServiceRemoved ServiceCdiEvent<SomeService> event)
```

The `@ServiceAdded` and `@ServiceRemoved` annotations have the same service filtering semantics as `@Reference` described in the following section.

5.6.5 Service Filters

Service filtering can be done using the `@Reference` value parameter using the standard OSGi service filter (LDAP like) syntax:

```
@Reference("(somekey=somevalue")
```

As a convenience alternatively the same could be done using CDI Qualifiers:

```
@Qualifier
```

```
@ReferenceFilter
```

```
public @interface SomeKey {
```

```
String value();
```

```
}
```

```
@Inject @Reference @SomeKey("somevalue")
```

```
MyService service;
```

The name of the qualifier is used as the name of the property, the value passed into the qualifier annotation the value. If the value is not a String (e.g. an enum value), the String representation of the value is used. If the qualifier has a default value, the annotation can be used without specifying a value. In the following example the used filter is "(somekey=somevalue)". This mechanism provides a slightly more type-safe approach to using service filters.

```
@Qualifier
```

```
@ReferenceFilter
```

```
public @interface SomeKey {
```

```
String value() default "somevalue";
```

```
}
```

```
@Inject @Reference @SomeKey
```

```
MyService service;
```

It is possible to combine multiple qualifiers to create AND filters. In the following example both annotations are qualifiers, and the resulting filter is "(&(somekey=somevalue)(someotherkey=someothervalue))".

```
@Inject @Reference @SomeKey("somevalue") @SomeOtherKey("someothervalue")
```

```
MyService service;
```

More complex filters are not supported using qualifiers, the standard filter syntax should be used instead with the `@Reference` annotation.

When using OSGi service filters it is common to use dots in property names, e.g. 'service.ranking'. It is not possible however to use dots in a Java Annotation type name. To work around this issue the Annotation type name is parsed and certain markers in the name are interpreted as dots. Because service properties are case insensitive, camel casing can be used as a marker.

For example the qualifier `@MyServiceProperty("example")` translates to "(my.service.property=example)". The first character is lowercased. Each following capital is translated to a dot.

Requiring configuration

An `@Service` can require a Config Admin Configuration object with a specific PID. The component will only become available when a configuration object with the specified PID is found. This is useful when a component does not have usable default configuration values. If the configuration object is not available, the behaviour is the same as for a unavailable required service dependency.

A configuration dependency can be configured as follows:

```
@Service(requireConfiguration="PID.of.configuration")
```

5.7 BundleContext injection

It's possible to inject the BundleContext using CDI annotations.

```
@Inject BundleContext context;
```

This will always inject the BundleContext of the bundle that registered the component, even if the component's class was imported from another bundle. For example we could have the following scenario. Although the @Inject BundleContext annotation is declared in a class exported by Bundle A, Bundle B does the actual component registration. This means that the BundleContext of bundle B will be injected.

Bundle A

```
public abstract class MyBaseClass {  
  
    @Inject BundleContext bundleContext;  
  
}
```

Bundle B

```
@Service  
  
public class MySubClass extends MyBaseClass {  
  
}
```

5.8 BeanManager service

The implementation will register a service registered under the `javax.enterprise.inject.spi.BeanManager` interface. The BeanManager provides a standard portable introspective interfaces into the CDI container.

The BeanManager service is registered under the Bundle Context of the associated CDI bundle, as each CDI bundle has its own container. As a result many CdiContainer services will be present in the system.

5.9 osgi.extender Capability

The implementation must provide an `osgi.extender` capability as follows:

```
Provide-Capability: osgi.extender;  
    osgi.extender="osgi.cdi";  
    uses:="org.osgi.service.cdi,javax.enterprise.inject.spi";  
    version:Version="1.0"
```

5.10 osgi.contract Capability

The OSGi Enterprise specification version 5 defines the `osgi.contract` capability namespace and RFC 180 defines mappings of JSR-defined technologies to these capabilities. Relevant technologies from RFC 180 to this specification are the `JavaCDI` and `JavaInject` API contracts.

An implementation of this specification is not required to export the associated `javax.**` packages, but if it does, it must also provide the `JavaCDI` and `JavaInject` capabilities in the `osgi.contract` namespace.

5.11 Events

The CDI Container must track all CDI Listener services and keep the listeners updated of the progress of all its managed bundles.

CDI Events must be sent to each registered CDI Listeners service. The service has the following method:

- `cdiEvent(CdiEvent)` – notify the listener of a new CDI Event synchronously.

5.11.1 CDI Event

The CDI Event supports the following event types:

- **CREATING** - The CDI extender has started creating a CDI Container for the bundle.
- **CREATED** - The CDI Container is ready. The application is now running.
- **WAITING** - A service reference is blocking because of unsatisfied mandatory dependencies. This event can happen multiple times in a row.
- **DESTROYING** - The CDI Container is being destroyed because the CDI bundle or CDI extender has stopped.
- **DESTROYED** - The CDI Container is completely destroyed.
- **FAILURE** - An error occurred during the creation of the CDI Container.

The CDI Event provides the following methods:

- `getBundle()` - The CDI bundle
- `getCause()` - Any occurred exception or null
- `getDependencies()` - A list of filters that specify the unsatisfied mandatory references.
- `getExtenderBundle()` - The CDI extender bundle.
- `getTimestamp()` - The time the event occurred
- `getType()` - The type of the event.
- `isReplay()` - Indicates if the event is a replay (`true`) or if it is a new event (`false`)

5.11.2 Replay

The CDI Extender must remember the last CDI Event for each ready bundle that it manages. The replay event must be delivered to the CDI Listener service as the first event, before any other event is delivered , during the registration of the CDI Listener service. The `CdiEvent` object for a replay event must return `true` for the `isReplay()` method in this situation, and `false` in all other situations.

6 Data Transfer Objects

RFC 185 defines Data Transfer Objects as a generic means for management solutions to interact with runtime entities in an OSGi Framework. DTOs provides a common, easily serializable representation of the technology.

For all new functionality added to the OSGi Framework the question should be asked: would this feature benefit from a DTO? The expectation is that in most cases it would.

The DTOs for the design in this RFC should be described here and if there are no DTOs being defined an explanation should be given explaining why this is not applicable in this case.

This section is optional and could also be provided in a separate RFC.

7 Javadoc

OSGi Javadoc

10/14/13 12:26 PM

Package Summary		Page
org.osgi.service.cdi	CDI Integration Package Version 1.0.	29

Package org.osgi.service.cdi

CDI Integration Package Version 1.0.

See:

[Description](#)

Interface Summary		Page
CdiContainer	A CdiContainer object is registered by the the cdi extender in the OSGi registry for each managed CDI bundle.	31
CdiListener	A CdiListener object can be registered in the OSGi registry.	35

Class Summary		Page
CdiEvent	CdiEvent are sent by the cdi extender and received by registered CdiListener services.	32
ComponentEvent	CDI Event sent by the CDI extender whenever a component has been registered or unregistered to/from the OSGi registry.	37
Constants	Defines CDI constants	41
ServiceEvent	The event sent by the CDI extender whenever a service that matches an injection point is registered or unregistered from the OSGi registry.	45

Enum Summary		Page
ServiceType	Defines the type of service injected.	48

Exception Summary		Page
ServiceNotAvailableException	Exception that can be thrown from the injected Service if a matching service is not available.	46

Annotation Types Summary		Page
Component	The @Component annotation exposes a CDI bean in the OSGi registry.	36
ComponentProperty	Annotation used to define a property that will be associated to Component registered in the OSGi registry.	38
ComponentRegistered	The @ComponentRegistered can be used to observe ComponentEvent events whenever a component has been registered from the OSGi registry.	39
ComponentUnregistered	The @ComponentUnregistered can be used to observe ComponentEvent events whenever a component has been unregistered from the OSGi registry.	40
Filter	The @Filter annotation can be used to filter objects.	42
Service	The @Service annotation can be used to annotate a CDI injection point and inform the CDI extender that the injection should be done by a service grabbed from the OSGi registry.	43
ServiceAdded	The @ServiceAdded can be used to observe ServiceEvent events whenever a matching service injected via @Service is registered in the OSGi registry.	44
ServiceRemoved	The @ServiceRemoved can be used to observe ServiceEvent events whenever a matching service injected via @Service is unregistered in the OSGi registry.	47

Package org.osgi.service.cdi Description

CDI Integration Package Version 1.0.

Bundles wishing to use this package must list the package in the Import-Package header of the bundle's manifest. This package has two types of users: the consumers that use the API in this package and the providers that implement the API in this package.

Example import for consumers using the API in this package:

```
Import-Package: org.osgi.service.cdi; version="[1.0,2.0)"
```

Example import for providers implementing the API in this package:

```
Import-Package: org.osgi.service.cdi; version="[1.0,1.1)"
```

Interface CdiContainer

org.osgi.service.cdi

public interface **CdiContainer**

A CdiContainer object is registered by the the cdi extender in the OSGi registry for each managed CDI bundle.

Method Summary		Page
BeanManager	getBeanManager ()	31

Method Detail

getBeanManager

BeanManager **getBeanManager** ()

Class CdiEvent

[org.osgi.service.cdi](#)

```
java.lang.Object
└─ org.osgi.service.cdi.CdiEvent
```

```
public class CdiEvent
extends Object
```

CdiEvent are sent by the cdi extender and received by registered CdiListener services.

See Also:
[CdiListener](#)

Field Summary		Pag e
static int	CREATED	32
static int	CREATING	32
static int	DESTROYED	33
static int	DESTROYING	33
static int	FAILURE	33

Constructor Summary		Pag e
CdiEvent (int type, org.osgi.framework.Bundle bundle, org.osgi.framework.Bundle extenderBundle)		33
CdiEvent (int type, org.osgi.framework.Bundle bundle, org.osgi.framework.Bundle extenderBundle, Throwable cause)		33
CdiEvent (CdiEvent event, boolean replay)		33

Method Summary		Pag e
org.osgi.f ramework.B undle	getBundle ()	33
Throwable	getCause ()	34
org.osgi.f ramework.B undle	getExtenderBundle ()	34
long	getTimestamp ()	33
int	getType ()	33
boolean	isReplay ()	34

Field Detail

CREATING

```
public static final int CREATING = 1
```

CREATED

```
public static final int CREATED = 2
```

DESTROYING

```
public static final int DESTROYING = 3
```

DESTROYED

```
public static final int DESTROYED = 4
```

FAILURE

```
public static final int FAILURE = 5
```

Constructor Detail

CdiEvent

```
public CdiEvent(int type,  
                org.osgi.framework.Bundle bundle,  
                org.osgi.framework.Bundle extenderBundle)
```

CdiEvent

```
public CdiEvent(int type,  
                org.osgi.framework.Bundle bundle,  
                org.osgi.framework.Bundle extenderBundle,  
                Throwable cause)
```

CdiEvent

```
public CdiEvent(CdiEvent event,  
                boolean replay)
```

Method Detail

getType

```
public int getType()
```

getTimestamp

```
public long getTimestamp()
```

getBundle

```
public org.osgi.framework.Bundle getBundle()
```

getExtenderBundle

```
public org.osgi.framework.Bundle getExtenderBundle()
```

getCause

```
public Throwable getCause()
```

isReplay

```
public boolean isReplay()
```

Interface CdiListener

org.osgi.service.cdi

public interface **CdiListener**

A CdiListener object can be registered in the OSGi registry. The cdi extender will call each listener whenever an event happens.

See Also:

[CdiEvent](#)

Method Summary		Pag e
void	cdiEvent (CdiEvent event)	35

Method Detail

cdiEvent

void **cdiEvent**([CdiEvent](#) event)

Annotation Type Component

org.osgi.service.cdi

```
@Qualifier
@Target (value={
    ElementType.FIELD,
    ElementType.TYPE,
    ElementType.PARAMETER,
    ElementType.CONSTRUCTOR
})
@Retention (value=RetentionPolicy.RUNTIME)
@Documented
public @interface Component
```

The @Component annotation exposes a CDI bean in the OSGi registry.

Required Element Summary		Page
Class<?>[]	interfaces	36
ComponentProperty []	properties	36
String	requireConfiguration	36

Element Detail

interfaces

```
public abstract Class<?>[] interfaces

    Default:
    {}
```

properties

```
public abstract ComponentProperty[] properties

    Default:
    {}
```

requireConfiguration

```
public abstract String requireConfiguration

    Default:
    ""
```

Class ComponentEvent

[org.osgi.service.cdi](#)

```
java.lang.Object
└─ org.osgi.service.cdi.ComponentEvent
```

```
public class ComponentEvent
extends Object
```

CDI Event sent by the CDI extender whenever a component has been registered or unregistered to/from the OSGi registry.

See Also:
[ComponentRegistered](#), [ComponentUnregistered](#), [javax.enterprise.event.Observes](#)

Constructor Summary	Page
ComponentEvent (org.osgi.framework.ServiceRegistration< T > registration, T service)	37

Method Summary	Page
org.osgi.framework.ServiceRegistration< T > getRegistration ()	37
T getService ()	37

Constructor Detail

ComponentEvent

```
public ComponentEvent (org.osgi.framework.ServiceRegistration<T> registration,
                        T service)
```

Method Detail

getRegistration

```
public org.osgi.framework.ServiceRegistration<T> getRegistration ()
```

getService

```
public T getService ()
```

Annotation Type ComponentProperty

org.osgi.service.cdi

```
@Retention(value=RetentionPolicy.RUNTIME)
public @interface ComponentProperty
```

Annotation used to define a property that will be associated to Component registered in the OSGi registry.

Required Element Summary		Page
String	key	38
String	value	38

Element Detail

key

```
public abstract String key
```

value

```
public abstract String value
```

Annotation Type `ComponentRegistered`

org.osgi.service.cdi

```
@Target (value=ElementType.PARAMETER)
@Retention (value=RetentionPolicy.RUNTIME)
@Documented
public @interface ComponentRegistered
```

The `@ComponentRegistered` can be used to observe `ComponentEvent` events whenever a component has been registered from the OSGi registry.

See Also:

[ComponentEvent](#), `javax.enterprise.event.Observes`

Annotation Type ComponentUnregistered

org.osgi.service.cdi

```
@Target(value=ElementType.PARAMETER)
@Retention(value=RetentionPolicy.RUNTIME)
@Documented
public @interface ComponentUnregistered
```

The `@ComponentUnregistered` can be used to observe `ComponentEvent` events whenever a component has been unregistered from the OSGi registry.

See Also:

[ComponentEvent](#), `javax.enterprise.event.Observes`

Class Constants

[org.osgi.service.cdi](#)

```
java.lang.Object
└─ org.osgi.service.cdi.Constants
```

```
final public class Constants
extends Object
```

Defines CDI constants

Field Summary		Page
static String	CDI_EXTENDER Opt-in manifest header, starting a CDI container	41
static String	CDI_EXTENSION_CAPABILITY	41
static String	EXTENDER_CAPABILITY	41

Field Detail

CDI_EXTENDER

```
public static final String CDI_EXTENDER = "osgi.cdi"

    Opt-in manifest header, starting a CDI container
```

EXTENDER_CAPABILITY

```
public static final String EXTENDER_CAPABILITY = "osgi.extender"
```

CDI_EXTENSION_CAPABILITY

```
public static final String CDI_EXTENSION_CAPABILITY = "osgi.cdi.extension"
```

Annotation Type Filter

org.osgi.service.cdi

```
@Target (value={
    ElementType.FIELD,
    ElementType.TYPE,
    ElementType.PARAMETER,
    ElementType.CONSTRUCTOR
})
@Retention (value=RetentionPolicy.RUNTIME)
@Documented
public @interface Filter
```

The @Filter annotation can be used to filter objects. It can be applied to @Service or @EventAdmin injection points.

See Also:
[Service](#), EventAdmin

Required Element Summary		Pag e
String	value	42

Element Detail

value

```
public abstract String value
```

Default:
""

Annotation Type Service

org.osgi.service.cdi

```
@Qualifier
@Target (value={
    ElementType.FIELD,
    ElementType.PARAMETER,
    ElementType.CONSTRUCTOR
})
@Retention (value=RetentionPolicy.RUNTIME)
@Documented
public @interface Service
```

The @Service annotation can be used to annotate a CDI injection point and inform the CDI extender that the injection should be done by a service grabbed from the OSGi registry.

See Also:
[Filter](#)

Required Element Summary		Page
boolean	required	43
ServiceType	type	43

Element Detail

required

```
public abstract boolean required

    Default:
        false
```

type

```
public abstract ServiceType type

    Default:
        ServiceType.NullObject
```

Annotation Type ServiceAdded

org.osgi.service.cdi

```
@Target(value=ElementType.PARAMETER)
@Retention(value=RetentionPolicy.RUNTIME)
@Documented
public @interface ServiceAdded
```

The `@ServiceAdded` can be used to observe `ServiceEvent` events whenever a matching service injected via `@Service` is registered in the OSGi registry.

See Also:

[ServiceEvent](#), `javax.enterprise.event.Observes`

Class ServiceEvent

[org.osgi.service.cdi](#)

```
java.lang.Object
└─ org.osgi.service.cdi.ServiceEvent
```

```
public class ServiceEvent
extends Object
```

The event sent by the CDI extender whenever a service that matches an injection point is registered or unregistered from the OSGi registry.

See Also:
[ServiceAdded](#), [ServiceRemoved](#), [javax.enterprise.event.Observes](#)

Constructor Summary	Page
ServiceEvent (org.osgi.framework.ServiceReference< T > reference, T service)	45

Method Summary	Page
org.osgi.framework.ServiceReference< T > getReference ()	45
T getService ()	45

Constructor Detail

ServiceEvent

```
public ServiceEvent (org.osgi.framework.ServiceReference<T> reference,
                    T service)
```

Method Detail

getReference

```
public org.osgi.framework.ServiceReference<T> getReference ()
```

getService

```
public T getService ()
```

Class ServiceNotAvailableException

[org.osgi.service.cdi](#)

```
java.lang.Object
├─ java.lang.Throwable
│   └─ java.lang.Exception
│       └─ java.lang.RuntimeException
│           └─ org.osgi.service.cdi.ServiceNotAvailableException
```

All Implemented Interfaces:
Serializable

```
public class ServiceNotAvailableException
extends RuntimeException
```

Exception that can be thrown from the injected Service if a matching service is not available.

Constructor Summary	Page
ServiceNotAvailableException (String message)	46

Constructor Detail

ServiceNotAvailableException

```
public ServiceNotAvailableException(String message)
```

Annotation Type **ServiceRemoved**

org.osgi.service.cdi

```
@Target (value=ElementType.PARAMETER)
@Retention (value=RetentionPolicy.RUNTIME)
@Documented
public @interface ServiceRemoved
```

The `@ServiceRemoved` can be used to observe `ServiceEvent` events whenever a matching service injected via `@Service` is unregistered in the OSGi registry.

See Also:

[ServiceEvent](#), `javax.enterprise.event.Observes`

Enum `ServiceType`

[org.osgi.service.cdi](#)

```
java.lang.Object
├─ java.lang.Enum<ServiceType>
│   └─ org.osgi.service.cdi.ServiceType
```

All Implemented Interfaces:

`Comparable<ServiceType>`, `Serializable`

```
public enum ServiceType
extends Enum<ServiceType>
```

Defines the type of service injected.

Enum Constant Summary

	Page
NullObject A dummy proxy that simply returns <code>null</code> when a matching OSGi service is not available.	48

Method Summary

	Page
static ServiceType valueOf (String name)	48
static ServiceType [] values ()	48

Enum Constant Detail

`NullObject`

```
public static final ServiceType NullObject
```

A dummy proxy that simply returns `null` when a matching OSGi service is not available.

Method Detail

`values`

```
public static ServiceType[] values()
```

`valueOf`

```
public static ServiceType valueOf(String name)
```

Java API documentation generated with [DocFlex/Doclet](#) v1.5.6


DocFlex/Doclet is both a multi-format Javadoc doclet and a free edition of [DocFlex/Javadoc](#). If you need to customize your Javadoc without writing a full-blown doclet from scratch, DocFlex/Javadoc may be the only tool able to help you! Find out more at www.docflex.com

8 Considered Alternatives

8.1 EventAdmin integration

This section has moved into the Considered Alternatives chapter as it's postponed to a later release.

Send EventAdmin event using CDI events



EventAdmin and CDI events are conceptually similar. The CDI programming model is much more user-friendly however. EventAdmin events can both be produced and observed using CDI annotations. Because not every event should be published to EventAdmin the developer has to use the `@EventAdmin` annotation. The value of this annotation should also contain the name of the *Topic*, or alternatively you can define your own qualifier that extends `@EventAdmin` to define the Topic.

The following is an example of using the `@EventAdmin` qualifier.

```
@Inject @EventAdmin("MyTopic") Event<MyEvent> event;

public void send() {
    event.fire(new MyEvent("example"));
}
```


The following is an example of extending the EventAdmin qualifier.

```
@EventAdmin
public @interface Demo {
```

```
String value();  
}  
  
@Inject @Demo Event<MyEvent> event;  
  
public void send() {  
    event.fire(new MyEvent("example"));  
}  
}
```

The CDI-OSGi bridge observes `@EventAdmin` events and republish them as EventAdmin events.

Listener to EventAdmin events using CDI observers



EventAdmin events can be observed using the CDI `@Observes` annotation. Similar to publishing EventAdmin events we need the `@EventAdmin` qualifier to specify the Topic name.

```
public class EventExample {  
  
    public void process(@Observes @EventAdmin("MyTopic") MyEvent event) {}  
  
}
```

Alternatively, similar with publishing events, a qualifier can be used to define the topic name.

```
@EventAdmin  
  
public @interface Demo {  
  
    String value();  
}
```

```
}

public class EventExample {

    public void process(@Observes @Demo MyEvent event) {}

}
```

9 Security Considerations

Description of all known vulnerabilities this may either introduce or address as well as scenarios of how the weaknesses could be circumvented.

10 Document Support

10.1 References

- [1]. Bradner, S., Key words for use in RFCs to Indicate Requirement Levels, RFC2119, March 1997.
- [2]. Software Requirements & Specifications. Michael Jackson. ISBN 0-201-87712-0
- [3]. **JSR 299: Contexts and Dependency Injection for Java EE platform**
- [4]. **JSR 346: Contexts and Dependency Injection for Java EE**
- [5]. **Weld OSGi Reference: <http://docs.jboss.org/weld/reference/1.2.0.Beta1/weld-osgi/user-guide/html/ch01.html>**

10.2 Author's Address

Name	Emily Jiang
Company	IBM
Address	Hursley Lab, UK, IBM
Voice	
e-mail	emijiang@uk.ibm.com

10.3 Acronyms and Abbreviations

10.4 End of Document
