



OSGiTM Alliance

RFC 220 Bundle Annotations

Draft

31 Pages

Abstract

In the light of the enRoute project bnd pioneered the use of build time annotations to generate manifest headers. The use of annotations makes it easier to manage manifest headers per component, significantly minimizes errors, and leverages the Java type system to provide content assist in IDEs.

0 Document Information

0.1 License

DISTRIBUTION AND FEEDBACK LICENSE, Version 2.0

The OSGi Alliance hereby grants you a limited copyright license to copy and display this document (the “Distribution”) in any medium without fee or royalty. This Distribution license is exclusively for the purpose of reviewing and providing feedback to the OSGi Alliance. You agree not to modify the Distribution in any way and further agree to not participate in any way in the making of derivative works thereof, other than as a necessary result of reviewing and providing feedback to the Distribution. You also agree to cause this notice, along with the accompanying consent, to be included on all copies (or portions thereof) of the Distribution. The OSGi Alliance also grants you a perpetual, non-exclusive, worldwide, fully paid-up, royalty free, limited license (without the right to sublicense) under any applicable copyrights, to create and/or distribute an implementation of the Distribution that: (i) fully implements the Distribution including all its required interfaces and functionality; (ii) does not modify, subset, superset or otherwise extend the OSGi Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the OSGi Name Space other than those required and authorized by the Distribution. An implementation that does not satisfy limitations (i)-(ii) is not considered an implementation of the Distribution, does not receive the benefits of this license, and must not be described as an implementation of the Distribution. “OSGi Name Space” shall mean the public class or interface declarations whose names begin with “org.osgi” or any recognized successors or replacements thereof. The OSGi Alliance expressly reserves all rights not granted pursuant to these limited copyright licenses including termination of the license at will at any time.

EXCEPT FOR THE LIMITED COPYRIGHT LICENSES GRANTED ABOVE, THE OSGi ALLIANCE DOES NOT GRANT, EITHER EXPRESSLY OR IMPLIEDLY, A LICENSE TO ANY INTELLECTUAL PROPERTY IT, OR ANY THIRD PARTIES, OWN OR CONTROL. Title to the copyright in the Distribution will at all times remain with the OSGi Alliance. The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted therein are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

THE DISTRIBUTION IS PROVIDED “AS IS,” AND THE OSGi ALLIANCE (INCLUDING ANY THIRD PARTIES THAT HAVE CONTRIBUTED TO THE DISTRIBUTION) MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DISTRIBUTION ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

NEITHER THE OSGi ALLIANCE NOR ANY THIRD PARTY WILL BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THE DISTRIBUTION.

Implementation of certain elements of this Distribution may be subject to third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a member of the OSGi Alliance). The OSGi Alliance is not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

The Distribution is a draft. As a result, the final product may change substantially by the time of final publication, and you are cautioned against relying on the content of this Distribution. You are encouraged to update any implementation of the Distribution if and when such Distribution becomes a final specification.

The OSGi Alliance is willing to receive input, suggestions and other feedback (“Feedback”) on the Distribution. By providing such Feedback to the OSGi Alliance, you grant to the OSGi Alliance and all its Members a non-exclusive, non-transferable,

worldwide, perpetual, irrevocable, royalty-free copyright license to copy, publish, license, modify, sublicense or otherwise distribute and exploit your Feedback for any purpose. Likewise, if incorporation of your Feedback would cause an implementation of the Distribution, including as it may be modified, amended, or published at any point in the future ("Future Specification"), to necessarily infringe a patent or patent application that you own or control, you hereby commit to grant to all implementers of such Distribution or Future Specification an irrevocable, worldwide, sublicenseable, royalty free license under such patent or patent application to make, have made, use, sell, offer for sale, import and export products or services that implement such Distribution or Future Specification. You warrant that (a) to the best of your knowledge you have the right to provide this Feedback, and if you are providing Feedback on behalf of a company, you have the rights to provide Feedback on behalf of your company; (b) the Feedback is not confidential to you and does not violate the copyright or trade secret interests of another; and (c) to the best of your knowledge, use of the Feedback would not cause an implementation of the Distribution or a Future Specification to necessarily infringe any third-party patent or patent application known to you. You also acknowledge that the OSGi Alliance is not required to incorporate your Feedback into any version of the Distribution or a Future Specification.

I HEREBY ACKNOWLEDGE AND AGREE TO THE TERMS AND CONDITIONS DELINEATED ABOVE.

0.2 Trademarks

OSGi™ is a trademark, registered trademark, or service mark of the OSGi Alliance in the US and other countries. Java is a trademark, registered trademark, or service mark of Oracle Corporation in the US and other countries. All other trademarks, registered trademarks, or service marks used in this document are the property of their respective owners and are hereby recognized.

0.3 Feedback

This document can be downloaded from the OSGi Alliance design repository at <https://github.com/osgi/design>. The public can provide feedback about this document by opening a bug at <https://www.osgi.org/bugzilla/>.

0.4 Table of Contents

0 Document Information.....	2
0.1 License.....	2
0.2 Trademarks.....	3
0.3 Feedback.....	3
0.4 Table of Contents.....	3
0.5 Terminology and Document Conventions.....	4
0.6 Revision History.....	4
 1 Introduction.....	 4
 2 Application Domain.....	 5
 3 Problem Description.....	 6
 4 Requirements.....	 6
 5 Technical Solution.....	 7
5.1 General.....	7
5.2 Export.....	8
5.3 Capability.....	8
5.4 Requirement.....	8
5.5 Header.....	8
5.6 Directive and Attribute.....	8
 6 Javadoc.....	 9

7 Considered Alternatives.....	30
8 Security Considerations.....	31
9 Document Support.....	31
9.1 References.....	31
9.2 Author's Address.....	31
9.3 Acronyms and Abbreviations.....	31
9.4 End of Document.....	31

0.5 Terminology and Document Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in 1.

Source code is shown in this typeface.

0.6 Revision History

The last named individual in this history is currently responsible for this document.

Revision	Date	Comments
Initial	2016-01-08	Initial draft. BJ Hargrave
2 nd draft	2016-01-12	Comments from Madrid CPEG mtg BJ Hargrave
3 rd draft	2016-01-21	Clean up after CPEG call BJ Hargrave

1 Introduction

This RFC is in response to RFP 167 Manifest Annotations. The OSGi enRoute project used annotations to define bundle metadata in source code. Bnd then processes the annotations into manifest headers.

This RFC will define OSGi standard annotations in support of those ideas.

2 Application Domain

Bnd/Bndtools provides a tool chain to build bundles and/or OSGi manifests used in most OSGi builds. It is supported in Maven, Gradle, Ant, SBT, etc. Bnd uses information in the class files to create a number of headers in the manifest.

Though the class files contain enough information to find the code dependencies, there are many dependencies that are indirect. For example, extenders are often a requirement to make a bundle function correctly but often have no code dependency between their clients whatsoever. Declarative Services (DS) went out of its way to allow components to be Plain Old Java Objects. The result is that the resolving a closure would not drag in the Declarative Services resulting in a satisfied but rather useless closure.

One of the goals of the enRoute project is to rely on Java and not escape to strings. The Java language is a rather steep cost from the point of view of coding but the type engine makes this cost-effective especially since it enables the IDE to assist the developers. However, when information then gets encoded in strings the advantages are voided and what is left is the cost.

Over the past few years a number of annotations were developed to control the creation of bundle resources. The most popular are the Declarative Services annotations and Metatype annotations. Over time these annotations have made it into the OSGi specifications. The OSGi enRoute project decided to develop a number of *manifest annotations*, annotations whose sole purpose is to generate the manifest headers.

Since the manifest headers for requirements and capabilities are error prone to use, the OSGi enRoute project added manifest annotations for the Require-Capability and Provide-Capability headers to bnd:

- `@RequireCapability(ns,effective,filter,resolution)`
- `@ProvideCapability(ns,name,effective,version,uses,mandatory)`

These annotations can be applied to a type or any other annotation. If applied to a type then the annotation's requirement or capability will be added to the manifest. If applied to an annotation then this annotation is a *customized annotation*. Nothing happens until the annotated annotation is used. When this annotation is applied somewhere, bnd will automatically add the requirement or capability to the manifest.

For example:

```
@RequireCapability(  
    ns          = "osgi.extender",  
    filter      = "(&(osgi.extender=osgi.enroute.configurer)${frange;1.2.3})",  
    effective   = "active")  
@Retention(RetentionPolicy.CLASS)  
public @interface RequireConfigurer {}
```

By itself the previous snippet is only a declaration, no actual requirement is added to the manifest. However, if the `@RequireConfigurer` annotation is used to annotate a type that is included in the bundle then the requirement is actually added to the manifest.

The annotations generate proper headers with any duplicates removed. All text fields of the annotations are also run through the macro preprocessor. One of the macros that was added specifically for this purpose was the `${frange;<version>}`, this macro created a version range in OSGi filter syntax. However, all `bnd` macros were available which then also provides access to the local package-info.

3 Problem Description

Entering manifest headers is error prone since these headers are complex and singletons. Because they are singletons, there is only one place where they can be entered. This is in contrast with the promoted component model. Components should be cheap and easy to rename or move between bundles. If a component is moved from one bundle to another bundle, it is easy to also move its corresponding headers from the manifest. This can cause orphaned headers or missing headers either in the old bundle or the new bundle. The old bundle can miss the header because multiple components were depending on that header but it was mistakenly removed.

The other problem is that these headers are notoriously hard to write, it often takes several trials to get all the parts of the requirements correct.

4 Requirements

- G0010 – It must be possible to provide the content of manifest headers through manifest annotations.
- G0020 – The following headers must be supported by dedicated annotations:
 - `Provide-Capability`
 - `Require-Capability`
- G0030 – It must be possible to enter a clause for a specific header through an annotation
- G0040 – It must be possible to create customized annotations for specific requirements. This can be done via a meta-annotation which can be used to define other custom annotations.

- G0060 – Generated headers must be valid OSGi or generate an error
- G0070 – The annotations must use enums and other Java constructs to enable type safety and IDE support
- G0080 – Duplicate clauses must be removed in the manifest
- G0100 – The solution must simplify the writing of a version import filter in a requirement.
- G0110 – DS and Metatype annotations must be retrofitted to use the meta-annotation from G0040.
- G0120 – The solution must include a package annotation for marking a package to be exported. The annotation must support specifying directives (e.g. mandatory, include, exclude) and attributes. The package version must come from the existing Version annotation.

5 Technical Solution

A new package, `org.osgi.annotation.bundle`, is defined containing new annotations for defining OSGi bundle metadata. These annotations are CLASS retention annotations to be processed by bundle assembly tools like Bnd.

5.1 General

When annotations support being applied to other annotations, so called meta-annotations, bundle assembly tools must look for the use of annotations which are meta annotated. This allows, for example, the DS Component annotation to be meta-annotated with a Requirement annotation for the `osgi.component` extender. So the use of the Component annotation by code in a bundle must then result in the bundle having a requirement on the `osgi.component` extender.

When annotations support Repeatable, bundle assembly tools must support the annotation container annotation holding the repeated annotation.

Bundle assembly tools must detect duplicate header information and remove duplicates. This is especially important given the support for meta-annotations. For example, there can be many DS components all annotated with Component which itself is meta-annotated with a Requirement for the `osgi.component` extender.

Since manifest headers only appear once in the manifest, bundle assembly tools must collect up all clauses for a specific manifest header separating the values with commas. For example, there can be multiple packages annotation with Export.

For OSGi specified manifest headers, the bundle assembly tool must check that the resulting manifest header is valid.

5.2 Export

An Export annotation is defined which can be applied to a package. The version of the package is taken from the Version annotation on the package. Other information regarding the package can be specified in the Export annotation including how the exported package should be substitutably imported.

5.3 Capability

A Capability annotation is defined to express a capability for a bundle. This annotation can be used as a meta-annotation and also applied to a package or class. This annotation supports Repeatable using the Capabilities container annotation.

A Capability annotation must specify the namespace of the capability. Other information regarding the capability can be specified including version, attributes and the uses and effective directive values.

5.4 Requirement

A Requirement annotation is defined to express a requirement for a bundle. This annotation can be used as a meta-annotation and also applied to a package or class. This annotation supports Repeatable using the Requirements container annotation.

A Requirement annotation must specify the namespace of the requirement. Other information regarding the requirement can be specified including filter and the effective, cardinality and resolution directive values.

5.5 Header

A Header annotation is defined to express a header for a bundle. This annotation can be used as a meta-annotation and also applied to a package or class. This annotation supports Repeatable using the Headers container annotation.

A Header annotation must specify the header name and value.

5.6 Directive and Attribute

Directive and Attribute annotations are defined which can be used when using Requirement and Capability as meta annotations. These annotations mark the annotated element as a directive or attribute of the generated requirement or capability.

For example:

```
@Requirement(namespace = "foo")
public @interface MyRequirement {
    @Attribute("foo")
    String value();
}
```

```
@MyRequirement("bar")
public class MyClass {}
```

This will result in the attribute `foo=bar` on the generated requirement.

6 Javadoc

OSGi Javadoc

1/12/16 12:34 PM

Package Summary		Page
org.osgi.annotation.bundle	OSGi Bundle Annotations Package Version 1.0.	11

Package org.osgi.annotation.bundle

@org.osgi.annotation.versioning.Version(value="1.0")

OSGi Bundle Annotations Package Version 1.0.

See:

[Description](#)

Enum Summary		Page
Export.Substitution	Substitution policy for this package.	19
Requirement.Cardinality	Cardinality for this requirement.	26
Requirement.Resolution	Resolution for this requirement.	28

Annotation Types Summary		Page
Attribute	Mark an annotation element as an attribute.	12
Capabilities	Container annotation for repeated Capability annotations.	13
Capability	Define a capability for a bundle.	14
Directive	Mark an annotation element as a directive.	16
Export	Mark a package to be exported from its bundle.	17
Header	Define a manifest header for a bundle.	21
Headers	Container annotation for repeated Header annotations.	22
Requirement	Define a requirement for a bundle.	23
Requirements	Container annotation for repeated Requirement annotations.	30

Package org.osgi.annotation.bundle Description

OSGi Bundle Annotations Package Version 1.0.

This package is not used at runtime.

Annotation Type Attribute

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value=ElementType.METHOD)
public @interface Attribute
```

Mark an annotation element as an attribute.

This is used when applying [Capability](#) or [Requirement](#) as a meta annotation to an annotation declaration. The value of the annotation element annotated with `Attribute` is used as the value of an attribute in the generated capability or requirement clause. For example:

```
@Capability(namespace = "my.namespace")
public @interface MyCapability {
    @Attribute("attr")
    String value();
}

@MyCapability("foo")
public MyClass {}
```

The use of the `MyCapability` annotation, which is meta annotated with the `Capability` and `Attribute` annotations, will result in a capability in the namespace `my.namespace` with the attribute `attr=foo`.

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests.

Required Element Summary		Page
String	value The name of the attribute.	12

Element Detail

value

```
public abstract String value
```

The name of the attribute.

If not specified, the name of the annotated element is used as the name of the attribute.

Default:
""

Annotation Type Capabilities

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
public @interface Capabilities
```

Container annotation for repeated [Capability](#) annotations.

Required Element Summary		Page
Capability []	value Repeated Capability annotations.	13

Element Detail

value

```
public abstract Capability[] value

    Repeated Capability annotations.
```

Annotation Type Capability

[org.osgi.annotation.bundle](https://www.osgi.org/specs/standard/annotation/1.3.0/)

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
@Repeatable(value=Capabilities.class)
public @interface Capability
```

Define a capability for a bundle.

For example:

```
@Capability(namespace=ExtenderNamespace.EXTENDER_NAMESPACE,
    name="osgi.component", version="1.3.0")
```

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests or otherwise process the type or package.

Required Element Summary		Page
String[]	attribute A list of attribute or directive names and values.	15
String	effective The effective time of this capability.	15
String	name The name of this capability within the namespace.	14
String	namespace The namespace of this capability.	14
Class<?>[]	uses A list of classes whose packages are inspected to calculate the <code>uses</code> directive for this capability.	15
String	version The version of this capability.	15

Element Detail

namespace

```
public abstract String namespace
```

The namespace of this capability.

name

```
public abstract String name
```

The name of this capability within the namespace.

If specified, adds an attribute with the name of the namespace and the value of the specified name to the capability clause.

Default:
""

version

```
public abstract String version
```

The version of this capability.

If specified, adds an attribute with the name and type of `version:Version` and the value of the specified version to the capability clause.

The specified version must be a valid OSGi version string.

Default:
""

uses

```
public abstract Class<?>[] uses
```

A list of classes whose packages are inspected to calculate the `uses` directive for this capability.

If not specified, the `uses` directive is omitted from the capability clause.

Default:
{}

effective

```
public abstract String effective
```

The effective time of this capability.

Specifies the time the capability is available. The OSGi framework resolver only considers capabilities without an effective directive or `effective:=resolve`. Capabilities with other values for the effective directive can be considered by an external agent.

If not specified, the `effective` directive is omitted from the capability clause.

Default:
"resolve"

attribute

```
public abstract String[] attribute
```

A list of attribute or directive names and values.

Each string should be specified in the form:

- ! "name=value" for attributes.
- ! "name:type=value" for typed attributes.
- ! "name:=value" for directives.

These are added, separated by semicolons, to the export package clause.

Default:
{}

Annotation Type Directive

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value=ElementType.METHOD)
public @interface Directive
```

Mark an annotation element as a directive.

This is used when applying [Capability](#) or [Requirement](#) as a meta annotation to an annotation declaration. The value of the annotation element annotated with `Directive` is used as the value of a directive in the generated capability or requirement clause. For example:

```
@Capability(namespace = "my.namespace")
public @interface MyCapability {
    @Directive("resource")
    String value();
}

@MyCapability("foo")
public MyClass {}
```

The use of the `MyCapability` annotation, which is meta annotated with the `Capability` and `Directive` annotations, will result in a capability in the namespace `my.namespace` with the directive `resource:=foo`.

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests.

Required Element Summary		Page
String	value The name of the directive.	16

Element Detail

value

```
public abstract String value
```

The name of the directive.

If not specified, the name of the annotated element is used as the name of the directive.

Default:
""

Annotation Type Export

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value=ElementType.PACKAGE)
public @interface Export
```

Mark a package to be exported from its bundle.

The package must also be annotation with the `org.osgi.annotation.versioning.Version` annotation to specify the export version of the package.

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests or otherwise process the package.

Nested Class Summary		Page
static enum	Export.Substitution Substitution policy for this package.	19

Required Element Summary		Page
String[]	attribute A list of attribute or directive names and values.	17
Export.Substitution	substitution Specify the policy for substitutably importing this package.	18
String[]	uses A list of package names that are used by this package.	17

Element Detail

uses

```
public abstract String[] uses
```

A list of package names that are used by this package.

If the `uses` directive must be omitted from the export package clause for this package, the empty value `{}` must be specified.

If not specified, the `uses` directive for the export package clause is calculated by inspection of the classes in this package.

Default:
`{}`

attribute

```
public abstract String[] attribute
```

A list of attribute or directive names and values.

Each string should be specified in the form:

```
! "name=value" for attributes.
```

```
! "name:type=value" for typed attributes.  
! "name:=value" for directives.
```

These are added, separated by semicolons, to the export package clause.

Default:
{}

substitution

```
public abstract Export.Substitution substitution
```

Specify the policy for substitutably importing this package.

Bundles that collaborate require the same class loader for types used in the collaboration. If multiple bundles export packages with collaboration types then they will have to be placed in disjoint class spaces, making collaboration impossible. Collaboration is significantly improved when bundles are willing to import exported packages; these imports will allow a framework to substitute exports for imports.

If not specified, the [Export.Substitution.CALCULATED](#) substitution policy is used for this package.

Default:
[Export.Substitution.CALCULATED](#)

Enum Export.Substitution

[org.osgi.annotation.bundle](#)

```
java.lang.Object
├─ java.lang.Enum<Export.Substitution>
│   └─ org.osgi.annotation.bundle.Export.Substitution
```

All Implemented Interfaces:

Comparable<[Export.Substitution](#)>, Serializable

Enclosing class:

[Export](#)

```
public static enum Export.Substitution
extends Enum<Export.Substitution>
```

Substitution policy for this package.

Enum Constant Summary	Page
CALCULATED The policy value is calculated by inspection of the classes in the package.	20
CONSUMER Use a consumer type version range for the import package clause when substitutably importing a package.	19
NOIMPORT The package must not be substitutably imported.	20
PROVIDER Use a provider type version range for the import package clause when substitutably importing a package.	19

Method Summary	Page
static Export.Substitution valueOf (String name)	20
static Export.Substitution [] values ()	20

Enum Constant Detail

CONSUMER

```
public static final Export.Substitution CONSUMER
```

Use a consumer type version range for the import package clause when substitutably importing a package.

See Also:

[org.osgi.annotation.versioning.ConsumerType](#)

PROVIDER

```
public static final Export.Substitution PROVIDER
```

Use a provider type version range for the import package clause when substitutably importing a package.

See Also:

`org.osgi.annotation.versioning.ProviderType`

NOIMPORT

```
public static final Export.Substitution NOIMPORT
```

The package must not be substitutably imported.

CALCULATED

```
public static final Export.Substitution CALCULATED
```

The policy value is calculated by inspection of the classes in the package.

Method Detail

values

```
public static Export.Substitution[] values()
```

valueOf

```
public static Export.Substitution valueOf(String name)
```

Annotation Type Header

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
@Repeatable(value=Headers.class)
public @interface Header
```

Define a manifest header for a bundle.

For example:

```
@Header(name=Constants.BUNDLE_CATEGORY, value="osgi")
```

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests.

Required Element Summary		Page
String	name The name of this header.	21
String	value The value of this header.	21

Element Detail

name

```
public abstract String name

    The name of this header.
```

value

```
public abstract String value

    The value of this header.
```

Annotation Type Headers

[org.osgi.annotation.bundle](#)

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
public @interface Headers
```

Container annotation for repeated [Header](#) annotations.

Required Element Summary		Page
Header []	value Repeated Header annotations.	22

Element Detail

value

```
public abstract Header[] value

    Repeated Header annotations.
```

Annotation Type Requirement

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
@Repeatable(value=Requirements.class)
public @interface Requirement
```

Define a requirement for a bundle.

For example:

```
@Requirement(namespace=ExtenderNamespace.EXTENDER_NAMESPACE,
    name="osgi.component", version="1.3.0")
```

This annotation is not retained at runtime. It is for use by tools to generate bundle manifests or otherwise process the a package.

Nested Class Summary		Page
static enum	Requirement.Cardinality Cardinality for this requirement.	26
static enum	Requirement.Resolution Resolution for this requirement.	28

Required Element Summary		Page
String[]	attribute A list of attribute or directive names and values.	24
Requirement.Cardinality	cardinality The cardinality of this requirement.	25
String	effective The effective time of this requirement.	24
String	filter The filter expression of this requirement, if any.	24
String	name The name of this requirement within the namespace.	24
String	namespace The namespace of this requirement.	23
Requirement.Resolution	resolution The resolution policy of this requirement.	25
String	version The floor version of the version range for this requirement.	24

Element Detail

namespace

```
public abstract String namespace
```

The namespace of this requirement.

name

```
public abstract String name
```

The name of this requirement within the namespace.

If specified, adds an expression, using the & operator with any specified [filter\(\)](#), to the requirement's filter directive to test that an attribute with the name of the namespace is equal to the value of the specified name.

Default:
""

version

```
public abstract String version
```

The floor version of the version range for this requirement.

If specified, adds a version range expression, using the & operator with any specified [filter\(\)](#), to the requirement's filter directive. The ceiling version of the version range is the next major version from the floor version. For example, if the specified version is 1.3, then the version range expression is (&(version>=1.3) (! (version>=2.0))).

The specified version must be a valid OSGi version string.

Default:
""

filter

```
public abstract String filter
```

The filter expression of this requirement, if any.

Default:
""

effective

```
public abstract String effective
```

The effective time of this requirement.

Specifies the time the requirement is available. The OSGi framework resolver only considers requirement without an effective directive or effective:=resolve. Requirements with other values for the effective directive can be considered by an external agent.

If not specified, the `effective` directive is omitted from the requirement clause.

Default:
"resolve"

attribute

```
public abstract String[] attribute
```


A list of attribute or directive names and values.

Each string should be specified in the form:

```
! "name=value" for attributes.  
! "name:type=value" for typed attributes.  
! "name:=value" for directives.
```

These are added, separated by semicolons, to the export package clause.

Default:
{}

cardinality

public abstract [Requirement.Cardinality](#) **cardinality**

The cardinality of this requirement.

Indicates if this requirement can be wired a single time or multiple times.

If not specified, the `cardinality` directive is omitted from the requirement clause.

Default:
[Requirement.Cardinality.SINGLE](#)

resolution

public abstract [Requirement.Resolution](#) **resolution**

The resolution policy of this requirement.

A mandatory requirement forbids the bundle to resolve when this requirement is not satisfied; an optional requirement allows a bundle to resolve even if this requirement is not satisfied.

If not specified, the `resolution` directive is omitted from the requirement clause.

Default:
[Requirement.Resolution.MANDATORY](#)

Enum Requirement.Cardinality

[org.osgi.annotation.bundle](#)

```
java.lang.Object
├─ java.lang.Enum<Requirement.Cardinality>
│   └─ org.osgi.annotation.bundle.Requirement.Cardinality
```

All Implemented Interfaces:

Comparable<[Requirement.Cardinality](#)>, Serializable

Enclosing class:

[Requirement](#)

```
public static enum Requirement.Cardinality
extends Enum<Requirement.Cardinality>
```

Cardinality for this requirement.

Enum Constant Summary

	Page
MULTIPLE Indicates if the requirement can be wired multiple times.	26
SINGLE Indicates if the requirement can only be wired a single time.	26

Method Summary

	Page
static Requirement.Cardinality valueOf (String name)	27
static Requirement.Cardinality values ()	26

Enum Constant Detail

SINGLE

```
public static final Requirement.Cardinality SINGLE
```

Indicates if the requirement can only be wired a single time.

MULTIPLE

```
public static final Requirement.Cardinality MULTIPLE
```

Indicates if the requirement can be wired multiple times.

Method Detail

values

```
public static Requirement.Cardinality[] values()
```

valueOf

```
public static Requirement.Cardinality valueOf(String name)
```

Enum Requirement.Resolution

[org.osgi.annotation.bundle](#)

```
java.lang.Object
└─ java.lang.Enum<Requirement.Resolution>
    └─ org.osgi.annotation.bundle.Requirement.Resolution
```

All Implemented Interfaces:

Comparable<[Requirement.Resolution](#)>, Serializable

Enclosing class:

[Requirement](#)

```
public static enum Requirement.Resolution
extends Enum<Requirement.Resolution>
```

Resolution for this requirement.

Enum Constant Summary

	Pag e
MANDATORY A mandatory requirement forbids the bundle to resolve when the requirement is not satisfied.	28
OPTIONAL An optional requirement allows a bundle to resolve even if the requirement is not satisfied.	28

Method Summary

	Pag e
static Requirement.Resolution valueOf (String name)	29
static Requirement.Resolution [] values ()	28

Enum Constant Detail

MANDATORY

```
public static final Requirement.Resolution MANDATORY
```

A mandatory requirement forbids the bundle to resolve when the requirement is not satisfied.

OPTIONAL

```
public static final Requirement.Resolution OPTIONAL
```

An optional requirement allows a bundle to resolve even if the requirement is not satisfied.

Method Detail

values

```
public static Requirement.Resolution[] values()
```

valueOf

```
public static Requirement.Resolution valueOf(String name)
```

Annotation Type Requirements

org.osgi.annotation.bundle

```
@Documented
@Retention(value=RetentionPolicy.CLASS)
@Target(value={
    ElementType.TYPE,
    ElementType.PACKAGE
})
public @interface Requirements
```

Container annotation for repeated [Requirement](#) annotations.

Required Element Summary		Page
Requirement t[]	value Repeated Requirement annotations.	30

Element Detail

value

```
public abstract Requirement[] value

    Repeated Requirement annotations.
```

Java API documentation generated with [DocFlex/Doclet](#) v1.5.6

DocFlex/Doclet is both a multi-format Javadoc doclet and a free edition of [DocFlex/Javadoc](#). If you need to customize your Javadoc without writing a full-blown doclet from scratch, DocFlex/Javadoc may be the only tool able to help you! Find out more at www.docflex.com

7 Considered Alternatives

The following requirement is deferred for now.

- G0090 – It must be possible to refer to a package name, package version, context information, class name, bundle version and bundle symbolic name in the manifest annotations. This must be done by computing the desired information from a class constant per G0070.

8 Security Considerations

~~Description of all known vulnerabilities this may either introduce or address as well as scenarios of how the weaknesses could be circumvented.~~

Since these are CLASS retention annotations, there are no runtime security considerations.

9 Document Support

9.1 References

- [1]. Bradner, S., Key words for use in RFCs to Indicate Requirement Levels, RFC2119, March 1997.
- [2]. Software Requirements & Specifications. Michael Jackson. ISBN 0-201-87712-0

9.2 Author's Address

Name	BJ Hargrave
Company	IBM

9.3 Acronyms and Abbreviations

9.4 End of Document