

SESSION 3 · NEXT-G VIDEO CODECS · SPEAKER SLIDES

Yan Ye

Distinguished Scientist, Alibaba Group U.S

Video Codecs Towards 2030

Future Media Townhall, IBC 2026
September 12, 2026

Yan Ye
Distinguished Scientist
Lab Director, DAMO Video Technology Lab, Alibaba Group U.S.



01

Video Coding Standard Beyond H.266/VVC

Enhanced Compression Model (ECM)

- In April 2021, shortly after VVC version 1 was finalized, JVET-U0100 showed 11.5% coding performance gain vs. VVC based on “known” coding tools
- In July 2021, enhanced compression model (ECM) software platform was established to facilitate exploration of coding tools
- From the first version (ECM-1.0, July 2021) to the last version (ECM-20.0, July 2026), coding performance steadily improves
- ECM-20.0 achieves 27.6% gain vs. VVC, with 10x encoder and 14x decoder runtime
- Based on hybrid block-based video coding framework
- Mainly traditional signal processing algorithms, but more data-driven training, e.g. PDP, NN intra, NSPT


ECM evolution: performance vs. runtime

Random Access (RA)
config. of ECM
common test
conditions

YUV4:2:0 10b coding,
covering SD, HD, UHD
resolutions

BD rate savings (%) in
terms of Y PSNR

Encoding and
decoding time relative
to VVC ref. sw. VTM



Neural Network-based Video Coding (NNVC)

- Besides ECM (more focused on non-NN coding tools), JVET also has been exploring neural network-based video coding since 2020
- NNVC software uses fixed point implementation for inference and therefore results reproducible
- NNVC-17.1 default (NN intra + low complexity loop filters) achieves 8.2% gain over VTM with 20x decoder runtime on CPU
- Other variations (other loop filter flavors, deep reference frame, etc) achieve lower/higher gains with different complexity implications


	Luma BD-rate (%)	CPU EncT (times)	CPU DecT (times)	kMAC/pixel	Params (M)
NN-Intra + LOP (default)	−8.2	1.2	20	21.3	1.5
NN-Intra + VLOP	−6.1	1.2	15	9.9	1.3
NN-Intra + HOP	−14.1	3.4	1180	471	2.7
Default + L-DRF	−9.6	1.3	230	83	5.2
Default + H-DRF	−10.6	1.7	869	477	7.7
E2E AI for intra picture	−1.7	1.0	5.3	23	36.4

Towards the next gen. codec standard

- Observing the significant progress in coding efficiency gain that JVET has made, 20 companies proposed timeline and requirements for the next gen codec standard in October 2024
- In January 2025, ITU-T SG21 and ISO/IEC JTC 1 SC 29 jointly held “Workshop on Future video coding – advanced signal processing, AI and standards” in Geneva, Switzerland
- In July 2025, the joint Call for Evidence was issued, 5 responses were received in October, with subjective testing showing sufficient evidence to move forward with the next gen. project
- ECM- and NNVC-based responses
- In July 2026, the joint Call for Proposals was formally issued


The Joint CfP

- Categories:
 - Improved compression
 - Improved compression with runtime-constrained encoding
 - Additional functionality
- First time to include runtime constrained encoding, 5 VTM configurations for different encoding runtime
 - 1x (default VTM), 1.5x, 2/3x, 0.4x, 0.2x
- In September, JVET announced 32 registered CfP responses from 33 companies
- Tentative timeline for the next gen. project
 - 2027-01 Initial test model selection process begins
 - 2027-10 Initial test model selection completed (at latest)
 - 2029-10 Final standard completed




02 | Deploying an Advanced Codec

Encoders must serve a wide range of applications



- 31 HD sequences (movie, sports, UGC, games, JVET, etc.)
- Compute platform: AMD EPYC 7T83 64-Core Processor, ~2.6 GHz (2021)
- PSNR is the quality metric used to calculate BD-rate

- To serve different applications, commercial-grade encoders must cover a meaningfully **wide range of operating points** with **desirable quality vs. throughput tradeoffs**
- In contrast, ref. encoders only provide a “theoretical” performance ceiling



- VTM: BD-rate calculated against anchor VTM default config, performance and speed data from 8 HD sequences in CfP (JVET-AQ2021), mainstream platform
- x265: BD-rate anchor veryslow preset, 31 HD proprietary sequences, configs according to typical VOD and live transcoding applications, compute platform AMD EPYC 7T83 64-Core Processor, ~2.6 GHz (2021)
- PSNR is the quality metric used to calculate BD-rate

Decoders must be fast, lean and green


- For video playback, mobile is the most relevant target device for mass-scale consumer video applications
- As hardware decoding support on mobile has typically lagged standardization (gap of 3-5 years), **efficient software decoders** are the most essential enabler for meaningful deployment
- Software decoding: speed, memory and power consumption/battery drain
- Well-optimized software decoders are fast and lean, and can sustain handset battery for hours on end without causing overheating and user discomfort

		Speed (fps)	Memory (MB)
3 threads	DAMO266	334	122
	VVdeC	233	225

8 sequences, resolution 1920x1080, coded bit rate ~2 Mbps
Test device is Xiaomi 14 Pro, Qualcomm Snapdragon 8 Gen 3

Hours to drain 50% battery	1080p30 (3 threads)	1080p60 (3 threads)	4K30 (4 threads)
dav1d	5.8	3.6	3.6
DAMO266	5.3	3.3	3.0
VVdeC	4.0	2.3	2.5

VCAT-d: Open-source benchmark platform, measures frame decode time, CPU utilization and battery consumption under controlled conditions
 2 Netflix sequences coded with aligned quality (PSNR ≈ 39 dB)
 Test device is Xiaomi 14 Pro, Qualcomm Snapdragon 8 Gen 3, display at 50% brightness
 Charged to full, non-stop playback till 50% battery remains



vivo x100sPro, SOC MediaTek Dimensity 9300+
 vivo x80, SOC MediaTek Dimensity 9000"

03

AI and Video Coding

AI and video coding: putting the two together

- AI inside a video codec
 - Coding performance gain: a few percentages
 - Implementation hurdles: hardware area, CPU-GPU data transfer, memory footprint, battery drain, and so on
 - A reasonable tradeoff must be sorted out before NN tools can be deployed at mass scale, challenges for software-based decoding solutions in the near term
- AI in video workflows
 - As upstream and downstream tasks, AI is already deployed, and scale of deployment continues to ramp up quickly
 - AI content generation: very popular for content creators
 - AI content enhancement: super-resolution, temporal interpolation, etc.
 - AI content understanding: cross-platform content (e.g. summarization, landscape-to-portrait), end-user interaction, etc.
 - AI for 3D: 3D-fication of 2D content, etc.



Thank
s

