



synrc research center s.r.o.
ROHÁČOVA 141/18, PRAHA 3 13000, CZECH REPUBLIC

Intermediate Language with Dependent Types for Erlang/OTP applications.

Technical Article

Maxim Sokhatsky, Synrc Research Center

Kyiv 2016

Contents

1	Introduction	3
2	Motivation	4
3	Intermediate Language Om	5
3.1	BNF	5
3.2	AST	5
4	Exe Macrosystem	6
4.1	Compiler Passes	6
4.2	BNF	6
4.3	Pure Macro Types	7
4.4	Effectful Macro Types	7
4.5	Prelude Base Library	7
4.6	Inductive Types	8
4.7	Lists	8
4.8	Berrarducci Inductive Encoding	9
4.9	Normal Forms	9

1 Introduction

LISP. Untyped lambda calculus was discovered as an inner language of the space at origin (Curry, Church, 1932). This language was manifested as LISP (McCarthy, 1958) that was built upon: cons, nil, eq, atom, car, cdr, lambda, apply and id. It was parts of inductive types lately known as inductive type constructors. Still untyped lambda calculus is used as an extraction target for many provers (Idris, F*), and also manifests in different domain languages (JavaScript, Erlang).

ML/LCF. Further teardown of inner space language was ML language, founded merely on algebraic datatypes and algebra on higher terms rather than categorical semantic. Lately it was fixed with categorical methods in CPL (Hagino, 1987) and Charity (Cockett, 1992). Milner, assisted by Morris and Newey designed Meta Language for the purpose of building LCF in early 70-s. LCF was a predecessor family of automated math provers: HOL88, HOL90, HOL98 and HOL/Isabelle which is now built using Poly/ML.

Fully Automated Provers. In that period during 80-90s other automated math systems were appeared: AUTOMATH (de Bruijn, 1967), Mizar (Trybulec, 1989), PVS (Owre, Rushby, Shankar, 1995), ACL2 (Boyer, Kaufmann, Moore, 1996) and Otter (McCune, 1996).

MLTT. Contemporary provers (built upon consistent Martin-Löf Type Theory, 1972) like Agda, Coq, Lean, F*, Idris are based on Barendregt and Coquand' CoC with different flavours of infinity universe hierarchies and Calculus of Inductive Constructions. Some of them are automated and some are trying to be and general purpose programming languages with proving facilities.

2 Motivation

No Fixpoint and Induction in Core. We came up with pure CoC core having predicative and impredicative universe hierarchies and macro extensions. Other MLTT cores has additional axioms like Fixpoint and Induction (and even more) — something we strive to escape, because it leads to clean and understandable core. No, we don't have Fixpoint, and yes, we implemented Induction principle in pure CoC.

Extensible Language Design. Encoding of inductive types is based on categorical semantic of compilation to CoC. All other syntax constructions are inductive definitions, plugged into the stream parser. AST of the CoC language is also defined in terms of inductive constructions and thus allowed in the macros. The language of polynomial functors (data and record) and core language of the process calculus (spawn, receive and send) are just macrosystem over CoC language, its syntax extensions.

Changable Encodings. In pure CoC we have only arrows, so all inductive type encodings would be Church-encoding variations. Most extended nowadays is Church-Boehm-Berrarducci encoding, which dedicated to inductive types. Another well known are Scott (lazyness), Parigot (lazyness and constant-time iterators) and CPS (continuations) encodings.

Proved Categorical Semantic. There was modeled a math model (using higher-order categorical logic) of encoding, which calculates (co)limits in a category of (co)algebras built with given set of (de)constructors. We call such encoding in honour of Lambek lemma that leads us to the equality of (co)initial object and (co)limit in the categories of (co)algebras. Such encoding works with dependent types and its consistency is proved in Lean model.

3 Intermediate Language Om

The Om language is a dependently typed lambda calculus, an extension of Barendregt' and Coquand Calculus of Constructions with predicative hierarchy of indexed universes. There is no fixpoint axiom needed for the definition of infinity term dependance.

All terms respect ranking A inside sequence of universes S and complexity of the dependent term is equal maximum complexity of term and its dependency R. The type system is completely described by the following PTS notation (due to Barendregt):

$$\begin{cases} \text{Sorts} = \text{Type}.\{i\}, i : \text{Nat} \\ \text{Axioms} = \text{Type}.\{i\} : \text{Type}.\{\text{inc } i\} \\ \text{Rules} = \text{Type}.\{i\} \rightsquigarrow \text{Type}.\{j\} : \text{Type}.\{\text{max } i \ j\} \end{cases}$$

An intermediate Om language is based on Henk [3] languages described first by Erik Meyer and Simon Peyton Jones in 1997. Later on in 2015 Morte implementation of Henk design appeared in Haskell, using Boem-Berrarducci encoding of non-recursive lambda terms. It is based only on π , λ and *apply* constructions, infinity number of universes, one axiom and one deduction rule. The design of Om language resemble Henk and Morte both design and implementation. This language intended to be small, concise, easy provable and clean and produce verifiable piece of code that can be distributed over the networks and compiled at target with safe linkage.

3.1 BNF

Om resemble both the Henk theory of pure type system and λC calculus of constructions and Morte Core Specification

```
<> ::= #option
I ::= #identifier
U ::= * < #number >
0 ::= U | I | ( 0 ) | 0 0 |  $\lambda$  ( I : 0 )  $\rightarrow$  0 |
      0  $\rightarrow$  0 |  $\forall$  ( I : 0 )  $\rightarrow$  0
```

3.2 AST

$$\begin{array}{lcl} E & ::= & K \\ & | & x \\ & | & EE \\ & | & \lambda(x : E) \rightarrow E \\ & | & \Pi(x : E) \rightarrow E \end{array}$$

4 Exe Macrosystem

Exe is a general purpose functional language with functors, lambdas on types, recursive algebraic types, higher order functions, corecursion, free monad for effects encoding. It compiles to a small core of dependent type system without recursion called Om. This language is intended to be useful enough to encode KVS (database), N2O (web framework) and BPE (processes) applications.

4.1 Compiler Passes

The underlying OM typechecker and compiler is a target language for EXE general purpose language.

EXPAND	EXE – Macroexpansion
NORMAL	OM – Term normalization and typechecking
ERASE	OM – Delete information about types
COMPACT	OM – Term Compactification
EXTRACT	OM – Extract Erlang Code

4.2 BNF

```
<> ::= #option
[] ::= #list
I ::= #identifier
U ::= * < #number >
O ::= I | ( O ) |
      U | O → O | O O
      | λ ( I : O ) → O
      | ∀ ( I : O ) → O
L ::= I | L I
A ::= O | A → A | ( L : O )
F ::= | F ( I : O ) | ( )
E ::= O | E data L : A := F
      | E record L : A < extend F > := F
      | E let F in E
      | E case E [ | I O → E ]
      | E receive E [ | I O → E ]
      | E spawn E raise L := E
      | E send E to E
```

4.3 Pure Macro Types

CASE	Control Branch Pattern Matching
LET	Variable Bind
DATA	Inductive Tree
RECORD	Coinductive Tuple

4.4 Effectful Macro Types

SPAWN	Spawn IOI Corecursion
TRY	Exception Effect
SEND	Send Message to IOI Cofree Comonad
RECEIVE	Control Branch Pattern Matching

4.5 Prelude Base Library

```
inductive Nat: * :=
  (zero: () → Nat)
  (succ: Nat → Nat)

inductive List: (A:*) → * :=
  (nil: () → list A)
  (cons: A → list A → list A)

record List: (A B: *) :=
  (len: list A → integer)
  ((++): list A → list A → list A)
  (map: (A → B) → (list A → list B))
  (filter: (A → bool) → (list A → list A))

record String: List Nat := ()

inductive IO: * :=
  (getLine: (String → IO) → IO)
  (putLine: String → IO)
  (pure: () → IO)

record IO: * :=
  (data: String)
  ([>=>]: )

record Morte: * :=
  (recursive: IO.replicateM Nat.Five
    (IO.[>=>] IO.data Unit IO.getLine IO.putLine))
```

4.6 Inductive Types

There is two types of recursion: one is least fixed point (as $F_A X = 1 + A \times X$ or $F_A X = A + X \times X$), in other words the recursion with a base (terminated with a bounded value), lists are trees are examples of such recursive structures (so we call induction recursive sums); and the second is greatest fixed point or recursion without base (as $F_A X = A \times X$) — such kind of recursion on infinite lists (codata, streams, coinductive types) we can call recursive products.

Natural Numbers: $\mu X \rightarrow 1 + X$

List A: $\mu X \rightarrow 1 + A \times X$

Lambda calculus: $\mu X \rightarrow 1 + X \times X + X$

Stream: $\nu X \rightarrow A \times X$

Potentially Infinite List A: $\nu X \rightarrow 1 + A \times X$

Finite Tree: $\mu X \rightarrow \mu Y \rightarrow 1 + X \times Y = \mu X = List\ X$

As we know there are several ways to appear for variable in recursive algebraic type. Least fixpoint are known as an recursive expressions that have a base of recursion Both recursive and corecursive datatypes could be encoded using Boem-Berarducci encoding as an non-recursive definitions of folds that include in indentity signature all the constructor components of (co)inductive type.

4.7 Lists

The data type of lists over a given set A can be represented as the initial algebra $(\mu L_A, in)$ of the functor $L_A(X) = 1 + (A \times X)$. Denote $\mu L_A = List(A)$. The constructor functions $nil : 1 \rightarrow List(A)$ and $cons : A \times List(A) \rightarrow List(A)$ are defined by $nil = in \circ inl$ and $cons = in \circ inr$, so $in = [nil, cons]$. Given any two functions $c : 1 \rightarrow C$ and $h : A \times C \rightarrow C$, the catamorphism $f = \llbracket [c, h] \rrbracket : List(A) \rightarrow C$ is the unique solution of the equation system:

$$\begin{cases} f \circ nil = c \\ f \circ cons = h \circ (id \times f) \end{cases}$$

where $f = foldr(c, h)$. Having this the initial algebra is presented with functor $\mu(1 + A \times X)$ and morphisms $sum : [1 \rightarrow List(A), A \times List(A) \rightarrow List(A)]$ as catamorphism. Using this encoding the base library of List will have following form:

$$\begin{cases} foldr = \llbracket [f \circ nil, h] \rrbracket, f \circ cons = h \circ (id \times f) \\ len = \llbracket [zero, \lambda a\ n \rightarrow succ\ n] \rrbracket \\ (++) = \lambda\ xs\ ys \rightarrow \llbracket [\lambda(x) \rightarrow ys, cons] \rrbracket(xs) \\ map = \lambda\ f \rightarrow \llbracket [nil, cons \circ (f \times id)] \rrbracket \end{cases}$$

4.8 Berrarducci Inductive Encoding

```

inductive list: (A: *) → * :=
  (nil: list A)
  (cons: A → list A → list A)

{ list = λ ctor → λ cons → λ nil → ctor
  cons = λ x → λ xs → λ list → λ cons → λ nil → cons x (xs list cons nil)
  nil = λ list → λ cons → λ nil → nil }

record lists: (A B: *) :=
  (len: list A → integer)
  ((++): list A → list A → list A)
  (map: (A → B) → (list A → list B))
  (filter: (A → bool) → (list A → list A))

{ len = foldr (λ x n → succ n) 0
  (++) = λ ys → foldr cons ys
  map = λ f → foldr (λ x xs → cons (f x) xs) nil
  filter = λ p → foldr (λ x xs → if p x then cons x xs else xs) nil
  foldl = λ f v xs = foldr (λ xg → (λ → g (f a x))) id xs v }

```

4.9 Normal Forms

Lists/Map

```

λ (a: *) → λ (b: *) → λ (f: a → b) → λ (xs: ∀ (List: *) →
  ∀ (Cons: ∀ (head: a) → ∀ (tail: List) → List) → ∀ (Nil: List)
  → List) → xs (∀ (List: *) → ∀ (Cons: ∀ (head: b) → ∀ (tail: List)
  → List) → ∀ (Nil: List) → List) (λ (head: a) → λ (tail: ∀ (List:
  *) → ∀ (Cons: ∀ (head: b) → ∀ (tail: List) → List) → ∀ (Nil:
  List) → List) → λ (List: *) → λ (Cons: ∀ (head: b) → ∀ (tail:
  List) → List) → λ (Nil: List) → Cons (f head) (tail List Cons Nil))
  (λ (List: *) → λ (Cons: ∀ (head: b) → ∀ (tail: List) → List)
  → λ (Nil: List) → Nil)

```

References

- [1] Henk Barendregt *The Lambda Calculus. Its syntax and semantics* 1981
- [2] Henk Barendregt *Lambda Calculus With Types* 2010
- [3] Erik Meijer, Symon Peyton Jones *Henk: a typed intermediate language* 1984
- [4] Per Martin-Löf *Intuitionistic Type Theory* 1984
- [5] Pierre-Louis Curien *Category theory: a programming language-oriented introduction*
- [6] Varmo Vene *Categorical programming with (co)inductive types* 2000
- [7] Frank Pfenning *Inductively defined types in the Calculus of Constructions* 1989
- [8] Bart Jacobs *Categorical Logic and Type Theory* 1999