REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	04/01/2022	



LEGEND PLATE
- LM922422, .062 THK, ROWMARK.COM (OR EQUIVALENT)
- PAINT FED-STD-595, FS37038, FLAT BLACK
- ROTARY ENGRAVE OR LASER ENGRAVE MIN .003 DEPTH SO WHITE LEGEND SHOWS WITH FULLY DEFINED & LEGIBLE TEXT AND SYMBOLS WITH NO VISIBLE DEFECTS.

BOND LEGEND PLATE TO LIGHT PLATE WITH WELD-ON #4 (OR EQUIVALENT)

PAINT EDGES AND INSIDES OF HOLES OF LEGEND/LIGHT PLATE ASSY WITH FED-STD-595, FS37038, FLAT BLACK

LIGHT PLATE
- 2447 WHITE TRANSLUCENT ACRYLIC, .1875[4.5] THK

BACKPLATE
- BLACK OPAQUE ACRYLIC, .125[3] THK
- PAINT FED-STD-595, FS37038, FLAT BLACK

DO NOT BOND BACKPLATE TO LIGHTPLATE

(TYPE A BACKLIGHTING PCB)

PANEL TYPE A
METHOD 1

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES.

DUAL DIMENSIONS ARE IN MILIMETERS AND ENCLOSED IN SQUARE BRACKETS.

INTERPRET DRAWING IAW ASME Y14.100-2017.

INTERPRET DIM AND TOL IAW ASME Y14.5-2009.

REMOVE ALL BURRS AND SHARP EDGES TO .05 MAX.

DIMENSIONS APPLY BEFORE FINISH.

UOS INCH TOLERANCES ARE:

DECIMALS:
.X ± .1
.XX ± .03
.XXX ± .010

ANGLES:
MACHINED ± .5°
LOCATING ± .5°
FORMED ± 2°
CHAMFERS ± 5°

DRILLED HOLE DIAMETERS:
.0135 - .125: +.004/-.001
.126 - .250: +.005/-.001
.251 - .500: +.006/-.001
.501 - .750: +.008/-.001
.751 - 1.000: +.010/-.001
1.001 - 2.000: +.012/-.001

OPEN HORNET
https://www.OpenHornet.com

TITLE
COMPONENT FABRICATION METHODS

DESIGNED	J. STEENSEN 04/01/2023	SIZE D	DWG NO OH-SPEC-001	REV -
CHECKED			
DRAWN	J. STEENSEN 04/01/2022	SCALE N/A	SHEET 1/2

CC BY NC SA



INDICATOR TYPE A
METHOD 1

METHODS 2 THRU 4 SAME AS METHOD 1 EXCEPT AS NOTED. METHODS 2 THRU 4 MAY BE SUBSTITUTED FOR METHOD 1 AS DESIRED.

INDICATOR TYPE A, METHOD 2

- OMIT INDICATOR LEGEND LAYER,
- PAINT BACK OF INIDCATOR COVER LAYER IAW METHOD 1, INDICATOR LEGEND LAYER
- REVERSE ENGRAVE THE LEGEND ON THE BACK OF THE INDICATOR COVER LAYER.

INDICATOR TYPE A, METHOD 3

- **WARNING: DO NOT LASER CUT OR ENGRAVE VINYL. LASER CUTTING OR OTHERWISE BURNING VINYL PRODUCES CHLORINE GAS AND HYDROCHLORIC ACID. IT MAY RESULT IN EQUIPMENT DAMAGE, INJURY OR DEATH.**
- REPLACE INDICATOR LEGEND LAYER WITH OPAQUE BLACK VINYL BONDED TO EITHER DIFFUSAL LAYER OR BACK OF COVER LAYER.

INDICATOR TYPE A, METHOD 4

- REPLACE INDICATOR LEGEND LAYER WITH CLEAR TRANSPARANCY BONDED TO EITHER DIFFUSAL LAYER OR BACK OF COVER LAYER. TRANSPARANCY SHOULD BE PRINTED OPAQUE BLACK WITH CLEAR LETTERS.

CC BY NC SA

OPEN HORNET
https://www.OpenHornet.com

SIZE	DWG NO	REV
D	OH-SPEC-001	-
SCALE N/A		SHEET 2/2