

# Kathará

A container-based framework for experimenting  
computer networking

<b>Version</b>	1.0
<b>Author(s)</b>	L. Ariemma, G. Bonofiglio, G. Di Battista, V. Iovinella, G. Lospoto, M. Patrignani, M. Pizzonia, M. Rimondini
<b>E-mail</b>	contact@kathara.org
<b>Web</b>	<a href="http://www.kathara.org/">http://www.kathara.org/</a>
<b>Description</b>	an introduction to the architecture, setup, and usage of kathará – based on a similar presentation of netkit

# copyright notice

- All the pages/slides in this presentation, including but not limited to, images, photos, animations, videos, sounds, music, and text (hereby referred to as “material”) are protected by copyright.
- This material, with the exception of some multimedia elements licensed by other organizations, is property of the authors and/or organizations appearing in the first slide.
- This material, or its parts, can be reproduced and used for didactical purposes within universities and schools, provided that this happens for non-profit purposes.
- Information contained in this material cannot be used within network design projects or other products of any kind.
- Any other use is prohibited, unless explicitly authorized by the authors on the basis of an explicit agreement.
- The authors assume no responsibility about this material and provide this material “as is”, with no implicit or explicit warranty about the correctness and completeness of its contents, which may be subject to changes.
- This copyright notice must always be redistributed together with the material, or its portions.

# about computer networks

- computer networks are quite complex
  - several devices (computers, routers, etc.)
  - several interfaces
  - several protocols running
  - physical interconnections originate complex topologies

# how to perform experiments?

- performing experiments may be unfeasible
- the currently used network cannot be exploited for experiments
  - it hosts services that are critical for the company
  - it would be necessary to coordinate different departments of the company
- network equipments are expensive
  - sometimes, even for performing simple experiments, several equipments should be available in the same test bed

# simulation vs. emulation


- emulation and simulation systems put at user's disposal a virtual environment that can be exploited for tests, experiments, measures
- **simulation systems** aim at reproducing the **performance** of a real-life system (latency time, packet loss, etc.)
  - e.g.: ns, real, ...
- **emulation systems** aim at accurately reproducing the **functionalities** of a real-life system (configurations, architectures, protocols), with limited attention to performance

# kathará: a system for emulating computer networks

- based on Docker
- each emulated network device (in what follows *device*) is a container
- note: several container images available, e.g.:
  - Quagga (standard routing and switching protocols) and Open vSwitch (Open Flow enabled switch)
  - Behavioral Model (software implementation of a P4 target switch)

# emulated network devices


- each device has:
  - a console (a terminal window)
  - a memory
  - a filesystem
  - (one or more) network interfaces
- each network interface can be connected to a (virtual) collision domain
- each virtual collision domain can be connected to several interfaces





# emulating a computer network using kathará

- basic idea:
  - several containers are created inside a single host machine
  - containers are connected to virtual collision domains and thus can communicate with each other
- each container can be configured as a device that plays the role of a regular host, of a router, of a switch, ....





Università degli Studi Roma Tre  
Dipartimento di Ingegneria  
Computer Networks Research Group

# setting up kathará

# setting up kathará

- available for:
  - Windows 8 Pro, Windows 10 Pro
  - Linux
  - MacOS
- download at <http://www.kathara.org/>
- follow the wiki



Università degli Studi Roma Tre  
Dipartimento di Ingegneria  
Computer Networks Research Group

using kathará

# kathará commands

- kathará provides users with two sets of commands
  - v-prefixed commands (v-commands)
  - l-prefixed commands (l-commands)
- v-commands act as low level tools for configuring and starting up devices
- l-commands provide an easier-to-use environment to set up complex labs consisting of several devices

# kathará v-commands

- allow to startup devices with arbitrary configurations (network interfaces, etc.)
  - **vstart**: starts a new device
  - **vlist**: lists currently running devices
  - **vconfig**: attaches network interfaces to running device
  - **vclean**: gracefully halts a device cleaning the device disk

# kathará l-commands

- ease setting up complex labs consisting of several virtual machines
  - **lstart**: starts a kathará lab
  - **lclean**: gracefully halts all the devices of a lab cleaning the device disks
  - **lwipe**: gracefully halts all the devices OF KATHARÁ cleaning the device disks
  - **linfo**: provides information about a lab without starting it
  - **ltest**: allows to run tests to check that the lab is working properly



# accessing the “external world” from a device

the directory `/hosthome` inside a device directly points to the home directory of the current user on the real host

- read/write access is allowed



Università degli Studi Roma Tre  
Dipartimento di Ingegneria  
Computer Networks Research Group

# preparing a kathará lab

# kathará lab

- a **kathará lab** is a set of preconfigured devices that can be started and halted together
- a standard kathará lab is a directory tree containing:
  - a **lab.conf** file describing the network topology
  - a set of **subdirectories** that contain the configuration settings for each device
  - **.startup** and **.shutdown** files that describe actions performed by virtual machines when they are started or halted

# lab.conf

- this file describes
  - the settings of the vms that make up a lab
  - the topology of the network that interconnects the vms of the lab
- list of **machine**[**arg**]=**value** assignments
  - **machine** is the name of the vm (e.g., **pc1**)
  - if **arg** is an integral number (say *i*), then **value** is the name of the collision domain to which interface **eth*i*** should be attached
  - if **arg** is a string, then it must be the name of a **vstart** option and **value** is the argument (if any) to that option

# lab.conf


## ■ example

```
pc1[0]=A
```

```
pc2[0]=A
```

```
pc2[1]=B
```

```
pc3[0]=B
```



# lab subdirectories

- kathará starts a device for device specified in `lab.conf`
- the contents of subdirectory `vm` are mapped (=copied) into the root (/) of `vm`'s filesystem
  - for example, `vm/foo/file.txt` is copied to `/foo/file.txt` inside virtual machine `vm`

# startup files

- shell scripts that tell virtual machines what to do when starting up
- they are executed inside virtual machines
- a typical usage of a `.startup` file is to configure network interfaces and/or start network services

```
ifconfig eth0 10.0.0.1 up  
/etc/init.d/zebra start
```

- sample of `vm_name.startup`

# launching/stopping a lab

- enter the lab directory (`cd lab_directory`)
- *lcommand*
  - where *lcommand* can be one of the following:
    - `lstart`, to start the lab
    - `lclean`, to stop the lab



# more information

- further information can be found...
  - ...on GitHub's kathará wiki
  - ...on the web site <http://www.kathara.org/>