



Apothecaries' Sundries Manufacturing Co.

PO BOX NO. 1, NEW DELHI-110001, INDIA

ADMIN OFFICE:

'ASCO' HOUSE, I-30 (A), KIRTI NAGAR, NEW DELHI-110015(INDIA)
PHONES: 25420779, 25410008, 25420783
FAX: (+91-11) 25410007, 25429633

EMAIL: info@ascoindia.com
WEBSITE: www.ascoindia.com

Representative:



CE
0434

ISO 9001-2000 CERTIFIED
asco
S I N C E 1 9 4 8



I V C A N N U L A

Serving The Healthcare Trade Worldwide

ASCO



■	IV 101 I.V. Cannula with injection port & wings. Sizes: G 14, 16, 17, 18, 20, 22, 24, 26
■	IV 102 I.V. Cannula without injection port, with wings. Sizes: G 14, 16, 17, 18, 20, 22
■	IV 103 I.V. Cannula without injection port & with small wings for paediatric use only. Sizes: G 24, 26
■	IV 104 I.V. Cannula without injection port & without wings. Sizes: G 14, 16, 17, 18, 20, 22, 24, 26
■	IV 105 I.V. Cannula with special injection port & suturable wings. Sizes: G 14, 16, 17, 18, 20, 22, 24, 26.

S e r v i n g T h e H e a l t h c a r e T r a d e W o r l d w i d e

■ I.V. CANNULA GENERAL FEATURES

- Needle** ■ Back Cut ground, siliconised, and bevelled, stainless steel needle for smooth and painless puncture
- Needle Hub** ■ Needle Hub is designed in a special way to prevent destabilisation and for better grip and control during cannulation
- Needle Protector** ■ A needle protector is provided for protection against contamination and accidental damage
- Catheter** ■ Catheter is made of P.T.F.E. (Poly Tetra Fluro Ethylene)- a high quality biocompatible material, which has lowest coefficient of friction and reduces the chances of thrombophlebitis and sticking to vascular walls ■ High flow rate is achieved due to thin wall construction ■ Distance between needle bevel and catheter tip is optimised ideally
- Flash Back Chamber** ■ Unique air vented hub for higher flow rate and quick easy confirmation of correct vascular access.
■ Avoid blood spillage ■ Prevents formation of air bubbles.
- Threaded stopper** ■ A threaded stopper is provided on each IV Cannula
- Packing** ■ Individually packed in rigid blister sealed with peel open type medical grade paper

■ TECHNICAL SPECIFICATIONS

Gauge	Color Code	Catheter O.D.mm	Catheter Length mm	Water Flow Rate (ml/min)	Quantity Per Box (Pcs.)	Quantity Per Carton (Pcs.)
14G	Orange	2.10	45	240	100	1000
16G	Grey	1.74	45	180	100	1000
17G	White	1.40	45	125	100	1000
18G	Green	1.20	45	80	100	1000
20G	Pink	1.11	32	54	100	1000
22G	Blue	0.80	25	31	100	1000
24G	Yellow	0.60	19	13	100	1000
26G	Dark Blue	0.60	19	13	100	1000