

Chapter 3: Program Statements

Presentation slides for

Java Software Solutions

for AP* Computer Science

by John Lewis, William Loftus, and Cara Cocking

Java Software Solutions is published by Addison-Wesley

Presentation slides are copyright 2002 by John Lewis, William Loftus, and Cara Cocking. All rights reserved.

Instructors using the textbook may use and modify these slides for pedagogical purposes.

*AP is a registered trademark of The College Entrance Examination Board which was not involved in the production of, and does not endorse, this product.

Program Statements



- Now we will examine some other program statements
- Chapter 3 focuses on:
 - program development stages
 - the flow of control through a method
 - decision-making statements
 - expressions for making complex decisions
 - repetition statements
 - drawing with conditionals and loops

Program Development



- **The creation of software involves four basic activities:**
 - establishing the requirements
 - creating a design
 - implementing the code
 - testing the implementation
- **The development process is much more involved than this, but these are the four basic development activities**

Requirements



- *Software requirements* specify the tasks a program must accomplish (what to do, not how to do it)
- They often include a description of the user interface
- An initial set of requirements often are provided, but usually must be critiqued, modified, and expanded
- Often it is difficult to establish detailed, unambiguous, complete requirements
- Careful attention to the requirements can save significant time and expense in the overall project

Design



- A *software design* specifies how a program will accomplish its requirements
- A design includes one or more *algorithms* to accomplish its goal
- An *algorithm* is a step-by-step process for solving a problem
- An algorithm may be expressed in *pseudocode*, which is code-like, but does not necessarily follow any specific syntax
- In object-oriented development, the design establishes the classes, objects, methods, and data that are required

Implementation



- *Implementation* is the process of translating a design into source code
- Most novice programmers think that writing code is the heart of software development, but actually it should be the least creative step
- Almost all important decisions are made during requirements and design stages
- Implementation should focus on coding details, including style guidelines and documentation

Testing



- A program should be executed multiple times with various input in an attempt to find errors
- *Debugging* is the process of discovering the causes of problems and fixing them
- Programmers often think erroneously that there is "only one more bug" to fix
- Tests should consider design details as well as overall requirements

Flow of Control



- Unless specified otherwise, the order of statement execution through a method is linear: one statement after the other in sequence
- Some programming statements modify that order, allowing us to:
 - decide whether or not to execute a particular statement, or
 - perform a statement over and over, repetitively
- These decisions are based on a *boolean expression* (also called a *condition*) that evaluates to true or false
- The order of statement execution is called the *flow of control*

Conditional Statements



- A *conditional statement* lets us choose which statement will be executed next
- Therefore they are sometimes called *selection statements*
- Conditional statements give us the power to make basic decisions
- Some conditional statements in Java are
 - the *if statement*
 - the *if-else statement*

The if Statement



- The *if statement* has the following syntax:

`if` is a Java
reserved word

The *condition* must be a boolean expression.
It must evaluate to either true or false.

`if (condition)
 statement;`

If the *condition* is true, the *statement* is executed.
If it is false, the *statement* is skipped.

The if Statement



➤ An example of an `if` statement:

```
if (sum > MAX)
    delta = sum - MAX;
System.out.println ("The sum is " + sum);
```


First, the condition is evaluated. The value of `sum` is either greater than the value of `MAX`, or it is not.

If the condition is true, the assignment statement is executed. If it is not, the assignment statement is skipped.

Either way, the call to `println` is executed next.

➤ See [Age.java](#) (page 126)

Logic of an if statement



Boolean Expressions



- A condition often uses one of Java's *equality operators* or *relational operators*, which all return boolean results:

==	equal to
!=	not equal to
<	less than
>	greater than
<=	less than or equal to
>=	greater than or equal to

- Note the difference between the equality operator (==) and the assignment operator (=)

The if-else Statement




- An *else clause* can be added to an **if** statement to make an *if-else statement*

```
if ( condition )  
    statement1;  
else  
    statement2;
```

- If the *condition* is true, *statement1* is executed; if the condition is false, *statement2* is executed
- One or the other will be executed, but not both
- See [Wages.java](#) (page 130)

Logic of an if-else statement



Block Statements



- Several statements can be grouped together into a *block statement*
- A block is delimited by braces : `{ ... }`
- A block statement can be used wherever a statement is called for by the Java syntax
- For example, in an `if-else` statement, the `if` portion, or the `else` portion, or both, could be block statements
- See [Guessing.java](#) (page 132)

Nested if Statements



- The statement executed as a result of an `if` statement or `else` clause could be another `if` statement
- These are called *nested if statements*
- See [MinOfThree.java](#) (page 134)
- An `else` clause is matched to the last unmatched `if` (no matter what the indentation implies)
- Braces can be used to specify the `if` statement to which an `else` clause belongs

Logical Operators



- Boolean expressions can use the following *logical operators*:

!	Logical NOT
&&	Logical AND
	Logical OR

- They all take boolean operands and produce boolean results
- Logical NOT is a unary operator (it operates on one operand)
- Logical AND and logical OR are binary operators (each operates on two operands)

Logical NOT



- The *logical NOT* operation is also called *logical negation* or *logical complement*
- If some boolean condition **a** is true, then **!a** is false; if **a** is false, then **!a** is true
- Logical expressions can be shown using *truth tables*

a	!a
true	false
false	true

Logical AND and Logical OR



➤ The *logical AND* expression

`a && b`

is true if both `a` and `b` are true, and false otherwise

➤ The *logical OR* expression

`a || b`

is true if `a` or `b` or both are true, and false otherwise

Truth Tables



- A truth table shows the possible true/false combinations of the terms
- Since `&&` and `||` each have two operands, there are four possible combinations of conditions `a` and `b`

a	b	a && b	a b
true	true	true	true
true	false	false	true
false	true	false	true
false	false	false	false

Logical Operators



- Conditions can use logical operators to form complex expressions

```
if (total < MAX+5 && !found)
    System.out.println ("Processing...");
```

- Logical operators have precedence relationships among themselves and with other operators
 - all logical operators have lower precedence than the relational or arithmetic operators
 - logical NOT has higher precedence than logical AND and logical OR

Short Circuited Operators



- The processing of logical AND and logical OR is “short-circuited”
- If the left operand is sufficient to determine the result, the right operand is not evaluated

```
if (count != 0 && total/count > MAX)
    System.out.println ("Testing..");
```

- This type of processing must be used carefully

Truth Tables



- Specific expressions can be evaluated using truth tables

<code>total < MAX</code>	<code>found</code>	<code>!found</code>	<code>total < MAX && !found</code>
false	false	true	false
false	true	false	false
true	false	true	true
true	true	false	false

Comparing Characters



- We can use the relational operators on character data
- The results are based on the Unicode character set
- The following condition is true because the character `+` comes before the character `J` in the Unicode character set:

```
if ('+' < 'J')  
    System.out.println ("+ is less than J");
```

- The uppercase alphabet (A-Z) followed by the lowercase alphabet (a-z) appear in alphabetical order in the Unicode character set

Comparing Strings



- Remember that a character string in Java is an object
- We cannot use the relational operators to compare strings
- The `equals` method can be called with strings to determine if two strings contain exactly the same characters in the same order
- The `String` class also contains a method called `compareTo` to determine if one string comes before another (based on the Unicode character set)

Lexicographic Ordering



- Because comparing characters and strings is based on a character set, it is called a *lexicographic ordering*
- This is not strictly alphabetical when uppercase and lowercase characters are mixed
- For example, the string "Great" comes before the string "fantastic" because all of the uppercase letters come before all of the lowercase letters in Unicode
- Also, short strings come before longer strings with the same prefix (lexicographically)
- Therefore "book" comes before "bookcase"

Comparing Float Values



- We also have to be careful when comparing two floating point values (`float` or `double`) for equality
- You should rarely use the equality operator (`==`) when comparing two floats
- In many situations, you might consider two floating point numbers to be "close enough" even if they aren't exactly equal
- Therefore, to determine the equality of two floats, you may want to use the following technique:

```
if (Math.abs(f1 - f2) < 0.00001)
    System.out.println ("Essentially equal.");
```

More Operators



- To round out our knowledge of Java operators, let's examine a few more
- In particular, we will examine
 - the increment and decrement operators
 - the assignment operators

Increment and Decrement



- The increment and decrement operators are arithmetic and operate on one operand
- The *increment operator* (++) adds one to its operand
- The *decrement operator* (--) subtracts one from its operand
- The statement

```
count++;
```

is functionally equivalent to

```
count = count + 1;
```

Assignment Operators



- Often we perform an operation on a variable, and then store the result back into that variable
- Java provides *assignment operators* to simplify that process
- For example, the statement

```
num += count;
```

is equivalent to

```
num = num + count;
```

Assignment Operators



- There are many assignment operators, including the following:

<u>Operator</u>	<u>Example</u>	<u>Equivalent To</u>
<code>+=</code>	<code>x += y</code>	<code>x = x + y</code>
<code>-=</code>	<code>x -= y</code>	<code>x = x - y</code>
<code>*=</code>	<code>x *= y</code>	<code>x = x * y</code>
<code>/=</code>	<code>x /= y</code>	<code>x = x / y</code>
<code>%=</code>	<code>x %= y</code>	<code>x = x % y</code>

Assignment Operators



- The right hand side of an assignment operator can be a complex expression
- The entire right-hand expression is evaluated first, then the result is combined with the original variable
- Therefore

```
result /= (total-MIN) % num;
```

is equivalent to

```
result = result / ((total-MIN) % num);
```

Assignment Operators



- The behavior of some assignment operators depends on the types of the operands
- If the operands to the `+=` operator are strings, the assignment operator performs string concatenation
- The behavior of an assignment operator (`+=`) is always consistent with the behavior of the "regular" operator (`+`)

Repetition Statements



- *Repetition statements* allow us to execute a statement multiple times
- Often they are referred to as *loops*
- Like conditional statements, they are controlled by boolean expressions
- The text covers two kinds of repetition statements:
 - the *while loop*
 - the *for loop*
- The programmer should choose the right kind of loop for the situation

The while Statement


- The *while statement* has the following syntax:

while is a reserved word → `while (condition)
 statement;`

If the *condition* is true, the *statement* is executed.
Then the *condition* is evaluated again.

The *statement* is executed repeatedly until the *condition* becomes false.

Logic of a while Loop



The while Statement



- Note that if the condition of a `while` statement is false initially, the statement is never executed
- Therefore, the body of a `while` loop will execute zero or more times
- See [Counter.java](#) (page 143)
- See [Average.java](#) (page 144)
 - A *sentinel value* indicates the end of the input
 - The variable `sum` maintains a *running sum*
- See [WinPercentage.java](#) (page 147)
 - A loop is used to *validate the input*, making the program more *robust*

Infinite Loops



- The body of a `while` loop eventually must make the condition false
- If not, it is an *infinite loop*, which will execute until the user interrupts the program
- This is a common logical error
- You should always double check to ensure that your loops will terminate normally
- See [Forever.java](#) (page 148)

Nested Loops



- Similar to nested `if` statements, loops can be nested as well
- That is, the body of a loop can contain another loop
- Each time through the outer loop, the inner loop goes through its full set of iterations
- See [PalindromeTester.java](#) (page 151)

The StringTokenizer Class



- The elements that comprise a string are referred to as *tokens*
- The process of extracting these elements is called *tokenizing*
- Characters that separate one token from another are called *delimiters*
- The `StringTokenizer` class, which is defined in the `java.util` package, is used to separate a string into tokens

The StringTokenizer Class



- The default delimiters are space, tab, carriage return, and the new line characters
- The `nextToken` method returns the next token (substring) from the string
- The `hasMoreTokens` returns a boolean indicating if there are more tokens to process
- See [CountWords.java](#) (page 155)

The for Statement



- The *for statement* has the following syntax:

Reserved word The *initialization* is executed once before the loop begins The *statement* is executed until the *condition* becomes false

↓ ↙ ↘

```
for ( initialization ; condition ; increment )  
    statement;
```

The *increment* portion is executed at the end of each iteration
The *condition-statement-increment* cycle is executed repeatedly


The for Statement



- A `for` loop is functionally equivalent to the following `while` loop structure:

```
initialization;  
while ( condition )  
{  
    statement;  
    increment;  
}
```

Logic of a for loop



The for Statement



- Like a `while` loop, the condition of a `for` statement is tested prior to executing the loop body
- Therefore, the body of a `for` loop will execute zero or more times
- It is well suited for executing a loop a specific number of times that can be determined in advance
- See [Counter2.java](#) (page 157)
- See [Multiples.java](#) (page 159)
- See [Stars.java](#) (page 161)

The for Statement



- Each expression in the header of a for loop is optional
 - If the *initialization* is left out, no initialization is performed
 - If the *condition* is left out, it is always considered to be true, and therefore creates an infinite loop
 - If the *increment* is left out, no increment operation is performed
- Both semi-colons are always required in the `for` loop header

Choosing a Loop Structure



- When you can't determine how many times you want to execute the loop body, use a `while` statement
- If you can determine how many times you want to execute the loop body, use a `for` statement

Program Development



- We now have several additional statements and operators at our disposal
- Following proper development steps is important
- Suppose you were given some initial requirements:
 - accept a series of test scores
 - compute the average test score
 - determine the highest and lowest test scores
 - display the average, highest, and lowest test scores

Program Development



- **Requirements Analysis – clarify and flesh out specific requirements**
 - How much data will there be?
 - How should data be accepted?
 - Is there a specific output format required?
- **After conferring with the client, we determine:**
 - the program must process an arbitrary number of test scores
 - the program should accept input interactively
 - the average should be presented to two decimal places
- **The process of requirements analysis may take a long time**

Program Development



- **Design – determine a possible general solution**
 - Input strategy? (Sentinel value?)
 - Calculations needed?
- **An initial algorithm might be expressed in pseudocode**
- **Multiple versions of the solution might be needed to refine it**
- **Alternatives to the solution should be carefully considered**

Program Development



- Implementation – translate the design into source code
- Make sure to follow coding and style guidelines
- Implementation should be integrated with compiling and testing your solution
- This process mirrors a more complex development model we'll eventually need to develop more complex software
- The result is a final implementation
- See [ExamGrades.java](#) (page 164)

Program Development



- **Testing – attempt to find errors that may exist in your programmed solution**
- **Compare your code to the design and resolve any discrepancies**
- **Determine test cases that will stress the limits and boundaries of your solution**
- **Carefully retest after finding and fixing an error**

More Drawing Techniques



- Conditionals and loops can greatly enhance our ability to control graphics
- See [Bullseye.java](#) (page 169)
- See [Boxes.java](#) (page 171)
- See [BarHeights.java](#) (page 173)

Summary



➤ Chapter 3 has focused on:

- program development stages
- the flow of control through a method
- decision-making statements
- expressions for making complex decisions
- repetition statements
- drawing with conditionals and loops