Lab 4.1 – Converting IPv4 Addresses to Binary and Identifying IPv4 Addresses

Group No	Section
1	

Objectives

Part 1: Convert IPv4 Addresses from Dotted Decimal to Binary

Part 2: Use Bitwise ANDing Operation to Determine Network Addresses

Part 3: Apply Network Address Calculations

Part 4: Identify IPv4 Addresses

Part 5: Classify IPv4 Addresses

Background / Scenario

Every IPv4 address is comprised of two parts: a network portion and a host portion. The network portion of an address is the same for all devices that reside in the same network. The host portion identifies a specific host within a given network. The subnet mask is used to determine the network portion of an IP address. Devices on the same network can communicate directly; devices on different networks require an intermediary Layer 3 device, such as a router, to communicate.

To understand the operation of devices on a network, we need to look at addresses the way devices do—in binary notation. To do this, we must convert the dotted decimal form of an IP address and its subnet mask to binary notation. After this has been done, we can use the bitwise ANDing operation to determine the network address.

This lab provides instructions on how to determine the network and host portion of IP addresses by converting addresses and subnet masks from dotted decimal to binary, and then using the bitwise ANDing operation. You will then apply this information to identify addresses in the network. Then, you will examine the structure of Internet Protocol version 4 (IPv4) addresses. You will identify the various types of IPv4 addresses and the components that help comprise the address, such as network portion, host portion, and subnet mask. Types of addresses covered include public, private, unicast, and multicast.

Required Resources

- Device with Internet access
- Optional: IPv4 address calculator

Part 1: Convert IPv4 Addresses from Dotted Decimal to Binary

In Part 1, you will convert decimal numbers to their binary equivalent. After you have mastered this activity, you will convert IPv4 addresses and subnet masks from dotted decimal to their binary form.

Step 1: Convert decimal numbers to their binary equivalent.

Fill in the following table by converting the decimal number to an 8-bit binary number. The first number has been completed for your reference. Recall that the eight binary bit values in an octet are based on the powers of 2, and from left to right are 128, 64, 32, 16, 8, 4, 2, and 1.

Decimal	Binary
192	11000000
168	
10	
255	
2	

Step 2: Convert the IPv4 addresses to their binary equivalent.

An IPv4 address can be converted using the same technique you used above. Fill in the table below with the binary equivalent of the addresses provided. To make your answers easier to read, separate the binary octets with a period.

Decimal	Binary
192.168.10.10	11000000.10101000.00001010.00001010
172.16.18.183	
255.255.255.128	

Part 3: Use Bitwise ANDing Operation to Determine Network Addresses

In Part 2, you will use the bitwise ANDing operation to calculate the network address for the provided host addresses. You will first need to convert an IPv4 decimal address and subnet mask to their binary equivalent. Once you have the binary form of the network address, convert it to its decimal form.

Note: The ANDing process compares the binary value in each bit position of the 32-bit host IP with the corresponding position in the 32-bit subnet mask. If there two 0s or a 0 and a 1, the ANDing result is 0. If there are two 1s, the result is a 1, as shown in the example here.

Step 1: Determine the number of bits to use to calculate the network address.

Description	Decimal	Binary
IP Address	192.168.10.131	11000000.10101000.00001010.10000011
Subnet Mask	255.255.255.192	11111111.11111111.11111111.11000000
Network Address	192.168.10.128	11000000.10101000.00001010.10000000

In the example above, how many bits are used to calculate the network address?

Step 2: Use the ANDing operation to determine the network address.

How do you determine what bits to use to calculate the network address?

a. Enter the missing information into the table below:

Description	Decimal	Binary
IP Address	172.16.145.29	
Subnet Mask	255.255.0.0	
Network Address		

b. Enter the missing information into the table below:

Description	Decimal	Binary
IP Address	192.168.10.10	
Subnet Mask	255.255.255.0	
Network Address		

Part 4: Apply Network Address Calculations

In Part 3, you must calculate the network address for the given IP addresses and subnet masks. After you have the network address, you should be able to determine the responses needed to complete the lab.

Step 1: Determine whether IP addresses are on same network.

a.	You are configuring two PCs for your network. PC-A is given an IP address of 192.168.1.18, and PC-B is given an IP address of 192.168.1.33. Both PCs receive a subnet mask of 255.255.255.240.
	What is the network address for PC-A?
	What is the network address for PC-B?
	Will these PCs be able to communicate directly with each other?
	What is the highest address that can be given to PC-B that allows it to be on the same network as PC-A?
b.	You are configuring two PCs for your network. PC-A is given an IP address of 10.0.0.16, and PC-B is given an IP address of 10.1.14.68. Both PCs receive a subnet mask of 255.254.0.0.
	What is the network address for PC-A?
	What is the network address for PC-B?
	Will these PCs be able to communicate directly with each other?
	What is the lowest address that can be given to PC-B that allows it to be on the same network as PC-A?
Step 2	: Identify the default gateway address.
a.	Your company has a policy to use the first IP address in a network as the default gateway address. A host on the local-area network (LAN) has an IP address of 172.16.140.24 and a subnet mask of 255.255.192.0.
	What is the network address for this network?
	What is the default gateway address for this host?

Part 5: Identify IPv4 Addresses

In Part 5, you will be given several examples of IPv4 addresses and will complete tables with appropriate information.

Step 1: Analyze the table shown below and identify the network portion and host portion of the given IPv4 addresses.

The first two rows show examples of how the table should be completed.

Key for table:

N = all 8 bits for an octet are in the network portion of the address

n = a bit in the network portion of the address

H = all 8 bits for an octet are in the host portion of the address

h = a bit in the host portion of the address

IP Address/Prefix	Network/Host N,n = Network, H,h = Host	Subnet Mask	Network Address
192.168.10.10/24	N.N.N.H	255.255.255.0	192.168.10.0
10.101.99.17/23	N.N.nnnnnnh.H	255.255.254.0	10.101.98.0
209.165.200.227/27			
172.31.45.252/24			

Step 2: Analyze the table below and list the range of host and broadcast addresses given a network/prefix mask pair.

The first row shows an example of how the table should be completed.

IP Address/Prefix	First Host Address	Last Host Address	Broadcast Address
192.168.10.10/24	192.168.10.1	192.168.10.254	192.168.10.255
10.101.99.17/23			
172.31.45.252/24			

Part 6: Classify IPv4 Addresses

In Part 6, you will identify and classify several examples of IPv4 addresses.

Step 1: Analyze the table shown below and identify the type of address (network, host, multicast, or broadcast address).

The first row shows an example of how the table should be completed.

IP Address	Subnet Mask	Address Type
10.1.1.1	255.255.255.252	host
192.168.33.63	255.255.255.192	
239.192.1.100	255.252.0.0	
10.255.0.0	255.0.0.0	
224.10.1.11	255.255.255.0	

Step 2: Analyze the table shown below and identify the address as public or private.

IP Address/Prefix	Public or Private
209.165.201.30/27	
192.168.255.253/24	

Step 3: Analyze the table shown below and identify whether the address/prefix pair is a valid host address.

IP Address/Prefix	Valid Host Address?	Reason
127.1.0.10/24		
172.16.255.0/16		
241.19.10.100/24		
192.31.7.255/24		

Reflection

inchedion .	
1.	Why is the subnet mask important in determining the network address?
2.	Why should we continue to study and learn about IPv4 addressing if the available IPv4 address space is depleted?