



Pin Configuration

Connector 1 Pin #	Connector 2 Pin #
1	3
2	2
3	1

Notes

1. This assembly must have material compliance recognized by UL
2. Contact & Connector housing must be from the same manufacturer
3. Stripping & Crimping instructions, use qualified connector Manufacturer individual instructions

S.No	Open Cellular Part #	Manufacturer Part #	Description	Manufacturer	Quantity
1	213-000148	B3B-PH-K-S	2.0 mm Pitch 3 Connector	JST	1
2	213-000139	-	Marking tube	BRADY	1
3	207-000293	-	Semi-flexible cable 24/26/28 AWG	-	1
4	213-000196	PHR-3	2.0 mm Pitch 3 Pin Wire Connector	JST	1
5	213-000146	SPH-002T-P0.5L	Crimp Contacts-PHR-3	JST	3

02		CHANGED CONNECTORS ON ONE END	07/14/2017
01		DRAFT RELEASE	30/11/2016
REV	CRQ NO	DESCRIPTION	RELEASED DATE
FINISH SPECIFICATION		NA	
MATERIAL SPECIFICATION		REFER TABLE	
UNLESS OTHERWISE SPECIFIED LINEAR TOL =NA ANGULAR TOL=NA SURFACE FINISH TOL=NA		 DOCUMENT CODE PART DRAWING	
THIRD ANGLE 		UNIT mm	SCALE 4.000
SHEET SIZE A4		PART NAME BATTERY CABLE ASSEMBLY	
		PART NO 233-000044	SHEET 1/1