Introduction to Git and GitHub

General Assembly – Data Science

Agenda

- I. Introduction
- II. Exploring GitHub
- III. Using Git with GitHub
- IV. Contributing on GitHub
- V. Bonus Content

I. Introduction

Why learn version control?

- Version control is useful when you write code, and data scientists write code
- Enables teams to easily collaborate on the same codebase
- Enables you to contribute to open source projects
- Attractive skill for employment

What is Git?

- Version control system that allows you to track files and file changes in a repository ("repo")
- Primarily used by software developers
- Most widely used version control system
 - Alternatives: Mercurial, Subversion, CVS
- Runs from the command line (usually)
- Can be used alone or in a team

What is GitHub?

- A website, not a version control system
- Allows you to put your Git repos online
 - Largest code host in the world
 - Alternative: Bitbucket
- Benefits of GitHub:
 - Backup of files
 - Visual interface for navigating repos
 - Makes repo collaboration easy
- "GitHub is just Dropbox for Git"
- Note: Git does not require GitHub

Git can be challenging to learn

- Designed (by programmers) for power and flexibility over simplicity
- Hard to know if what you did was right
- Hard to explore since most actions are "permanent" (in a sense) and can have serious consequences
- We'll focus on the most important 10% of Git

II. Exploring GitHub

GitHub setup

- Create an account at github.com
- There's nothing to install
 - "GitHub for Windows" & "GitHub for Mac" are GUI clients (alternatives to command line)

Navigating a GitHub repo (1 of 2)

- Account name, repo name, description
- Folder structure
- Viewing files:
 - Rendered view (with syntax highlighting)
 - Raw view
- README.md:
 - Describes a repo
 - Automatically displayed
 - Written in Markdown

Navigating a GitHub repo (2 of 2)


• Commits:

- One or more changes to one or more files
- Revision highlighting
- Commit comments are required
- Most recent commit comment shown by filename
- Profile page

Creating a profile

Click on the signup button on the top-right

Choose a plan (one of them is free)



Remember your email and password!!!! You will need it again soon!!!!

Basic Markdown


- Easy-to-read, easy-to-write markup language
- Usually (always?) rendered as HTML
- Many implementations (aka "flavors")
- Let's edit README.md using GitHub!
- Common syntax:
 - ## Header size 2
 - *italics* and **bold**
 - [link to GitHub](https://github.com)
 - * bullet
 - 'inline code' and '''code blocks'''
- Valid HTML can also be used within Markdown

III. Using Git with GitHub

Cloning a GitHub repo

- Cloning == copying to your local computer
 - Like copying your Dropbox files to a new machine
- First, change your working directory to where you want the repo you created to be stored: cd
- Then, clone the repo: git clone <URL>
 - Get HTTPS or SSH URL from GitHub (ends in .git)
 - Clones to a subdirectory of the working directory
 - No visual feedback when you type your password
- Navigate to the repo (cd) then list the files (ls)

The url is on the repo page



First Clone

First we will clone the main class repo!

 You will need to do this to stay up to date with all of class info

Before Cloning

```
Sinans-MacBook-Pro:test_dir sinanozdemir$ pwd
/Users/sinanozdemir/Dropbox/test_dir
Sinans-MacBook-Pro:test_dir sinanozdemir$ ls
stuff
Sinans-MacBook-Pro:test_dir sinanozdemir$
```

 Move into a Directory that you want to store the info for the next 11 weeks

Before Cloning

```
Sinans-MacBook-Pro:test_dir sinanozdemir$ pwd
/Users/sinanozdemir/Dropbox/test_dir
Sinans-MacBook-Pro:test_dir sinanozdemir$ ls
stuff
Sinans-MacBook-Pro:test_dir sinanozdemir$
```

During Cloning

```
test_dir - bash - 125x36

Sinans-MacBook-Pro:test_dir sinanozdemir$ pwd
/Users/sinanozdemir/Dropbox/test_dir
Sinans-MacBook-Pro:test_dir sinanozdemir$ ls
stuff
Sinans-MacBook-Pro:test_dir sinanozdemir$ git clone https://github.com/sinanuozdemir/SF_DAT_17.git
```

• git clone https://github.com/sinanuozdemir/SF DAT 17.git

After Cloning

```
test_dir - bash - 125×36
Sinans-MacBook-Pro:test dir sinanozdemir$ pwd
/Users/sinanozdemir/Dropbox/test dir
Sinans-MacBook-Pro:test dir sinanozdemir$ ls
stuff
Sinans-MacBook-Pro:test dir sinanozdemir$ git clone https://github.com/sinanuozdemir/SF DAS
Cloning into 'SF DAT 17' ....
remote: Counting objects: 67, done.
remote: Compressing objects: 100% (61/61), done.
remote: Total 67 (delta 10), reused 56 (delta 5), pack-reused 0
Unpacking objects: 100% (67/67), done.
Checking connectivity... done.
Sinans-MacBook-Pro:test dir sinanozdemir$ pwd
/Users/sinanozdemir/Dropbox/test dir
Sinans-MadBook-Pro:test dir sinanozdemir$ ls
SF DAT 17
                stuff
Sinans-MagBook-Pro:test dir sinanozdemir$
```

You have a new folder!

Same as on Github!

- cd into it and Is
- Try this now! (take 5-10 minutes)


Second Clone

Now we will clone your new repo!

First we have to make one

Creating a repo on GitHub

- Click "Create New" (plus sign) on your profile:
 - Define name, description, public or private
 - Initialize with README (if you're going to clone)
 - Please call it SF_DAT_17_WORK
- Notes:
 - Nothing has happened to your local computer
 - This was done on GitHub, but GitHub add the README.md file



Preview of what you're about to do

Copy ("clone") your new GitHub repo to your computer

Make some file changes locally

Save those changes locally ("commit" them)

Update your GitHub repo with those changes ("push")

Preview of what you're about to do

Copy ("clone") your new GitHub repo to your computer

Try this now! (take 5-10 minutes)

- SUPER IMPORTANT:
 - Make sure that you LEAVE SF_DAT_17 before cloning the new repo
 - cd ..

Making changes, checking your status

- Making changes:
 - Modify README.md in any text editor
 - Create a new file: touch <filename>
- Check your status:
 - git status
- File statuses (possibly color-coded):
 - Untracked (red)
 - Tracked and modified (red)
 - Staged for committing (green)
 - Committed
- Try this now! (take 5-10 minutes)

Committing changes

- Stage changes for committing:
 - Add all "red" files: git add .
- Check your status:
 - git status
 - Red files have turned green
- Commit changes:
 - git commit -m "message about commit"
- Check your status again!
- Try this now! (take 5-10 minutes)

Pushing to GitHub

- Everything you've done to your cloned repo (so far) has been local
- You've been working in the "master" branch
- Push committed changes to GitHub:
 - Like syncing local file changes to Dropbox
 - git push <remote> <branch>
 - Often: git push origin master
- Refresh your GitHub repo to check!

Quick recap of what you've done

- Created a repo on GitHub
- Cloned repo to your local computer (git clone)
 - Automatically sets up your "origin" remote
- Made two file changes
- Staged changes for committing (git add)
- Committed changes (git commit)
- Pushed changes to GitHub (git push)
- Inspected along the way (git remote, git status, git log)

Let's do it again!

- Modify or add a file, then git status
- git add ., then git status
- git commit -m "message"
- git push origin master
- Refresh your GitHub repo
- Note if you want to add a folder, the folder must have an item in it or else github will not recognize it

Try this now! (take 5-10 minutes)

Lab -- Before you leave

Install <u>Git</u> on your machine

Make a <u>Github</u> Profile on the web

 Create your own repo, call it "SF_DAT_17_WORK" and clone it to your machine

Clone the <u>class repo</u>

IV. Bonus Content

Git installation and setup

- Installation: <u>tiny.cc/installgit</u>
- Open Git Bash (Windows) or Terminal (Mac/Linux):
 - git config --global user.name "YOUR FULL NAME"
 - git config --global user.email "YOUR EMAIL"
- Use the same email address you used with your GitHub account
- Generate SSH keys (optional): <u>tiny.cc/gitssh</u>
 - More secure that HTTPS
 - Only necessary if HTTPS doesn't work for you

Checking your remotes

- A "remote alias" is a reference to a repo not on your local computer
 - Like a connection to your Dropbox account
- View remotes: git remote -v
- "origin" remote was set up by "git clone"
- Note: Remotes are repo-specific

Two ways to initialize Git

- Initialize on GitHub:
 - Create a repo on GitHub (with README)
 - Clone to your local machine
- Initialize locally:
 - Initialize Git in existing local directory: git init
 - Create a repo on GitHub (without README)
 - Add remote: git remote add origin <URL>

Deleting or moving a repo

- Deleting a GitHub repo:
 - Settings, then Delete
- Deleting a local repo:
 - Just delete the folder!
- Moving a local repo:
 - Just move the folder!

Excluding files from a repo

- Create a ".gitignore" file in your repo: touch .gitignore
- Specify exclusions, one per line:
 - Single files: pip-log.txt
 - All files with a matching extension: *.pyc
 - Directories: env/
- Templates: github.com/github/gitignore

Gists: lightweight repos

- You have access to Gist: gist.github.com
- Add one or more files
- Supports cloning, forking, commenting, committing
- Can be public or secret (not private)
- Useful for snippets, embedding, IPython nbviewer, etc.

Useful to learn next

- Working with branches
- Rolling back changes
- Resolving merge conflicts
- Fixing LF/CRLF issues