```
UDP
                     192.168.0.16
                                          128.119.245.12
                                                                       70
    73 3.897834
                                                                              33877 → 33435 Len=28
Frame 73: 70 bytes on wire (560 bits), 70 bytes captured (560 bits) on interface 0
Ethernet II, Src: Apple_0c:6b:03 (a0:99:9b:0c:6b:03), Dst: Netgear_f6:28:ea (50:6a:03:f6:28:ea)
Internet Protocol Version 4, Src: 192.168.0.16, Dst: 128.119.245.12
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
   Total Length: 56
   Identification: 0x8456 (33878)
   Flags: 0x00
   Fragment offset: 0
   Time to live: 1
       [Expert Info (Note/Sequence): "Time To Live" only 1]
           ["Time To Live" only 1]
           [Severity level: Note]
           [Group: Sequence]
   Protocol: UDP (17)
   Header checksum: 0xff22 [validation disabled]
   Source: 192.168.0.16
   Destination: 128.119.245.12
    [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
User Datagram Protocol, Src Port: 33877 (33877), Dst Port: 33435 (33435)
   Source Port: 33877
   Destination Port: 33435
       [Expert Info (Chat/Sequence): Possible traceroute: hop #1, attempt #1]
           [Possible traceroute: hop #1, attempt #1]
           [Severity level: Chat]
           [Group: Sequence]
   Length: 36
   Checksum: 0xc278 [validation disabled]
       [Good Checksum: False]
       [Bad Checksum: False]
   [Stream index: 1]
Data (28 bytes)
0010 00 00 00 00 00 00 00 00 00 00 00
```