

```
2 0.023172      128.119.245.12      192.168.1.102      TCP      62      80 → 1161 [SYN, ACK] Seq=0 Ack=1 Win=5840
Len=0 MSS=1460 SACK_PERM=1
Frame 2: 62 bytes on wire (496 bits), 62 bytes captured (496 bits)
Ethernet II, Src: LinksysG_da:af:73 (00:06:25:da:af:73), Dst: Actionte_8a:70:1a (00:20:e0:8a:70:1a)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.102
Transmission Control Protocol, Src Port: 80 (80), Dst Port: 1161 (1161), Seq: 0, Ack: 1, Len: 0
  Source Port: 80
  Destination Port: 1161
  [Stream index: 0]
  [TCP Segment Len: 0]
  Sequence number: 0 (relative sequence number)
  Acknowledgment number: 1 (relative ack number)
  Header Length: 28 bytes
  Flags: 0x012 (SYN, ACK)
    000. .... = Reserved: Not set
    ...0 .... = Nonce: Not set
    .... 0... = Congestion Window Reduced (CWR): Not set
    .... .0.. = ECN-Echo: Not set
    .... ..0. = Urgent: Not set
    .... ...1 = Acknowledgment: Set
    .... .... 0... = Push: Not set
    .... .... .0.. = Reset: Not set
    .... .... ..1. = Syn: Set
    .... .... ...0 = Fin: Not set
  [TCP Flags: *****A**S*]
  Window size value: 5840
  [Calculated window size: 5840]
  Checksum: 0x774d [validation disabled]
    [Good Checksum: False]
    [Bad Checksum: False]
  Urgent pointer: 0
  Options: (8 bytes), Maximum segment size, No-Operation (NOP), No-Operation (NOP), SACK permitted
  [SEQ/ACK analysis]
    [This is an ACK to the segment in frame: 1]
    [The RTT to ACK the segment was: 0.023172000 seconds]
    [iRTT: 0.023265000 seconds]
```