

```
20 5.044796      128.119.245.12      192.168.0.15      HTTP      506      HTTP/1.1 200 OK (text/html)
Frame 20: 506 bytes on wire (4048 bits), 506 bytes captured (4048 bits)
Ethernet II, Src: Netgear_f6:28:ea (50:6a:03:f6:28:ea), Dst: Apple_0c:6b:03 (a0:99:9b:0c:6b:03)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.15
Transmission Control Protocol, Src Port: 80 (80), Dst Port: 55876 (55876), Seq: 1, Ack: 343, Len: 440
Hypertext Transfer Protocol
  HTTP/1.1 200 OK\r\n
  Date: Fri, 12 Feb 2016 18:45:41 GMT\r\n
  Server: Apache/2.4.6 (CentOS) OpenSSL/1.0.1e-fips PHP/5.4.16 mod_perl/2.0.9dev Perl/v5.16.3\r\n
  Last-Modified: Fri, 12 Feb 2016 06:59:01 GMT\r\n
  ETag: "51-52b8d33b6c05a"\r\n
  Accept-Ranges: bytes\r\n
  Content-Length: 81\r\n
  Keep-Alive: timeout=5, max=100\r\n
  Connection: Keep-Alive\r\n
  Content-Type: text/html; charset=UTF-8\r\n
\r\n
[HTTP response 1/3]
[Time since request: 0.084877000 seconds]
[Request in frame: 16]
[Next request in frame: 22]
[Next response in frame: 24]
Line-based text data: text/html
```