```
    298 62.481642       128.93.162.84         192.168.0.12           ICMP    106    Echo (ping) reply    id=0x0001,
seq=118/30208, ttl=45 (request in 297)
Frame 298: 106 bytes on wire (848 bits), 106 bytes captured (848 bits) on interface 0
Ethernet II, Src: Netgear_f6:28:ea (50:6a:03:f6:28:ea), Dst: IntelCor_95:25:b7 (00:21:5c:95:25:b7)
Internet Protocol Version 4, Src: 128.93.162.84, Dst: 192.168.0.12
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 92
    Identification: 0x7403 (29699)
    Flags: 0x00
        0... .... = Reserved bit: Not set
        .0.. .... = Don't fragment: Not set
        ..0. .... = More fragments: Not set
    Fragment offset: 0
    Time to live: 45
    Protocol: ICMP (1)
    Header checksum: 0x3638 [validation disabled]
    Source: 128.93.162.84
    Destination: 192.168.0.12
    [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
Internet Control Message Protocol
    Type: 0 (Echo (ping) reply)
    Code: 0
    Checksum: 0xff88 [correct]
    Identifier (BE): 1 (0x0001)
    Identifier (LE): 256 (0x0100)
    Sequence number (BE): 118 (0x0076)
    Sequence number (LE): 30208 (0x7600)
    [Request frame: 297]
    [Response time: 97.988 ms]
    Data (64 bytes)
0000  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00   ................
0010  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00   ................
0020  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00   ................
0030  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00   ................
        Data: 00000000000000000000000000000000000000000000000000...
        [Length: 64]
```