x86 & PE



28th December 2011

Ange Albertini

before you decide to read further...

HIDDEN SLIDE

Contents of this slide deck:

1. Introduction
    1. introduce Corkami, my reverse engineering site
    2. explain (in easy terms)
        1. why correct disassembly is important for analysis
        2. why undocumented opcodes are a dead end
2. Main part
    1. a few examples of undocumented opcodes and CPU weirdness
    2. theory-only sucks, so I created CoST for practicing and testing.
    3. CoST also tests PE, but it's not enough by itself
    4. So I documented PE separately, and give some examples.

Improved, but similar



Author

- Corkami
  - reverse engineering
  - technical, really free
  - MANY handmade and focused PoCs
    - nightly builds
    - summary wiki pages
  - but... only a hobby!

“there's a PoC for that”

and if there's none yet, there will be soon ;)

```
istruc IMAGE_DOS_HEADER
    at IMAGE_DOS_HEADER.e_magic, db 'ZM'
;   at IMAGE_DOS_HEADER.e_cblp, db LAST_BYTE    ; not rec
    at IMAGE_DOS_HEADER.e_cp, dw PAGES
    at IMAGE_DOS_HEADER.e_cparhdr, dw dos_stub >> 4

; code start must be paragraph-aligned
align 10h, db 0
dos_stub:
    push    cs
    pop     ds
```

```
demoZM

D>dosZMXP.exe
 * EXE with ZM signature
```

```
File  Edit  View  Window  Help

Hello World!
```

```
helloworld-X - Notepad
File  Edit  Format  View  Help
%PDF-1.
1 0 obj<</Kids[<</Parent 1 0 R/Contents[2 0 R]>>]/Resources<<>>>>
2 0 obj<<>>
streamBT/default 99 Tf 1 0 0 1 1 715 Tm(Hello World!)Tj ET
endstream
endobj
trailer<</Root<</Pages 1 0 R>>>>
```

```
code = "".join([
    GETSTATIC, struct.pack(">H", 16),
    LDC, struct.pack(">B", 18),
    INVOKEVIRTUAL, struct.pack(">H", 23)
    RETURN,
    ])

attribute_code = "".join([
struct.pack(">H", 7), # code
u4length("".join([
    struct.pack(">H
    struct.pack(">H
    u4length(code),
```

```
demo java

D>java HelloWorld
Hello World !
```

```
istruc IMAGE_OPTIONAL_HEADER32
        at IMAGE_OPTIONAL_HEADER32.Magic,
bits 32
EntryPoint:
    push message
    call [__imp__printf]
    jmp _2
        at IMAGE_OPTIONAL_HEADER32.AddressOfEntry
        at IMAGE_OPTIONAL_HEADER32.BaseOfCode, dd
_2:
    add esp, 1 * 4
    retn
        at IMAGE_OP
```

```
demo PE

D>tiny
 * 268b universal tiny PE
```

the story behind this presentation





Command "MakeCode" failed




BACK
TO THE BASICS


CORKAMI
x86
PE
PDF,JAVA,...


CORKAMI
x86
PE
THIS TALK
PDF,JAVA,...

“Achievement unlocked”







(Authors notified, and most bugs already fixed)

Agenda

I. why does it matter?
    I. assembly
    II. undocumented assembly
II. x86 oddities
        (technical stuff starts now)
III. CoST
IV. a bit more of PE

assembly, in 8 slides

from C to binary

```c
#include "stdafx.h"
#include "helloworld.h"

int APIENTRY _tWinMain(HINSTANCE hInstance,
                       HINSTANCE hPrevInstance,
                       LPTSTR    lpCmdLine,
                       int       nCmdShow)
{
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
    ExitProcess(0);
}
```



inside the binary

```
#include "stdafx.h"
#include "helloworld.h"

int APIENTRY _tWinMain(HINSTANCE hInstance,
                       HINSTANCE hPrevInstance,
                       LPTSTR    lpCmdLine,
                       int       nCmdShow)
{
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
00121000 6A 40                push        40h
00121002 68 F4 20 12 00       push        offset string "Tada !" (1220F4h)
00121007 68 FC 20 12 00       push        offset string "Hello World !" (1220FCh)
0012100C 6A 00                push        0
0012100E FF 15 AC 20 12 00    call        dword ptr [__imp__MessageBoxA@16 (1220ACh)]
    ExitProcess(0);
00121014 6A 00                push        0
00121016 FF 15 00 20 12 00    call        dword ptr [__imp__ExitProcess@4 (122000h)]
```

order

```
#include "stdafx.h"
#include "helloworld.h"

int APIENTRY _tWinMain(HINSTANCE hInstance,
                       HINSTANCE hPrevInstance,
                       LPTSTR    lpCmdLine,
                       int       nCmdShow)
{
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
00121000 6A 40                push        40h
00121002 68 F4 20 12 00       push        offset string "Tada !" (1220F4h)
00121007 68 FC 20 12 00       push        offset string "Hello World !" (1220FCh)
0012100C 6A 00                push        0
0012100E FF 15 AC 20 12 00    call        dword ptr [__imp__MessageBoxA@16 (1220ACh)]
    ExitProcess(0);
00121014 6A 00                push        0
00121016 FF 15 00 20 12 00    call        dword ptr [__imp__ExitProcess@4 (122000h)]
```

1

2

3

our code, 'translated'

```
#include "stdafx.h"
#include "helloworld.h"

int APIENTRY _tWinMain(HINSTANCE hInstance,
                       HINSTANCE hPrevInstance,
                       LPTSTR    lpCmdLine,
                       int       nCmdShow)
{
    MessageBoxA(0,"Hello World !","Tada !",MB_ICONINFORMATION);
00121000 6A 40                push        40h
00121002 68 F4 20 12 00       push        offset string "Tada !" (1220F4h)
00121007 68 FC 20 12 00       push        offset string "Hello World !" (1220FCh)
0012100C 6A 00                push        0
0012100E FF 15 AC 20 12 00    call        dword ptr [__imp_MessageBoxA@16 (1220ACh)]
    ExitProcess(0);
00121014 6A 00                push        0
00121016 FF 15 00 20 12 00    call        dword ptr [__imp_ExitProcess@4 (122000h)]
```

opcodes ⇔ assembly

```
#include "stdafx.h"
#include "helloworld.h"

int APIENTRY _tWinMain(HINSTANCE hInstance,
                       HINSTANCE hPrevInstance,
                       LPTSTR    lpCmdLine,
                       int       nCmdShow)
{
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
00121000 6A 40                push        40h
00121002 68 F4 20 12 00       push        offset string "Tada !" (1220F4h)
00121007 68 FC 20 12 00       push        offset string "Hello World !" (1220FCh)
0012100C 6A 00                push        0
0012100E FF 15 AC 20 12 00    call        dword ptr [__imp__MessageBoxA@16 (1220ACh)]
    ExitProcess(0);
00121014 6A 00                push        0
00121016 FF 15 00 20 12 00    call        dword ptr [__imp__ExitProcess@4 (122000h)]
```

what's (only) in the binary

```
    MessageBoxA(0, "Hello World !", "
00121000 6A 40                push
00121002 68 F4 20 12 00       push
00121007 68 FC 20 12 00       push
0012100C 6A 00                push
0012100E FF 15 AC 20 12 00    call
    ExitProcess(0);
00121014 6A 00                push
00121016 FF 15 00 20 12 00    call
```



execution ⇔ CPU + opcodes





opcodes

- generated by compilers, tools,...
  - or written by hand
- executed directly by the CPU
- the only code information, in a standard binary
  - what 'we' read
    - **after** disassembly

- disassembly is only for humans
  - no text code in the final binary

let's mess a bit now...

let's insert 'something'

```
{
    __asm {__emit 0xd6}
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
    ExitProcess(0);
}
```



```
    __asm {__emit 0xd6}
00051000 ??                 db          d6h
    MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
00051001 6A 40              push        40h
00051003 68 F4 20 05 00     push        offset string "Tada !" (5
00051008 68 FC 20 05 00     push        offset string "Hello Wor
0005100D 6A 00              push        0
0005100F FF 15 AC 20 05 00  call        dword ptr [__imp__Message
```

Table A-2. One-byte Opcode Map: (00H — F7H) *

	0	1	2	3	4	5	6	7
0	ADD						PUSH ES^{i64}	POP ES^{i64}
	Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz		
1	ADC						PUSH SS^{i64}	POP SS^{i64}
	Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz		
2	AND						SEG=ES (Prefix)	DAA^{i64}
	Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz		
3	XOR						SEG=SS (Prefix)	AAA^{i64}
	Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz		
4	INC^{i64} general register / REX^{o64} Prefixes							
	eAX REX	eCX REX.B	eDX REX.X	eBX REX.XB	eSP REX.R	eBP REX.RB	eSI REX.RX	eDI REX.RXB
5	PUSH^{d64} general register							
	rAX/r8	rCX/r9	rDX/r10	rBX/r11	rSP/r12	rBP/r13	rSI/r14	rDI/r15
6	PUSHA^{i64}/ PUSHAD^{i64}	POPA^{i64}/ POPAD^{i64}	BOUND^{i64} Gv, Ma	ARPL^{i64} Ew, Gw MOVSXD^{o64} Gv, Ev	SEG=FS (Prefix)	SEG=GS (Prefix)	Operand Size (Prefix)	Address Size (Prefix)
7	Jcc^{f64}, Jb - Short-displacement jump on condition							
	O	NO	B/NAE/C	NB/AE/NC	Z/E	NZ/NE	BE/NA	NBE/A
8	Immediate Grp 1^{1A}				TEST		XCHG	
	Eb, Ib	Ev, Iz	Eb, Ib^{i64}	Ev, Ib	Eb, Gb	Ev, Gv	Eb, Gb	Ev, Gv
9	NOP PAUSE(F3) XCHG r8, rAX	XCHG word, double-word or quad-word register with rAX						
		rCX/r9	rDX/r10	rBX/r11	rSP/r12	rBP/r13	rSI/r14	rDI/r15
A	MOV				MOVS/B Xb, Yb	MOVS/W/D/Q Xv, Yv	CMPS/B Xb, Yb	CMPS/W/D Xv, Yv
	AL, Ob	rAX, Ov	Ob, AL	Ov, rAX				
B	MOV immediate byte into byte register							
	AL/R8L, Ib	CL/R9L, Ib	DL/R10L, Ib	BL/R11L, Ib	AH/R12L, Ib	CH/R13L, Ib	DH/R14L, Ib	BH/R15L, Ib
C	Shift Grp 2^{1A}		RETN^{f64} Iw	RETN^{f64}	LES^{i64} Gz, Mp	LDS^{i64} Gz, Mp	Grp 11^{1A} - MOV	
	Eb, Ib	Ev, Ib					Eb, Ib	Ev, Iz
D	Shift Grp 2^{1A}				AAM^{i64} Ib	AAD^{i64} Ib		XLAT/ XLATB
	Eb, 1	Ev, 1	Eb, CL	Ev, CL				
E	LOOPNE^{f64}/ LOOPNZ^{f64} Jb	LOOPE^{f64}/ LOOPZ^{f64} Jb	LOOP^{f64} Jb	JrCXZ^{f64}/ Jb	IN		OUT	
					AL, Ib	eAX, Ib	Ib, AL	Ib, eAX
F	LOCK (Prefix)		REPNE (Prefix)	REP/REPE (Prefix)	HLT	CMC	Unary Grp 3^{1A}	
							Eb	Ev

what did we do?

- Inserting an unrecognized byte
  - directly in the binary
    - to be executed by the CPU
  - not even documented, nor identified!

“kids, don't try this at home!”

the CPU doesn't care

- **it** knows
  - and does its own stuff

```
__asm {__emit 0xd6}
MessageBoxA(0, "Hello World !", "Tada !", MB_ICONINFORMATION);
ExitProcess(0);
```

what happened ?

- D6 = S[ET]ALC
  - Set AL on Carry
    - AL = CF ? -1 : 0
- trivial
- but not documented
  - unreliable, or shameful ?

Table A-1. One-Byte Opcodes, Low Nibble 0–7h

Nibble[1]	0	1	2	3	4	5	6	7
0	ADD Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz	PUSH ES[3]	POP ES[3]
1	ADC Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz	PUSH SS[3]	POP SS[3]
2	AND Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz	seg ES[6]	DAA[3]
3	XOR Eb, Gb	Ev, Gv	Gb, Eb	Gv, Ev	AL, Ib	rAX, Iz	seg SS[6]	AAA[3]
4	INC[5] eAX	eCX	eDX	eBX	eSP	eBP	eSI	eDI
5	PUSH rAX/r8	rCX/r9	rDX/r10	rBX/r11	rSP/r12	rBP/r13	rSI/r14	rDI/r15
6	PUSHA/D[3]	POPA/D[3]	BOUND[3] Gv, Ma	ARPL[3] Ew, Gw MOVSXD[4] Gv, Ed	seg FS	seg GS	operand size	address size
7	JO Jb	JNO Jb	JB Jb	JNB Jb	JZ Jb	JNZ Jb	JBE Jb	JNBE Jb
8	Group 1[2] Eb, Ib	Ev, Iz	Eb, Ib[3]	Ev, Ib	TEST Eb, Gb	Ev, Gv	XCHG Eb, Gb	Ev, Gv
9	XCHG r8, rAX NOP,PAUSE	rCX/r9, rAX	rDX/r10, rAX	rBX/r11, rAX	rSP/r12, rAX	rBP/r13, rAX	rSI/r14, rAX	rDI/r15, rAX
A	MOV AL, Ob	rAX, Ov	Ob, AL	Ov, rAX	MOVSB Yb, Xb	MOVSW/D/Q Yv, Xv	CMPSB Xb, Yb	CMPSW/D/Q Xv, Yv
B	MOV AL, Ib r8b, Ib	CL, Ib r9b, Ib	DL, Ib r10b, Ib	BL, Ib r11b, Ib	AH, Ib r12b, Ib	CH, Ib r13b, Ib	DH, Ib r14b, Ib	BH, Ib r15b, Ib
C	Group 2[2] Eb, Ib	Ev, Ib	RET near Iw		LES[3] Gz, Mp	LDS[3] Gz, Mp	Group 11[2] Eb, Ib	Ev, Iz
D	Group 2[2] Eb, 1	Ev, 1	Eb, CL	Ev, CL	AAM[3]	AAD[3]	SALC[3]	XLAT
E	LOOPNE/NZ Jb	LOOPE/Z Jb	LOOP Jb	JrCXZ Jb	IN AL, Ib	eAX, Ib	OUT Ib, AL	Ib, eAX
F	LOCK:	INT1 ICE Bkpt	REPNE:	REP: REPE:	HLT	CMC	Group 3[2]	

“do what I do...”



XED version: [$Id: xed-version.c 2718 2011-10-12 21:09:59Z mjcharne $]

```
F1                  int1
D6                  salc
F7C890909090        test eax, 0x90909090
0F1E84C090909090    nop dword ptr [eax+eax*8-0x6f6f6f70], eax
0F2090              mov eax, cr2
660FC8              bswap ax
```

the problem (1/2)

- the CPU does its stuff
  - whatever we (don't) know
- if we/our tools don't know what's next, we're blind.

the problem (2/2)

no exhaustive or clean test set

- deep into malwares or packers
- scattered

$\rightarrow$ Corkami

let's start exploring x86...

Questions

Generalities

- opcodes
- registers
  - relation
  - initial values

Specificities

a multi-generation CPU: modern...

English	Assembly
let's go!	*push*
you win	*mov*
sandwich	*call*
hello	*retn*
f*ck	*jmp*

...shakespeare...

thou	*aaa*
porpentine	*xlat*
enmity	*verr*
hither	*smsw*
unkennel	*lsl*

(old, but fully supported)

```
CE              INTO
6202            BOUND EAX,QWORD PTR DS:[EDX]
0F00E1          VERR CX
0F02C1          LAR EAX,ECX
0F00CA          STR DX
37              AAA
0F03C1          LSL EAX,ECX
0FAEF8          SFENCE
63C1            ARPL CX,AX
D40A            AAM
0FC9            BSWAP ECX
F0:0FC70E       LOCK CMPXCHG8B QWORD PTR DS:[ESI]
C51E            LDS EBX,FWORD PTR DS:[ESI]
D7              XLAT BYTE PTR DS:[EBX+AL]
27              DAA
0FC1C1          XADD ECX,EAX
0F0D00          PREFETCH QWORD PTR DS:[EAX]
```

'over-disassembling'

- CD XX: int XX
- deprecated behaviors:
  - int 20h = VXD, int 35-39 = FPU

```
EB02          jmps      .000401017
CD20EB049090  vxdcall    9090.04EB
CD20EB049090  vxdcall    9090.04EB
CD209080C000  vxdjmp     00C0.0090
```

```
CD 35 D0              fnop; (emulator call)
C0 EB 02              shr     bl, 2
CD 20 EB 04 90 90     VxDCall 909004EBh
CD 20 EB 04 90 90     VxDCall 909004EBh
CD 20 90 80 C0 00     VxDJmp  0C00090h
```

```
CD 35 int     35h

      _0:
D0 C0 rol     al, 1
EB 02 jmp     short _1
      ; ---------------
CD 20 int     20h

      _1:
EB 04 jmp     short _2
      ; ---------------
90    nop
90    nop
CD 20 int     20h
```

...next generation

tweet	*crc32*
poke	*aesenc*
google	*pcmpistrm*
pwn	*vfmsubadd132ps*
apps	*movbe*

Fused Multiply-Alternating Subtract/Add
of Packed Single-Precision Floating-Point Values

only in netbooks!

all opcodes PoC

```
    int3                                ;cc
    int 3                               ;cd 03
    smi                                 ;f1 (386)
[...]
    aam                                 ;d40a
    aam 255                             ;d4xx   ; undocumented
[...]
    vaeskeygenassist xmm0, xmm0, 0   ;c4e379dfc000
[...]
    vfnmaddpd ymm0, ymm0, ymm0, ymm0 ;c4e37d79c000
[...]
; VIA Padlock
    rep xsha256                         ;f30fa6d0 calculate SHA256 as specified by FIPS 180-2
    rep montmul                         ;f30fa6c0 montgomery multiplier
```

registers

- Complex relations
  - FPU changes FST, STx, Mmx (ST0 overlaps MM7)
    - also changes CR0 (under XP)

- Initial values
  - AX = <OS generation>
    - OS = (EAX == 0) ? XP : newer
  - GS = <number of bits>

    bits = (GS == 0) ? 32 : 64

initial values PoC

```
[...]
EntryPoint:
    xchg esp, [fake_esp]
    pushf
    pusha
    xchg esp, [fake_esp]
[...]
    mov eax, [flags]
    cmp eax, 246h
[...]
    mov eax, [eax_]
    cmp eax, 0 ; good XP value
[...]
    cmp eax, 70000000h ; good >=Vista value

[...]

TLS:
[...]
    cmp ecx, 11h ; good >=Vista value
[...]
    cmp ecx, TLSSIZE ; good XP value
[...]
```



fully ctrl-ed

controlled

fixed

range

smsw

- CR0 access, from user-mode
  - 286 opcode
- higher word of reg32 'undefined'
- under XP
  - influenced by FPU
  - eventually reverts

DEMO

```
 smsw        eax
 cmp         ax,03B ;';'
 jnz         bad --↓1
 fnop
 smsw        eax
 cmp         ax,031 ;'1'
 jnz         bad --↓1
2smsw        eax
 cmp         ax,031 ;'1'
 jz          wait_loop --↑2
```

```
>smsw
* smsw trick: OK

>smsw  1>smsw.txt

>type smsw.txt
* smsw trick: fail
```

GS

- unused on Windows 32b
  - on 64b: FS, GS = TEB32, TEB64
- reset on thread switch
  - eventually reset
    - debugger stepping
    - wait
    - timings

DEMO



nop

- *nop* is *xchg *ax, *ax*
  - but *xchg *ax, *ax* can **do** something, in 64b !

    87 c0: xchg eax, eax

    `.. .. .. .. 01 23 45 67 => 00 00 00 00 01 23 45 67`
- *hint nop* `0F1E84C090909090 nop dword ptr [eax+eax*8-0x6f6f6f70], eax`
  - partially undocumented, actually 0f 18-1f
  - can trigger exception

mov

- documented, but sometimes tricky
  - *mov [cr0], eax* *mov cr0, eax*
    - mod/RM is ignored
  - *movsxd eax, ecx* *mov eax, ecx*
    - no REX prefix
  - *mov eax, cs* *movzx eax,cs*
    - 'undefined' upper word

non standard CR0 access



bswap

rax

```
 12 34 56 78 90 ab cd ef => ef cd ab 90 78 56 34 12
```

eax

```
 .. .. .. .. 01 23 45 67 => 00 00 00 00 67 45 23 01
```

ax

```
 .. .. .. .. .. .. 01 23 => .. .. .. .. .. .. 00 00
```

```
00400ff8 0000                add     byte ptr [rax],al
00400ffa 0000                add     byte ptr [rax],al
00400ffc 0000                add     byte ptr [rax],al
00400ffe 0000                add     byte ptr [rax],al
00401000 48b8efcdab8967452301 mov rax,123456789ABCDEFh
0040100a 87c0                xchg    eax,eax
0040100c 90                  nop
```

rax	89abcdef
rip	40100c
rcx	7ffff000
rdx	401000
rbx	0

DEMO

00401FFE	0F19C2	hint_nop edx

Access violation when reading [00402000] - use Shift+F7/F8/F9 to

push+ret

```
start:          push                    next  --↓1
.00401014:      retn ;  -^-^-^-^-^-^-^-^-^-^-^-^-^-
.00401016:      int                     3
next:         1push                     000401043 ;'Tada!'
.0040101D:      call                    printf
```

DEMO


0040100E . 90 NOP
<start> . 68 18104000 PUSH <pushret.next>
00401014 . 66:C3 RETN
00401016 CC INT3
00401017 CC INT3
<next> > 68 43104000 PUSH pushret.00401043
0040101D . FF15 1811400 CALL DWORD PTR DS:[401118]
00401023 . 83C4 04 ADD ESP,4
00401026 . 6A 00 PUSH 0
00401028 . FF15 1011400 CALL DWORD PTR DS:[401110]
0040102E CC INT3
0040102F CC INT3
RET used as a jump to next
format = "Tada!"
printf
D:_nc10\sources\corkami\trunk
* push/ret test: "fail"

...and so on...

- much more @ http://x86.corkami.com
  - also graphs, cheat sheet...

- too much theory for now...

Corkami Standard Test

CoST

- http://cost.corkami.com
- testing opcodes
- in a hardened PE
  - available in easy mode

more than 150 tests

- classic, rare
- jumps (JMP to IP, IRET, …)
- undocumented (IceBP, SetALc...)
- cpu-specific (MOVBE, POPCNT,...)
- os-dependant, anti-VM/debugs
- exceptions triggers, interrupts, OS bugs,...
- ...

CoST's internals

```
c>CoST.exe
CoST - Corkami Standard Test BETA 2011/09/XX
Ange Albertini, BSD Licence, 2009-2011 - http://

Info: Windows 7 found
Starting: jumps opcodes...
Starting: classic opcodes...
Starting: rare opcodes...
Starting: undocumented opcodes...
Starting: cpu-specific opcodes...
Info: CPUID GenuineIntel
Info[cpu]: MOVBE (Atom only) not supported
Starting: undocumented encodings...
Starting: os-dependant opcodes...
Starting: 'nop' opcodes...
Starting: opcode-based anti-debuggers...
Starting: opcode-based GetIPs...
Starting: opcode-based exception triggers...
Starting: 64 bits opcodes...
Starting: registers tests

...completed!
```

```
1   [trick] Adding TLS 2 in TLS callbacks list
2   [trick] the next call's operand is zeroed by the loader
3   CoST - Corkami Standard Test BETA 2011/09/XX
4   Ange Albertini, BSD Licence, 2009-2011 - http://corkami.com
5
6
7   [trick] TLS terminating by unhandled exception (EP is executed)
8   [trick] allocating buffer [0000-ffff]
9   testing: NULL buffer
10  checking OS version
11  Info: Windows 7 found
12  [trick] calling Main via my own export
13  Starting: jumps opcodes...
14  Testing: RETN word
```

```
    CoST.exe          ↓FRO ---------          a32 PE .7EFD0220|Hiew 8.15 (c)SEN
4_Main:      mov      d,[0CAFEBABE],07EFD2CF7 ;'Starting: jumps opcodes...' -
.7EFD022A:   call     jumps --↓2
.7EFD022F:   nop
.7EFD0230:   mov      d,[0CAFEBABE],07EFD2D14 ;'Starting: classic opcodes...'
.7EFD023A:   call     classics --↓4
```

32+64 = ...


.7EFD2540: mov eax,0F570D67C
.7EFD2545: mov ebx,3
.7EFD254A: push cs
.7EFD254B: push end --↓1
.7EFD2550: push 033 ;'3'
.7EFD2552: call push_eip --↓2
push_eip: 2arpl ax,bx
.7EFD2559: dec eax
.7EFD255A: add eax,eax
.7EFD255C: retf ; -^-^-^-^-^-^-^-^-^-
end: 1cmp ebx,0EAE1ACFC
.7EFD2563: jz next --↓3
.7EFD2565: call bad --↓4
next: 3cmp eax,0D5C359F8


00401001 90 nop
00401002 90 nop
00401003 90 nop
00401004 90 nop
00401005 6858104000 push offset image0000
0040100a ff15f8104000 call dword ptr [image
00401010 83c404 add esp,4
00401013 b87cd670f5 mov eax,0F570D67Ch
00401018 bb03000000 mov ebx,3
edi 0
esi 0
ebx 3
edx 8e3c8
ecx 7692c620
eax f570d67c
23
202
cff7c
2b
0
DEMO
disassembly possible
0040102a 63d8 movsxd ebx,eax
0040102c 4801c0 add rax,rax
0040102f cb retf
00401030 81fbfcace1ea cmp ebx,0EA
00401036 7515 jne image00
Reg Value
rax eae1acfc
rcx 7692c620
rdx 8e3c8

CoST vs WinDbg & Hiew

WinDbg 6.12.0002.633

```
*** ERROR: Module load completed but symbols co
image7efd0000:
7efd0000 4d              dec     ebp
7efd0001 5a              pop     edx
7efd0002 ce              into
7efd0003 0f              ???
7efd0004 1838            sbb     byte ptr [eax]
7efd0006 e9db010000      jmp     image7efd0000+
7efd000b 0d436f5354      or      eax,54536F43h
```

Hiew 8.15



a hardened PE



Top



PE 'footer'

CoST vs IDA


Error
bTree error: memory allocation error (for struct PAGE)
OK
Help


Warning
The imports segment seems to be destroyed. This MAY mean that the file was packed or otherwise modified in order to make it more difficult to analyze. If you want to see the imports segment in the original form, please reload it with the 'make imports section' checkbox cleared.
OK
Don't display this message again


Please confirm
Can't find translation for virtual address 0000A2BC, continue?
Yes
No


Warning
Unknown fixup type 0x7000 is ignored
OK
Don't display this message again


Please confirm
Entry point 0x7EFD0000 is not loaded into the database.Do you want to load the missing data?
Yes
No

a bit more of PE...

PE on Corkami

- still in progress
- more than 120 PoCs
  - covering many aspects
  - good enough to break <you name it>
- 'summary' page http://pe.corkami.com
- printable graphs

virtual section table vs Hiew

Folded header



Name	RVA	Size
Export	88660001	10009988
Import	866000l0	01000998
Resource	66000100	00100099
Exception	6000100F	F0010009
Security	000100FF	FF001000
Fixups	00100FF0	0FF00100
Debug	0100FF05	20FF0010
Description	100FF055	220FF001
MIPS GP	100FF055	220FF001
TLS	0100FF05	20FF0010
Load config	00100FF0	0FF00100
Bound Import	000100FF	FF001000
Import Table	6000100F	F0010009
Delay Import	66000100	00100099
COM Runtime	866000l0	01000998
(reserved)	88660001	10009988

Weird export names

- exports = <anything non null>, 0

65535 sections vs OllyDbg

a last one...

- TLS AddressOfIndex is overwritten on loading
- Imports are parsed until Name is 0



- under XP, overwritten after imports
  - imports are fully parsed
- under W7, before
  - truncated



same PE, loaded differently

Conclusion (1/2)

- x86 and PE are far from perfectly documented

official docs $\Rightarrow$ FAIL

Conclusion (2/2)

1. visit Corkami
2. download the PoCs
   - read the doc / source
3. fix the bugs ;)
   - or answer my bug reports ?#$!

Acknowledgments

- Peter Ferrie
- Ivanlef0u

Adam Błaszczyk, BeatriX, Bruce Dang, Candid Wüest, Cathal Mullaney, Czerno, Daniel Reynaud, Elias Bachaalany, Ero Carrera, Eugeny Suslikov, Georg Wicherski, Gil Dabah, Guillaume Delugré, Gunther, Igor Skochinsky, Ilfak Guilfanov, Ivanlef0u, Jean-Baptiste Bédrune, Jim Leonard, Jon Larimer, Joshua J. Drake, Markus Hinderhofer, Mateusz Jurczyk, Matthieu Bonetti, Moritz Kroll, Oleh Yuschuk, Renaud Tabary, Rewolf, Sebastian Biallas, StalkR, Yoann Guillot,...

Questions?

Thank YOU!

@ange4771

Bonus

- Mips relocs (on relocs)
- ImageBase reloc
- multi-subsystem PE
- regs on TLS & DllMain