

FHQ 2014 Manual's

Doc-Version: 13

Doc-Date-Build: January 15, 2015

Pages: 18

Dev.: Evgenii Sopov Dev.: Dmitrii Mukovkin

Tomsk

Russian Federation

Web-site: http://fhq.keva.su E-mails: mrseakg@gmail.com



Contents

1	Configuration's			
	1.1	MySQ	L (or MariaDB)	2
	1.2	iptable	<u>es</u>	2
	1.3	Firewa	all on CentOS 7 (use firewalld)	3
	1.4		e	3
	1.5	PHP5		4
2	API	[5
	2.1	Auth		6
		2.1.1	Sign in/Login	6
		2.1.2	Sign Out/Logoff	6
		2.1.3	Restore Password	7
		2.1.4	Registration	7
	2.2	Games		8
		2.2.1	List of games	8
		2.2.2	Get Game Info	Ĉ
		2.2.3		10
		2.2.4	Scoreboard	11
		2.2.5	Refresh User's Score	12
		2.2.6	Insert Game Info	
		2.2.7	Update Game Info	13
		2.2.8	Remove Game	
	2.3	Users		
		2.3.1	Get List Users	15
		2.3.2	Get User Info	15
		2.3.3	Get IP-Addresses of User	
		2.3.4	Insert User Info	
		2.3.5	Update User Info	
		2.3.6	Insert User Info	
		2.3.7	Delete User	
		2.3.8		17

Chapter 1

Configuration's

1.1 MySQL (or MariaDB)

Install on server git-core.

```
root@debian:~# apt-get install git-core
```

Clone repository:

or look sql-script

https://github.com/sea-kg/fhq/blob/master/sql/init_database_freehackquest.sql

1.2 iptables

Some settings.

Linux and iptables.

Add to the firewall permission for the server (if it is not on the local machine)

```
# iptables -A INPUT -p tcp -s 0/0 --sport 1024:65535 -d 172.16.53.102 \
    --dport 3306 -m state --state NEW,ESTABLISHED -j ACCEPT
# iptables -A OUTPUT -p tcp -s 172.16.53.102 --sport 3306 -d 0/0 \
    --dport 1024:65535 -m state --state ESTABLISHED -j ACCEPT
# iptables-save
```

Check that the records were

```
# iptables -L INPUT -n -v --line-numbers
# iptables -L OUTPUT -n -v --line-numbers
```

To delete an record: 1. find a number

```
# iptables -L INPUT -n -v --line-numbers
```

2. and delete

```
# iptables -D INPUT number_of_your_entry
```

And of course, keep

```
# iptables-save
```

1.3 Firewall on CentOS 7 (use firewalld)

Some settings.

CentOS and MariaDB and Firewall.

CentOS 7 +firewalld:

```
# firewall-cmd --zone=public --add-port=3306/tcp --permanent
# firewall-cmd --reload
```

1.4 Apache

Setting up a domain name.

Add to /etc/apache2/sites-available/default next text:

```
<VirtualHost *:80>
        Options -Indexes FollowSymLinks MultiViews
        DocumentRoot /var/www/fhq/
        ServerName fhq.keva.su
        ErrorLog /var/log/apache2/fhq.keva.su-error_log
        CustomLog /var/log/apache2/fhq.keva.su-access_log common
        <Directory "/var/www/fhq/files">
                AllowOverride None
                Options -Indexes
                Order allow, deny
                Allow from all
        </Directory>
        <Directory /var/www/fhq/config>
                Order deny, allow
                Deny from all
        </Directory>
</VirtualHost>
```

OR you can copy the file from

```
https://github.com/sea-kg/fhq/blob/master/manual/fhq.config.example
```

to file "/etc/apache2/sites-available/fhq.config"

1.5 PHP5

Install and configure

```
root@debian# apt-get install php5
```

If not working captcha:

```
root@debian# apt-get install php5-gd
```

To work with sending e-mails:

```
root@debian# apt-get install php-pear
root@debian# pear install Mail-1.2.0
root@debian# pear install Net_SMTP
```

Install git:

```
root@debian# apt-get install git-core
```

Download source code:

```
root@debian# cd ~
root@debian~# git clone https://github.com/sea-kg/fhq.git fhq.git
root@debian~# cd fhq.git
```

Then just do a link:

```
root@debian~# ln -s "'pwd'/php/fhq" "/var/www/fhq"
```

Next, copy and configure:

```
root@debian~# cp /var/www/fhq/config.php.inc /var/www/fhq/config.php
```

Chapter 2

\mathbf{API}

This chapter will talk about what external functions exist to work with the system. Also presented are various examples for the job. Also, this chapter is devoted to the frontend developers using kernel of fhq.

2.1 Auth

Code errors will be started from 10^* .

2.1.1 Sign in/Login

This function access for all.

URL:

```
http://fhq.keva.su/api/auth/sign_in.php
```

Input parameters (GET or POST):

- email identificator of user
- password password of user
- client indentifier for client (fhq-web or other frontends)

Successfully response:

```
{
    "result": "ok",
    "token" : "76558894-0AA9-11E4-09F0-D353D3CF86D5"
}
```

Code errors:

- Error 1001 parameters was not found email or password
- Error 1002 email or password was not found in system

2.1.2 Sign Out/Logoff

This function access for all.

URL:

```
http://fhq.keva.su/api/auth/sign_out.php
```

Input parameters (GET or POST):

• token - security token

Successfully response:

```
{
    "result": "ok",
    "token" : "76558894-0AA9-11E4-09F0-D353D3CF86D5"
}
```

Code errors:

• no

2.1.3 Restore Password

This function access for all.

URL:

```
http://fhq.keva.su/api/auth/restore.php
```

Captcha URL:

```
http://fhq.keva.su/captcha.php
```

Input parameters (GET or POST):

- email identificator of user
- captcha captcha

Successfully response:

```
{
    "result": "ok",
    "data": {
        "message": "Check your your e-mail (also check spam)."
    }
}
```

Also look ??

2.1.4 Registration

This function access for all.

URL:

```
http://fhq.keva.su/api/auth/registration.php
```

Captcha URL:

```
http://fhq.keva.su/captcha.php
```

Input parameters (GET or POST):

- email new identificator for user (email)
- captcha captcha

Successfully response:

```
{
    "result": "ok",
    "data": {
        "message": "Check your your e-mail (also check spam)."
    }
}
```

2.2 Games

2.2.1 List of games

This function access for all authorized users. URL:

```
http://fhq.keva.su/api/games/list.php
```

```
// TODO paging
Input parameters (GET or POST):
```

• token - token

Successfully response:

```
{
    "result": "ok",
    "data": {
        "2014-12-20 23:30:00": {
            "id": "5",
            "title": "FHQ 2014",
            "type_game": "jeopardy",
            "date_start": "2014-12-20 23:30:00",
            "date_stop": "2014-12-31 23:00:00",
            "date_restart": "2015-01-02 20:00:00",
            "description": "The game will be last<br>\nFor searching hackers<br>\n<a |
            "logo": "http:\/\/cs7009.vk.me\/c625821\/v625821429\/ff45\/dYYxQR1VhJg.jp
            "owner": "220",
            "nick": "[keva] sea-kg",
            "permissions": {
                "delete": true,
                "update": true
            }
        },
        "2014-04-01 10:00:00": {
            "id": "4",
            "title": "SibirCTF 2014 J (Copy)",
            "type_game": "jeopardy",
            "date_start": "2014-04-01 10:00:00",
            "date_stop": "2014-04-01 15:00:00",
            "date_restart": "2014-04-02 09:00:00",
            "description": "Copies tasks from\n<a href=\"http:\/\/sibirctf.org\"≯sibi
            "logo": "http:\/\/fhq.keva.su\/files\/icons\/logo_sibirctf2014.png",
            "owner": "220",
            "nick": "[keva] sea-kg",
            "permissions": {
                "delete": true,
```

```
"update": true
            }
        },
        "2013-10-06 09:00:00": {
            "id": "3",
            "title": "FHQ 2013",
            "type_game": "jeopardy",
            "date_start": "2013-10-06 09:00:00",
            "date_stop": "2013-10-18 21:00:00",
            "date_restart": "2013-10-20 09:00:00",
            "description": "Game for search hackers",
            "logo": "files\/orig\/minilogo_old.png",
            "owner": "220",
            "nick": "[keva] sea-kg",
            "permissions": {
                "delete": true,
                "update": true
        },
        "2012-10-06 09:00:00": {
            "id": "1",
            "title": "FHQ 2012",
            "type_game": "jeopardy",
            "date_start": "2012-10-06 09:00:00",
            "date_stop": "2012-10-17 16:00:00",
            "date_restart": "2012-10-19 09:00:00",
            "description": "The game for search hackers",
            "logo": "files\/orig\/minilogo_old.png",
            "owner": "220",
            "nick": "[keva] sea-kg",
            "permissions": {
                "delete": true,
                "update": true
            }
        }
    },
    "current_game": "5",
    "permissions": {
        "insert": true
    }
}
```

Also look ??

2.2.2 Get Game Info

This function access for all.

URL:

```
http://fhq.keva.su/api/games/get.php
```

Input parameters (GET or POST):

- id identificator of game (integer)
- token token

Successfully response:

```
{
    "result": "ok",
    "data": {
        "id": "5",
        "type_game": "jeopardy",
        "title": "SibirCTF 2014 J",
        "date_start": "2014-03-27 00:00:00",
        "date_stop": "2014-03-28 00:00:00",
        "date_restart": "2014-04-01 08:00:00",
        "description": "Game was offline at 1 April 2014 in Tomsk"
        "logo": "logo_2014-03-14_starosta.png",
        "owner": "46"
    }
}
```

??

2.2.3 Select Game

This function access for all.

URL:

```
http://fhq.keva.su/api/games/choose.php
```

Input parameters (GET or POST):

- id identificator of game (integer)
- token token

Successfully response:

```
{
    "result": "ok",
    "data": {
        "id": "5",
```

```
"type_game": "jeopardy",
    "title": "SibirCTF 2014 J",
    "date_start": "2014-03-27 00:00:00",
    "date_stop": "2014-03-28 00:00:00",
    "date_restart": "2014-04-01 08:00:00",
    "logo": "logo_2014-03-14_starosta.png",
    "owner": "46",
    "description": "Game was offline at 1 April 2014 in Tomsk",
}
```

Also look ??

2.2.4 Scoreboard

This function access for all.

URL:

```
http://fhq.keva.su/api/games/scoreboard.php
```

// TODO paging Input parameters (GET or POST):

• gameid - identificator of game (integer)

Successfully response:

2.2.5 Refresh User's Score

This function access for all authorized users.

Must be selected game.

Refreshing user's score.

URL:

```
http://fhq.keva.su/api/games/update_score.php
```

Input parameters (GET or POST):

• no

Successfully response:

```
{
    "result": "ok",
    "data": [],
    "user": {
        "score": "1161"
    }
}
```

Also look ??

2.2.6 Insert Game Info

This function access only for admin.

URL:

```
http://fhq.keva.su/api/games/insert.php
```

Input parameters (GET or POST):

- uuid_game global identificator of the game (text)
- title name of the game (text)
- logo link to image (text)
- type_game type of the game (text) possible values: "jeopardy" or "attack-defence"
- date_start start date of the game (datetime, format: '0000-00-00 00:00:00')
- date_stop stop date of the game (datetime, format: '0000-00-00 00:00:00')
- date_restart restart date of the game (datetime, format: '0000-00-00 00:00:00')
- **description** description of the game

Successfully response:

```
{
    "result": "ok",
    "data" : {
        "game" : {
            "id" : 2
        }
    }
}
```

Also look ??

2.2.7 Update Game Info

This function access only for admin. URL:

```
http://fhq.keva.su/api/games/update.php
```

Input parameters (GET or POST):

- id identificator of the game (number)
- title name of the game (text)
- logo link to image (text)
- type_game type of the game (text) possible values: "jeopardy" or "attack-defence"
- date_start start date of the game (datetime, format: '0000-00-00 00:00:00')
- date_stop stop date of the game (datetime, format: '0000-00-00 00:00:00')
- date_restart restart date of the game (datetime, format: '0000-00-00 00:00:00')
- description description of the game

Successfully response:

```
{
    "result": "ok"
}
```

2.2.8 Remove Game

This function access only for admin. URL:

```
http://fhq.keva.su/api/games/delete.php
```

Captcha URL:

```
http://fhq.keva.su/captcha.php
```

Input parameters (GET or POST):

- id identificator of game (integer)
- captcha captcha (text)

Successfully response:

```
{
    "result": "ok"
}
```

2.3 Users

2.3.1 Get List Users

This function access for admin.

URL:

```
http://fhq.keva.su/api/users/list.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

??

2.3.2 Get User Info

This function access for authorized users.

URL:

```
http://fhq.keva.su/api/users/get.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

??

2.3.3 Get IP-Addresses of User

This function access for admin.

URL:

```
http://fhq.keva.su/api/users/get_ips.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

??

2.3.4 Insert User Info

This function access for admin.

URL:

```
http://fhq.keva.su/api/users/insert.php?userid=46&todo
```

Input parameters (GET or POST):

• TODO

Successfully response:

```
{
    // TODO
}
```

??

2.3.5 Update User Info

This function access for authorized users.

TODO URL:

```
http://fhq.keva.su/api/users/get.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

2.3.6 Insert User Info

This function access for admin.

URL:

```
http://fhq.keva.su/api/users/insert.php?userid=46&todo
```

Input parameters (GET or POST):

• TODO

Successfully response:

```
{
    // TODO
}
```

??

2.3.7 Delete User

This function access for admin.

URL:

```
http://fhq.keva.su/api/users/delete.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

??

2.3.8 Update User Location

Only for authorized user.

URL:

```
http://fhq.keva.su/api/users/get.php?userid=46
```

Input parameters (GET or POST):

• country - identificator of user (integer)

- city identificator of user (integer)
- university identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

Code Errors:

- 909 Not found parameter "country"
- 910 Not found parameter "city"
- 915 Not found parameter "university"
- 911 Problem with database or query

2.3.9 Update User Style

This function access for authorized users. URL:

```
http://fhq.keva.su/api/users/get.php?userid=46
```

Input parameters (GET or POST):

• userid - identificator of user (integer)

Successfully response:

```
{
    // TODO
}
```

??