

HACKSHEET^{MASTER}

Author: [Matthias Vallentin](#)

Web: <https://github.com/mavam/hacksheet>

License: [Attribution-NonCommercial-ShareAlike 3.0 Unported](#)

Terminology

Each command contains a list of flags that indicate the OS requirement: Linux (L), BSD (B), FreeBSD (F), Mac OS (M), UNIX (U), and Windows (W).

General Utility

Useful Powershell Commands

```
★ Download File from Internet
W # Powershell
$source = "http://www.download.com/file.txt"
$destination = "c:\temp\file.txt"
$wc = New-Object System.Net.WebClient
$wc.DownloadFile($source, $destination)
```

Reconnaissance

Scanning

```
★ Ping sweep of subnet and host range
U # nmap -sP 10.0.0.0/24 192.168.0.128-254

★ List all computers in network
W # net view

★ Scan specific TCP and UDP ports
U # nmap -pT:21-25,80,U:5000-6000 target

★ TCP SYN scan without connecting
U # nmap -P0 -sS target

★ Detect OS
U # nmap -O target
U # p0f -s trace.pcap

★ Grab application banners
U # nmap -sV target
U # echo QUIT | nc target 1-1024
```

Wireless

Vulnerability Scanning

Web

```
★ Look for web server vulnerabilities
U # nikto -host 10.0.0.1
```

Hardening

Physical

```
★ Check devices
  • Hardware keylogger (e.g., USB dongles)
  • Rogue WiFi cards
```

OS & Software

```
★ Check for package repositories
L # vi /etc/apt/sources.list (Ubuntu)
L # vi /etc/yum.repos.d/* (RHEL/Fedora)

★ Run package updates
L # yum upgrade package
L # apt-get upgrade package

★ Update Kernel
L # yum update kernel (RHEL/Fedora)
L # apt-cache search linux-image; apt-get
  install linux-image-x.x.x-xx (Debian)

★ Harden SSHD
U FAIL2BAN
U # vi /etc/ssh/sshd_config
Protocol 2
AllowUsers root admin webmaster
AllowGroup sshusers
PasswordAuthentication no
HostbasedAuthentication no
RSAAuthentication yes
PubkeyAuthentication yes
PermitEmptyPasswords no
PermitRootLogin no
ServerKeyBits 2048
IgnoreRhosts yes
RhostsAuthentication no
RhostsRSAAuthentication no
```

User Management

```
★ Show account security settings
U # passwd -l user
L # chage -l user
W # net accounts
W # net accounts /domain

★ View Users
W # wmic useraccount list brief

★ Look for users with root privileges
U # awk -F: ' $3 == 0 {print $1}' /etc/passwd
W # net localgroup administrators

★ Look for users with empty passwords
U # awk -F: ' $2 == "" {print $1}' /etc/shadow

★ Make Passwords Expire
W # wmic path Win32_UserAccount Set
  PasswordExpires=True
W # wmic path Win32_UserAccount where
  name="username" Set PasswordExpires=True
W # wmic path /Node:remotecomputer
  Win32_UserAccount where name="username"
  Set PasswordExpires=True

★ Verify group memberships
U # vi /etc/group (admin, sudo, wheel)

★ Check sudo users
U # visudo

★ Check crontab users
U # for u in $(cut -f1 -d: /etc/passwd); do
  crontab -u $u -l; done

★ Check remote authentication
U # vi ~/.rhosts
U # vi ~/.ssh/*

★ Change passwords
U # pwgen -sy (generate strong passwords)
U # passwd user
W # net user user *
```

File System

- ★ Secure mount points
 - U # mount -o nodev,noexec,nosuid /dev.. /tmp

- ★ List file attributes
 - L # lsattr /var/log/foo
 - B # ls -ol /var/log/foo
 - W # cacls.exe file.txt

- ★ File creation date
 - W # dir /tc /od
 - U # ls -li /etc | sort -n

- ★ System file checker
 - W # sfc /scannow

- ★ File signature serification
 - W # sigverif
 - W SIGCHECK
 - W # sigcheck -e -u -s c:\

- ★ Make files append-only
 - L # chattr +a /var/log/foo

Network

- ★ Show firewall rules
 - L # for t in nat mangle filter raw; do iptables -t \$t -nL; done
 - W # netsh firewall show portopening
 - W # netsh firewall show allowedprogram
 - W # netsh firewall show config
- ★ Close ports
 - W # netsh advfirewall firewall add rule name="BlockAIM" protocol=TCP dir=out remoteport=4099 action=block
- ★ Shut down SMB vulnerable services
 - W SECONFIG XP ☒Disable NetBIOS over TCP/IP (all interfaces) ☒Disable SMB over TCP/IP ☒Disable RPC over TCP/IP → Apply → Yes
- ★ Check DNS resolver
 - U # vi /etc/resolv.conf
- ★ Disable IPv6
 - L # ipv6.disable=1 (add to kernel line)
 - L # vi /etc/sysctl.conf
 - net.ipv6.conf.all.disable_ipv6 = 1
 - net.ipv6.conf.<interface0>.disable_ipv6 = 1
 - net.ipv6.conf.<interfaceN>.disable_ipv6 = 1
 - vi /etc/hosts (comment IPv6 hosts)
 - L # vi /etc/sysconfig/network
 - NETWORKING_IPV6=no
 - IPV6INIT=no
 - service network restart
 - L # vi /etc/modprobe.conf
 - install ipv6 /bin/true (append to file)
 - L # vi /etc/modprobe.conf (RHEL/CentOS)
 - alias net-pf-10 off
 - L # vi /etc/modprobe.conf (Debian/Ubuntu)
 - alias net-pf-10 off
 - alias ipv6 off
 - W # reg add hklm\system\currentcontrolset\services\tcpip6\parameters /v DisabledComponents /t REG_DWORD /d 255
- ★ Check network configuration
 - L # vi /etc/network/interfaces (Ubuntu)
 - L # vi /etc/sysconfig/network-scripts/ifcfg-eth* (RHEL)

Forensics

Processes

- ★ Inspect startup items
 - L # initctl show-config (upstart, Ubuntu)
 - F # less /etc/rc.local (deprecated)
 - F # grep local_start /etc/defaults/rc.conf
 - W AUTORUNS → Options → Filter Options ☒Verify code signatures ☒Hide Microsoft entries
- ★ Find SETUID and SETGID files and types
 - U # find / \(-perm -4000 -o -perm -2000 \) -exec file \{\} \;
 - U # crontab -e
 - 0 4 * * * find / \(-perm -4000 -o -perm -2000 \) -type f > /var/log/sidlog.new && diff /var/log/sidlog.new /var/log/sidlog && mv /var/log/sidlog.new /var/log/sidlog
- ★ Find world/group writeable directories
 - U # find / \(-perm -g+w -o -perm -o+w \) -type d -exec ls -ald \{\} \;
- ★ Find all unsigned processes
 - W PROCEXPLORER Options → Verify Image Signatures
- ★ View Process File Location
 - W PROCEXPLORER View → Select Columns... → Image Path
- ★ Display listening TCP/UDP ports
 - LWU # netstat -tun
 - W TCPVIEW
 - B # netstat -p tcp -an | egrep 'Proto|LISTEN|udp'
 - U # lsof -nPi | awk '/LISTEN/'
 - F # sockstat -4 -l
- ★ Check active connections to find backdoors
 - U # lsof -nPi | awk '/ESTABLISHED/'
- ★ Currently Running Tasks/Processes
 - W # tasklist -svc
 - LU # ps aux | less
 - LU # top
 - LU # ps -u user
- ★ Kill Tasks/Processes
 - W # taskkill -pid pid
 - LU # kill pid

Users

★ Inspect logged in and past users

```
U # w
U # last | head
U # ps -ef | awk '$6 != "?"' (interactive procs)
W PsLOGGEDON
W TASK MANAGER (OPEN AS ADMINISTRATOR) -> USERS
TAB
W # wmic computersystem get username
W # wmic /node:remotecomputer computersystem
  get username
```

Cleanup

★ Kill all processes accessing a mount point

```
U # fuser -k -c /mnt/secret
```

Drivers

★ Driver query

```
windows # driverquery (-v)
```

References

- <http://bit.ly/cmd-line-kung-fu>
- <http://www.robvanderwoude.com/ntadmincommands.php>
- <http://pubs.vmware.com/vsphere-50/topic/com.vmware.ICbase/PDF/vsphere-esxi-vcenter-server-50-security-guide.pdf>

Very Useful Downloads

- Sys Internals: <http://technet.microsoft.com/en-us/sysinternals/bb842062>
- Seconfig XP: <http://seconfig.sytes.net/>