
open source watch Documentation

Release 1.0.0

jj

Jan 31, 2020

CONTENTS

1	author:	3
2	LICENSE:	5
3	Zephyr for the pinetime smartwatch	7
4	Install zephyr	9
4.1	In case you already have zephyr installed:	9
4.2	In case you start from scratch :	9
5	Starting with some basic applications	11
5.1	Blinky example	11
5.2	Reading out the button on the watch	11
6	bluetooth (BLE) example	13
6.1	Using a standard zephyr application under pinetime:	13
6.2	Eddy Stone	13
6.3	Using the created bluetooth sample:	13
6.4	Ble Peripheral	14
6.5	using Python to read out bluetoothservices	14
7	display (st7789)	15
7.1	Display example	15
8	GFX Library Sample	17
8.1	Overview	17
8.2	Usage	17
9	LittlevGL Basic Sample	19
9.1	Overview	19
9.2	Requirements	19
9.3	Building and Running	19
9.4	Todo	20
9.5	References	20
10	LittlevGL Clock Sample	21
10.1	Overview	21
10.2	Requirements	21
10.3	Building and Running	21
10.4	Todo	22
10.5	References	22

11 Real Time Clock	23
11.1 Overview	23
11.2 Requirements	23
11.3 Building and Running	23
11.4 Todo	23
11.5 References	24
12 Current Time Service	25
12.1 Overview	25
12.2 Requirements	25
12.3 Building and Running	25
12.4 Todo	25
12.5 References	25
13 Drivers	27
13.1 configuring I2C	27
13.2 sensors on the I2C bus	27
13.3 Bosch BMA421	28
13.4 HYNITRON CST816S	29
13.5 HX HRS3300	30
13.6 Serial Nor Flash	32
13.7 Battery	34
14 Behind the scene	37
14.1 Behind the scene	37
14.2 development trajectory	37
14.3 Bosch BMA280	37
14.4 Touchscreen Hynitron	38
14.5 Troubleshooting drivers	39
14.6 placing a button on the screen	40
15 Samples and Demos	41
15.1 Basic Samples	41
15.2 Sensor Samples	43
15.3 Driver Samples	45
15.4 Display Samples	46
15.5 GUI Samples	46
15.6 Bluetooth Samples	48
16 Menuconfig	51
16.1 Zephyr is like linux	51
17 hacking the pinetime smartwatch	53
18 debugging the pinetime smartwatch	55
19 scanning the I2C_1 port	57
19.1 Building and Running	57
20 howto flash your zephyr image	59
21 howto remove the write protection	61
22 howto generate pdf documents	63

23 About	65
23.1 Todo	65



Note : You may at any time read the book, store it in your ereaders

The book itself is subject to copyright.

You cannot use the book, or parts of the book into your own publications, without the permission of the author.

CHAPTER

ONE

AUTHOR:

Jan Jansen najnesnaj@yahoo.com

LICENSE:

All the software is subject to the Apache 2.0 license (same as zephyr), which is very liberal.

ZEPHYR FOR THE PINETIME SMARTWATCH

this document describes the installation of zephyr RTOS on the PineTime smartwatch.

<https://wiki.pine64.org/index.php/PineTime>

It should be applicable on other nordic nrf52832 based watches (Desay D6....).

the approach **in** this manual **is** to get quick results :

- minimal effort install (pinetime works **as** an external (out of tree) application **for** zephyr)
- **try** out the samples
- inspire you to modify **and** enhance

suggestion :

- follow the installation instructions
- try some examples
- try out bluetooth
- try out the display



INSTALL ZEPHYR

4.1 In case you already have zephyr installed:

Pinetime works as external (out of tree) application. You can clone pinetime next to zephyr in the working directory and update manifest and west.

```
west config manifest.path pinetime
```

4.2 In case you start from scratch :

https://docs.zephyrproject.org/latest/getting_started/index.html

the documentation describes an installation process under Ubuntu/macOS/Windows

I picked Debian (which is not listed) and soon afterwards ran into trouble

this behaviour is known as : stubborn or stupid, but I remain convinced it could work

In the Zephyr getting started page :

- 1) select and update OS
- 2) install dependencies
- 3) Get the source code

instead of following the procedure:

```
cd ~
west init zephyrproject
cd zephyrproject
west update
```

you should do this :

```
cd ~
mkdir work
cd work
west init -m https://github.com/najnesnaj/pinetime-zephyr
west update
```

- 4) complete the other steps

to test if your install works :

cd ~/work/pinetime

west build -p -b pinetime samples/basic/blinky

TIP : sometimes you run into trouble compiling: removing the build directory can help in that case

STARTING WITH SOME BASIC APPLICATIONS

The best way to get a feel of zephyr for the PineTime watch, is to start building applications.

The gpio ports, i2c communication, memory layout, stuff that is particular for the watch is defined in the board definition file.

The provided samples are standard zephyr application, with some minor modifications.

5.1 Blinky example

The watch does **not** contain a led **as** such, but it has background leds **for** the LCD.

Once lit, you can barely see it, cause the screen-LCD remains black.

The screen contains three leds, this way the intensity **is** set.

have a look at the pinetime.dts file, here you see the definition of the background leds.

building an image, which can be found under the build directory

see : [*Blinky Application*](#)

```
$ cd ~/work/pinetime
$ west build -p -b pinetime samples/basic/blinky
```

once the compilation is completed, you can find the firmware under : ~/work/pinetime/build/zephyr/zephyr.bin

5.2 Reading out the button on the watch

The pinetime does have a button on the side.

In order to check **if** the button **is** pressed, it sets a value **in** memory.
With openocd you can peek at this memory location.

5.2.1 Building and Running

see : [*Button demo*](#)

Note:: The watch has a button out port (15) and button in port (13). You have to set the out-port high. Took me a while to figure this out...

```
west build -p -b pinetime samples/basic/button
```

Note: #define MY_REGISTER (*(volatile uint8_t*)0x2000F000)

in the program you can set values: MY_REGISTER=(read button value);

this way you know till whether the code executes

a way to set port 15 high (hard-coded of course :))

```
gpio_pin_configure(gpiob, 15,GPIO_DIR_OUT); //push button out
gpio_pin_write(gpiob, 15, &button_out); //set port high
```

```
#telnet 127.0.0.1 4444
```

Peeking

```
once your telnet sessions started:
Trying 127.0.0.1...
Connected to 127.0.0.1.
Escape character is '^]'.
Open On-Chip Debugger
>mdw 0x2000F000 0x1
0x2000f000: 00000100 (switch pushed)
```

BLUETOOTH (BLE) EXAMPLE

The PineTime uses a Nordic nrf52832 chip, which has BLE functionality build into it.

To test, you can compile a standard application : Eddy Stone.

The watch will behave as a bluetooth beacon, and you should be able to detect it with your smartphone or with bluez under linux.

6.1 Using a standard zephyr application under pinetime:

Each sample has its own directory. In this directory you will notice a file : “CMakeLists.txt”.

In order to use a standard, you can just copy it under the pinetime directory.

In order to be able to compile it, you just have to add one line in the CMakeList.txt :

```
include($ENV{ZEPHYR_BASE}/../pinetime/cmake/boilerplate.cmake)
```

Have a look in the samples/bluetooth/eddystone directory.

6.2 Eddy Stone

see: *Bluetooth: Eddystone*

Note: compile the provided example, so a build directory gets created

```
$ west build -p -b pinetime samples/bluetooth/eddystone
```

this builds an image, which can be found under the build directory

6.3 Using the created bluetooth sample:

I use linux with a bluetoothadapter 4.0. You need to install bluez.

```
#bluetoothctl  
[bluetooth] #scan on
```

And your Eddy Stone should be visible.

If you have a smartphone, you can download the nrf utilities app from nordic.

6.4 Ble Peripheral

this example is a demo of the services under bluetooth

first build the image

```
$ west build -p -b pinetime samples/bluetooth/peripheral
```

With linux you can have a look using bluetoothctl:

```
#bluetoothctl
[bluetooth]#scan on

[NEW] Device 60:7C:9E:92:50:C1 Zephyr Peripheral Sample Long
once you see your device
[blueooth]#connect 60:7C:9E:92:50:C1 (the device mac address as displayed)

then you can already see the services
```

same thing with the app from nordic, you could try to connect and display value of e.g. heart rate

6.5 using Python to read out bluetoothservices

In this repo you will find a python script : readbat.py In order to use it you need bluez on linux and the python *bluepy* module.

It can be used in conjunction with the peripheral bluetooth demo. It just reads out the battery level, and prints it.

```
import binascii
from bluepy.btle import UUID, Peripheral

temp_uuid = UUID(0x2A19)

p = Peripheral("60:7C:9E:92:50:C1", "random")

try:
    ch = p.getCharacteristics(uuid=temp_uuid)[0]
    print binascii.b2a_hex(ch.read())
finally:
    p.disconnect()
```

DISPLAY (ST7789)

7.1 Display example

This is just a simple display test. It displays coloured squares, but it allows you to check if the screen is OK.

TIP: While connecting 5V, do not connect 3.3V at the same time

The watch has background leds **for** the LCD.

They need to be on (LOW) to visualize the display.
Have a look **in** the source code.

```
$ west build -p -b pinetime samples/display/st7789v
```

Once the compilation is completed you can upload the firmware.

If all goes well, you should see some coloured squares on your screen.

Note : in order to get the display st7789 Picture-Perfect, you might need a zephyr patch

have a look at : <https://github.com/zephyrproject-rtos/zephyr/pull/20570/files> You will find them in this repo under patches-zephyr.

GFX LIBRARY SAMPLE

8.1 Overview

This sample is built on top of the ST7789 display sample (*display (st7789)*), extending it with the [Adafruit GFX Library](#). The library was ported from Arduino and has the same functionality and API. See `src/main.cpp` for examples on the GFX API usage.

See *display (st7789)* for more details on working with the display itself.

8.2 Usage

Add the gfx sample from this repo into your project:

```
$ cp samples/gui/gfx ~/zephyrproject/zephyr/samples/gui/
```

Note: In order to make the library work the sample is built with C++ support. This is achieved by having the following line in the sample's *prj.conf* configuration:

```
CONFIG_CPLUSPLUS=y
```

Build & flash the sample:

```
$ west build -p -b pinetime samples/gui/gfx
$ west flash
```

If all goes well, you should see a looping graphical test: drawing lines, rectangles, triangles etc.

LITTLEVGL BASIC SAMPLE

9.1 Overview

This sample application displays “Hello World” in the center of the screen and a counter at the bottom which increments every second.

LittlevGL is a free and open-source graphics library providing everything you need to create embedded GUI with easy-to-use graphical elements, beautiful visual effects and low memory footprint.

9.2 Requirements

The program has been modified to light up the background leds.

TIP: matching label : DISPLAY

```
Matching labels are necessary!  
pinetime.conf:CONFIG_LVGL_DISPLAY_DEV_NAME="DISPLAY"  
pinetime.overlay:          label = "DISPLAY"; (spi definition)
```

9.3 Building and Running

```
west build -p -b pinetime samples/gui/lvgl
```

9.3.1 modifying the font size :

```
west build -t menuconfig
```

goto:

- additional libraries
- lvgl gui library

(look for fonts, and adapt according to your need)

9.3.2 apply changes of the changed config:

```
west build
```

(instead of west build -p (pristine) which wipes out your customisation)

9.4 Todo

- Create a button
- touchscreen activation (problem cause zephyr does not support this yet)
- lvgl supports lv_canvas_rotate(canvas, &imd_dsc, angle, x, y, pivot_x, pivot_y) should be cool for a clock, chrono...

9.5 References

<https://docs.littlevgl.com/en/html/index.html>

LittlevGL Web Page: <https://littlevgl.com/>


LITTLEVGL CLOCK SAMPLE

see : *LittlevGL Clock Sample*

10.1 Overview

This sample application displays a “clockbackground” in the center of the screen.

LittlevGL is a free and open-source graphics library providing everything you need to create embedded GUI with easy-to-use graphical elements, beautiful visual effects and low memory footprint.



10.2 Requirements

Make sure the prj.conf contains the following :

```
CONFIG_LVGL=y
CONFIG_LVGL_OBJ_IMAGE=y
```

LittlevGL uses a “c” file to store the image. You need to convert a jpg, or png image to this c file. There is an online tool : <https://littlevgl.com/image-to-c-array>

10.3 Building and Running

```
west build -p -b pinetime samples/gui/clock
```

10.4 Todo

- create an internal clock (and adjustment mechanism, eg. bluetooth cts)
- lvgl supports `lv_canvas_rotate(canvas, &imd_dsc, angle, x, y, pivot_x, pivot_y)` should be cool for a clock, chrono...

10.5 References

<https://docs.littlevgl.com/en/html/index.html>

LittlevGL Web Page: <https://littlevgl.com/>

REAL TIME CLOCK

11.1 Overview

This sample application “clock” uses the RTC0 timer. It uses the counter driver. (based on the alarm sample)

Basically an interrupt is set to go off after 1 second. The number of seconds is incremented and the interrupt is launched again.

It will serve as a building block for a “time of the day” clock.

In addition it will need a function to set the time.

In bluetooth one can use CTS (central time service)

11.2 Requirements

Make sure the prj.conf contains the following :

```
CONFIG_COUNTER=y
```

You need the Kconfig file, which contains :

```
config COUNTER_RTC0
    bool
    default y if SOC_FAMILY_NRF
```

see : *LittlevGL Clock Sample*

11.3 Building and Running

```
west build -p -b pinetime samples/gui/clock
```

11.4 Todo

- time of day clock
- setting the time

11.5 References

CURRENT TIME SERVICE

12.1 Overview

The bluetooth peripheral sample has a cts server in place. By installing this sample on a bluetoothboard, one can simulate the CTS.

Another option is to use a smartphone or computer to connect and bond to your Pinetime. As soon as a device is bonded, Pinetime will look for a CTS server (Current Time Service) on the connected device.

Here is how to do it with an Android smartphone running NRFCConnect: Build and program the firmware on the Pinetime Install NRFCConnect (<https://www.nordicsemi.com/Software-and-Tools/Development-Tools/nRF-Connect-for-desktop>) Start NRFCConnect and create a CTS server : Tap the hamburger button on the top left and select "Configure GATT server" Tap "Add service" on the bottom Select server configuration "Current Time Service" and tap OK Go back to the main screen and scan for BLE devices. A device called "PineTime" should appear Tap the button "Connect" next to the PineTime device. It should connect to the PineTime and switch to a new tab. On this tab, on the top right, there is a 3 dots button. Tap on it and select Bond. The bonding process begins, and if it is successful, the PineTime should update its time and display it on the screen.

12.2 Requirements

12.3 Building and Running

```
west build -p -b pinetime samples/bluetooth/peripheral-cts
```

12.4 Todo

- make it work

12.5 References

13.1 configuring I2C

13.1.1 board level definitions

under boards/arm/pinetime are the board definitions

- pinetime.dts
- pinetime_defconfig

The sensors **in** the pinetime use the I2C bus.

```
&i2c1 {  
    compatible = "nordic,nrf-twi";  
    status = "okay";  
    sda-pin = <6>;  
    scl-pin = <7>;  
  
};
```

13.1.2 definition on project level

In the directory of a sample, you will find a prj.conf file. Here you can set values specific for you project/sample.

In the "prj.conf" file we define the sensor (eg adxl372)

```
CONFIG_STDOUT_CONSOLE=y  
CONFIG_LOG=y  
CONFIG_I2C=y  
CONFIG_SENSOR=y  
CONFIG_ADXL372=y  
CONFIG_ADXL372_I2C=y  
CONFIG_SENSOR_LOG_LEVEL_WRN=y
```

note: this gets somehow merged (overlayed) with the board definition pinetime_defconfig

13.2 sensors on the I2C bus

0x18: Accelerometer: BMA423-DS000 <https://github.com/BoschSensortec/BMA423-Sensor-API>

0x44: Heart Rate Sensor: HRS3300_Heart

0x15: Touch Controller: Hynitron CST816S Touch Controller

13.3 Bosch BMA421

this driver does not exist, so it has been created. Still work in progress

```
west build -p -b pinetime samples/gui/lvaccel
```

13.3.1 Overview

BMA421 is not a part number available to the general public, and therefore all the supporting documentation and design resources are neither discussed in public forums, nor disclosed on GitHub.

CHIP_ID=0X11 (so the Bosch BMA423 drivers need to be adapted)

The Bosch documentation on the bma423 seems to apply to the bma421.

13.3.2 Requirements

for this sensor does not exist any driver, so here's what I did to create one under zephyr

adapt CMakeLists.txt

```
~/zephyrproject-2/zephyr/drivers/sensor      add_subdirectory_ifdef(CONFIG_BMA280      bma280)
add_subdirectory_ifdef(CONFIG_BMA421 bma421)
```

adapt Kconfig

```
~/zephyrproject-2/zephyr/drivers/sensor
```

add yaml file

```
~/zephyrproject-2/zephyr/dts/bindings/sensor cp bosch,bma280-i2c.yaml bosch,bma421-i2c.yaml
```

edit KConfig

```
source "drivers/sensor/bma280/Kconfig" source "drivers/sensor/bma421/Kconfig"
```

```
source "drivers/sensor/bmc150_magn/Kconfig"
```

```
source "drivers/sensor/bme280/Kconfig"
```

create driver

see under drivers/sensor/bma421

complement the pinetime.dts file with the following (under samples/sensor/bma280)

```
&i2c1 {
    bma421@18 {
        compatible = "bosch,bma421";
        reg = <0x18>;
        label = "BMA421";
        int1-gpios = <&gpio0 8 0>;
    };
};
```

Create a file: `/dts/bindings/sensor/bosch,bma421-i2c.yaml`. Which contains:

```
compatible: "bosch,bma421"
include: i2c-device.yaml
properties:
    int1-gpios:
        type: phandle-array
        required: false
```

13.3.3 Building and Running

13.3.4 Todo

- the driver is interrupt driven as well – need to test software
- the sensor has algorithm for steps – read out register
- temperature some attempt has been made, but ... (OK, temp can be read)

13.3.5 References

Bosch has documented the BMA423 very well. I kind of hope it will apply to the bma421.

A mechanism to adapt the 0x5E register is provided. (burst read/write)

All kind of parameters can be set to trigger an interrupt. (e.g. number of steps taken : think of the 10000 steps threshold)

13.4 HYNITRON CST816S

this driver does not exist, so it has been created. Still work in progress

there is a sample in this repository which can be copied to the zephyr samples directory

```
west build -p -b pinetime samples/sensor/cst816s
```

13.4.1 Overview

the Hynitron cst816s is a touchscreen. In zephyr doesn't handle touchscreens yet. In order to investigate, the touch-screen driver has been created as a sensor. In fact it senses your finger ;)

13.4.2 Requirements

for this sensor does not exist any driver, so here's what I did to create one under zephyr
adapt CMakeLists.txt adapt Kconfig add yaml file

create driver

The driver reads only one position. Multitouch is possible, but the screen is small. ...

see under drivers/sensor/cst816s

have a look at the pinetime.dts (under board/arm/pinetime) file:

```
&i2c1 {
    cst816s@15 {
        compatible = "hynitron,cst816s";
        reg = <0x15>;
        label = "CST816S";
    };
};
```

13.4.3 Building and Running

There are two samples :

- samples/gui/lvtouch (graphical)
- samples/sensor/cst816s (no graphics)

13.4.4 Todo

The graphical sample doesn't handle interrupts.

13.4.5 References

There is little available for this touchscreen.

13.5 HX HRS3300

this driver does not exist, so it has been created. Still work in progress


there is a sample in this repository which can be copied to the zephyr samples directory

```
west build -p -b pinetime samples/sensor/hrs3300
```

13.5.1 Overview

The HX HRS3300 sensor is a heart rate sensor, it produces 2 values: ALS and HRS. Ambient LIGHT SENSOR and HEART RATE SENSOR. Which have to be processed by an algorithm. I have no knowledge of a good open source algorithm yet.

I have used the settings of an arduino port of this library.



13.5.2 Requirements

for this sensor does not exist any driver, so here's what I did to create one under zephyr

adapt CMakeLists.txt

```
~/zephyrproject-2/zephyr/drivers/sensor add_subdirectory_ifdef(CONFIG_HRS3300 hrs3300)
```

adapt Kconfig

```
~/zephyrproject-2/zephyr/drivers/sensor
```

add yaml file

~/zephyrproject-2/zephyr/dts/bindings/sensor add hx,hrs3300.yaml

edit KConfig

source “drivers/sensor/hrs3300/Kconfig”

create driver

see under drivers/sensor/hrs3300

complement the pinetime.dts file with the following (under samples/sensor/bma280)

```
&i2c1 {
    hrs3300@44 {
        compatible = "hx,hrs3300";
        reg = <0x44>;
        label = "HRS3300";
    };
};
```

Create a file: `/dts/bindings/sensor/hx,hrs3300.yaml`. Which contains:

```
compatible: "hx,hrs3300"
properties:
```

13.5.3 Building and Running

13.5.4 Todo

- algorithm for heartrate
- power saving
- switching off/on mechanism

13.5.5 References

HRS3300 Heart Rate Sensor.pdf <https://github.com/atc1441/HRS3300-Arduino-Library>

13.6 Serial Nor Flash

```
west build -p -b pinetime samples/drivers/spi_flash -DCONF=prj.conf
```

13.6.1 Overview

This sample application should unlock the serial nor flash memory. This can be very usefull to store e.g. background for the watch.

compilation problematic

```
/root/zephyrproject/zephyr/samples/drivers/spi_flash/src/main.c:17:22: error: 'DT_INST_0_JEDEC_SPI_NOR_LABEL'
undeclared (first use in this function); did you mean 'DT_INST_0_NORDIC_NRF_RTC_LABEL'?
```

Turns out this is some problem with the board definition file.

I found it to be very useful to consult the generated dts file. Here you can check if everything is present.

Guess the dts-file has to be well intended.(structured)

****TIP: consult the generated dts board file ****

consulting the generated board definition file

```
vi /root/zephyrproject/zephyr/build/zephyr/include/generated/generated_dts_board.conf
```

13.6.2 Requirements

complement the pinetime.dts file with the following (under spi) #define JEDEC_ID_MACRONIX_MX25L64 0xC22017

```
&spi0 {
    compatible = "nordic,nrf-spi";
    status = "okay";
    sck-pin = <2>;
    mosi-pin = <3>;
    miso-pin = <4>;
    cs-gpios = <&gpio0 27 0>, <&gpio0 5 0>;
    st7789v@0 {
        compatible = "sitronix,st7789v";
        label = "DISPLAY";
        spi-max-frequency = <8000000>;
        reg = <0>;
        cmd-data-gpios = <&gpio0 18 0>;
        reset-gpios = <&gpio0 26 0>;
        width = <240>;
        height = <240>;
        x-offset = <0>;
        y-offset = <0>;
        vcom = <0x19>;
        gctrl = <0x35>;
        vrhs = <0x12>;
        vdvs = <0x20>;
        mdac = <0x00>;
        gamma = <0x01>;
        colmod = <0x05>;
        lcm = <0x2c>;
        porch-param = [0c 0c 00 33 33];
        cmd2en-param = [5a 69 02 01];
        pwctrl1-param = [a4 a1];
```

(continues on next page)

(continued from previous page)

```
pvgam-param = [D0 04 0D 11 13 2B 3F 54 4C 18 0D 0B 1F 23];
nvgam-param = [D0 04 0C 11 13 2C 3F 44 51 2F 1F 1F 20 23];
ram-param = [00 F0];
rgb-param = [CD 08 14];

};

mx25r64: mx25r6435f@1 {
    compatible = "jedec,spi-nor";
    reg = <1>;
    spi-max-frequency = <1000000>;
    label = "MX25R64";
    jedec-id = [0b 40 16];
    size = <67108864>;
    has-be32k;
};
```

13.6.3 Building and Running

```
west build -p -b pinetime samples/drivers/spi_flash
```

13.6.4 Todo

- detect ID memory : it is not the macronix one as suggestion on the pinetime website

I found the following : jedec-id = [0b 40 16]; (OK: can execute sample program)

- create working board definition (OK: see above)

13.6.5 References

<http://files.pine64.org/doc/datasheet/pinetime/MX25L6433F,%203V,%2064Mb,%20v1.6.pdf>

13.7 Battery

the samples just gets an analog reading from the battery

```
west build -p -b pinetime samples/sensor/battery
```

13.7.1 Overview

The battery level is measured on port 31, trough an ADC conversion.

$\text{voltage} = (\text{value} * 6) / 1024$ percentage remaining $((\text{voltage} - 3.55) * 100) * 3.9;$

A module should be able to report battery status in milivolts and charge level in percentage. Additionally, it should notify when external power is connected and when battery is being charged. Module will use adc (saadc peripheral) to measure battery voltage and gpio driver to monitor charge indication pin (pin 0.12) and power presence pin (0.19). Battery voltage can be in range from 3.0V - 4.2V (?). Unfortunately, internal reference (0.6V) can only be used for

voltages up to 3.6V (due to minimal gain of 1/6). VDD/4 reference can be used with 1/6 gain to measure voltages up to 4.95V. Test is needed to check how accurate is VDD as reference. Discharge curve (<https://forum.pine64.org/showthread.php?tid=8147>) will be used to calculate charge level in percent. Things to consider: saadc periodical calibration (spec suggests calibration if temperature changes by 10°C) inaccuracy of results: oversampling? never report higher level than before (if charge not connected), etc.

13.7.2 Todo

check pin when charging

13.7.3 References

<https://forum.pine64.org/showthread.php?tid=8147>

BEHIND THE SCENE

14.1 Behind the scene

14.1.1 Overview

I'm not a zephyr expert and am learning on the way.

In this chapter I let you glimpse behind the scene. (and notice all the struggle)

In case of the accel sensor, I used the bosch bma280 as a template.

In case of the touchscreen, I soon ran into trouble. So I tried splitting a complex problem into simpler ones.

This allowed me to detect problems easier.

The created samples might be of some use, if you run into trouble or if you want to extend the functionality.

14.2 development trajectory

The final goal is to use the accel-sensor in the watch (BMA423), which does not exist yet. In order to minimize the effort:

- we'll use something that looks like it (ADXL372), because there exists an example.
- next we adapt it to use the existing BMA280 sensor (under drivers/sensor), so we get a sample that works with the BMA280.
- we create a driver for the BMA423, based upon the BMA280
- we adapt the sample for the BMA280 to BMA423

14.3 Bosch BMA280

```
west build -p -b pinetime samples/drivers/bma280
```

14.3.1 Overview

This sample application mimics the presence of a bosch, bma280 accel sensor. For this sensor exists a driver in zephyr, but no sample. Remember, I'm not a zephyr expert and am learning on the way.

14.3.2 Requirements

complement the pinetime.dts file with the following (under samples/sensor/bma280)

This will supplement / override what's already definition on the board level (boards/arm/pinetime)

```
&i2c1 {
    bma280@18 {
        compatible = "bosch,bma280";
        reg = <0x18>;
        label = "BMA280";
        int1-gpios = <&gpio0 8 0>;
    };
};
```

Create a file: `/dts/bindings/sensor/bosch,bma280-i2c.yaml`. Which contains:

```
compatible: "bosch,bma280"
include: i2c-device.yaml
properties:
    int1-gpios:
        type: phandle-array
        required: false
```

14.3.3 Building and Running

14.3.4 Todo

- since no serial port and no J-LINK, I have to print messages to the screen (see sample gui/lvaccel)
- I adapted the BMA driver so it accepts the CHIP_ID, further registers are subject to investigation, since no doc

14.3.5 References

BMA421 is not a part number available to the general public, and therefore all the supporting documentation and design resources are neither discussed in public forums, nor disclosed on GitHub.

CHIP_ID=0X11 (so 423 drivers need to be adapted)

14.4 Touchscreen Hynitron

```
git clone https://github.com/lupyuen/hynitron_i2c_cst0xxse
```

14.4.1 Overview

this does not exist yet in zephyr, but there is work in progress <https://github.com/zephyrproject-rtos/zephyr/pull/16119>

14.4.2 Requirements

complement the pinetime.dts file with the following (under samples/sensor/bma280)

```
&i2c1 {
    touch@18 {
    };
};
```

Create a file: `/dts/bindings/sensor/touch.yaml`. Which contains:

```
compatible: "touch"
include: i2c-device.yaml
properties:
  intl-gpios:
  type: phandle-array
  required: false
```

14.4.3 Building and Running

14.4.4 Todo

-create touchscreen driver -create sample

14.4.5 References

14.5 Troubleshooting drivers

Drivers, like the one for the accel sensor BMA421 or the touchscreen CST816S, can deal with interrupts.

Adapting existing drivers did not get me the desired quick results.

Even after analysing the behaviour, setting values at each function step, did not get me any further.

14.5.1 Overview

The drivers can use interrupts.

In the settings/config one can choose between `OWN_THREAD` and `GLOBAL_THREAD`.

This affect the behaviour of how threads are handled.

The tread-handling and interrupt-handling occurs in the driver itself.

An interrupt is handled immediatly, the processing is offloaded to the threading.

14.5.2 Example

- You touch the touchscreen
- the touchscreen generates an interrupt
- the driver handles the interrupt
- a thread is created by the interrupt

- the threadhandling read the I2C-bus

14.5.3 Requirements

In order to create a working driver, I took it apart :

(split a complex problem into simple problems)

a sample to detect interrupt

`samples/basic/testirq`

Each time the touchscreen gets touched, it increases a counter.

a sample to scan the I2C-BUS

(scanning the I2C_1 port),

a sample to read the I2C-BUS

`samples/basic/touched` It is based on the Hynitron touchscreen code. Mass reading 63 bytes was not possible.

I did add a write of 1 to register 0x00.

a samples to handle semaphores

`samples/basic/testsemaphore`

14.6 placing a button on the screen

This sample **is not** really important, but it will teach you that you need to **set** LVGL_
↪CONFIG values, **in** order to be able to use LVGL functions.

14.6.1 Building and Running

In this repo under samples you will find an adapted gui/clock program. A button from the LVGL library is placed on the screen.

Later on when the touch-screen driver is ready, we'll be able to manipulate it.

Make sure that `prj.conf` file in clock directory contains the following:

Note: `CONFIG_LVGL_OBJ_CONTAINER=y CONFIG_LVGL_OBJ_BUTTON=y`

problem the canvas heigh*width eats up RAM and exceeds once > 40

SAMPLES AND DEMOS

In each sample directory is a Readme file. This is just a collection of them.

15.1 Basic Samples

15.1.1 Blinky Application

Overview

The Blinky example shows how to configure GPIO pins as outputs which can also be used to drive LEDs on the hardware usually delivered as “User LEDs” on many of the supported boards in Zephyr.

Requirements

The demo assumes that an LED is connected to one of GPIO lines. The sample code is configured to work on boards that have defined the led0 alias in their board devicetree description file. Doing so will generate these variables:

- DT_ALIAS_LED0_GPIOS_CONTROLLER
- DT_ALIAS_LED0_GPIOS_PIN

Building and Running

This samples does not output anything to the console. It can be built and flashed to a board as follows:

After flashing the image to the board, the user LED on the board should start to blink.

15.1.2 Button demo

Overview

A simple button demo showcasing the use of GPIO input with interrupts. If the button is pressed, it will set a value at the location 0x2000F000 in memory. With openocd or any other debugger you can peek at this location.

Requirements

The demo assumes that a push button is connected to one of GPIO lines. The sample code is configured to work on boards with user defined buttons and that have defined the `SW0_*` variables.

To use this sample, you will require a board that defines the user switch in its header file. The `board.h` must define the following variables:

- `SW0_GPIO_NAME` (or `DT_ALIAS_SW0_GPIOS_CONTROLLER`)
- `DT_ALIAS_SW0_GPIOS_PIN`

Alternatively, this could also be done by defining ‘sw0’ alias in the board devicetree description file.

Building and Running

This sample can be built for multiple boards, in this example we will build it for the pinetime

After startup, the program looks up a predefined GPIO device, and configures the pin in input mode, enabling interrupt generation on falling edge. During each iteration of the main loop, the state of GPIO line is monitored and printed to the serial console. When the input button gets pressed, the interrupt handler will print an information about this event along with its timestamp.

15.1.3 I2C Scanner sample

Overview

This sample sends I2C messages without any data (i.e. stop condition after sending just the address). If there is an ACK for the address, it prints the address as `FOUND`.

Warning: As there is no standard I2C detection command, this sample uses arbitrary SMBus commands (namely SMBus quick write and SMBus receive byte) to probe for devices. This sample program can confuse your I2C bus, cause data loss, and is known to corrupt the Atmel AT24RF08 EEPROM found on many IBM Thinkpad laptops. See also the [i2cdetect man page](#)

Building and Running

15.1.4 Touchscreen IRQ

Overview

The touchscreen generates an interrupt when touched.

Requirements

A counter that keeps track of the number of times touched.

This value is stored at a fixed location in memory, because I have a simple test setup.

Building and Running

15.1.5 Touchpoints

Overview

When touched the touchscreen triggers an interrupt, it's address 0x15 becomes visible.

Requirements

Catch the interrupts and act upon it.

Only the first touchpoint is usable.

But a sequence of 64 has to be read.

Building and Running

the purpose is just testing howto read the touchpoints of the touchscreen

15.2 Sensor Samples

15.2.1 BMA280: Three Axis High-g I2C/SPI Accelerometer

Description

This sample application produces slightly different outputs based on the chosen driver configuration mode:

- In **Measuring Mode with trigger support**, the acceleration on all three axis is printed in m/s^2 at the sampling rate (ODR).
- In **Polled Measuring Mode**, the instantaneous acceleration is polled every 2 seconds.
- In **Max Peak Detect Mode**, the device returns only the over-threshold peak acceleration between two consecutive sample fetches or trigger events. (In most high-g applications, a single 3-axis acceleration sample at the peak of an impact event contains sufficient information about the event, and the full acceleration history is not required.) Instead of printing the acceleration on all three axis, the sample application calculates the vector magnitude (root sum squared) and displays the result in g 's rather than in m/s^2 , together with an bar graph.

References

- BMA280: <http://www.analog.com/bma280>

Wiring

This sample uses the BMA280 sensor controlled either using the I2C or SPI interface. Connect supply **VDD**, **VS** and **GND**. The supply voltage can be in the 1.6V to 3.5V range.

I2C mode

Connect Interface: **SDA**, **SCL** and optionally connect the **INT1** to a interrupt capable GPIO. It is a requirement that **SCLK** must be connected to **GND** in I2C mode. Depending on the baseboard used, the **SDA** and **SCL** lines require Pull-Up resistors. With the **MISO** pin low, the I2C address for the device is 0x1D, and an alternate I2C address of 0x53 can be chosen by pulling the **MISO** pin high.

I2C Address:

- **0x1D**: if MISO is pulled low
- **0x53**: if MISO is pulled high

Note: When sharing an SDA bus, the BMA280 Silicon Revision < 3 may prevent communication with other devices on that bus.

SPI mode

Connect Interface: **SCLK**, **MISO**, **MOSI** and **/CS** and optionally connect the **INT1** to a interrupt capable GPIO.

Building and Running

This project outputs sensor data to the console. It requires an BMA280 sensor. It should work with any platform featuring a I2C/SPI peripheral interface. It does not work on QEMU.

Sample Output: Max Peak Detect Mode

Sample Output: Measurement Mode

15.2.2 CST816S HYNITRON TOUCHSCREEN

Description

When touched the touchscreen triggers an interrupt. This is handled in the driver.

In the sample a handler is defined. This one gets activated by the driver.

References

Wiring

I2C mode

Building and Running

Sample Output: X & Y coordinates

Sample Output: Measurement Mode



15.2.3 HRS3300 Heart Rate Sensor

Overview

A sensor application that demonstrates how to poll data from the hrs3300 heart rate sensor.

It is based on the max30101 sample.

Building and Running

Sample Output

15.3 Driver Samples

The following samples demonstrate how to use various drivers supported by Zephyr.

15.3.1 I2C Scanner sample

Overview

This sample sends I2C messages without any data (i.e. stop condition after sending just the address). If there is an ACK for the address, it prints the address as `FOUND`.

Warning: As there is no standard I2C detection command, this sample uses arbitrary SMBus commands (namely SMBus quick write and SMBus receive byte) to probe for devices. This sample program can confuse your I2C bus, cause data loss, and is known to corrupt the Atmel AT24RF08 EEPROM found on many IBM Thinkpad laptops. See also the [i2cdetect man page](#)

Building and Running

15.3.2 I2C Scanner sample

Overview

This sample sends I2C messages without any data (i.e. stop condition after sending just the address). If there is an ACK for the address, it prints the address as `FOUND`.

Warning: As there is no standard I2C detection command, this sample uses arbitrary SMBus commands (namely SMBus quick write and SMBus receive byte) to probe for devices. This sample program can confuse your I2C bus, cause data loss, and is known to corrupt the Atmel AT24RF08 EEPROM found on many IBM Thinkpad laptops. See also the [i2cdetect man page](#)

Building and Running

15.4 Display Samples

15.4.1 ST7789V Display driver

make sure this patch is applied : <https://github.com/zephyrproject-rtos/zephyr/pull/20570/files>

Overview

This sample will draw some basic rectangles onto the display. The rectangle colors and positions are chosen so that you can check the orientation of the LCD and correct RGB bit order. The rectangles are drawn in clockwise order, from top left corner: Red, Green, Blue, grey. The shade of grey changes from black through to white. (if the grey looks too green or red at any point then the LCD may be endian swapped).

Note: The display driver rotates the display so that the ‘natural’ LCD orientation is effectively 270 degrees clockwise of the default display controller orientation.

Building and Running

References

- [ST7789V datasheet](#)

15.5 GUI Samples

15.5.1 LittlevGL Clock Sample

Overview

This sample application displays a clock background.

This samples demonstrates the use of the counter.

Have a look at the `test_counter_interrupt_fn` function in `src/main.c`

Requirements

You have to convert a graphical file to a “C” file, which is like a giant array.

Have a look at the `prj.conf` file.

It should contain `CONFIG_LVGL=y` and `CONFIG_LVGL_OBJ_IMAGE=y`.

For the clock function it needs `CONFIG_COUNTER=y`.

Building and Running

References

15.5.2 Adafruit GFX Library on ST7789V Display

Overview

This is a sample C++ firmware running Adafruit GFX Library on a ST7789V display. The library is ported from Arduino.

15.5.3 Display accel values

Overview

This sample application displays “Hello World” in the center of the screen and a counter at the bottom which increments every second.

It display the values x,y,z from the bosch BMA421 accel sensor.

Requirements

Pinetime watch definitions can be found under the boards sub-directory

- pinetime.conf
- pinetime.overlay

Building and Running

```
west build -p -b pinetime samples/gui/lvgl
```

References

15.5.4 LittlevGL Basic Sample

Overview

This sample application displays “Hello World” in the center of the screen and a counter at the bottom which increments every second.

Requirements

Pinetime watch definitions can be found under the boards sub-directory

- pinetime.conf
- pinetime.overlay

Building and Running

```
west build -p -b pinetime samples/gui/lvgl
```

References

15.5.5 Touchscreen Basic Sample

Overview

This sample application displays touchscreen-values x and y in the center of the screen.

The touchscreen triggers an interrupt when touched. This means that data is ready and can be collected.

However, using the interrupt with the handler, does not seem to work within the GUI. When used in samples/sensor/cst816s, it runs. . . .

Requirements

Pinetime watch zephyr cst816s driver

Building and Running

```
west build -p -b pinetime samples/gui/lvtouch
```

References

15.6 Bluetooth Samples

15.6.1 Bluetooth: Eddystone

Overview

Application demonstrating [Eddystone Configuration Service](#)

The Eddystone Configuration Service runs as a GATT service on the beacon while it is connectable and allows configuration of the advertised data, the broadcast power levels, and the advertising intervals. It also forms part of the definition of how Eddystone-EID beacons are configured and registered with a trusted resolver.

Requirements

- BlueZ running on the host, or
- A board with BLE support

Building and Running

This sample can be found under **:zephyr_file:'samples/bluetooth/eddytone'** in the Zephyr tree.

See [bluetooth samples section](#) for details.

15.6.2 Bluetooth: Peripheral_cts

Overview

Application demonstrating reading the time from a CTS service.

(reading out the cts service with bluez)

```
[Ds      D6      sample      cts      server:/service0014/char0015]# read      Attempting      to      read
/org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      [CHG]      Attribute
/org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0xdf      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x07      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x05      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x1e      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x0c      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x2d      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x1e      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x01      [CHG]      At-
tribute /org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015      Value:      0x00      [CHG]      Attribute
/org/bluez/hci0/dev_75_D3_E5_20_20_26/service0014/char0015 Value: 0x00
```

Requirements

- a bluetoothdevice running the CTS service (I used the bluetooth/samples/peripheral for this, it simulates a cts server)
- a board with this software (pinetime)

Building and Running

This sample can be found under **:pinetime_file:'samples/bluetooth/peripheral_cts'** in the Zephyr tree.

See [bluetooth samples section](#) for details.

15.6.3 Bluetooth: Peripheral

Overview

Application demonstrating the BLE Peripheral role. It has several well-known and vendor-specific GATT services that it exposes.

Requirements

- BlueZ running on the host, or
- A board with BLE support

Building and Running

This sample can be found under **:pinetime_file:'samples/bluetooth/peripheral'** in the Zephyr tree.

See [bluetooth samples section](#) for details.

MENUCONFIG

16.1 Zephyr is like linux

TIP: the pinetime specific drivers are located under Modules

Note: to get a feel, compile a program, for example

```
west build -p -b pinetime samples/bluetooth/peripheral -D CONF_FILE="prj.conf"
```

the pinetime contains an external 32Kz crystal now you can have a look in the configurationfile (and modify if needed)

```
$ west build -t menuconfig
```

```
Modules --->
Board Selection (nRF52832-MDK) --->
Board Options --->
SoC/CPU/Configuration Selection (Nordic Semiconductor nRF52 series MCU) --->
Hardware Configuration --->
ARM Options --->
Architecture (ARM architecture) --->
General Architecture Options --->
[ ] Floating point ----
General Kernel Options --->
Device Drivers ---> *****SELECT THIS ONE*****
C Library --->
Additional libraries --->
[*] Bluetooth --->
[ ] Console subsystem/support routines [EXPERIMENTAL] ----
[ ] C++ support for the application ----
System Monitoring Options --->
Debugging Options --->
[ ] Disk Interface ----
File Systems --->
-- Logging --->
Management --->
Networking --->
```

```
[ ] IEEE 802.15.4 drivers options ----
(UART_0) Device Name of UART Device for UART Console
[*] Console drivers --->
[ ] Net loopback driver ----
[*] Serial Drivers --->
```

(continues on next page)

(continued from previous page)

[illegible][illegible]

HACKING THE PINETIME SMARTWATCH

The pinetime **is** preloaded **with** firmware.
This firmware **is** secured, you cannot peek into it.

Note: The pinetime has a swd interface. To be able to write firmware, you need special hardware. I use a stm-link which is very cheap(2\$). You can also use the GPIO header of a raspberry pi. (my repo: <https://github.com/najnesnaj/openocd> is adapted for the orange pi)

To flash the software I use openocd : example for stm-link usb-stick

```
# openocd -s /usr/local/share/openocd/scripts -f interface/stlink.cfg -f target/nrf52.  
↪cfg
```

example for the orange-pi GPIO header (or raspberry)

```
# openocd -f /usr/local/share/openocd/scripts/interface/sysfsgpio-raspberrypi.cfg -c 'transport select swd'  
-f /usr/local/share/openocd/scripts/target/nrf52.cfg -c 'bindto 0.0.0.0'
```

once you started the openocd background server, you can connect to it using:

```
#telnet 127.0.0.1 4444
```

programming

```
once your telnet sessions started:  
Trying 127.0.0.1...  
Connected to 127.0.0.1.  
Escape character is '^]'.  
Open On-Chip Debugger  
> program zephyr.bin  
  
target halted due to debug-request, current mode: Thread  
xPSR: 0x01000000 pc: 0x00001534 msp: 0x20004a10  
** Programming Started **  
auto erase enabled  
using fast async flash loader. This is currently supported  
only with ST-Link and CMSIS-DAP. If you have issues, add  
"set WORKAREASIZE 0" before sourcing nrf51.cfg/nrf52.cfg to disable it  
target halted due to breakpoint, current mode: Thread  
xPSR: 0x61000000 pc: 0x2000001e msp: 0x20004a10  
wrote 24576 bytes from file zephyr.bin in 1.703540s (14.088 KiB/s)  
** Programming Finished **
```

(continues on next page)

(continued from previous page)

```
And finally execute a reset :  
>reset
```

removing write protection see: *[howto flash your zephyr image](#)*

DEBUGGING THE PINETIME SMARTWATCH

The pinetime does **not** have a serial port.
I do **not** have a segger debugging probe.
A way around this, it to put a value **in** memory at a fixed location.
With openocd you can peek at this memory location.

Note: #define MY_REGISTER (*(volatile uint8_t*)0x2000F000)

in the program you can set values: MY_REGISTER=1; MY_REGISTER=8;

this way you know till where the code executes

```
#telnet 127.0.0.1 4444
```

programming

```
once your telnet sessions started:  
Trying 127.0.0.1...  
Connected to 127.0.0.1.  
Escape character is '^]'.  
Open On-Chip Debugger  
>mdw 0x2000F000 0x1
```

the last byte shows the value of your program trace value

SCANNING THE I2C_1 PORT

```
The pinetime does not have a serial port.  
I do not have a segger debugging probe.  
A way around this, it to put a value in memory at a fixed location.  
With openocd you can peek at this memory location.
```

19.1 Building and Running

In this repo under samples you will find an adapted i2c scanner program.

```
west build -p -b pinetime samples/drivers/i2c_scanner
```

Note: #define MY_REGISTER (*(volatile uint8_t*)0x2000F000)

in the program you can set values: MY_REGISTER=1; MY_REGISTER=8;

this way you know till where the code executes

```
#telnet 127.0.0.1 4444
```

Peeking

```
once your telnet sessions started:  
Trying 127.0.0.1...  
Connected to 127.0.0.1.  
Escape character is '^]'.  
Open On-Chip Debugger  
>mdw 0x2000F000 0x1  
0x2000f000: 00c24418
```

Note::

this corresponds to 0x18, 0x44 and 0xC2 (which is endvalue of scanner, so it does not detect touchscreen, which should be touched first...)

HOWTO FLASH YOUR ZEPHYR IMAGE

Once you completed your west build , your image is located under the build directory

```
$ cd ~/work/pinetime/zephyr/build/zephyr
here you can find zephyr.bin which you can flash
```

I use Openocd to flash.
Just connect : telnet 127.0.0.1 4444

```
.. code-block:: console
```

```
program zephyr.bin
```


HOWTO REMOVE THE WRITE PROTECTION

:: the PineTime watch is read/write protected (at least the one I got) executing the following : `nrf52.dap apreg 1 0x0c` shows 0x0

Mind you, st-link does not allow you to execute that command, for this you will need a J-link.

There is a workaround using the GPIO of a raspberry pi or an OrangePi. (in this case you won't need an external programmer at all) (You can find an example for the orange pi in my repo :<https://github.com/najnesnaj/openocd>.) You have to reconfigure Openocd with the `-enable-cmsis-dap` option.

Unlock the chip by executing the command: `> nrf52.dap apreg 1 0x04 0x01`

HOWTO GENERATE PDF DOCUMENTS

sphinx cannot generate pdf directly, and needs latex

```
apt-get install latexmk
apt-get install texlive-fonts-recommended
apt-get install xzdec
apt-get install cmap
apt-get install texlive-latex-recommended
apt-get install texlive-latex-extra
```


ABOUT

I got a pinetime development kit very early.

I would like to thank the folks from <https://www.pine64.org/>.

I like to hack stuff, and I like the idea behind Open Source.

The smartwatches I hacked, contained microcontrollers from Nordic Semiconductor.

A lot of resources exist for this breed.

It is an Arm based, 32bit microcontroller with a lot of flash and RAM memory.

In fact it is a small computer on your wrist, with a battery and screen, and capable of bluetooth 4+ wireless communication.

A word of warning: this **is** work **in** progress.
You're likely to have a better skillset than me.
You are invited to add the missing pieces **and** to improve what's already there.

23.1 Todo

list with suggestions:

- better graphics (lvgl using images and rotating stuff)
- NOR flash (here one can store data)
- watchdog
- DFU (update over bluetooth)
- acceleration sensor
- heart rate sensor
- fun stuff
- useless stuff, but somehow cool
- applications, e.g. calculator, cycle computer, step counter, heart attack predictor ...