

naROOTo & S.A.S.U.K.E.

Rootkit Programming 2014/2015

Guru Chandrasekhara, Martin Herrmann

Technische Universität München

January 26, 2015

Overview

- 1 naROOTo
- 2 S.A.S.U.K.E. - rootkit detection
- 3 Other Detection methods
- 4 Conclusion

Overview

- 1 naROOTo
- 2 S.A.S.U.K.E. - rootkit detection
- 3 Other Detection methods
- 4 Conclusion

System call hooking

- Making write-protected memory writable using the CPU control register cr0

System call hooking

- Making write-protected memory writable using the CPU control register `cr0`
- Changing the pointers in the system call table

System call hooking

- Making write-protected memory writable using the CPU control register `cr0`
- Changing the pointers in the system call table
- Overwriting the first few instructions in selected functions (PUSH then RET hooking)

System call hooking

- Making write-protected memory writable using the CPU control register `cr0`
- Changing the pointers in the system call table
- Overwriting the first few instructions in selected functions (PUSH then RET hooking)
- **Problem:** Some processes don't leave read very fast causing slow unloading

Hooked System calls

- read: keylogging, covert communication

Hooked System calls

- read: keylogging, covert communication
- getdents: file hiding, process hiding (via /proc)

Hooked System calls

- read: keylogging, covert communication
- getdents: file hiding, process hiding (via /proc)
- recvmsg: socket hiding (TCP in ss)

Other hooked functions

- `packet_rcv`, `packet_rcv_spkt`, `tpacket_rcv`: packet hiding

Other hooked functions

- `packet_rcv`, `packet_rcv_spkt`, `tpacket_rcv`: packet hiding
- `show()` (for `/proc/tcp`): socket hiding (TCP in ss)

Other hooked functions

- `packet_rcv`, `packet_rcv_spkt`, `tpacket_rcv`: packet hiding
- `show()` (for `/proc/tcp`): socket hiding (TCP in `ss`)
- `show()` (for `/proc/udp`): socket hiding (UDP in `netstat` and `ss`)

Hiding modules

- Removing them from the list containing all struct module *

Hiding modules

- Removing them from the list containing all struct module *
- Removing them from the kernfs tree

Hiding modules

- Removing them from the list containing all struct module *
- Removing them from the kernfs tree
- Can hide multiple modules

Hiding modules

- Removing them from the list containing all struct module *
- Removing them from the kernfs tree
- Can hide multiple modules
- Restore from backup

Port knocking

- Using the Netfilter API in the kernel (also used by iptables)

Port knocking

- Using the Netfilter API in the kernel (also used by iptables)
- Very easy to use, just register a hook using provided functions and structures

Port knocking

- Using the Netfilter API in the kernel (also used by iptables)
- Very easy to use, just register a hook using provided functions and structures
- **Important:** Manually send *RST* for TCP and *ICMP Port Unreachable* for UDP

Port knocking

- Using the Netfilter API in the kernel (also used by iptables)
- Very easy to use, just register a hook using provided functions and structures
- **Important:** Manually send *RST* for TCP and *ICMP Port Unreachable* for UDP
- Connecting to specified ports only possible after "pinging" the following ports first (within two seconds): 12345, 666, 23, 1337, 42

Port knocking

- Using the Netfilter API in the kernel (also used by iptables)
- Very easy to use, just register a hook using provided functions and structures
- **Important:** Manually send *RST* for TCP and *ICMP Port Unreachable* for UDP
- Connecting to specified ports only possible after "pinging" the following ports first (within two seconds): 12345, 666, 23, 1337, 42
- Host may now connect to all ports with enable port knocking (until another host completes the knocking sequence)

Overview

- 1 naROOTo
- 2 S.A.S.U.K.E. - rootkit detection
- 3 Other Detection methods
- 4 Conclusion

LKM

- **Scan And Subvert User-manipulated Kernel Exploits**

LKM

- **S**can **A**nd **S**ubvert **U**ser-manipulated **K**ernel **E**xploits
- Check the system call table

LKM

- **S**can **A**nd **S**ubvert **U**ser-manipulated **K**ernel **E**xploits
- Check the system call table
- Check the first 16 Bytes of function instructions

LKM

- **S**can **A**nd **S**ubvert **U**ser-manipulated **K**ernel **E**xploits
- Check the system call table
- Check the first 16 Bytes of function instructions
- Loop all processes (using the struct task * list)

LKM

- **S**can **A**nd **S**ubvert **U**ser-manipulated **K**ernel **E**xploits
- Check the system call table
- Check the first 16 Bytes of function instructions
- Loop all processes (using the struct task * list)
- List contents of the module list, the kobject list, and the kernfs tree

LKM

- **S**can **A**nd **S**ubvert **U**ser-manipulated **K**ernel **E**xploits
- Check the system call table
- Check the first 16 Bytes of function instructions
- Loop all processes (using the struct task * list)
- List contents of the module list, the kobject list, and the kernfs tree
- List all Netfilter hooks

User-mode

- Shell script that uses `kill -0` on every possible PID (filters for good processes with existing `proc` entries)

User-mode

- Shell script that uses `kill -0` on every possible PID (filters for good processes with existing `proc` entries)
- Call a C program to hook to every TCP socket.

- We were not able to compile our tools on the system

chytryroot

- Broken ip command, extremely slow scp

chytryroot

- Broken ip command, extremely slow scp
- sshd on port 5167 (PID 2842)

chytryroot

- Broken ip command, extremely slow scp
- sshd on port 5167 (PID 2842)
- Manipulated syscall pointer to read and recvmsg

chytryroot

- Broken ip command, extremely slow scp
- sshd on port 5167 (PID 2842)
- Manipulated syscall pointer to read and recvmsg
- Manipulated instructions in all three functions of the packet_rcv family

chytryroot

- Broken ip command, extremely slow scp
- sshd on port 5167 (PID 2842)
- Manipulated syscall pointer to read and recvmsg
- Manipulated instructions in all three functions of the packet_rcv family
- Found the name of the rootkit in the kernfs

rootkit

- Could not compile while rootkit is inserted

rootkit

- Could not compile while rootkit is inserted
- Extreme memory issues (could not run user-mode script)

rootkit

- Could not compile while rootkit is inserted
- Extreme memory issues (could not run user-mode script)
- Hidden sshd on port 22 (PID 2446)

rootkit

- Could not compile while rootkit is inserted
- Extreme memory issues (could not run user-mode script)
- Hidden sshd on port 22 (PID 2446)
- No manipulation of the system call table

rootkit

- Could not compile while rootkit is inserted
- Extreme memory issues (could not run user-mode script)
- Hidden sshd on port 22 (PID 2446)
- No manipulation of the system call table
- Manipulated instructions in all three functions of the `packet_rcv` family

rootkit

- Could not compile while rootkit is inserted
- Extreme memory issues (could not run user-mode script)
- Hidden sshd on port 22 (PID 2446)
- No manipulation of the system call table
- Manipulated instructions in all three functions of the `packet_rcv` family
- Netfilter hook for port knocking

- Random kernel panics, reboot/shutdown not working

- Random kernel panics, reboot/shutdown not working
- Two hidden processes: nc on port 4321 and bash (PIDs 2515, 2529)

- Random kernel panics, reboot/shutdown not working
- Two hidden processes: nc on port 4321 and bash (PIDs 2515, 2529)
- No manipulation of the system call table

- Random kernel panics, reboot/shutdown not working
- Two hidden processes: nc on port 4321 and bash (PIDs 2515, 2529)
- No manipulation of the system call table
- Manipulated instructions in read, recvmsg, packet_rcv_spkt, and tpacket_rcv

g6_rkit_comcon

- Hidden sshd on port 7865 (PID 2834)

g6_rkit_comcon

- Hidden sshd on port 7865 (PID 2834)
- Manipulated syscall pointer to read, getdents, and recvmsg

g6_rkit_comcon

- Hidden sshd on port 7865 (PID 2834)
- Manipulated syscall pointer to read, getdents, and recvmsg
- Manipulated instructions in tpacket_rcv

Marvin

- Could not run user-mode script (multiple errors while using pipes)

Marvin

- Could not run user-mode script (multiple errors while using pipes)
- Hidden nc (PID 2799)

Marvin

- Could not run user-mode script (multiple errors while using pipes)
- Hidden nc (PID 2799)
- Manipulated syscall pointer to read, getdents, and open

Marvin

- Could not run user-mode script (multiple errors while using pipes)
- Hidden nc (PID 2799)
- Manipulated syscall pointer to read, getdents, and open
- Manipulated instructions in `packet_rcv`

Marvin

- Could not run user-mode script (multiple errors while using pipes)
- Hidden nc (PID 2799)
- Manipulated syscall pointer to read, getdents, and open
- Manipulated instructions in packet_rcv
- Found the name of the rootkit in the list of kobjecs

Marvin

- Could not run user-mode script (multiple errors while using pipes)
- Hidden nc (PID 2799)
- Manipulated syscall pointer to read, getdents, and open
- Manipulated instructions in packet_rcv
- Found the name of the rootkit in the list of kobjecs
- Netfilter hook for port knocking

External Analysis

- Looking at the .vdi file

External Analysis

- Looking at the .vdi file
- Looking at the memory

External Analysis

- Looking at the .vdi file
- Looking at the memory
- Looking at traffic from and to the VM

Conclusion

- Fun experience (both writing and detecting rootkits)

Conclusion

- Fun experience (both writing and detecting rootkits)
- Important lesson: never use copy&paste!

Discussion and comments

Thank you for your attention!