# welcome to



# Mission:

To offer a AI education to anyone on Earth for free. Our doors are open to all those who wish to learn. We are a learning community that spans almost every country dedicated to teaching our students how to make a positive impact in the world using AI technology, whether that's through employment or entrepreneurship.

# Values:

- 1. Embrace the Weird
- 2. Inspire and Educate
- 3. Data Driven Optimism

- 4. Rapid Experimentation
- 5. Be Frugal
- 6. Choose Love, not Fear

# Beril Sirmacek www.BerilSirmacek.com

- Artificial Intelligence
- Augmented Reality
- Computer Vision
- Remote Sensing
- Medical Applications
- create4D <u>www.create4D.com</u>
- farmAR

# https://www.youtube.com/user/DrSirmacek/videos



School of Al Deans (Kareem Elsafty as the Dean for...

230 views • 3 weeks ago



School of Al Deans (Carson Bentley as the Dean for San...

86 views · 3 weeks ago



School of Al Deans (Simbarashe Timothy Motsi...

90 views • 3 weeks ago



School of Al Deans (Fazl Barez the dean of Edinburg...

77 views · 3 weeks ago



School of Al Deans (Sathish Krishnasamy Ravichandran...

144 views • 1 month ago



School of Al Deans (Vamsi Annabathula the dean of...

40 views • 1 month ago



School of Al Deans (Ngong Constantine Mbufung the ...

94 views • 1 month ago



School of Al Deans (Joao Areias the dean of Itabira...

142 views • 1 month ago



School of Al Deans (Gregory Shavers the dean of Buffalo...

139 views • 1 month ago



School of Al Deans (Jubeen Shah the dean of Raleigh...

124 views • 1 month ago



School of Al Deans (Karan Kharecha the dean of Rajko...

144 views • 1 month ago




School of Al Deans (Ricardo Enrique Pretelt the dean of...

63 views • 1 month ago



School of Al Deans (Rafael Villca Poggian the dean of L ...

51 views • 1 month ago



School of Al Deans (Pravin Vedurla dean of...

174 views • 1 month ago



School of Al Deans (Beril and Ernest the deans of...

78 views • 1 month ago



School of Al Deans (Nurbek the dean of Tampere School...

63 views • 1 month ago



School of Al Deans (Devansh Trivedi the dean of Rajkot...

88 views • 1 month ago



School of Al Deans (Kaushal Sharma the dean of Noida...

192 views • 1 month ago

# Review questions:

Which learning algorithm would you choose in order to solve these problems?

Classify different fruits

Predict weather

Learn to play chess by trial and error

based on various sensor data







# Review questions:

Which learning algorithm would you choose in order to solve these problems?

Classify different fruits

**Predict weather** 

based on various sensor data

Learn to play chess by trial and error









REINFORCEMENT

# Goals for today:


- 1. Features
- 2. Dimensionality Reduction
- 3. Autoencoders & PCA
- 4. Tensors
- 5. TensorFlow Session
- 6. TensorBoard

What are good features?











Lots of features

Lots of information


?!?!?!?!!!!!!






## Few things to consider;

- Noisy? (reliably distinguishing the classes?)
- Causing over-fitting?
- Highly correlated with other features?
- Slowing down the system?






The distance between the ground truth and the prediction is called the cost.

The essence of a supervised machine-learning algorithm to find the parameters of a model which result in the least cost.

Optimization problem: Looking for a  $\Theta$  that minimizes the cost among all data points  $x \in X$ 

 $Cost(\Theta|X) = \sum ||g(x|\Theta) - f(x)||$  (distance between the prediction and the groundtruth)





Cost on the training set is very low, but Cost on the test set is very high,

means you have overfitting problem!

??

# Make everything as simple as possible, But not simpler.






https://rpubs.com/sandipan/197468

#### Goal:

Find small number of "directions" that explain variation, re-represent data by projecting along those directions

Important assumption:

Variation contains information



- Input and output layers have the same number of neurons
- Feedforward
- Linear Autoencoders are directly related to PCA
- Weights are not equal to the principal components, and are generally not orthogonal, yet the principal components may be recovered from them <a href="https://youtu.be/H1AllrJ-30">https://youtu.be/H1AllrJ-30</a>

# Matrix



# Tensor





A **tensor** is a generalization of vectors and matrices to potentially higher dimensions. Internally, TensorFlow represents tensors as n-dimensional arrays of base datatypes.

1-d tensor	2-d tensor	3-d tensor
4-d tenso	or !	5-d tensor



https://github.com/bsirmacek/schoolofAl\_enschede

```
import tensorflow as tf

x = tf.constant([[1.,2.]])
negMatrix = tf.negative(x)

print(x)

with tf.Session() as sess:
    result = sess.run(negMatrix)

print(result)

Tensor("Const_1:0", shape=(1, 2), dtype=float32)
[[-1. -2.]]
```

Defining a tensor is different than running it.

You have to Run the Session to fill the values of the defined tensor.

```
import tensorflow as tf
x = tf.constant([[1.,2.]])
negMatrix = tf.negative(x)
num1 = tf.constant(5)
num2 = tf.constant(10)
num3 = tf.multiply(num1,num2)
with tf.Session() as sess:
    result = sess.run([negMatrix, num3])
print(result)
[array([[-1., -2.]], dtype=float32), 50]
```

A session not only configures where your code will be computed on your machine,


but also crafts how the computation will be laid out in order to parallelize the computation.






tf.zeros(shape) tf.ones(shape)


Question: Initialize a 100x100 size tensor with all elements equal to 2








```
model = Sequential()
model.add(Conv2D(32, kernel_size=(5, 5), strides=(1, 1), activation='relu', input_shape=input_shape))
model.add(MaxPooling2D(pool_size=(2, 2), strides=(2, 2)))
model.add(Conv2D(64, (5, 5), activation='relu'))
model.add(MaxPooling2D(pool_size=(2, 2)))
model.add(Flatten())
model.add(Dense(1000, activation='relu'))
model.add(Dense(num_classes, activation='softmax'))


model.compile(loss=keras.losses.categorical_crossentropy, optimizer=keras.optimizers.SGD(lr=0.01), metrics=['accuracy'])
model.fit(x_train, y_train, batch_size=batch_size, epochs=epochs, verbose=1, validation_data=(x_test, y_test), callbacks=[history])
score = model.evaluate(x_test, y_test, verbose=0)
print('Test loss:', score[0])
print('Test accuracy:', score[1])
```



















Interactive visualization environment

A flow Chart of the way data transforms






>>tensorboard -logdir=./output

http://copymetothebrowser





https://www.tensorflow.org/guide/summaries\_and\_tensorboard

https://www.tensorflow.org/guide/tensorboard histograms

#### Discussion

## HORIZON: FACEBOOK'S OPEN SOURCE APPLIED REINFORCEMENT LEARNING PLATFORM

Jason Gauci <sup>1</sup> Edoardo Conti <sup>1</sup> Yitao Liang <sup>1</sup> Kittipat Virochsiri <sup>1</sup> Yuchen He <sup>1</sup> Zachary Kaden <sup>1</sup> Vivek Narayanan <sup>1</sup> Xiaohui Ye <sup>1</sup>

Historically, we have used supervised learning models for predicting click through rate (CTR) and likelihood that the notification leads to meaningful interactions. These predictions are combined into a score that is used to filter the notifications.

https://arxiv.org/pdf/1811.00260.pdf

# Discussion

# https://experiments.withgoogle.com/ai/ai-duet/view/

