

zplugin-install.zsh(1)

NAME

zplugin-install.zsh - a shell script

SYNOPSIS

Documentation automatically generated with `zshelldoc`

FUNCTIONS

```
-zplg-compile-plugin  
-zplg-download-file-stdout  
-zplg-forget-completion  
-zplg-install-completions  
-zplg-setup-plugin-dir
```

DETAILS

Script Body

Has 3 line(s). No functions are called (may attach to Zle or do hooks, etc.).

-zplg-compile-plugin

```
# Compiles given plugin (its main source file, and also an  
# additional "....zsh" file if it exists).  
#  
# $1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)  
# $2 - plugin (only when $1 - i.e. user - given)
```

Has 13 line(s). Calls functions:

```
-zplg-compile-plugin  
'-- zplugin-side.zsh/-zplg-first
```

Uses feature(s): *zcompile*

Called by:

```
-zplg-setup-plugin-dir
zplugin-autoload.zsh/-zplg-compile-uncompile-all
zplugin.zsh/zplugin
```

-zplg-download-file-stdout

```
# Downloads file to stdout. Supports following backend commands:
# curl, wget, lftp, lynx. Used by snippet loading.
```

Has 31 line(s). Calls functions:

```
-zplg-download-file-stdout
```

Uses feature(s): *type*

Called by:

```
zplugin.zsh/-zplg-load-snippet
```

-zplg-forget-completion

```
# Implements alternation of Zsh state so that already initialized
# completion stops being visible to Zsh.
#
# $1 - completion function name, e.g. "_cp"; can also be "cp"
```

Has 17 line(s). Doesn't call other functions.

Uses feature(s): *unfunction*

Called by:

```
-zplg-install-completions
zplugin-autoload.zsh/-zplg-compinit
zplugin-autoload.zsh/-zplg-uninstall-completions
zplugin.zsh/zplugin
```

-zplg-install-completions

```
# Installs all completions of given plugin. After that they are
# visible to 'compinit'. Visible completions can be selectively
# disabled and enabled. User can access completion data with
# 'clist' or 'completions' subcommand.
#
# $1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
# $2 - plugin (only when $1 - i.e. user - given)
# $3 - if 1, then reinstall, otherwise only install completions that aren't there
```

Has 33 line(s). Calls functions:

```
-zplg-install-completions
|-- -zplg-forget-completion
|-- zplugin-side.zsh/-zplg-exists-physically-message
`-- zplugin.zsh/-zplg-any-to-user-plugin
```

Called by:

```
-zplg-setup-plugin-dir
zplugin.zsh/zplugin
```

-zplg-setup-plugin-dir

```
# Clones given plugin into PLUGIN_DIR. Supports multiple
# sites (respecting 'from' and 'proto' ice modifiers).
# Invokes compilation of plugin's main file.
#
# $1 - user
# $2 - plugin
```

Has 40 line(s). Calls functions:

```
-zplg-setup-plugin-dir
|-- -zplg-compile-plugin
|   `-- zplugin-side.zsh/-zplg-first
|-- -zplg-install-completions
|   |-- -zplg-forget-completion
|   |-- zplugin-side.zsh/-zplg-exists-physically-message
|   `-- zplugin.zsh/-zplg-any-to-user-plugin
`-- zplugin-side.zsh/-zplg-any-colorify-as-uspl2
```

Uses feature(s): *eval*

Called by:

zplugin.zsh/-zplg-load