

zplugin-side.zsh(1)

NAME

zplugin-side.zsh - a shell script

SYNOPSIS

Documentation automatically generated with `zshelldoc`

FUNCTIONS

```
-zplg-any-colorify-as-uspl2
-zplg-exists-physically
-zplg-exists-physically-message
-zplg-first
-zplg-shands-exp
-zplg-store-ices
-zplg-two-paths
```

DETAILS

Script Body

Has 1 line(s). No functions are called (may set up e.g. a hook, a Zle widget bound to a key, etc.).

-zplg-any-colorify-as-uspl2

Returns ANSI-colored "user/plugin" string, from any supported plugin spec (user--plugin, user/plugin, user plugin, plugin).

```
$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
$2 - plugin (only when $1 - i.e. user - given)
$REPLY = ANSI-colored "user/plugin" string
```

Has 11 line(s). Calls functions:

```
-zplg-any-colorify-as-uspl2
`-- zplugin.zsh/-zplg-any-to-user-plugin
```

Called by:

```

-zplg-exists-physically-message
zplugin-autoload.zsh/-zplg-clear-completions
zplugin-autoload.zsh/-zplg-compile-uncompile-all
zplugin-autoload.zsh/-zplg-compiled
zplugin-autoload.zsh/-zplg-create
zplugin-autoload.zsh/-zplg-exists-message
zplugin-autoload.zsh/-zplg-get-completion-owner-uspl2col
zplugin-autoload.zsh/-zplg-list-bindkeys
zplugin-autoload.zsh/-zplg-recently
zplugin-autoload.zsh/-zplg-search-completions
zplugin-autoload.zsh/-zplg-show-completions
zplugin-autoload.zsh/-zplg-show-registered-plugins
zplugin-autoload.zsh/-zplg-show-times
zplugin-autoload.zsh/-zplg-uncompile-plugin
zplugin-autoload.zsh/-zplg-unload
zplugin-autoload.zsh/-zplg-update-or-status-all
zplugin-autoload.zsh/-zplg-update-or-status
zplugin-install.zsh/-zplg-install-completions
zplugin-install.zsh/-zplg-setup-plugin-dir

```

-zplg-exists-physically

Checks if directory of given plugin exists in PLUGIN_DIR.

Testable.

\$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
 \$2 - plugin (only when \$1 - i.e. user - given)

Has 10 line(s). Calls functions:

```

-zplg-exists-physically
|-- -zplg-shands-exp
`-- zplugin.zsh/-zplg-any-to-user-plugin

```

Called by:

```

-zplg-exists-physically-message
zplugin-autoload.zsh/-zplg-create
zplugin-autoload.zsh/-zplg-get-path

```

-zplg-exists-physically-message

Checks if directory of given plugin exists in PLUGIN_DIR,
and outputs error message if it doesn't.

Testable.

\$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
\$2 - plugin (only when \$1 - i.e. user - given)

Has 11 line(s). Calls functions:

```
-zplg-exists-physically-message  
|-- -zplg-any-colorify-as-uspl2  
|   '-- zplugin.zsh/-zplg-any-to-user-plugin  
|-- -zplg-exists-physically  
|   |-- -zplg-shands-exp  
|   '-- zplugin.zsh/-zplg-any-to-user-plugin  
 '-- -zplg-shands-exp
```

Called by:

```
zplugin-autoload.zsh/-zplg-changes  
zplugin-autoload.zsh/-zplg-delete  
zplugin-autoload.zsh/-zplg-edit  
zplugin-autoload.zsh/-zplg-glance  
zplugin-autoload.zsh/-zplg-stress  
zplugin-autoload.zsh/-zplg-uninstall-completions  
zplugin-autoload.zsh/-zplg-update-or-status  
zplugin-install.zsh/-zplg-install-completions
```

-zplg-first

Finds the main file of plugin. There are multiple file name formats, they are ordered in order starting from more correct ones, and matched. `-zplg-load-plugin()` has similar code parts and doesn't call `-zplg-first()` – for performance. Obscure matching is done in `-zplg-find-other-matches`, here and in `-zplg-load()`. Obscure = non-standard main-file naming convention.

\$1 - plugin spec (4 formats: `user---plugin`, `user/plugin`, `user`, `plugin`)
\$2 - plugin (only when \$1 - i.e. `user` - given)

Has 25 line(s). Calls functions:

```
-zplg-first  
|-- zplugin.zsh/-zplg-any-to-user-plugin  
'-- zplugin.zsh/-zplg-find-other-matches
```

Called by:

```
zplugin-autoload.zsh/-zplg-edit  
zplugin-autoload.zsh/-zplg-glance  
zplugin-autoload.zsh/-zplg-stress  
zplugin-install.zsh/-zplg-compile-plugin
```

-zplg-shands-exp

Does expansion of currently little unstandarized shorthands like `"%SNIPPETS"`, `"%HOME"`, `"OMZ::"`, `"PZT::"`.

Has 7 line(s). Doesn't call other functions.

Called by:

```
-zplg-exists-physically-message  
-zplg-exists-physically  
zplugin-autoload.zsh/-zplg-delete  
zplugin-autoload.zsh/-zplg-get-path
```

-zplg-store-ices

Saves ice mods in given hash onto disk.

\$1 - directory where to create / delete files
\$2 - name of hash that holds values
\$3 - additional keys of hash to store, space separated
\$4 - additional keys of hash to store, empty-meaningful ices, space separated

Has 16 line(s). Doesn't call other functions.

Called by:

zplugin-autoload.zsh/-zplg-update-or-status
zplugin-install.zsh/-zplg-download-snippet
zplugin-install.zsh/-zplg-setup-plugin-dir

-zplg-two-paths

Obtains a snippet URL without specification if it is an SVN URL (points to directory) or regular URL (points to file), returns 2 possible paths for further examination

Has 22 line(s). Doesn't call other functions.

Called by:

zplugin-autoload.zsh/-zplg-compute-ice
zplugin-autoload.zsh/-zplg-delete
zplugin-autoload.zsh/-zplg-get-path