## Mustang project user documentation

Jochen Stärk

For Mustangproject 1.3.1, 2016-06-01

http://www.mustangproject.org

#### Inhaltsverzeichnis

Mustang project user documentation	1
About Mustangproject	1
Overview of ZUGFeRD-Solutions.	
Download/Project setup	
Source code	
Project setup without Maven	
With Maven	
Reading ZUGFeRD data	3
Complete sample source code for reading ZUGFeRD data	
Writing a ZUGFeRD-PDF file.	4
Complete source code example for writing ZUGFeRD PDFs	7
Writing custom XML-Data	
Supplementary functions.	7
Writing custom XML-Data.	7
Supplementary functions	

## About Mustangproject

Mustangproject is a Java-Library for extended ("ZUGFeRD"-)metadata in PDF-invoices. It requires the Apache PDFBox library, uses PDF/A files as input and is, like Apache PDFBox subject to the APL-License and can therefore, within the terms of the Apache Public License, be used for free in commercial and noncommercial projects as long as e.g. a according "Notice"-file is placed.

#### **Overview of ZUGFeRD-Solutions**

	Platform	License	Functionality				Viable for			Price
			Read PDF	create XML	write PDF	PDF/A-Conversion	Commercial software	Freeware	Open Source	
intarsys	Java	proprieta ry	Yes	Yes	Yes	Yes	Yes	Yes	No	On request

Konik	Java	AGPL	Yes	Yes	Yes	No	No	No	Yes	0 €
Mustang	Java	APL	Yes	Yes	Yes	No	Yes	Yes	Yes	0 €
https://git hub.com/ stephanst apel/ZU GFeRD- csharp		APL	Yes	Yes	No	No	Yes	Yes	Yes	0 €

## Download/Project setup

#### Source code

Home of the Mustangprojekt source code is <a href="https://github.com/Rayman2200/PDFA3">https://github.com/Rayman2200/PDFA3</a>

#### Project setup without Maven

With installed OpenOffice.org or LibreOffice and Eclipse for Java.

- 1. Start Eclipse, create a new Java-Eclipse-project, e.g. "MustangSample".
- 2. Change to that folder.
- 3. Download
  - 1. Apache PDFBox
    - 1. from <a href="http://apache.openmirror.de/pdfbox/1.8.11/pdfbox-1.8.11.jar">http://apache.openmirror.de/pdfbox/1.8.11/pdfbox-1.8.11.jar</a>
    - 2. from <a href="http://apache.openmirror.de/pdfbox/1.8.11/preflight-app-1.8.11.jar">http://apache.openmirror.de/pdfbox/1.8.11/preflight-app-1.8.11.jar</a>
    - 3. from <a href="http://apache.openmirror.de/pdfbox/1.8.11/xmpbox-1.8.11.jar">http://apache.openmirror.de/pdfbox/1.8.11/xmpbox-1.8.11.jar</a>
  - 2. Mustang
    - 1. the JAR file <a href="http://mustangproject.org/deploy/mustang-1.3.1.pdf">http://mustangproject.org/deploy/mustang-1.3.1.pdf</a>
    - 2. the notice file <a href="http://mustangproject.org/deploy/NOTICE">http://mustangproject.org/deploy/NOTICE</a>
  - 3. Download the sample
    - 1. from <a href="http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008">http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008</a> 504.pdf
    - 2. Either
      - 1. Download <a href="http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008\_504.pdf">http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008\_504.pdf</a>
      - 2. Open this OpenOffice.org source file in Writer

- 3. File|Export as PDF: Set the Checkbox PDF/A-1a in the export options
- 4. Save the PDF file as "MustangGnuaccountingBeispielRE-20151008 504blanko.pdf"
- 3. alternatively
  - 1. dowload blank PDF without ZUGFeRD metadata from <a href="http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008">http://www.mustangproject.org/MustangGnuaccountingBeispielRE-20151008</a> 504blanko.pdf
- 4. Switch back to Eclipse. Add all four downloaded JAR files to your project (right click on project name, Properties) add as "external Jar" to the "Build Path" in the "libraries" tab.

#### With Maven

```
The following repository
<repositories>
    <repository>
        <id>mustang-mvn-repo</id>
        <url>https://raw.github.com/Rayman2200/PDFA3/mvn-repo/</url>
    </repository>
</repositories>
serves the following dependency
<dependency>
  <groupId>org.mustangproject.ZUGFeRD</groupId>
  <artifactId>mustang</artifactId>
  <version>1.3.1-SNAPSHOT</version>
</dependency>
It's a good idea to also import PDFBox
<dependency>
    <groupId>org.apache.pdfbox</groupId>
    <artifactId>pdfbox</artifactId>
    <version>1.8.8
</dependency>
```

# Reading ZUGFeRD data

- 5. Create a new class in the src folder, called Reader. Check the "Public static void main()" checkbox.
- 6. Within the main method, enter "ZUGFeRDImporter zi=new ZUGFeRDImporter();" and add the import by pressing STRG+SHIFT+O
- 7. use zi.extract(PDF-filename) and canParse() to find out if ZUGFeRD-Data is present.
- 8. After invoking zi.parse() you can access the getter-Methods like getAmount()
- 9. There are only getters for few properties but additional ones can be addded easily. Which data is available can be seen in the ZUGFeRD-invoice.xml file embedded any ZUGFeRD compliant PDF

#### Complete sample source code for reading ZUGFeRD data

```
package sample;
import org.mustangproject.ZUGFeRD.ZUGFeRDImporter;
public class Read {
      public static void main(String[] args) {
            ZUGFeRDImporter zi=new ZUGFeRDImporter();
            zi.extract("./MustangGnuaccountingBeispielRE-20151008 504.pdf");
            System.out.println("Reading ZUGFeRD");
            if (zi.canParse()) {
                  zi.parse();
                  System.out.println("Due amount:"+zi.getAmount());
                  System.out.println("BIC:"+zi.getBIC());
                  System.out.println("IBAN:"+zi.getIBAN());
                  System.out.println("Account holder name:"+zi.getHolder());
                  System.out.println("Document:"+zi.getForeignReference());
            }
      }
```

# Writing a ZUGFeRD-PDF file

A sample for writing ZUGFeRD PDFs is more comprehensive, because

- 1) more data is being written than read in the read example and
- 2) the exporter interacts via interfaces with your software.
- 1. Create a new class in the src-folder, e.g. MustangWriter. Check the checkbox to generate "Public static void main()".
- 2. Change public class MustangWriter to public class MustangWriter implements IZUGFeRDExportableTransaction
- 3. Add the following classes in in the same file:

```
    class <u>Contact</u> implements IZUGFeRDExportableContact {}
    class <u>Item</u> implements IZUGFeRDExportableItem {
        private BigDecimal price, quantity;
        private Product product;
    }
    class Product implements IZUGFeRDExportableProduct {
        private String description, name, unit;
        private BigDecimal VATPercent;
    }
```

- 4. Generate the imports by pressing CTRL+SHIFT+O
- 5. Click left on MustangWriter and press ALT+SHIFT+S, select Override/Implement Methods and press return.

- 6. Click on Contact and repeat the last step.
- 7. Click Item, mark the variables, press ALT+SHIFT+S and select "Generate Getters and Setters" first. Mark all members and press return.
- 8. Click again on Item, press ALT+SHIFT+S and select "Generate Constructor using Fields". Choose again all member variables and press return.
- 9. Repeat the last two steps for "Product": Click Product, mark the variables, press ALT+SHIFT+S and select "Generate Getters and Setters". Choose all members and press return.
- 10. Item also needs other methods besides the getter/setters, press ALT+SHIFT+S, and choose Override/Implement Methods
- 11. Click on Product again, press ALT+SHIFT+S and select "Generate Constructor using Fields". Choose all members again and press return.
- 12. The following methods of Contact should return the following:

```
1. getCountry(): "DE"
2. getLocation(): "Spielkreis"
3. getName(): "Theodor Est"
4. getStreet(): "Bahnstr. 42"
5. getVATID(): "DE999999999"
6. getZIP(): "88802";
```

13. The following methods of the main class should return the following:

```
1. getDeliveryDate(): new
          GregorianCalendar(2015, Calendar. OCTOBER, 7) .getTime()
       2. Pressing CTRL+SHIFT+O twice will import the necessary GregorianCalendar
          and Calendar class
       3. getDueDate(): new GregorianCalendar(2015, Calendar. OCTOBER, 29).getTime()
       4. getIssueDate(): new GregorianCalendar(2015, Calendar. OCTOBER, 8).getTime()
       5. getNumber(): "RE-20151008/504"
       6. getOwnBIC(): "COBADEFXXX"
       7. getOwnBankName(): "Commerzbank"
       8. getOwnCountry() "DE"
       9. getOwnIBAN(): "DE88 2008 0000 0970 3757 00"
      10.
                 getOwnLocation() "Stadthausen"
      11. getOwnOrganisationName().

12. getOwnStreet() "Ecke 12"

13. getOwnTaxID(): "22/815/0815/4"

14. getOwnVATID(): "DE136695976"

20+OwnZIP() "12345"
                 getOwnOrganisationName(): "Bei Spiel GmbH"
          getOwnZIP() "12345"
    getOwnOrganisationFullPlaintextInfo(): "Bei Spiel GmbH\n"+
"Ecke 12\n"+
          "12345 Stadthausen\n"+
          "Geschäftsführer: Max Mustermann"
                 getRecipient(): new Contact()
       18. getZFItems() of the main class can now create products and return them as a array of items:
                    Item[] allItems=new Item[3];
             Product designProduct=new Product("", "Künstlerische Gestaltung
(Stunde)", "HUR", new BigDecimal("7.000000"));
             Product balloonProduct=new Product("", "Luftballon", "C62", new
BigDecimal("19.000000"));
```

Product airProduct=new Product("", "Heiße Luft pro Liter", "LTR", new

- 19. Now create a private void apply method
- 20. Please instantiate this main MustangWriter class in the main method and invoke the apply() function
- 21. In the apply-method you can now
  - 1. instantiate a ZUGFeRDExporter,
  - 2. invoke the ZUGFeRDExporter's PDFmakeA3compliant (with the file name, the "Producer", i.e. Application- and "Creator", i.e. Author name parameters) and
  - 3. finally use the PDFattachZugferdFile-method (with the IZUGFeRDExportableTransation, i.e. "this" as parameter) and
  - 4. use export to save again. The apply-method then looks with according try/catchblocks- as follows:

```
try {
                  System.out.println("Lese Blanko-PDF");
                  // automatically add <u>Zugferd</u> to all outgoing invoices
                  ZUGFeRDExporter ze = new ZUGFeRDExporter();
                  System.out.println("Wandle in PDF/A-3u um");
                  ze.PDFmakeA3compliant("./MustangGnuaccountingBeispielRE-
20151008 504blanko.pdf", "My Application",
                              System.getProperty("user.name"), true);
                  System.out.println("ZUGFeRD-Daten generieren und anhängen");
                  ze.PDFattachZugferdFile(this);
                  System.out.println("Schreibe ZUGFeRD-PDF");
                  ze.export("./MustangGnuaccountingBeispielRE-
20151008 504new.pdf");
                  System.out.println("Fertig.");
            } catch (IOException e) {
                  e.printStackTrace();
            } catch (TransformerException e) {
                  e.printStackTrace();
            } catch (JAXBException e) {
                  e.printStackTrace();
```

- 22. CTRL+SHIFT+O again helps with the imports
- 23. "My Application" and System. getProperty("user.name") are stored in the meta data as "Producer" (producing application) respectively "Creator" (author). Please adjust

accordingly.

- 24. Start it to write the ZUGFeRD invoice to the file specified in export.
- 25. Adjust the NOTICE-File and add it to your application.

#### Complete source code example for writing ZUGFeRD PDFs

Please refer to the file MustangWriter.java in this directory.

#### Writing custom XML-Data

If you create your own ZUGFeRD-XML you can attach them using setZUGFeRDXMLData, in this case PDFattachZugferdFile is invoked with a null argument as follows:

## **Supplementary functions**

- ZUGFerdexporter.setTest() sets a attribute in the XML struture used to identify test invoices.
- ZUGFerdexporter.ignoreAlerrors() skips the check of the input file whether it's valid PDF/A-1

# Writing custom XML-Data

If you create your own ZUGFeRD-XML you can attach them using setZUGFeRDXMLData, in this case PDFattachZugferdFile is invoked with a null argument as follows:

# **Supplementary functions**

- zugferdExporter->setTest() sets the indicator in the xml structure that the invoice has been created in or is ment for nonproductive use only.
- ZUGFeRDExporter.ignoreAlErrors() skips checking the input file for PDF/A-1-violations