`dot(dot(X, Y), Z) => dot(X, dot(Y, Z))`

LHS: T = dot(X, Y), O = dot(T, Z). RHS: U = dot(Y, Z).

dot(X, Y) leaves I, J and contracts K.

1. Select axes

	I		J	
T	i0	i1	j0	j1
	0	1	2	3

`c_L = [3, 0]`

Selected axes: `j1` `i0`

Pairing slots: 0 1

Tensor order is unchanged

→

2. Partition by origin

`I = [i0, i1]`

`Group positions: [0, 1]`

`I_sel [i0]` `I_rem [i1]`

`J = [j0, j1]`

`Group positions: [0, 1]`

`J_sel [j1]` `J_rem [j0]`

Views retain axis positions

→

3. Preserve pairings

Physical Z axes

Z	z0	f	z1
	0	1	2

`c_R = [2, 0]`

Slot	From T		From Z	Z pos
0	j1	↔	z1	2
1	i0	↔	z0	0

Selected subgroup mappings

Positions are zero-based

Selected subgroup	Positions within group	Pairing slots	Partner positions in Z
`I_sel`	`v_I = [0]`	`u_I = [1]`	`z_I = [0]`
`J_sel`	`v_J = [1]`	`u_J = [0]`	`z_J = [2]`

U = dot(Y, Z) contracts J_sel; final dot contracts I_sel + K.

U retains K and I_sel's partners. Output: I_rem ++ J_rem ++ F (F = [f]).