



Use it when:

• you need something to run immediately after current code

• you want consistent async behaviour

Avoid it:

• you're looping or scheduling repeatedly (can block everything) → Search Query

API endpoint → `app.get('/menu', (req, res) => {`

registered as

req: ...

(when we don't use req, we tend to replace it with —)

RE: Read the article

chaiode.com/cart?q=biryani&limit=5

26 March 2026
Thursday

Weekend Class
(March 15)

RE: watch

after ? query parameter starts

Chai Aur Express

Class Start → 21:46

• mention the packages of express

=> Route params / path params

• Anything can be applied
get/post/put

`app.get('/menu/:id')`

`process.exit(0)`

↳ (what is the work)

=> Post route

app.use → middleware

Article

what is serialisation & deserialisation?

• There are limited no. of way data will come

↳ JSON

↳ form data

↳ URL encoded



server.address().port
↳ console.log output check

```
method: 'POST',
headers: {
  'content-type': 'app/json',
  body: JSON.stringify({
    dish: 'biryani',
    // case sensitive
  })
}
```

res.get('x-powered-by', '...')
res.set('x-request-id', '...')

standard ways to declare paths
for custom-headers endpoints

used in
↳ CORS
↳ caching
↳ tracing

28 MAY 2016

Saur

1:31:45 → routing

Q What is "/health" ?

when someone (or a system) hits /health, the server responds with a basic status like:

```
{
  status: OK
}
```

[2:08:00 - 2:29:00] Break

[2:31:00 → middleware & use]

→ creating basic middleware (built-in)

/health → basic route endpoint used to check if your application is running & healthy

→ creating custom middleware (auth / getRole)

→ creating rate limiter

2) Custom Headers

app.use → built-in middlewares



Read about apprise

→ express.static

↳ and its options

| 3:19:00 → class ends |

Assignment (no code)

↳ authentication

↳ e-commerce