Chapter 10: IC Technology

Outline

- Anatomy of integrated circuits
- Full-Custom (VLSI) IC Technology
- Semi-Custom (ASIC) IC Technology
- Programmable Logic Device (PLD) IC Technology

CMOS transistor

- Source, Drain
  - Diffusion area where electrons can flow
  - Can be connected to metal contacts (via's)
- Gate
  - Polysilicon area where control voltage is applied
- Oxide
  - Si O_2 Insulator so the gate voltage can't leak



End of the Moore's Law?

- Every dimension of the MOSFET has to scale
  - (PMOS) Gate oxide has to scale down to
    - Increase gate capacitance
    - Reduce leakage current from S to D
    - Pinch off current from source to drain
  - Current gate oxide thickness is about 2.5-3nm
- That's about 25 atoms!!!



Proposed Structures: FinFET

Body is a Thin Silicon Film
Double Gate Structure + Raised Source Drain



X. Huang, et al, 1999 IEDM, p.67-70

20Ghz +

- FinFET has been manufactured to 18nm
  - Still acts as a very good transistor
- Simulation shown that it can be scaled to 10nm
  - Quantum effect start to kick in
    - Reduce mobility by ~10%
  - Ballistic transport become significant
    - Increase current by about ~20%



NAND

- Metal layers for routing (~10)
- PMOS don't like 0
- NMOS don't like 1
- A stick diagram form the basis for mask sets



Silicon manufacturing steps

- Tape out
  - Send design to manufacturing
- Spin
  - One time through the manufacturing process
- Photolithography
  - Drawing patterns by using photoresist to form barriers for deposition



Full Custom

- Very Large Scale Integration (VLSI)
- Placement
  - Place and orient transistors
- Routing
  - Connect transistors
- Sizing
  - Make fat, fast wires or thin, slow wires
  - May also need to size buffer
- Design Rules
  - “simple” rules for correct circuit function
    - Metal/metal spacing, min poly width…



Full Custom

- Best size, power, performance
- Hand design
  - Horrible time-to-market/flexibility/NRE cost…
  - Reserve for the most important units in a processor
    - ALU, Instruction fetch…
- Physical design tools
  - Less optimal, but faster…







Semi-Custom

- Gate Array
  - Array of prefabricated gates
  - “place” and route
  - Higher density, faster time-to-market
  - Does not integrate as well with full-custom



- Standard Cell
  - A library of pre-designed cell
  - Place and route
  - Lower density, higher complexity
  - Integrate great with full-custom



Semi-Custon

- Most popular design style
- Jack of all trade
  - Good
    - Power, time-to-market, performance, NRE cost, per-unit cost, area…
- Master of none
  - Integrate with full custom for critical regions of design



Programmable Logic Array (PLA)

PLA exploits structure of expression.



$F = AB + C$

$G = AB + \bar{C} + \overline{A}\overline{B}$

Programmable Logic Device

- Programmable Logic Device
  - Programmable Logic Array, Programmable Array Logic, Field Programmable Gate Array
- All layers already exist
  - Designers can purchase an IC
  - To implement desired functionality
    - Connections on the IC are either created or destroyed to implement
- Benefits
  - Very low NRE costs
  - Great time to market
- Drawback
  - High unit cost, bad for large volume
  - Power
    - Except special PLA
  - slower

1600 usable gate, 7.5 ns
$7 list price

Xilinx FPGA



Configurable Logic Block (CLB)



Figure 1: Simplified Block Diagram of XC4000-Series CLB (RAM and Carry Logic functions not shown)

I/O Block



Simplified Block Diagram of XC4000E IOB