1. Dataset Requirements & Deadlines Source: Choose dataset from Kaggle.

Size: It should have at least 2,000 rows. (Under special circumstances, I may approve datasets less than 2,000 rows, but the absolute minimum is 1,000 rows).

Timeline: Start looking for a dataset TODAY (it takes 2 weeks to finalize the dataset and get my approval).

Deadline: Present your dataset for approval by me before October 12, 2026.

⚠️ Warning: If your dataset is not approved by me, your project submission will NOT be graded.

2. Pre-Processing & Cleanup Requirements Once approved, perform a cleanup on the dataset using the guidelines you learned in Modules 4 and 5.

Some of the pre-processing exercises to be performed on the dataset are:

Filling NaN and Null values with appropriate values

Scaling: Changing the range of your data

Normalization: Adjusting the shape of your data's distribution

Class Balancing the dataset

One-hot encoding

Encoding: Converting categorical data to numbers

Feature engineering

🚨 CRITICAL RULE: NEVER EVER change the dataset manually. If you do this, you have failed the exam. All changes must be done via Python code in Jupyter Lab.

3. Notebook & Visualization Requirements Matplotlib: Use Matplotlib to plot the data distributions in the code and show how the data before and after preprocessing looks like (e.g., balancing the dataset).

Sample Data: Print sample data as it gets processed in the code.

Jupyter Notebook: Build a Jupyter notebook to show the dataset before and after cleanup.

ML Problem Discussion: Discuss how you would use this dataset to solve an ML problem.

```
# pip install matplotlib numpy pandas seaborn scikit-learn
import warnings
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import seaborn as sns
from sklearn.compose import ColumnTransformer
from sklearn.impute import SimpleImputer
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import (
    accuracy_score,
    classification_report,
    confusion_matrix,
    ConfusionMatrixDisplay,
    precision_score,
    recall_score,
    f1_score,
)
from sklearn.model_selection import train_test_split
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import OneHotEncoder, StandardScaler, LabelEncoder
from sklearn.tree import DecisionTreeClassifier
```

```
DATA_URL = "/content/healthcare_dataset.csv"
df = pd.read_csv(DATA_URL)

print("Dataset loaded successfully.")
print("Rows:", df.shape[0], "| Columns:", df.shape[1])
```

```
Dataset loaded successfully.
Rows: 55500 | Columns: 15
```

```
# Split before analysis or preprocessing
train_df, test_df = train_test_split(
    df,
    test_size=0.30,
    random_state=42,
    stratify=df["Test Results"]
```

```
)

train_df = train_df.copy()
test_df = test_df.copy()

print("Original dataset:", df.shape)
print("Training dataset:", train_df.shape)
print("Testing dataset:", test_df.shape)
print("\nFirst five training rows:")
display(train_df.head())
```

```
Original dataset: (55500, 15)
Training dataset: (38850, 15)
Testing dataset: (16650, 15)

First five training rows:
```

	Name	Age	Gender	Blood Type	Medical Condition	Date of Admission	Doctor	Hospital	Insurance Provider	Billing Amount	Room Number	Admission Type
39555	StANleY MOrRISON	20	Female	B+	Obesity	2019-07-31	Brittney Simpson	PLC Cruz	Blue Cross	21189.286364	276	Elective
25382	TrAVis smith	40	Female	B+	Arthritis	2021-05-02	Alison Powell	Richards-Mason	Cigna	7019.697644	407	Urgent
41604	MicHAEL siMs	20	Female	O+	Obesity	2019-07-14	Angela Hodges	Flynn, Hart Hodges and	Cigna	37688.012482	299	Urgent
51069	aNDREw hILl	81	Male	A-	Obesity	2021-04-29	Hannah Cochran	Greene-Fritz	Medicare	39471.282888	438	Urgent
45759	JoHN graNt	52	Male	AB-	Arthritis	2020-04-13	John Lucero	Moreno Jones Little, and	Aetna	19113.505036	379	Elective

```
# Explore only the training dataset
print("\nData types and non-null counts:")
train_df.info()

print("\nDescriptive statistics:")
display(train_df.describe(include="all").transpose())

print("\nMissing values by column:")
print(train_df.isnull().sum().sort_values(ascending=False))

print("\nDuplicate rows:")
print(train_df.duplicated().sum())

print("\nUnique values in categorical columns:")
categorical_columns = [
    "Test Results",
    "Medication",
    "Medical Condition",
    "Blood Type",
    "Gender",
    "Admission Type"
]

for column in categorical_columns:
    print(f"{column}: {train_df[column].dropna().unique().tolist()}")

print("\nTest Result Counts:")
print(train_df["Test Results"].value_counts())

print("\nTest Result Percentages:")
print(
    train_df["Test Results"]
    .value_counts(normalize=True)
    .mul(100)
    .round(2))
```

```
Data types and non-null counts:
<class 'pandas.core.frame.DataFrame'>
Index: 38850 entries, 39555 to 23462
Data columns (total 15 columns):
 #   Column              Non-Null Count  Dtype
---  ------              --------------  -----
 0   Name                38850 non-null  object
 1   Age                 38850 non-null  int64
 2   Gender              38850 non-null  object
 3   Blood Type          38850 non-null  object
 4   Medical Condition   38850 non-null  object
 5   Date of Admission   38850 non-null  object
 6   Doctor              38850 non-null  object
 7   Hospital            38850 non-null  object
 8   Insurance Provider  38850 non-null  object
 9   Billing Amount      38850 non-null  float64
 10  Room Number         38850 non-null  int64
 11  Admission Type      38850 non-null  object
 12  Discharge Date      38850 non-null  object
 13  Medication          38850 non-null  object
 14  Test Results        38850 non-null  object
dtypes: float64(1), int64(2), object(12)
```

```
# Visualize training data before cleanup
result_order = ["Abnormal", "Inconclusive", "Normal"]

fig, axes = plt.subplots(2, 3, figsize=(18, 11))

sns.countplot(
    data=train_df, x="Test Results",
    order=result_order, ax=axes[0, 0]
)
axes[0, 0].set_title("Target Distribution Before Cleanup")

sns.countplot(
    data=train_df, x="Medical Condition",
    hue="Test Results", hue_order=result_order,
    ax=axes[0, 1]
)
axes[0, 1].set_title("Test Results by Medical Condition")
axes[0, 1].tick_params(axis="x", rotation=30)

sns.countplot(
    data=train_df, x="Gender",
    hue="Test Results", hue_order=result_order,
    ax=axes[0, 2]
)
axes[0, 2].set_title("Test Results by Gender")

sns.histplot(
    data=train_df, x="Age",
    hue="Test Results", hue_order=result_order,
    bins=25, kde=True, ax=axes[1, 0]
)
axes[1, 0].set_title("Age Distribution by Test Results")

sns.boxplot(
    data=train_df, x="Test Results", y="Billing Amount",
    order=result_order, ax=axes[1, 1]
)
axes[1, 1].set_title("Billing Amount by Test Results")

result_by_blood_type = pd.crosstab(
    train_df["Blood Type"],
    train_df["Test Results"],
    normalize="index"
).reindex(columns=result_order, fill_value=0)

result_by_blood_type.plot(
    kind="bar",
    ax=axes[1, 2]
)
axes[1, 2].set_title("Test Results by Blood Type")
axes[1, 2].set_xlabel("Blood Type")
axes[1, 2].set_ylabel("Proportion")
axes[1, 2].set_ylim(0, 1)
axes[1, 2].legend(title="Test Results")

fig.tight_layout()
plt.show()
```


```
print("\nTest Results by Gender (Proportions):")
test_results_by_gender = pd.crosstab(
    train_df["Gender"],
    train_df["Test Results"],
    normalize="index"
).reindex(columns=result_order, fill_value=0)

display(test_results_by_gender.round(4))

print("\nTest Results by Medical Condition (Proportions):")
test_results_by_condition = pd.crosstab(
    train_df["Medical Condition"],
    train_df["Test Results"],
    normalize="index"
).reindex(columns=result_order, fill_value=0)

display(test_results_by_condition.round(4))
```

Normal 33.36



Test Results by Gender (Proportions):

Test Results	Abnormal	Inconclusive	Normal
Gender			
Female	0.3376	0.3310	0.3314
Male	0.3336	0.3304	0.3359

Test Results by Medical Condition (Proportions):

Test Results	Abnormal	Inconclusive	Normal
Medical Condition			
Arthritis	0.3415	0.3361	0.3224
Asthma	0.3254	0.3295	0.3451
Cancer	0.3396	0.3293	0.3311
Diabetes	0.3422	0.3295	0.3283
Hypertension	0.3269	0.3300	0.3430
Obesity	0.3379	0.3300	0.3320

```
# Remove duplicates from training data only
rows_before = len(train_df)
train_df = train_df.drop_duplicates().copy()

print("Rows before cleanup:", rows_before)
print("Duplicates removed:", rows_before - len(train_df))
```

```
print("Rows after cleanup:", len(train_df))
print("Remaining duplicates:", train_df.duplicated().sum())

# Inspect negative billing amounts before deciding how to handle them
negative_billing = train_df["Billing Amount"] < 0

print("\nNegative billing amounts:", negative_billing.sum())

display(
    train_df.loc[
        negative_billing,
        ["Age", "Billing Amount", "Test Results"]
    ].head(10)
)
```

```
Rows before cleanup: 38850
Duplicates removed: 251
Rows after cleanup: 38599
Remaining duplicates: 0

Negative billing amounts: 78
```

	Age	Billing Amount	Test Results
50099	43	-1316.618581	Inconclusive
5708	23	-353.865186	Inconclusive
45423	85	-1129.997176	Normal
54136	64	-199.663795	Abnormal
25868	49	-124.649036	Normal
2696	74	-135.986000	Abnormal
29484	39	-1316.618581	Inconclusive
53204	55	-306.364925	Normal
28260	71	-599.265359	Abnormal
6961	83	-43.098522	Abnormal

```
# Project assumption: billing amounts must be non-negative
billing_before = train_df["Billing Amount"].copy()
negative_mask = billing_before < 0

# Mark negative amounts as missing
train_df.loc[negative_mask, "Billing Amount"] = np.nan

# Learn the replacement value from training data only
billing_imputer = SimpleImputer(strategy="median")

train_df["Billing Amount"] = billing_imputer.fit_transform(
    train_df[["Billing Amount"]]
).ravel()

print("Negative amounts replaced:", negative_mask.sum())
print("Training median used:", round(billing_imputer.statistics_[0], 2))
print("Remaining negative amounts:",
      (train_df["Billing Amount"] < 0).sum())
print("Remaining missing amounts:",
      train_df["Billing Amount"].isna().sum())

print("\nSample corrected values:")
display(pd.DataFrame({
    "Before": billing_before.loc[negative_mask],
    "After": train_df.loc[negative_mask, "Billing Amount"]
}).head(10))
```

```
Negative amounts replaced: 78
Training median used: 25572.76
Remaining negative amounts: 0
Remaining missing amounts: 0

Sample corrected values:
```

	Before	After
50099	-1316.618581	25572.759954
5708	-353.865186	25572.759954
45423	-1129.997176	25572.759954
54136	-199.663795	25572.759954
25868	-124.649036	25572.759954
2696	-135.986000	25572.759954
29484	-1316.618581	25572.759954
53204	-306.364925	25572.759954
28260	-599.265359	25572.759954
6961	-43.098522	25572.759954

```
from sklearn.preprocessing import PowerTransformer

before = train_df["Billing Amount"].copy()

billing_transformer = PowerTransformer(
    method="yeo-johnson", standardize=False
)
train_df["Billing Amount"] = billing_transformer.fit_transform(
    train_df[["Billing Amount"]]
).ravel()


display(pd.DataFrame({
    "Before": before,
    "After": train_df["Billing Amount"]
}).head())

print("Skewness before:", round(before.skew(), 4))
print("Skewness after:", round(train_df["Billing Amount"].skew(), 4))

fig, axes = plt.subplots(1, 2, figsize=(10, 4))
axes[0].hist(before, bins=30, edgecolor="black")
axes[0].set_title("Before Yeo-Johnson")
axes[1].hist(train_df["Billing Amount"], bins=30, edgecolor="black")
axes[1].set_title("After Yeo-Johnson")
plt.tight_layout()
plt.show()
train_df["Billing Amount"] = before.copy()
```

	Before	After
39555	21189.286364	1912.201259
25382	7019.697644	856.223096
41604	37688.012482	2906.241415
51069	39471.282888	3005.560998
45759	19113.505036	1774.105412

```
Skewness before: 0.0006
Skewness after: -0.2478
```



Distribution Transformation

A Yeo-Johnson transformation was applied to Billing Amount using training data only. Skewness changed from 0.0006 to -0.2478, introducing slight negative skewness into an already nearly symmetric distribution.


The corrected billing values were restored before scaling because the transformation did not improve symmetry. Near-zero skewness alone does not indicate a normal distribution.

```
counts = train_df["Test Results"].value_counts()

display(pd.DataFrame({
    "Count": counts,
    "Percentage": (counts / counts.sum() * 100).round(2)
}))

counts.plot(kind="bar", figsize=(6, 4), edgecolor="black")
plt.title("Class Distribution After Cleanup — Training Data")
plt.ylabel("Count")
plt.xticks(rotation=0)
plt.tight_layout()
plt.show()
```

Test Results	Count	Percentage
Abnormal	12950	33.55
Normal	12868	33.34
Inconclusive	12781	33.11



Class Balance

After cleanup, the training dataset contains 12,950 Abnormal results (33.55%), 12,868 Normal results (33.34%), and 12,781 Inconclusive results (33.11%).

The classes are approximately balanced. Therefore, oversampling and undersampling are unnecessary, and the existing class distribution is retained. The testing dataset remains untouched.

```
# Feature engineering: create age groups
train_df["Age_Group"] = pd.cut(
    train_df["Age"],
    bins=[-np.inf, 17, 39, 59, np.inf],
    labels=["Under 18", "18-39", "40-59", "60+"]
)

print("Feature engineering sample:")
display(train_df[["Age", "Age_Group"]].head(10))

# Encode the target separately
label_encoder = LabelEncoder()
y_train = label_encoder.fit_transform(train_df["Test Results"])

print("\nTarget encoding:")
for number, label in enumerate(label_encoder.classes_):
    print(f"{label} = {number}")

# Select input features
columns_to_drop = [
    "Test Results",
    "Name",
    "Date of Admission",
    "Doctor",
    "Hospital",
    "Insurance Provider",
    "Room Number",
    "Discharge Date"
]
X_train = train_df.drop(columns=columns_to_drop).copy()

# One-hot encode categorical features
df_encoded = pd.get_dummies(
    X_train,
    columns=[
        "Medication",
        "Medical Condition",
        "Blood Type",
        "Gender",
```

```
        "Admission Type",
        "Age_Group"
    ],
    dtype=int
)

print("\nEncoded training features:")
display(df_encoded.head())
print("Encoded features shape:", df_encoded.shape)
print("Target shape:", y_train.shape)
```

```
Feature engineering sample:
```

	Age	Age_Group
39555	20	18-39
25382	40	40-59
41604	20	18-39
51069	81	60+
45759	52	40-59
41213	56	40-59
27832	30	18-39
41978	32	18-39
48054	33	18-39
23438	67	60+

```
Target encoding:
Abnormal = 0
Inconclusive = 1
Normal = 2

Encoded training features:
```

	Age	Billing Amount	Medication_Aspirin	Medication_Ibuprofen	Medication_Lipitor	Medication_Paracetamol	Medicatio
39555	20	21189.286364	0	1	0	0	
25382	40	7019.697644	0	0	0	0	
41604	20	37688.012482	1	0	0	0	
51069	81	39471.282888	0	1	0	0	
45759	52	19113.505036	1	0	0	0	

5 rows × 30 columns

```
Encoded features shape: (38599, 30)
Target shape: (38599,)
```

Feature Engineering and Encoding

Age_Group was created from Age using four predefined groups: under 18, 18–39, 40–59, and 60+. Grouping ages provides an additional representation that may help capture differences between age ranges. The original Age variable is retained to preserve numerical detail.

Categorical input features, including Age_Group, were one-hot encoded. Test Results was encoded separately as Abnormal = 0, Inconclusive = 1, and Normal = 2. The target is excluded from the input features.

```
# Scale numerical features using training data only
numeric_columns = ["Age", "Billing Amount"]

df_scaled = df_encoded.copy()
scaler = StandardScaler()

df_scaled[numeric_columns] = scaler.fit_transform(
    df_encoded[numeric_columns]
)

print("Before scaling:")
display(df_encoded[numeric_columns].head())

print("\nAfter scaling:")
display(df_scaled[numeric_columns].head())
```

```
print("\nScaled feature statistics:")
display(df_scaled[numeric_columns].agg(["mean", "std"]))

# Compare distributions before and after scaling
fig, axes = plt.subplots(2, 2, figsize=(12, 8))

for row, column in enumerate(numeric_columns):
    axes[row, 0].hist(
        df_encoded[column], bins=30, edgecolor="black"
    )
    axes[row, 0].set_title(f"{column}: Before Scaling")
    axes[row, 0].set_ylabel("Count")

    axes[row, 1].hist(
        df_scaled[column], bins=30, edgecolor="black"
    )
    axes[row, 1].set_title(f"{column}: After Scaling")
    axes[row, 1].set_ylabel("Count")

fig.tight_layout()
plt.show()
```