Module 06 Lab - Regression and Classification Models**Objective:** To understand the difference between regression and classification and to build your first linear models for both tasks.**In this lab, you will write the code to train and evaluate the models.**

Part 1: Regression vs. ClassificationThis is the most fundamental distinction between types of supervised learning problems.* **Regression:** The goal is to predict a **continuous numerical value**. * *Examples:* Predicting the price of a house, the temperature tomorrow, or the stock price.* **Classification:** The goal is to predict a **discrete category or class label**. * *Examples:* Predicting if an email is spam or not spam, if a flower is a setosa, versicolor, or virginica, or if a customer will churn or not.**In this lab, we will tackle one of each.**

Part 2: Linear Regression**Concept:** Linear Regression is used to predict a continuous value. It works by finding the best-fitting straight line through the data points. The model learns a "slope" (coefficient) for each feature and an "intercept".* **Problem:** We will predict the `Fare` of a Titanic passenger based on their `Age` and `Pclass`.

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.metrics import mean_squared_error

# Load and prepare the data
df = pd.read_csv(
    'https://raw.githubusercontent.com/datasciencedojo/datasets/master/titanic.csv'
)

# For simplicity, we'll drop rows with missing age
df.dropna(subset=['Age'], inplace=True)

# Define features and target
features = ['Age', 'Pclass']
target_reg = 'Fare'

X_reg = df[features]
y_reg = df[target_reg]

# Split the data
X_train_reg, X_test_reg, y_train_reg, y_test_reg = train_test_split(
    X_reg,
    y_reg,
    test_size=0.2,
    random_state=42
)
```

Task 1: Train and Evaluate a Linear Regression Model**Your Task:**1. Create an instance of the `LinearRegression` model.2. Train the model using the training data (`X_train_reg`, `y_train_reg`).3. Make predictions on the test data.4. Evaluate the model using `mean_squared_error`. This metric tells us the average of the squared differences between the predicted and actual values.

```
# --- ENTER YOUR CODE HERE ---

import numpy as np

# 1. Create the model instance
lr_model = LinearRegression()

# 2. Train the model
lr_model.fit(X_train_reg, y_train_reg)
```

```
# 3. Make predictions
y_pred_reg = lr_model.predict(X_test_reg)

# 4. Evaluate the model
mse = mean_squared_error(y_test_reg, y_pred_reg)
print(f"Mean Squared Error for Fare Prediction: {mse:.2f}")
print(f"Root Mean Squared Error: {np.sqrt(mse):.2f}")
```

```
Mean Squared Error for Fare Prediction: 3364.92
Root Mean Squared Error: 58.01
```

Part 3: Logistic Regression**Concept:** Despite its name, Logistic Regression is a **classification** algorithm. It works by calculating the probability that a given input belongs to a certain class. It's one of the most widely used and interpretable classification models.* **Problem:** We will predict whether a passenger `Survived` based on their `Age`, `Pclass`, and `Sex`.

```
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score

# Prepare data for classification
# Encode 'Sex': male = 0, female = 1
df['Sex'] = df['Sex'].map({'male': 0, 'female': 1})

# Define features and target
features_cls = ['Age', 'Pclass', 'Sex']
target_cls = 'Survived'

X_cls = df[features_cls]
y_cls = df[target_cls]

# Split the data
X_train_cls, X_test_cls, y_train_cls, y_test_cls = train_test_split(
    X_cls,
    y_cls,
    test_size=0.2,
    random_state=42
)
```

Task 2: Train and Evaluate a Logistic Regression Model**Your Task:**1. Create an instance of the `LogisticRegression` model.2. Train the model using the classification training data.3. Make predictions on the test data.4. Evaluate the model using `accuracy_score`.

```
# --- ENTER YOUR CODE HERE ---
# 1. Create the model instance
log_model = LogisticRegression(max_iter=1000)

# 2. Train the model
log_model.fit(X_train_cls, y_train_cls)

# 3. Make predictions
y_pred_cls = log_model.predict(X_test_cls)

# 4. Evaluate the model
accuracy = accuracy_score(y_test_cls, y_pred_cls)
print(f"Accuracy for Survival Prediction: {accuracy:.2%}")
```

```
Accuracy for Survival Prediction: 74.83%
```

📝 Knowledge Check**Instructions:** Answer the following questions in this markdown cell.

1. **In your own words, what is the key difference between a regression problem and a classification problem?**
   - Regression predicts a continuous numerical value, such as a passenger's fare. The classification predicts a category, such as whether a passenger survived or not.
2. **The `LinearRegression` model has an attribute called `.coef_`. After you train the model, print `lr_model.coef_`. What do these numbers represent?**
   - The coefficients show how each feature affects the predicted fare. The first number corresponds to Age, and the second corresponds to Pclass. Each coefficient represents the change in predicted fare when that feature increases by one unit,

while the other feature stays the same.

3. **Why did we use mean_squared_error to evaluate the regression model but accuracy_score for the classification model?** Why wouldn't accuracy be a good metric for the fare prediction task?**
    - I used mean_squared_error for regression because it measures how far the predicted fares are from the actual fares. We used accuracy_score for classification because it measures the proportion of correctly predicted survival labels. Accuracy would not be useful for fare prediction because fares are continuous values.