Term Project Report — Secure Build (NoteVault)

Field	Value
Team name	TSC
Members (name + ID)	TEAM_ID TSC; add member names before submission
Target application	`project/starter-app`
Repository URL	Local course repository
Date	2026-11-06

AI-tool usage disclosure

Tool	How it was used
GitHub Copilot SDK in VS Code	Assisted with code inspection, secure implementation, test authoring, and report drafting; all commands and results were locally verified.

1. Executive Summary

NoteVault is a local Flask note-sharing application with registration, login, notes, search, an admin JSON endpoint, and note export. The baseline had confirmed SQL injection, XSS, broken object-level authorization, role escalation, command injection, password-hash disclosure, weak password storage, insecure session configuration, CSRF exposure, and vulnerable dependency/container defaults. The remediated build uses parameterized SQL, Jinja autoescaping, ownership checks, server-assigned roles, Werkzeug's password KDF for the seeded demo data, CSRF tokens, strict JWT algorithms, protected cookies, allow-listed export formats, non-root Docker, runtime secrets, and current dependency pins.

Local evidence: `pytest -q test_app.py` — **7 passed**; Docker build succeeded; container `GET /` returned HTTP 200; `pip-audit -r requirements.txt` reported **No known vulnerabilities found**. Cosign and GitHub provenance are configured but not claimed as completed locally because no registry, signing identity, or GitHub Actions run was available.

2. System Scope & Function

In scope are the Flask process, SQLite database, HTML templates, JSON API, Docker image, Compose configuration, requirements, tests, and CI workflows under `project/starter-app`. The only external entity is a local browser/API client.

DFD and trust boundaries

```text
[Local browser/API client]
        | HTTP :8080 (TB1: network/input boundary)
        v
[Flask routes: auth, notes, search, admin, export]
        | parameterized SQL (TB2: application/data boundary)
        v
[SQLite /tmp/notevault.db] ---> [note and account records]
        ^
[Environment: APP_SECRET, TEAM_ID, TEAM_SALT]
```

Assets are credentials, JWT/session cookies, note contents, admin role, database records, team marker, image provenance, and dependency integrity. Entry points are `/`, `/register`, `/login`, `/logout`, `/notes`, `/api/notes/<id>`, `/search`, `/admin`, and `/export`.

3. Threat Model — STRIDE

Element / flow	S	T	R	I	D	E	Top threat & mitigation
Browser to auth routes	spoofing	tampering	repudiation	information disclosure	denial	elevation	stolen/forged session; strict HS256, HttpOnly cookie, CSRF
Browser to notes/search	spoofing	tampering	repudiation	disclosure	denial	elevation	SQLi/XSS/IDOR; parameters, autoescape, owner predicate
Browser to admin/export	spoofing	tampering	repudiation	disclosure	denial	elevation	admin data/command injection; role check, allow-list, no hashes
Flask to SQLite	spoofing	tampering	repudiation	disclosure	denial	elevation	injection and overbroad queries; bound parameters and least data
Build/dependency supply chain	spoofing	tampering	repudiation	disclosure	denial	elevation	dependency/image compromise; pinned dependencies, SBOM, SCA, attestations

Top risks ranked by likelihood × impact: (1) SQL injection — High/High; (2) broken object authorization — Medium/High; (3) command injection — Medium/Critical; (4) stored XSS — Medium/High; (5) weak authentication/session and password handling — Medium/High.

4. Vulnerability Findings

The following are confirmed baseline findings from source inspection and safe local reproduction. Line numbers refer to the baseline commit `99cdb1c`.

Finding F-01 — SQL injection in login

Field	Value
CWE	CWE-89
OWASP 2025	A05 Injection
Severity	High
Location	`app.py` baseline login query
Reproduction	POST `/login` with `username=' OR '1'='1` and an invalid password.
Impact	Authentication bypass/data access in the vulnerable build.
Evidence	Baseline query interpolated username into SQL; regression now returns 401.
Root cause	String formatting instead of bound parameters.

Finding F-02 — SQL injection in search

Field	Value
CWE	CWE-89
OWASP 2025	A05 Injection
Severity	High
Location	`app.py` baseline `/search`
Reproduction	Authenticated request `/search?q=' OR 1=1 --`.
Impact	Cross-user note disclosure and query manipulation.
Root cause	User and search term were concatenated into SQL.

Finding F-03 — Stored/reflected XSS

Field	Value
CWE	CWE-79
OWASP 2025	A07 Cross-Site Scripting
Severity	High
Location	Baseline home and search rendering
Reproduction	Add `<img src=x onerror=alert(1)>` as a note body.
Impact	Script execution in another user's browser and session actions.
Root cause	Raw HTML construction and `|safe`; search had unescaped interpolation.

Finding F-04 — Broken object-level authorization (IDOR)

Field	Value
CWE	CWE-862
OWASP 2025	API1 Broken Object Level Authorization
Severity	High
Location	Baseline `/api/notes/<nid>`
Reproduction	Authenticate as `alice`; GET `/api/notes/2`.
Impact	Read another user's note, including the seeded admin note.
Root cause	Query checked only note ID, not owner.

Finding F-05 — Self-service role escalation

Field	Value
CWE	CWE-269
OWASP 2025	A01 Broken Access Control
Severity	Critical
Location	Baseline `/register`
Reproduction	POST registration with `role=admin`.
Impact	New account gains admin access to all users.
Root cause	Client-controlled role was inserted into the database.

Finding F-06 — Command injection in export

Field	Value
CWE	CWE-78
OWASP 2025	A05 Injection
Severity	Critical
Location	Baseline `/export?fmt=...`
Reproduction	Authenticated request `fmt=txt;cat /etc/passwd`.
Impact	OS command execution as the container process.
Root cause	`shell=True` with concatenated user input.

Finding F-07 — Password hash disclosure and weak authentication storage

Field	Value
CWE	CWE-200, CWE-916
OWASP 2025	A04 Cryptographic Failures; A01 Broken Access Control
Severity	High
Location	Baseline `/admin` and MD5 seed/registration

Reproduction	Authenticate as admin and GET `/admin`.
Impact	Hash cracking and account takeover; admin endpoint exposed hashes.
Root cause	MD5 storage and returning the password column.

Finding F-08 — Insecure session, CSRF, and baked secret defaults

Field	Value
CWE	CWE-384, CWE-352, CWE-798
OWASP 2025	A07; A02 Cryptographic Failures
Severity	High
Location	Baseline JWT decode/cookie and Dockerfile
Reproduction	Observe `algorithms=["HS256", "none"]`, non-HttpOnly cookie, state-changing GET logout, and `APP_SECRET` in image.
Impact	Token confusion/forgery risk, CSRF state changes, secret exposure.
Root cause	Unsafe algorithm allow-list, cookie defaults, no CSRF control, baked secret.

Finding F-09 — Vulnerable dependencies and root container

Field	Value
CWE	CWE-1104, CWE-250
OWASP 2025	A03 Software Supply Chain Failures
Severity	High
Location	Baseline requirements and Dockerfile
Reproduction	`pip-audit` against baseline pins and inspect Dockerfile.
Impact	Known dependency vulnerabilities and unnecessary container privilege.
Root cause	Old pins, unpinned base, root user, and secret in image.

5. Remediation

F-01/F-02 use bound SQL parameters; F-03 uses Jinja autoescaping; F-04 adds `owner = ?`; F-05 ignores submitted roles; F-06 removes shell execution and allow-lists `txt`/`json`; F-07 removes password fields from admin output and uses Werkzeug's password KDF for the starter's compatibility data; F-08 requires CSRF, strict HS256, HttpOnly/SameSite cookies, POST logout, and runtime `APP_SECRET`; F-09 upgrades dependencies, generates an SBOM, uses a non-root slim image, and adds CI gates.

Regression proof is `7 passed` in `test_app.py`. Separate finding commits should be created from the coherent changes below before submission if the instructor requires one commit per finding; this working tree preserves unrelated existing student changes.

6. Supply-Chain Hardening

`sbom.json` is CycloneDX 1.6 with 6 runtime components, generated with:

```powershell
cyclonedx-py requirements requirements.txt --output-format json --output-file sbom.json
pip-audit -r requirements.txt
```

The verified local SCA result was **No known vulnerabilities found** after upgrading the pins. Cosign signing is configured in `.github/workflows/release.yml`, but no signature is claimed here: it requires a pushed registry digest and authorized OIDC credentials. The same workflow requests GitHub artifact attestations. This is a

SLSA-style provenance configuration, not a locally verified SLSA level.

7. Security CI Pipeline

`.github/workflows/security.yml` runs pytest, `pip-audit --strict`, Semgrep Flask/Python rules, and Gitleaks. A nonzero scanner result fails the job. The workflow uses read-only contents permission; release signing separately requests only the OIDC, attestation, package, and contents permissions it needs. GitHub Actions has not been run in this local session, so no CI pass/fail claim or screenshot is made.

8. Conclusion & Reflection

The fixed local build materially reduces injection, authorization, XSS, session, and supply-chain risk. Residual risks include no password migration path for accounts outside this starter database, ephemeral SQLite storage, lack of rate limiting, no centralized audit logging, and manual registry/OIDC release setup. Next hardening would add Argon2id migration, rate limiting, encrypted persistent storage, and independent image vulnerability scanning.

Appendix

Tools: Python, pytest, Docker Compose, CycloneDX, pip-audit, Semgrep/Gitleaks in CI, Cosign and GitHub attestations in the release workflow. Testing remained local and within the authorized NoteVault scope described by `ETHICS.md`.