

```

import os
import requests
from flask import Flask, request, render_template_string, redirect, session
import secrets

app = Flask(__name__)
app.secret_key = secrets.token_hex(32)

CLIENT_ID = "1496753618861424700"
CLIENT_SECRET = os.environ.get("CLIENT_SECRET")
BOT_TOKEN = os.environ.get("BOT_TOKEN")
GUILD_ID = "1488422873415811092"
ROLE_NAME = "apex | member"
REDIRECT_URI = os.environ.get("REDIRECT_URI")

DISCORD_API = "https://discord.com/api/v10"

HTML = """<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8"/>
<meta name="viewport" content="width=device-width,initial-scale=1.0"/>
<title>APEX Verification</title>
<link href="https://fonts.googleapis.com/css2?family=Bebas+Neue&family=DM+Sans:wght@400;500;700;900">
<style>
*,*::before,*::after{box-sizing:border-box;margin:0;padding:0}
:root{--orange:#ff5a1e;--bg:#0a0a0b;--surface:#111113;--border:rgba(255,255,255,0.1);
html,body{height:100%;background:var(--bg);color:var(--text);font-family:'DM Sans'}
body::before{content:'';position:fixed;inset:0;background-image:linear-gradient(to top right,transparent 49%,var(--border) 49%,var(--border) 51%,transparent 51%);background-size:3px 3px;background-position:50%;background-repeat:repeat;opacity:0.05}
body::after{content:'';position:fixed;width:600px;height:600px;background:radial-gradient(circle,transparent 1px,black 1px);background-size:20px 20px;background-position:50%;background-repeat:repeat;opacity:0.05}
.card{position:relative;z-index:1;background:var(--surface);border:1px solid var(--border);border-radius:12px;overflow:hidden}
@keyframes rise{from{opacity:0;transform:translateY(24px)}to{opacity:1;transform:translateY(0)}}
.icon{width:72px;height:72px;border-radius:50%;background:rgba(255,90,30,0.15);background-size:cover;background-position:center;position:relative}
h1{font-family:'Bebas Neue',sans-serif;font-size:2.8rem;letter-spacing:0.08em;margin-bottom:16px}
.subtitle{color:var(--muted);font-size:0.95rem;margin-bottom:32px;line-height:1.6}
.btn{display:inline-block;background:var(--orange);color:#fff;border:none;border-radius:8px;padding:12px 24px;text-align:center}
.btn:hover{background:#ff6e37;box-shadow:0 0 36px rgba(255,90,30,0.55);transform:scale(1.05)}
.success{background:rgba(34,197,94,0.12);border:1px solid rgba(34,197,94,0.3);color:#2e7d32}
.error{background:rgba(239,83,83,0.12);border:1px solid rgba(239,83,83,0.3);color:#c00000}
.avatar{width:64px;height:64px;border-radius:50%;border:2px solid var(--orange);position:relative}
.footer{margin-top:24px;color:var(--muted);font-size:0.78rem}
</style>
</head>
<body>

```

```

<div class="card">
    <div class="icon">{{ icon }}</div>
    <h1>{{ title }}</h1>
    {% if avatar %}
    
    {% endif %}
    <p class="subtitle">{{ subtitle }}</p>
    {% if status == "success" %}<div class="success">{{ message }}</div>{% endif %}
    {% if status == "error" %}<div class="error">{{ message }}</div>{% endif %}
    {% if show_button %}
    <form method="POST" action="/do_verify">
        <button class="btn" type="submit">Verify Me</button>
    </form>
    {% endif %}
    <p class="footer">APEX Verification System</p>
</div>
</body>
</html>""

```

```

def render(icon, title, subtitle, status=None, message=None, show_button=False, a
    return render_template_string(HTML, icon=icon, title=title, subtitle=subtitle
        status=status, message=message, show_button=sh

```

```

@app.route("/")
def index():
    return render("lightning", "APEX Verify", "Use the Verify button in the Disco

```

```

@app.route("/callback")
def callback():
    code = request.args.get("code")
    error = request.args.get("error")

    if error or not code:
        return render("X", "Access Denied", "You declined the verification.", sta

    token_res = requests.post(
        DISCORD_API + "/oauth2/token",
        data={
            "client_id": CLIENT_ID,
            "client_secret": CLIENT_SECRET,
            "grant_type": "authorization_code",
            "code": code,
            "redirect_uri": REDIRECT_URI,
        },

```

```

        headers={"Content-Type": "application/x-www-form-urlencoded"},
    )

    if token_res.status_code != 200:
        return render("X", "Error", "Something went wrong.", status="error", mess

    access_token = token_res.json().get("access_token")

    user_res = requests.get(DISCORD_API + "/users/@me", headers={"Authorization":
    if user_res.status_code != 200:
        return render("X", "Error", "Could not fetch your account.", status="erro

    user = user_res.json()
    session["user_id"] = user["id"]
    session["username"] = user.get("global_name") or user.get("username", "Member
    avatar_hash = user.get("avatar")
    if avatar_hash:
        session["avatar"] = "https://cdn.discordapp.com/avatars/" + user["id"] +
    else:
        session["avatar"] = None

    return render(
        "lightning",
        "Welcome, " + session["username"] + "!",
        "You are logged in with Discord. Click below to complete your verificatio
        show_button=True,
        avatar=session.get("avatar"),
    )

@app.route("/do_verify", methods=["POST"])
def do_verify():
    user_id = session.get("user_id")
    username = session.get("username", "Member")
    avatar = session.get("avatar")

    if not user_id:
        return render("X", "Session Expired", "Please try again.", status="error"

    roles_res = requests.get(DISCORD_API + "/guilds/" + GUILD_ID + "/roles", head
    role_id = None
    unverified_id = None
    for role in roles_res.json():
        if role["name"].strip().lower() == "apex | member":
            role_id = role["id"]
        if role["name"].strip().lower() == "unverified":
            unverified_id = role["id"]

```

```

if not role_id:
    return render("X", "Error", "Role not found.", status="error", message="C

member_res = requests.get(DISCORD_API + "/guilds/" + GUILD_ID + "/members/" +

if member_res.status_code != 200:
    return render("X", "Not in Server", "Join the server first.", status="err

member_data = member_res.json()

if role_id in member_data.get("roles", []):
    return render("V", "Already Verified", "You already have access.", status

add_res = requests.put(
    DISCORD_API + "/guilds/" + GUILD_ID + "/members/" + user_id + "/roles/" +
    headers={"Authorization": "Bot " + BOT_TOKEN}
)

if unverified_id and unverified_id in member_data.get("roles", []):
    requests.delete(DISCORD_API + "/guilds/" + GUILD_ID + "/members/" + user_

if add_res.status_code in (200, 204):
    session.clear()
    return render("V", "Verified!", "Welcome to APEX, " + username + ".", sta
else:
    return render("X", "Error", "Could not assign role.", status="error", mes

if __name__ == "__main__":
    port = int(os.environ.get("PORT", 5000))
    app.run(host="0.0.0.0", port=port)

```